

SPECIFICATION

Customer Name: Zhuhai Zhidi Technology Co., LTD

Product Model: RG59

Customer P/N : 152000492

Jiade P/N:

SPECIFICATIONS: DG 0.6MM FR4 RG59 V10 恒宝士 4L 94V0 G

Production date: 2025-03-26

Sample Version: R1

JIA DE		
FICTION	QC	R&D
Customer		
PUR	QC	R&D

Manufacturer: Good Wireless Technology (Shenzhen) Co., LTD

Shenzhen Address: 601-602, North Block, Gangsong Building, Tairan Sixth Road, Futian District, Shenzhen

Tel: 0755-33353180 Email: olinama@jiadew.com

The website is: www.jiadew.com

[illegible]

1、The basic parameters

A. Electrical Characteristics	
Frequency	2400MHZ~2500MHZ
VSWR	< 2.0
Avg Efficiency	>30%
Impedance	50 ± 25 Ohm
Polarization	Linear
Peak Gain	2.4G:0.31dBi
B. Material & Mechanical Characteristics	
Material of Radiator	PCB black
antenna Type	PCB onboard antenna
Cable Type	/
Connector Type	/
Dimension (mm)	
C. Environmental	
Operation Temperature	- 20 °C ~ + 60 °C
Storage Temperature	- 30 °C ~ + 70 °C

2、Electrical Specification

Those specifications were specially defined for RG59 model.


3、VSWR

1 Measuring Method

1.A 50 Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR

2.Keeping this jig away from metal at least 20cm

2 Measurement frequency points and VSWR value



4、 Anechoic chamber


Introduction:

Microwave darkroom and no reflection chamber, absorbing short wave darkroom dark room. Microwave darkroom by electromagnetic shielding room, filtering and isolation, grounding device, the ventilation duct, indoor distribution system, monitoring system, ceiling wave material part. It is based on the wave absorbing material as the lining of the shield room, it can absorb the most of the electromagnetic energy into the six wall is a better simulation of the free space conditions.

The main working principle of microwave anechoic chamber is according to the electromagnetic wave in the medium from the low magnetic guide magnetic direction of propagation rules, absorbing materials to guide the electromagnetic wave using high permeability, through resonance, a substantial absorption of electromagnetic wave radiation energy, by coupling the electromagnetic energy into heat energy.





main performance :

Frequency range:400MHz ~ 6GHz ceiling reflected wave loss materials: 400MHz ~ 6GHz is equal to or more than 15dB (microwave absorbing material by composite wave absorbing materials, namely tapered containing carbon sponge suction wave material paste in ferrite)



5、Gain table of Antenna

Passive field pattern



Passive efficiency gain

Frequency (MHz)	Efficiency (dBi)	Gain (dBi)	Efficiency (%)
2400	-4.90	-0.27	32.33
2410	-4.77	0.19	33.38
2420	-4.67	0.25	34.10
2430	-4.65	0.24	34.25
2440	-4.62	0.18	34.51
2450	-4.65	0.31	34.28
2460	-4.70	0.31	33.87
2470	-4.81	0.20	33.00
2480	-4.89	0.16	32.47
2490	-5.15	-0.11	30.56
2500	-5.18	-0.21	30.35

6、 ROHS:

Antenna 152000492 meets RoHS requirements.

7、 Product packaging instructions:

A. packing should meet the moistureproof, vibration, pressure and mildew proof, etc.

B. the smallest packing unit logo must have the manufacturer trademarks, product model, name, code and quantity.

C. in the attached packing list, certificate of approval, and the factory inspection report.

*****END*****