

RF Exposure Evaluation declaration

Product Name : Motherboard

Model No. : P5AD2 Deluxe, P5AD2 Premium

FCC ID MSQMWOM6L

Applicant : ASUSTeK COMPUTER INC.

Address : 4FL., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan, R.O.C.

Date of Receipt : May. 18, 2004

Date of Declaration : May. 28, 2004

Report No. : 045L111FI

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Motherboard
Test Item : RF Exposure Evaluation
Test Site : No.3 OATS

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.94dBi in linear scale.

802.11b

Output Power Into Antenna & RF Exposure Evaluation Distance (Golden: 2.94dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	32.3594	0.0127
6	2437.00	33.8844	0.0133
11	2462.00	22.1309	0.0087

802.11g

Output Power Into Antenna & RF Exposure Evaluation Distance (Golden: 2.94dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	14.0929	0.0055
6	2437.00	10.7152	0.0042
11	2462.00	17.0216	0.0067

The distance r (4th column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.45dBi in linear scale.

802.11b

Output Power Into Antenna & RF Exposure Evaluation Distance (INPAQ: 2.45dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	32.3594	0.0113
6	2437.00	33.8844	0.0119
11	2462.00	22.1309	0.0077

802.11g

Output Power Into Antenna & RF Exposure Evaluation Distance (INPAQ: 2.45dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412.00	14.0929	0.0049
6	2437.00	10.7152	0.0037
11	2462.00	17.0216	0.0060

The distance r (4th column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.