Test Report

Product Name	:	Notebook P.C.
Model No.	:	A3400L, A3500L, A3800L, A3F00L, Z9100, A3000
Transmitter Module.	:	WL-120G V2
FCC ID	:	MSQWL-120G V2

Applicant : ASUSTeK COMPUTER INC.

Address : 4FL., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan, R.O.C.

Date of Receipt : June 21, 2005

Issued Date : July 08, 2005

Report No. : 056L122FI

The test results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Test Report Certification

Issued Date : July 08, 2005
Report No. : 056L122FI

QuieTek Corporation

Accredited by NIST (NVLAP)
NVLAP Lab Code: 200533-0

Product Name	: Notebook P.C.
Applicant	: ASUSTeK COMPUTER INC.
Address	: 4FL., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan, R.O.C.
Manufacturer	: ASUSTeK COMPUTER INC.
Model No.	: A3400L, A3500L, A3800L, A3F00L, Z9100, A3000
Rated Voltage	: AC 120V/60Hz
Working Voltage	: DC 3.3V (Powered by PC)
Trade Name	: ASUS
Applicable Standard	: FCC CFR Title 47 Part 15 Subpart C: 2003 ANSI C63.4: 2003
Test Result	: Complied

NVLAP
NVLAP Lab Code: 200533-0

Test results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Rita Huang
(Rita Huang)

Tested By : Tom Hsieh
(Tom Hsieh)

Approved By : Gene Chang
(Gene Chang)

CNLA
0914

FC

TABLE OF CONTENTS

Description Page

1. GENERAL INFORMATION 5

1.1. EUT Description 5

1.2. Operational Description 6

1.3. Tested System Datails 7

1.4. Configuration of tested System 8

1.5. EUT Exercise Software 8

1.6. Test Facility 9

2. Conducted Emission 10

2.1. Test Equipment 10

2.2. Test Setup 10

2.3. Limits 10

2.4. Test Procedure 11

2.5. Uncertainty 11

2.6. Test Result of Conducted Emission 12

3. Peak Power Output 16

3.1. Test Equipment 16

3.2. Test Setup 16

3.3. Limits 16

3.4. Uncertainty 16

3.5. Test Result of Peak Power Output 17

4. Radiated Emission 19

4.1. Test Equipment 19

4.2. Test Setup 19

4.3. Limits 20

4.4. Test Procedure 21

4.5. Uncertainty 21

4.6. Test Result of Radiated Emission 22

5. Band Edge 34

5.1. Test Equipment 34

5.2. Test Setup 34

5.3. Limits 35

5.4. Test Procedure 35

5.5. Uncertainty 35

5.6. Test Result of Band Edge 36

6. Occupied Bandwidth 44

6.1. Test Equipment 44

6.2. Test Setup 44

6.3. Limits 44

6.4. Uncertainty 44

6.5. Test Result of Occupied Bandwidth 45

7. Power Density 51

7.1. Test Equipment 51

7.2. Test Setup 51

7.3. Limits 51

7.4. Uncertainty 51

7.5. Test Result of Power Density 52

8. EMI Reduction Method During Compliance Testing 58

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	:	Notebook P.C.
Trade Name	:	ASUS
Model No.	:	A3400L, A3500L, A3800L, A3F00L, Z9100, A3000
FCC ID	:	MSQWL-120G V2
Frequency Range	:	2412MHz - 2462MHz
Channel Number	:	11
Data Speed	:	IEEE 802.11b – 1, 2, 5.5, 11Mbps IEEE 802.11g – 6, 9, 12, 18, 24, 36 48, 54Mbps
Type of Modulation	:	DSSS/ OFDM
Antenna Type	:	Connector
Antenna Gain	:	1.3dBi
Channel Control	:	Auto
Power Adapter	:	MFR: DELTA, M/N: SADP-65KB B Input: 100-240V, 50-60Hz, 1.5A Output: 19V-3.42A Cable out: Non-Shielded, 1.8m with one ferrite core bonded.

Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 1:	2412 MHz	Channel 5:	2432 MHz	Channel 9:	2452 MHz
Channel 2:	2417 MHz	Channel 6:	2437 MHz	Channel 10:	2457 MHz
Channel 3:	2422 MHz	Channel 7:	2442 MHz	Channel 11:	2462 MHz
Channel 4:	2427 MHz	Channel 8:	2447 MHz		

Note:

1. The EUT is including six models for different marketing requirement.
2. This device is a 2.4GHz Notebook P.C.including a 2.4GHz receiving function, a 2.4GHz transmitting function.
3. Regards to the frequency band operation; the highest rate that was included the lowest、middle and highest frequency of channel were selected to perform the test, then shown on this report.
4. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.

1.2. Operational Description

EUT is a Notebook P.C. with 11 channels. This device provided four kinds of transmitting speed 1, 2, 5.5 and 11Mbps. The device of RF carrier is DBPSK, DQPSK and CCK (IEEE 802.11b) or eight kinds of transmitting speed 6, 9, 12, 18, 24, 36, 48 and 54Mbps. The device of RF carrier is OFDM (IEEE 802.11g).

The device adapts direct sequence spread spectrum modulation. The antenna was Connector provides diversity function to improve the receiving function.

This Notebook P.C., compliant with IEEE 802.11b and IEEE 802.11g, is a high-efficiency Wireless LAN adapter. It allows your computer to connect to a wireless network and to share resources, such as files or printers without being bound to the network wires. Operation in 2.4GHz Direst Sequence Spread Spectrum (DSSS) radio transmission, the Notebook P.C. Wired Equivalent Protection (WEP) algorithm is used. In addition, its standard compliance ensures that it can communicate with any IEEE 802.11b and IEEE 802.11g network.

Test Mode	Mode 1: Transmitter 802.11b
	Mode 2: Transmitter 802.11g

1.3. Tested System Datails

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
(1)	N/A	N/A	N/A	N/A	N/A	N/A

Signal Cable Type		Signal cable Description
A.	N/A	N/A

1.4. Configuration of tested System



1.5. EUT Exercise Software

(1) Setup the EUT and simulators as shown on 1.4
(2) Turn on the power of all equipment.
(3) Notebook PC reads data from disk.
(4) Data will be transmitting and receiving through EUT.
(5) The transmitted and receive status will be shown on the monitor.
(6) Repeat the above procedure (3) to (5)

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: June 22, 2001 File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2

CNLA
0914

July 03, 2001 Accreditation on NVLAP
NVLAP Lab Code: 200533-0

Site Name: Quietek Corporation

Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,
Lin-Kou Shiang, Taipei,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

NVLAP
NVLAP Lab Code: 200533-0

2. Conducted Emission

2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2005	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2005	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2005	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2005	
5	No.1 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	uV	dBuV
0.15 - 0.50	66-56(注)	56-46(注)
0.50-5.0	56	46
5.0 - 30	60	50

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs.)
Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.
Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB

2.6. Test Result of Conducted Emission

Product : Notebook P.C.
Test Item : Conducted Emission Test
Power Line : Line 1
Test Mode : Mode 1: Transmitter 802.11b (2437MHz)

	Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level dBuV	Emission Level dBuV	Limits dBuV
Quasi-Peak						
*	0.209	0.20	0.10	48.47	48.77	63.26
	0.275	0.20	0.10	41.04	41.34	60.97
	0.340	0.20	0.10	32.89	33.19	59.20
	0.409	0.20	0.10	33.28	33.58	57.67
	0.549	0.20	0.10	31.16	31.46	56.00
	4.880	0.20	0.17	37.03	37.40	56.00
Average						
*	0.209	0.20	0.10	38.90	39.20	53.26
	0.275	0.20	0.10	33.30	33.60	50.97
	0.340	0.20	0.10	29.90	30.20	49.20
	0.409	0.20	0.10	31.20	31.50	47.67
	0.549	0.20	0.10	30.90	31.20	46.00
	4.880	0.20	0.17	29.60	29.97	46.00

Note:

1. All Reading Levels are Quasi-Peak value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + LISN Factor + Cable Loss.

Product : Notebook P.C.
Test Item : Conducted Emission Test
Power Line : Line 2
Test Mode : Mode 1: Transmitter 802.11b (2437MHz)

	Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level dBuV	Emission Level dBuV	Limits dBuV
Quasi-Peak						
*	0.205	0.20	0.10	49.03	49.33	63.42
	0.272	0.20	0.10	40.21	40.51	61.05
	0.342	0.20	0.10	34.89	35.19	59.15
	0.410	0.20	0.10	36.12	36.42	57.65
	0.547	0.20	0.10	31.32	31.62	56.00
	4.947	0.20	0.17	39.18	39.55	56.00
Average						
	0.205	0.20	0.10	39.60	39.90	53.42
	0.272	0.20	0.10	32.80	33.10	51.05
	0.342	0.20	0.10	31.60	31.90	49.15
*	0.410	0.20	0.10	34.00	34.30	47.65
	0.547	0.20	0.10	30.30	30.60	46.00
	4.947	0.20	0.17	30.80	31.17	46.00

Note:

1. All Reading Levels are Quasi-Peak value.
2. “ * ” means this data is the worst emission level.
3. Emission Level = Reading Level + LISN Factor + Cable Loss.

Product : Notebook P.C.
Test Item : Conducted Emission Test
Power Line : Line 1
Test Mode : Mode 2: Transmitter 802.11g (2437MHz)

	Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level dBuV	Emission Level dBuV	Limits dBuV
Quasi-Peak						
*	0.209	0.20	0.10	48.21	48.51	63.26
	0.274	0.20	0.10	40.76	41.06	61.01
	0.341	0.20	0.10	33.59	33.89	59.18
	0.411	0.20	0.10	36.74	37.04	57.63
	0.546	0.20	0.10	29.73	30.03	56.00
	5.084	0.20	0.17	39.94	40.31	60.00
Average						
	0.209	0.20	0.10	38.80	39.10	53.26
	0.274	0.20	0.10	33.30	33.60	51.01
	0.341	0.20	0.10	30.90	31.20	49.18
*	0.411	0.20	0.10	34.80	35.10	47.63
	0.546	0.20	0.10	28.80	29.10	46.00
	5.084	0.20	0.17	31.70	32.07	50.00

Note:

1. All Reading Levels are Quasi-Peak value.
2. “ * ” means this data is the worst emission level.
3. Emission Level = Reading Level + LISN Factor + Cable Loss.

Product : Notebook P.C.
Test Item : Conducted Emission Test
Power Line : Line 2
Test Mode : Mode 2: Transmitter 802.11g (2437MHz)

	Frequency MHz	Cable Loss dB	LISN Factor dB	Reading Level dBuV	Emission Level dBuV	Limits dBuV
Quasi-Peak						
*	0.206	0.20	0.10	48.89	49.19	63.37
	0.273	0.20	0.10	40.90	41.20	61.02
	0.341	0.20	0.10	34.10	34.40	59.18
	0.411	0.20	0.10	34.94	35.24	57.63
	5.084	0.20	0.17	38.57	38.94	60.00
	5.150	0.20	0.17	36.38	36.75	60.00
Average						
*	0.206	0.20	0.10	39.40	39.70	53.37
	0.273	0.20	0.10	33.20	33.50	51.02
	0.341	0.20	0.10	30.90	31.20	49.18
	0.411	0.20	0.10	33.00	33.30	47.63
	5.084	0.20	0.17	32.10	32.47	50.00
	5.150	0.20	0.17	29.80	30.17	50.00

Note:

1. All Reading Levels are Quasi-Peak value.
2. “ * ” means this data is the worst emission level.
3. Emission Level = Reading Level + LISN Factor + Cable Loss.

3. Peak Power Output

3.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	Advantest	R3162 / 100803480	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

3.2. Test Setup

Conduction Power Measurement



3.3. Limits

The maximum peak power shall be less 1 Watt.

3.4. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

3.5. Test Result of Peak Power Output

Product : Notebook P.C.
Test Item : Peak Power Output Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b

Data Speed: 11Mbps

Channel No.	Frequency (MHz)	Measurement	Required Limit	Result
1	2412.00	20.27dBm	1Watt= 30 dBm	Pass
6	2437.00	20.55dBm	1Watt= 30 dBm	Pass
11	2462.00	20.25dBm	1Watt= 30 dBm	Pass

11Mbps-CH01



11Mbps-CH 06



11Mbps-CH11



Product : Notebook P.C.
Test Item : Peak Power Output Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g

Data Speed: 54Mbps

Channel No.	Frequency (MHz)	Measurement	Required Limit	Result
1	2412.00	16.47dBm	1Watt= 30 dBm	Pass
6	2437.00	15.36dBm	1Watt= 30 dBm	Pass
11	2462.00	15.00dBm	1Watt= 30 dBm	Pass

54Mbps-CH01



54Mbps-CH 06



54Mbps-CH11



4. Radiated Emission

4.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1		Test Receiver	R & S	ESCS 30 / 825442/14	May, 2005
		Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2005
		Pre-Amplifier	HP	8447D/3307A01812	May, 2005
		Bilog Antenna	Chase	CBL6112B / 12452	Sep., 2004
		Horn Antenna	EM	EM6917 / 103325	May, 2005
Site # 2		Test Receiver	R & S	ESCS 30 / 825442/17	May, 2005
		Spectrum Analyzer	Advantest	R3261C / 71720609	May, 2005
		Pre-Amplifier	HP	8447D/3307A01814	May, 2005
		Bilog Antenna	Chase	CBL6112B / 2455	Sep., 2004
		Horn Antenna	EM	EM6917 / 103325	May, 2005
Site # 3	X	Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2005
	X	Spectrum Analyzer	Advantest	R3162 / 100803480	May, 2005
	X	Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2005
	X	Bilog Antenna	SCHAFFNER	CBL6112B / 2697	May, 2005
	X	Horn Antenna	ETS	3115 / 0005-6160	July, 2005
	X	Pre-Amplifier	QTK	QTK-AMP-01 / 0001	July, 2005

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

4.2. Test Setup





4.3. Limits

➢ **General Radiated Emission Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209(a) Limits		
Frequency MHz	uV/m @3m	dBuV/m@3m
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Remarks : 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.
The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field dtrength of harmonics measurement.
The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30)is 120 kHz, above 1GHz are 1 MHz.
The frequency range from 30MHz to 10th harminics is checked.

4.5. Uncertainty

The measurement uncertainty is defined as ± 3.8 dB above 1GHz as ± 3.9 dB

4.6. Test Result of Radiated Emission

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2412MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4824.500	3.86	31.21	34.65	49.26	49.69	24.31	74.00
7235.750	5.01	35.86	34.81	44.23	50.29	23.71	74.00
9648.000	6.15	37.84	35.10	44.48	53.37	20.63	74.00
Average Detector							
4824.500	3.86	31.21	34.65	38.56	38.99	15.01	54.00
7235.750	5.01	35.86	34.81	37.15	43.21	10.79	54.00
9648.000	6.15	37.84	35.10	36.72	45.61	8.39	54.00
Vertical							
Peak Detector							
4824.000	3.86	31.21	34.65	43.69	44.12	29.88	74.00
7235.000	5.01	35.86	34.81	44.80	50.86	23.14	74.00
9648.000	6.15	37.84	35.10	44.60	53.49	20.51	74.00
Average Detector							
4824.000	3.86	31.21	34.65	37.87	38.30	15.70	54.00
7235.000	5.01	35.86	34.81	36.18	42.24	11.76	54.00
9648.000	6.15	37.84	35.10	36.25	45.14	8.86	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2437 MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4873.500	3.88	31.31	34.65	43.49	44.04	29.96	74.00
7311.000	5.05	35.96	34.82	43.44	49.63	24.37	74.00
9748.000	6.19	37.91	35.11	43.92	52.92	21.08	74.00
Average Detector							
4873.500	3.88	31.31	34.65	38.24	38.79	15.21	54.00
7311.000	5.05	35.96	34.82	37.54	43.73	10.27	54.00
9748.000	6.19	37.91	35.11	37.10	46.10	7.90	54.00
Vertical							
Peak Detector							
4874.000	3.88	31.31	34.65	42.53	43.08	30.92	74.00
7311.000	5.05	35.96	34.82	42.75	48.94	25.06	74.00
9748.000	6.19	37.91	35.11	44.26	53.26	20.74	74.00
Average Detector							
4874.000	3.88	31.31	34.65	36.51	37.06	16.94	54.00
7311.000	5.05	35.96	34.82	35.49	41.68	12.32	54.00
9748.000	6.19	37.91	35.11	36.75	45.75	8.25	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2462 MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4924.000	3.92	31.48	34.64	43.33	44.09	29.91	74.00
7386.000	5.08	36.09	34.82	42.74	49.08	24.92	74.00
9848.000	6.25	37.99	35.12	43.10	52.23	21.77	74.00
Average Detector							
4924.000	3.92	31.48	34.64	36.10	36.86	17.14	54.00
7386.000	5.08	36.09	34.82	35.94	42.28	11.72	54.00
9848.000	6.25	37.99	35.12	35.45	44.58	9.42	54.00
Vertical							
Peak Detector							
4924.000	3.92	31.48	34.64	41.90	42.66	31.34	74.00
7386.000	5.08	36.09	34.82	41.86	48.20	25.80	74.00
9848.000	6.25	37.99	35.12	43.93	53.06	20.94	74.00
Average Detector							
4924.000	3.92	31.48	34.64	35.86	36.62	17.38	54.00
7386.000	5.08	36.09	34.82	35.25	41.59	12.41	54.00
9848.000	6.25	37.99	35.12	35.19	44.32	9.68	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3OATS
Test Mode : Mode 2: Transmitter 802.11g (2412 MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4824.000	3.86	31.21	34.65	42.98	43.41	30.59	74.00
7236.000	5.01	35.86	34.81	43.85	49.91	24.09	74.00
9648.000	6.15	37.84	35.10	43.42	52.31	21.69	74.00
Average Detector							
4824.000	3.86	31.21	34.65	36.81	37.24	16.76	54.00
7236.000	5.01	35.86	34.81	35.94	42.00	12.00	54.00
9648.000	6.15	37.84	35.10	35.45	44.34	9.66	54.00
Vertical							
Peak Detector							
4823.750	3.86	31.21	34.65	42.40	42.83	31.17	74.00
7236.000	5.01	35.86	34.81	43.87	49.93	24.07	74.00
9648.000	6.15	37.84	35.10	43.67	52.56	21.44	74.00
Average Detector							
4823.750	3.86	31.21	34.65	36.58	37.01	16.99	54.00
7236.000	5.01	35.86	34.81	36.94	43.00	11.00	54.00
9648.000	6.15	37.84	35.10	36.25	45.14	8.86	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2437 MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4875.000	3.88	31.31	34.65	44.09	44.64	29.36	74.00
7311.000	5.05	35.96	34.82	42.69	48.88	25.12	74.00
9748.000	6.19	37.91	35.11	42.84	51.84	22.16	74.00
Average Detector							
4875.000	3.88	31.31	34.65	37.56	38.11	15.89	54.00
7311.000	5.05	35.96	34.82	36.34	42.53	11.47	54.00
9748.000	6.19	37.91	35.11	36.49	45.49	8.51	54.00
Vertical							
Peak Detector							
4874.000	3.88	31.31	34.65	42.54	43.09	30.91	74.00
7310.500	5.05	35.96	34.82	43.36	49.55	24.45	74.00
9748.000	6.19	37.91	35.11	43.36	52.36	21.64	74.00
Average Detector							
4874.000	3.88	31.31	34.65	36.81	37.36	16.64	54.00
7310.000	5.05	35.96	34.82	36.91	43.10	10.90	54.00
9748.000	6.19	37.91	35.11	36.20	45.20	8.80	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : Harmonic Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2462 MHz)

Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal							
Peak Detector							
4924.000	3.92	31.48	34.64	43.26	44.02	29.98	74.00
7386.000	5.08	36.09	34.82	42.72	49.06	24.94	74.00
9848.000	6.25	37.99	35.12	44.16	53.29	20.71	74.00
Average Detector							
4924.000	3.92	31.48	34.64	37.23	37.99	16.01	54.00
7386.000	5.08	36.09	34.82	36.62	42.96	11.04	54.00
9848.000	6.25	37.99	35.12	35.99	45.12	8.88	54.00
Vertical							
Peak Detector							
4924.000	3.92	31.48	34.64	41.75	42.51	31.49	74.00
7386.000	5.08	36.09	34.82	42.90	49.24	24.76	74.00
9848.000	6.25	37.99	35.12	44.25	53.38	20.62	74.00
Average Detector							
4924.000	3.92	31.48	34.64	36.28	37.04	16.96	54.00
7386.000	5.08	36.09	34.82	36.82	43.16	10.84	54.00
9848.000	6.25	37.99	35.12	36.24	45.37	8.63	54.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. Receiver setting (Peak Detector) : RBW:1MHz; VBW:1MHz; Span:100MHz。
3. Receiver setting (AVG Detector) : RBW:1MHz; VBW:30Hz; Span:20MHz。
4. Emission Level = Reading Level + Probe Factor + Cable Loss- PreAMP.
5. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2412 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
	129.400	1.38	11.59	0.00	13.60	26.58	16.92	43.50
	160.900	1.54	9.42	0.00	22.94	33.90	9.60	43.50
*	194.900	1.72	8.05	0.00	26.03	35.80	7.70	43.50
	240.900	1.95	10.57	0.00	19.75	32.28	13.72	46.00
	367.080	2.60	13.98	0.00	17.77	34.36	11.64	46.00
	388.900	2.72	14.09	0.00	17.44	34.24	11.76	46.00
Vertical:								
	129.430	1.38	10.59	0.00	18.93	30.91	12.59	43.50
	163.300	1.55	8.47	0.00	23.99	34.02	9.48	43.50
	301.600	2.27	12.06	0.00	19.79	34.12	11.88	46.00
	335.550	2.45	12.63	0.00	19.08	34.16	11.84	46.00
*	388.900	2.72	15.43	0.00	19.35	37.50	8.50	46.00
	500.400	3.30	16.26	0.00	16.58	36.14	9.86	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2437 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
	228.710	1.89	9.52	0.00	15.32	26.74	19.26	46.00
	260.380	2.05	12.95	0.00	11.52	26.53	19.47	46.00
	335.500	2.45	12.68	0.00	21.77	36.90	9.10	46.00
	367.100	2.60	13.98	0.00	17.67	34.26	11.74	46.00
	432.550	2.94	15.81	0.00	16.75	35.50	10.50	46.00
*	468.900	3.13	16.78	0.00	19.44	39.35	6.65	46.00
Vertical:								
	240.980	1.95	10.96	0.00	19.70	32.61	13.39	46.00
	602.300	3.81	19.64	0.00	7.27	30.73	15.27	46.00
*	687.170	4.25	17.90	0.00	12.80	34.95	11.05	46.00
	745.380	4.55	20.80	0.00	8.90	34.25	11.75	46.00
	786.600	4.77	19.66	0.00	9.75	34.18	11.82	46.00
	844.800	5.07	18.88	0.00	10.31	34.25	11.75	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2462 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
	335.500	2.45	12.68	0.00	11.84	26.97	19.03	46.00
	388.900	2.72	14.09	0.00	15.62	32.42	13.58	46.00
*	432.500	2.94	15.81	0.00	17.75	36.50	9.50	46.00
	454.300	3.05	16.34	0.00	7.39	26.79	19.21	46.00
	468.920	3.13	16.78	0.00	13.44	33.35	12.65	46.00
	575.620	3.67	17.40	0.00	5.42	26.49	19.51	46.00
Vertical:								
	228.850	1.89	9.73	0.00	18.54	30.17	15.83	46.00
*	624.120	3.93	18.89	0.00	15.98	38.80	7.20	46.00
	687.170	4.25	17.90	0.00	15.75	37.90	8.10	46.00
	730.800	4.49	20.51	0.00	8.70	33.70	12.30	46.00
	803.580	4.86	19.27	0.00	6.25	30.39	15.61	46.00
	929.670	5.50	21.42	0.00	7.38	34.30	11.70	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2412 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
	129.430	1.38	11.59	0.00	21.27	34.25	9.25	43.50
	228.800	1.89	9.52	0.00	23.28	34.70	11.30	46.00
	597.450	3.79	17.71	0.00	13.01	34.52	11.48	46.00
*	730.830	4.49	18.79	0.00	15.14	38.42	7.58	46.00
	781.650	4.75	18.96	0.00	13.89	37.60	8.40	46.00
	929.670	5.50	20.31	0.00	9.00	34.82	11.18	46.00
Vertical:								
*	163.380	1.55	8.47	0.00	24.00	34.03	9.47	43.50
	335.550	2.45	12.63	0.00	19.08	34.16	11.84	46.00
	466.500	3.12	16.55	0.00	14.74	34.42	11.58	46.00
	527.120	3.43	16.81	0.00	10.92	31.16	14.84	46.00
	672.620	4.18	17.59	0.00	9.47	31.24	14.76	46.00
	864.200	5.16	19.47	0.00	8.17	32.80	13.20	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2437 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
	228.850	1.89	9.52	0.00	23.32	34.74	11.26	46.00
*	240.980	1.95	10.57	0.00	23.75	36.28	9.72	46.00
	335.550	2.45	12.68	0.00	19.84	34.97	11.03	46.00
	388.900	2.72	14.09	0.00	17.62	34.42	11.58	46.00
	454.380	3.05	16.34	0.00	15.39	34.79	11.21	46.00
	468.920	3.13	16.78	0.00	13.44	33.35	12.65	46.00
Vertical:								
*	260.330	2.05	13.10	0.00	19.65	34.80	11.20	46.00
	367.080	2.60	14.67	0.00	17.18	34.45	11.55	46.00
	466.500	3.12	16.55	0.00	14.74	34.42	11.58	46.00
	500.450	3.30	16.26	0.00	14.60	34.16	11.84	46.00
	534.400	3.46	17.29	0.00	13.53	34.28	11.72	46.00
	672.620	4.18	17.59	0.00	12.47	34.24	11.76	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

Product : Notebook P.C.
Test Item : General Radiated Emission Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2462 MHz)

	Frequency MHz	Cable Loss dB	Probe Factor dB/m	PreAMP dB	Reading Level dBuV	Emission Level dBuV/m	Margin dB	Limit dBuV/m
Horizontal:								
*	160.900	1.54	9.42	0.00	21.92	32.88	10.62	43.50
	334.500	2.44	12.56	0.00	19.90	34.90	11.10	46.00
	432.550	2.94	15.81	0.00	14.04	32.79	13.21	46.00
	468.820	3.13	16.78	0.00	10.23	30.14	15.86	46.00
	624.120	3.93	18.59	0.00	11.95	34.47	11.53	46.00
	713.850	4.39	18.28	0.00	11.52	34.19	11.81	46.00
Vertical:								
*	301.600	2.27	12.06	0.00	22.08	36.41	9.59	46.00
	367.080	2.60	14.67	0.00	17.18	34.45	11.55	46.00
	466.500	3.12	16.55	0.00	14.56	34.24	11.76	46.00
	500.450	3.30	16.26	0.00	16.58	36.14	9.86	46.00
	527.120	3.43	16.81	0.00	10.86	31.11	14.89	46.00
	534.400	3.46	17.29	0.00	13.58	34.33	11.67	46.00

Note:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. " * " means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

5. Band Edge

5.1. Test Equipment

The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	HP	E4407B / US39440758	May, 2005
X	Test Receiver	R & S	ESCS 30 / 825442/14	May, 2005
X	Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2005
X	Pre-Amplifier	HP	8447D/3307A01812	May, 2005
X	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 2004
X	Horn Antenna	EM	EM6917 / 103325	May, 2005

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

5.2. Test Setup

RF Conducted Measurement:



RF Radiated Measurement:



5.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement.
The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30)is 120 kHz, above 1GHz are 1 MHz.

5.5. Uncertainty

The measurement uncertainty Conducted is defined as ± 1 MHz and Radiated above 1GHz as ± 3.9 dB.

5.6. Test Result of Band Edge

Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b

RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
1 (Horizontal)	<2400	>20	Pass

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
1 (Peak)	2381.000	52.48	47.49	74.00	54.00	Pass
1 (Average)	--	--	--	74.00	54.00	Pass

Figure Channel 1: (Horizontal)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b

RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
1 (Vertical)	<2400	>20	Pass

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
1 (Peak)	2378.000	52.57	47.45	74.00	54.00	Pass
1 (Average)	--	--	--	74.00	54.00	Pass

Figure Channel 1: (Vertical)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
11(Peak)	2487.500	52.45	47.87	74.00	54.00	Pass
11(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 11: (Horizontal)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
11(Peak)	2489.000	52.20	47.62	74.00	54.00	Pass
11(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 11: (Vertical)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g

RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
1 (Horizontal)	<2400	>20	Pass

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
1 (Peak)	2344.250	53.15	47.96	74.00	54.00	Pass
1 (Average)	--	--	--	74.00	54.00	Pass

Figure Channel 1: (Horizontal)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g

RF Radiated Measurement:

Channel No.	Frequency (MHz)	Required Limit (dBc)	Result
1 (Vertical)	<2400	>20	Pass

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
1 (Peak)	2372.750	52.32	47.20	74.00	54.00	Pass
1 (Average)	--	--	--	74.00	54.00	Pass

Figure Channel 1: (Vertical)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g

RF Radiated Measurement (Horizontal):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
11 (Peak)	2486.750	52.14	47.56	74.00	54.00	Pass
11(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 11: (Horizontal)



Product : Notebook P.C.
Test Item : Band Edge Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g

RF Radiated Measurement (Vertical):

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Emission Level (dBuV/m)	Peak Limit (dBuV/m)	Arerage Limit (dBuV/m)	Result
11 (Peak)	2485.250	52.06	47.48	74.00	54.00	Pass
11(Average)	--	--	--	74.00	54.00	Pass

Figure Channel 11: (Vertical)



Note: The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

6. Occupied Bandwidth

6.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	Advantest	R3272 / 72421194	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

6.2. Test Setup



6.3. Limits

The minimum bandwidth shall be at least 500kHz.

6.4. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

6.5. Test Result of Occupied Bandwidth

Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1 (11Mbps)	2412	10850	>500	Pass

Figure Channel 1: 11Mbps



Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6 (11Mbps)	2437	10500	>500	Pass

Figure Channel 6: 11Mbps



Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11 (11Mbps)	2462	10650	>500	Pass

Figure Channel 11: 11Mbps



Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1 (54Mbps)	2412	16550	>500	Pass

Figure Channel 1: 54Mbps



Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6 (54Mbps)	2437	16150	>500	Pass

Figure Channel 6: 54Mbps



Product : Notebook P.C.
Test Item : Occupied Bandwidth Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11 (54Mbps)	2462	16500	>500	Pass

Figure Channel 11: 54Mbps



7. Power Density

7.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	Advantest	R3272 / 72421194	May, 2005

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.
2. Mark "X" test instruments are used to measure the final test results.

7.2. Test Setup



7.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

7.4. Uncertainty

The measurement uncertainty is defined as ± 1.27 dB

7.5. Test Result of Power Density

Product : Notebook P.C.
Test Item : Power Density Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1 (11Mbps)	2412	-9.47	< 8dBm	Pass

Figure Channel 1: 11Mbps



Product : Notebook P.C.
Test Item : Power Density Data
Test Site : No.3OATS
Test Mode : Mode 1: Transmitter 802.11b (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6 (11Mbps)	2437	-8.85	< 8dBm	Pass

Figure Channel 6: 11Mbps



Product : Notebook P.C.
Test Item : Density Data
Test Site : No.3 OATS
Test Mode : Mode 1: Transmitter 802.11b (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11 (11Mbps)	2462	-10.95	< 8dBm	Pass

Figure Channel 11: 11Mbps



Product : Notebook P.C.
Test Item : Power Density Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1 (54Mbps)	2412	-11.22	< 8dBm	Pass

Figure Channel 1: 54Mbps



Product : Notebook P.C.
Test Item : Power Density Data
Test Site : No.3OATS
Test Mode : Mode 2: Transmitter 802.11g (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6 (54Mbps)	2437	-18.86	< 8dBm	Pass

Figure Channel 6: 54Mbps



Product : Notebook P.C.
Test Item : Density Data
Test Site : No.3 OATS
Test Mode : Mode 2: Transmitter 802.11g (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11 (54Mbps)	2462	-12.87	< 8dBm	Pass

Figure Channel 11: 54Mbps



8. EMI Reduction Method During Compliance Testing

No modification was made during testing.

Attachment 1: EUT Test Photographs

Attachment 1: EUT Test Setup Photographs

Front View of Conducted Test

Back View of Conducted Test

Front View of Radiated Test

Back View of Radiated Test

Front View of Radiated Test (Horn)

Back View of Radiated Test (Horn)

Attachment 2: EUT Detailed Photographs

Attachment 2 : EUT Detailed Photographs

(1) EUT Photo

(2) EUT Photo

(3) EUT Photo

(4) EUT Photo

(5) EUT Photo

(6) EUT Photo

(7) EUT Photo



(8) EUT Photo



(9) EUT Photo



(10) EUT Photo

(11) EUT Photo



(12) EUT Photo



(13) EUT Photo



(14) EUT Photo



(15) EUT Photo



(16) EUT Photo

(17) EUT Photo

(18) EUT Photo

(19) EUT Photo