MEASUREMENT REPORT
of
ASUS USB WLAN Adapter

Applicant	**:**	ASUSTek Computer Inc.
EUT	**:**	ASUS USB WLAN Adapter
Model No.	**:**	WL-167g V2
FCC ID	**:**	MSQWL167GV2

Tested by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440

No. 255, Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

CERTIFICATION

We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (2003) as a reference. All test were conducted by ***Training Research Co., Ltd.***, 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart B (Declaration of Conformity) and C Section 15.247.

Applicant	:	ASUSTek Computer Inc.
Applicant Address	:	4F1., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan, R.O.C.
Product Name	:	ASUS USB WLAN Adapter
Model	:	WL-167g V2
Report No.	:	A5415060264
Test Date	:	August 3, 2006

Prepared by: Jack Tsai **Approved by:** Frank Tsai

Jack Tsai *Frank Tsai*

Conditions of issue :

(1) ***This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.***

(2) ***This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.***

(3) ***This test report, measurements made by TRC are traceable to the NIST only Conducted and Radiated Method.***

NVLAP®

NVLAP LAB CODE 200174-0

Federal Communications Commission

Declaration of Conformity

for the following equipment:

Product name : ASUS USB WLAN Adapter

Trade name : ASUS

Model name : WL-167g V2

Is herewith confirmed and found to comply with the requirements of CFR 47 part15 Subpart B - Unintentional Radiators regulation. The results of electromagnetic mission evaluation are shown in the report number : A5415060264

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and
(2) This device must accept any interference received,
including interference that may cause undesired operation

Manufacturer	***USA local representative***
Company name: ASUSTeK Computer Inc.	To be determined
Computer address: 4/F, 150, Li-Te Rd., Peitou, Taipei, Taiwan	
ZIP / Postal code 112	
Contact person: Lawrence Yu	
Title: Manager	
Internet e-mail address: lawrence_yu@asus.com.tw	
Tel / Fax: 886-2-28943447 / 886-2-28950113	

Tables of Contents

I. GENERAL 6
1.1 Introduction 6
1.2 Description of EUT 6
1.3 Test method 7
1.4 Description of Support Equipment 8
1.5 Configuration of System Under Test 10
1.6 Verify the Frequency and Channel 13
1.7 Test Procedure 14
1.8 Location of the Test Site 14
1.9 General Test Condition 14

II. Section 15.101(a) : Equipment Authorization of Unintentional Radiators 15

III. Section 15.203 : Antenna Requirement 16

IV. Section 15.207 : Power Line Conducted Emissions for AC Powered Units 17
4.1 Test Condition & Setup 17
4.2 List of Test Instruments 18
4.3 Test Result of Conducted Emissions 19
Standby mode 19
IEEE 802.11b TX mode 20
IEEE 802.11g TX mode 21

V. Section 15.247(a) : Technical Description of the EUT 23

VI. Section 15.247(a)(2) : Bandwidth for Direct Sequence System 24
6.1 Test Condition & Setup 24
6.2 Test Instruments Configuration 24
6.3 List of Test Instruments 24
6.4 Test Result of Bandwidth 24
Channel 01 25
Channel 06 26
Channel 11 27

VII. Section 15.247(b) : Power Output 28
7.1 Test Condition & Setup 28
7.2 List of Test Instruments 28
7.3 Test Result 28

VIII. Section 15.247(c) : Spurious Emissions (Radiated) 29
8.1 Test Condition & Setup 29
8.2 List of Test Instruments 31
8.3 Test Result of Spurious Radiated Emissions 32
Standby mode 32
IEEE 802.11b TX mode 34
IEEE 802.11g TX mode 40
8.4 Test Result of Bandedge 46
IEEE 802.11b TX mode 47
IEEE 802.11g TX mode 49

IX. Section 15.247(d) : Power Spectral Density 51
9.1 Test Condition & Setup 51
9.2 Test Instruments Configuration 51
9.3 List of Test Instruments 51
9.4 Test Result of Power Spectral Density 52
Channel 01 53
Channel 06 54
Channel 11 55

Ⅰ. GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of applicant in support that the certification in accordance with Part 2 Subpart J and Part 15 Subpart A, B and C of the Commission's Rules and Regulations.

1.2 Description of EUT

FCC ID	:	MSQWL167GV2
Product Name	:	ASUS USB WLAN Adapter
Model Name	:	WL-167g V2
Frequency Range	:	2.412GHz ~ 2.462GHz
Channel Spacing	:	5MHz
Support Channel	:	11 Channels
Modulation Skill	:	DBPSK, DQPSK, CCK, OFDM
Power Type	:	Powered by Client's USB

1.3 Test method

1. The USB WLAN Adapter connected with notebook computer :
   (a) Insert the WLAN adapter into the USB port of notebook computer.
2. Using the PC and software provided by the manufacturer to control EUT, the test is performed under the specific conditions.
3. Set different data rate, channels (CH1/CH6/CH11) being tested and repeat the procedures above:
   (a) Radiated for Intentional test:
   making WLAN adapter at the mode of continuous transmission mode
   (b) Conducted test and Radiated for unintentional test:
   making WLAN adapter at the standby or linking mode with support equipments

1.4 Description of Support Equipment

In order to construct the minimum testing, following equipment were used as the support units.

PC: IBM Think Pad T43

Model No.:2668-IVE

Serial No. :L3TGYY

FCC ID:Doc Approved

BSMI:R33B65

DGT:ETC093LPD0126, CTL093LPD0257

Power Adaptor:IBM

Part No.:92P1018

Serial No. :11S92P1018Z1ZAPU57M9W6 REV:D

FCC ID:Doc Approved

BSMI:D33030

Power type:100 ~ 240VAC / 50 ~ 60Hz, 1.0 ~ 0.4A, Switching

Power cord (Main power to adaptor) :Non-shielded, 1.0m length, Plastic hood, No ferrite core

Power cord (DC plug to adaptor) :Shielded, 1.84m length, Plastic hood, ferrite core

Printer :HP

Model No.:C6464A, C2642A

Serial No.:TH16LEB5PK, SG69A196GV

FCC ID :None (DoC Approved), B94C2642X

BSMI :3892H381, None

Power type:Switching adaptor

Power cord:Non-shielded, 173cm length, No ferrite core
(between adaptor and AC source)
Non-shielded, 180cm length, with ferrite core
(between printer and adaptor)

Data cable :Shielded, 1.70m length, No ferrite core

USB Gamepad	**:**	**Rockfire**
Model No.	:	QF-337uv
Serial No.	:	10600545, KR91379759
FCC ID	:	None (CE approval)
檢磁	:	3862A574
Power type	:	By computer
Data Cable	:	Shielded, 1.81m length, Plastic, with ferrite core

Notebook	**:**	**TWINHEAD**
Model No.	:	N222S8
Serial No.	:	SY3261000988
FCC ID	:	N/A, DoC Approved
檢磁	:	71001018
Adaptor	**:**	**LISHIN INTERNATIONAL ENTERPRISE CORP.**
Model No.	:	LSE9802A2060
Serial No.	:	A20231065818
檢磁	:	3882B381
Power type	:	I/P: 100 ~ 240Vac, 50/ 60 Hz, 1.5A；O/P: 20Vdc, 3A 60W Max.
Power cord	:	Non-shielded, 180cm length, No ferrite core (between adaptor and AC source) Non-shielded, 150cm length, with ferrite core (between NB and adaptor)

Wireless Router	**:**	**ASUS**
Model No.	:	WL-550gE
Serial No.	:	N/A
FCC ID	:	MSQWL550GE
Power type	:	Switching, 202cm length, non-shielded, without ferrite core
Data Cable	:	Non-shielded, 1.0m length, Plastic, without ferrite core

1.5 Configuration of System Under Test

1.5.1 Conducted and Radiated for Unintentional



Connections of Equipment

Notebook PC:

* Parallel Port ……..... a printer

* VGA Port …..... a monitor

* USB#1 Port …… **EUT**

* USB#2 Port …… Gamepad

EUT :*Connected to USB interface of notebook PC.

1.5.2 Radiated of Intentional



The tests below are carried with the EUT transmitter set at high power in TDD mode. The EUT is forced to select of output power level and channel number by LAN port.

The setting up procedure was recorded in 1.3 test method.

1.6 Verify the Frequency and Channel

Channel	Frequency (GHz)
1	2.412
2	2.417
3	2.422
4	2.427
5	2.432
6	2.437
7	2.442
8	2.447
9	2.452
10	2.457
11	2.462

Note:

1. This is for confirming that all frequencies are in 2.412GHz to 2.462GHz.
2. Section 15.31(m): Measurements on intentional radiators or receivers shall be performed at three frequencies for operating frequency range over 10 MHz
   (The locations of these frequencies one near the top, one near the middle and one near the bottom.)
3. After test, the EUT operating frequencies are in 2.412GHz to 2.462GHz. So all the items as followed in testing report are need to test these three frequencies:
   Top: Channel – 1; Middle: Channel – 6; Bottom: Channel – 11.

1.7 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in ANSI C63.4 (2003) and the pre-setup was written on 1.3 test method, the detail setup was written on each test item.

1.8 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter**, **Anechoic Chamber (FCC Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a anechoic chamber also located at Training Research Co., Ltd.

No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.9 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions, which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode that controlled by computer. The ch01, ch06 and ch11 of EUT were all tested. The setting up procedure is recorded on 1.3 test method.

II. Section 15.101(a): Equipment authorization of unintentional radiators

The EUT equipped with a LAN interface and should be operated with the computer. It was categorized to *Class B personal computers and peripherals* as cannot be operated stand-alone. The authorization requires **Declaration of Conformity (DoC)** and the items required such as Section15.107 (Conducted limits) and Section15.109 (Radiated emission limits) is same as Section15.207 and 15.247(C).

III. Section 15.203: Antenna requirement

The EUT has an integrated antenna permanently attached on the PCB, which inside the housing. In addition, there is no external antenna or connector employed. The antenna requirement stated in Sect.15.203 is inapplicable to this EUT.

The antenna specification of list as below:

Antenna Type : Printed Antenna

Antenna Gain : 3.48dBi (Max.)

VI. Section 15.207: Power Line Conducted Emissions for AC Powered Units

4.1 Test Condition & Setup

The power line conducted emission measurements were performed in an anechoic chamber. The EUT was assembled on a wooden table, which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and Line Impedance Stabilization Networks (LISNs). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer (or EMI receiver) was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak and average detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.3

There is a test condition apply in this test item, the test procedure description as <1.3>. Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11).

4.2 List of Test Instruments

Calibration Date

Instrument Name	Model	Brand	Serial No.	Next time
EMI Receiver	8546A	HP	3520A00242	09/01/06
RF Filter Section	85460A	HP	3448A00217	09/01/06
LISN (EUT)	LISN-01	TRC	99-05	12/10/06
LISN (Support E.)	LISN-01	TRC	9912-03, 04	11/26/06
Pre-amplifier	15542 ZFL-500	Mini – Circuits	0 0117	05/20/07
6dB Attenuator	MCL BW-S6W2	Mini – Circuits	9915 – Conducted	05/20/07
10dB Attenuator	A5542 VAT010	Mini – Circuits	0215 – Conducted	05/20/07
Coaxial Cable (2.0 meter)	A30A30-0058-50FS-2M	Jyebao	SMA-08	05/20/07
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	Jyebao	SMA-09	05/20/07
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-01	05/20/07
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-02	05/20/07
Auto Switch Box (< 30MHz)	ASB-01	TRC	9904-01	05/20/07

4.3 Test Result of Power Line Conducted Emissions

The following table shows a summary of the highest emissions of power line conducted emissions on the LIVE and NETURAL conductors of the EUT power cord. Show as follows.

Test Conditions: Temperature : 25 °C Humidity : 73 % RH

Test mode: Standby mode

Power Connected Emissions					***Class B***		
Conductor	***Frequency (KHz)***	***Peak (dBμV)***	***QP (dBμV)***	***Average (dBμV)***	***QP-limit (dBμV)***	***AVG-limit (dBμV)***	***Margin (Db)***
Line 1	182.000	49.79	---	---	65.09	55.09	-5.30
	222.000	48.08	---	---	63.94	53.94	-5.86
	277.000	47.55	---	---	62.37	52.37	-4.82
	447.000	43.87	---	---	57.51	47.51	-3.64
	681.000	41.57	---	---	56.00	46.00	-4.43
	945.000	40.70	---	---	56.00	46.00	-5.30
Line 2	175.000	49.05	---	---	65.29	55.29	-6.24
	226.000	46.26	---	---	63.83	53.83	-7.57
	277.000	47.43	---	---	62.37	52.37	-4.94
	384.000	42.51	---	---	59.31	49.31	-6.80
	1398.000	41.01	---	---	56.00	46.00	-4.99
	3542.000	39.82	---	---	56.00	46.00	-6.18

NOTE:

(1)Margin = Peak Amplitude – Limit, *The reading amplitudes are all under limit.*

(2)A "+" sign in the margin column means the emission is OVER the Class B Limit and "–" sign of means UNDER the Class B limit

Test mode: IEEE 802.11b Channel 1

Power Connected Emissions					Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	208.000	50.07	---	---	64.34	54.34	-4.27
	282.000	44.26	---	---	62.23	52.23	-7.97
	657.000	41.17	---	---	56.00	46.00	-4.83
	795.000	41.04	---	---	56.00	46.00	-4.96
	1243.000	38.29	---	---	56.00	46.00	-7.71
	4131.000	39.78	---	---	56.00	46.00	-6.22
Line 2	245.000	45.15	---	---	63.29	53.29	-8.14
	547.000	42.16	---	---	56.00	46.00	-3.84
	688.000	42.04	---	---	56.00	46.00	-3.96
	963.000	41.78	---	---	56.00	46.00	-4.22
	1187.000	39.39	---	---	56.00	46.00	-6.61
	4131.000	38.97	---	---	56.00	46.00	-7.03

Test mode: IEEE 802.11b Channel 6

Power Connected Emissions					Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	222.000	49.59	---	---	63.94	53.94	-4.35
	363.000	43.85	---	---	59.91	49.91	-6.06
	592.000	42.60	---	---	56.00	46.00	-3.40
	745.000	42.55	---	---	56.00	46.00	-3.45
	884.000	42.07	---	---	56.00	46.00	-3.93
	1187.000	40.18	---	---	56.00	46.00	-5.82
Line 2	220.000	49.26	---	---	64.00	54.00	-4.74
	405.000	41.62	---	---	58.71	48.71	-7.09
	688.000	42.04	---	---	56.00	46.00	-3.96
	884.000	41.99	---	---	56.00	46.00	-4.01
	1049.000	40.72	---	---	56.00	46.00	-5.28
	4210.000	39.53	---	---	56.00	46.00	-6.47

Test mode: IEEE 802.11b Channel 11

Power Connected Emissions					Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	197.000	50.18	---	---	64.66	54.66	-4.48
	238.000	49.07	---	---	63.49	53.49	-4.42
	394.000	44.26	---	---	59.03	49.03	-4.77
	569.000	42.30	---	---	56.00	46.00	-3.70
	858.000	42.70	---	---	56.00	46.00	-3.30
	1102.000	42.04	---	---	56.00	46.00	-3.96
Line 2	197.000	50.20	---	---	64.66	54.66	-4.46
	243.000	47.77	---	---	63.34	53.34	-5.57
	359.000	44.73	---	---	60.03	50.03	-5.30
	490.000	42.95	---	---	56.29	46.29	-3.34
	809.000	42.60	---	---	56.00	46.00	-3.40
	1006.000	42.04	---	---	56.00	46.00	-3.96

Test mode: IEEE 802.11g Channel 1

Power Connected Emissions					Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	187.000	49.19	---	---	64.94	54.94	-5.75
	317.000	47.69	---	---	61.23	51.23	-3.54
	443.000	43.73	---	---	57.63	47.63	-3.90
	1123.000	41.76	---	---	56.00	46.00	-4.24
	1398.000	40.23	---	---	56.00	46.00	-5.77
	3975.000	40.10	---	---	56.00	46.00	-5.90
Line 2	180.000	49.45	---	---	65.14	55.14	-5.69
	216.000	49.17	---	---	64.11	54.11	-4.94
	277.000	47.43	---	---	62.37	52.37	-4.94
	417.000	43.45	---	---	58.37	48.37	-4.92
	774.000	39.73	---	---	56.00	46.00	-6.27
	1320.000	41.38	---	---	56.00	46.00	-4.62

Test mode: IEEE 802.11g Channel 6

Power Connected Emissions					Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	189.000	49.52	---	---	64.89	54.89	-5.37
	240.000	48.55	---	---	63.43	53.43	-4.88
	409.000	44.46	---	---	58.60	48.60	-4.14
	587.000	39.68	---	---	56.00	46.00	-6.32
	867.000	39.99	---	---	56.00	46.00	-6.01
	1346.000	41.31	---	---	56.00	46.00	-4.69
Line 2	171.000	51.03	---	---	65.40	55.40	-4.37
	300.000	48.12	---	---	61.71	51.71	-3.59
	430.000	42.46	---	---	58.00	48.00	-5.54
	581.000	41.34	---	---	56.00	46.00	-4.66
	980.000	40.35	---	---	56.00	46.00	-5.65
	1219.000	41.60	---	---	56.00	46.00	-4.40

Test mode: IEEE 802.11g Channel 11

Power Connected Emissions					FCC Class B		
Conductor	**Frequency (KHz)**	**Peak (dBμV)**	**QP (dBμV)**	**Average (dBμV)**	**QP-limit (dBμV)**	**AVG-limit (dBμV)**	**Margin (dB)**
Line 1	226.000	49.81	---	---	63.83	53.83	-4.02
	380.000	44.49	---	---	59.43	49.43	-4.94
	434.000	44.66	---	---	57.89	47.89	-3.23
	668.000	42.04	---	---	56.00	46.00	-3.96
	774.000	42.27	---	---	56.00	46.00	-3.73
	1049.000	42.04	---	---	56.00	46.00	-3.96
Line 2	177.000	50.84	---	---	65.23	55.23	-4.39
	264.000	48.73	---	---	62.74	52.74	-4.01
	616.000	42.81	---	---	56.00	46.00	-3.19
	788.000	42.44	---	---	56.00	46.00	-3.56
	937.000	42.84	---	---	56.00	46.00	-3.16
	1059.000	42.14	---	---	56.00	46.00	-3.86

V. Section 15.247 (a): Technical description of the EUT

Direct Sequence System is a spread spectrum system in which the carrier has been modulated by a high speed spreading code and an information data stream. The high speed code sequence dominates the "modulating function" and is the direct cause of the wide spreading of the transmitted signal. In the operational description demonstrates the operation principles of the Baseband processor employed by the EUT, shows that which is a complete DSSS baseband processor and meets the definition of the direct sequence spread spectrum system.

VI. Section 15.247(a)(2): Bandwidth for Direct Sequence System.

6.1 Test Condition & Setup

The transmitter bandwidth measurements were performed by the contact manner. The EUT was set to transmit continuously, also various channels were investigated to find the maximum occupied bandwidth. The output of the EUT was connected to the spectrum analyzer. The bandwidth of the fundamental frequency is observed by the spectrum analyzer with 100kHz RBW and 100kHz VBW.

6.2 Test Instruments Configuration



PC to control the EUT at maximal power output and channel number and set antenna kit

6.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	11/15/06

6.4 Test Result of Bandwidth

Channel	802.11b	802.11g
01	12.32 MHz	16.80 MHz
06	12.28 MHz	16.80 MHz
11	12.28 MHz	16.80 MHz

Note: 1. The data in the above table are summarizing the following attachment spectrum analyzer hard copy. According to the guidance, we'd made the measurement with the spectrum analyzer's resolution bandwidth *(RBW)=100kHz* and set the *span>>RBW*. The results show the measured 6dB bandwidth comply with the minimum 500kHz requirement.

2. The attachments show these on the following pages.

6dB Bandwidth of Channel 1 (The minimum 6dB BW at least 500kHz)

IEEE 802.11b

IEEE 802.11g



6dB Bandwidth of Channel 6 (The minimum 6dB BW at least 500kHz)

IEEE 802.11b



IEEE 802.11g

6dB Bandwidth of Channel 11 (The minimum 6dB BW at least 500kHz)

IEEE 802.11b



IEEE 802.11g



VII. Section 15.247(b): Power Output

7.1 Test Condition & Setup



1. The output of the transmitter is connected to the BOONTON RF Power Meter.
2. The calibration is performed before every test. The values of the output power of the EUT will shown in the dBm directly are the transmitter output peak power. Recording as follows.

7.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Next time
RF Power Meter	4532	BOONTON	117501	05/18/07
Peak Power Sensor	57340	BOONTON	2696	05/18/07

7.3 Test Result

Formula:
RF Output of EUT + |Cable Loss| = Output Peak Power

Channel	RF Output	Cable Loss	Output Peak Power	
	dBm	dBm	dBm	mW
802.11b CH01	11.64	0.70	12.34	17.140
802.11b CH06	11.97	0.70	12.67	18.493
802.11b CH11	11.90	0.70	12.60	18.197
802.11g CH01	12.28	0.70	12.98	19.860
802.11g CH06	11.69	0.70	12.39	17.338
802.11g CH11	11.62	0.70	12.32	17.061

VIII. Section 15.247 (C): Spurious Emissions (Radiated)

8.1 Test Condition & Setup

We'd performed the test by the *radiated emission* skill: The EUT was placed in an anechoic chamber, and set the EUT transmitting continuously and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30MHz to 1000MHz using an Hewlett Packard 85460A EMI Receiver, SCHWARZECK whole range Small Biconical Antenna (Model No.: UBAA9114 & BBVU9135) is used to measure frequency from 30 MHz to 1GHz. The final test is used the HP 85460A spectrum and 8564E spectrum was examined from 1GHz to 25GHz using an Hewlett Packard Spectrum Analyzer, EMCO/HP Horn Antenna (Model 3115 / 84125-80008) for 1G - 25GHz.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 25GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 25GHz) and the analyzer was operated in the maximum hold mode. There is a test condition applies in this test item, the test procedure description as the following:

Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11). The setting up procedure is recorded on <1.3>

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dBμV/m) is determined by algebraically adding the measured reading in dBμV, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, no *duty cycle* is present.

For frequency between 30MHz to 1000MHz

FIa (dBuV/m) = FIr (dBμV) + Correction Factors

FIa : Actual Field Intensity

FIr : Reading of the Field Intensity

Correction Factors = Antenna Factor + (Cable Loss – Amplifier Gain) + Switching Box Loss

For frequency between 1GHz to 25GHz

FIa (dBμV/m) = FIr (dBμV) + Correction Factor

FIa : Actual Field Intensity

FIr : Reading of the Field Intensity

Correction Factors = Antenna Factor + (Cable Loss – Amplifier Gain) + Switching Box Loss

8.2 List of Test Instruments

Instrument Name	Model	Brand	Serial No.	Calibration Date Next time
EMI Receiver	8546A	HP	3520A00242	09/01/06
RF Filter Section	85460A	HP	3448A00217	09/01/06
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	08/17/06
Pre-amplifier	PA1F	TRC	1FAC	05/20/07
Auto Switch Box (>30MHz)	ASB-01	TRC	9904-01	05/20/07
Coaxial Cable (Double shielded, 15 meter)	A30A30-0058-50FS-15M	JYEBAO	SMA-01	05/20/07
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	JYEBAO	SMA-02	05/20/07
Spectrum Analyzer	8564E	HP	3720A00840	11/07/06
Microwave Preamplifier	84125C	HP	US36433002	11/07/06
Horn Antenna	3115	EMCO	9104-3668	01/23/07
Standard Guide Horn Antenna	84125-80008	HP	18-26.5GHz	11/09/06
Standard Guide Horn Antenna	84125-80001	HP	26.5-40GHz	11/09/06
Horn Antenna	1196E (3115)	HP (EMCO)	9704-5178	01/26/07
Pre-amplifier	PA2F	TRC	2F1GZ	06/20/07
Coaxial Cable (3 miter)	A30A30-0058-50FST118	JYEBAO	MSA-05	06/20/07
Coaxial Cable (1 meter)	A30A30-0058-50FST118	JYEBAO	MSA-04	06/20/07

8.3 Test Result of Spurious Radiated Emissions

The highest peak values of radiated emissions form the EUT at various antenna heights, antenna polarizations, EUT orientation, etc. are recorded on the following.

Test Conditions: Temperature : 25 ° C Humidity : 73 % RH

Test mode: Standby mode for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	35.99	1.00	84	-3.56	32.43	43.50	-11.07
304.02	37.32	1.00	24	-3.29	34.03	46.00	-11.97
370.71	36.63	1.00	101	-2.08	34.55	46.00	-11.45
461.65	33.62	1.00	249	1.18	34.80	46.00	-11.20
502.87	32.95	1.00	27	2.41	35.36	46.00	-10.64
568.35	26.86	1.00	360	5.20	32.06	46.00	-13.94

Test mode: Standby mode for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
133.06	27.06	1.00	138	-2.73	24.33	43.50	-19.17
198.54	31.92	1.00	330	-3.49	28.43	43.50	-15.07
287.05	31.54	1.00	57	-3.85	27.69	46.00	-18.31
461.65	32.62	1.00	61	1.18	33.80	46.00	-12.20
502.87	34.68	1.00	158	2.41	37.09	46.00	-8.91
670.20	28.42	1.00	233	8.57	36.99	46.00	-9.01

Note:

1. Margin = Amplitude – limit, *if margin is minus means under limit.*
2. Corrected Amplitude = Reading Amplitude + Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain) + Switching Box Loss

Test mode: Standby mode for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
1920.83	1.00	345	33.07	---	3.29	36.36	---	73.96	53.96	-17.60
3295.00	1.00	200	32.74	---	9.84	42.58	---	73.96	53.96	-11.38
7183.75	1.00	26	24.07	---	21.29	45.36	---	73.96	53.96	-8.60
10435.00	1.00	148	23.07	---	22.54	45.61	---	73.96	53.96	-8.35
19746.04	1.00	354	47.75	---	1.89	49.64	---	73.96	53.96	-4.32
24495.42	1.00	193	49.07	---	2.35	51.42	---	73.96	53.96	-2.54

Test mode: Standby mode for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2182.92	1.00	327	32.41	---	5.23	37.64	---	73.96	53.96	-16.32
3989.17	1.00	80	29.57	---	12.45	42.02	---	73.96	53.96	-11.94
6879.17	1.00	294	24.74	---	20.12	44.86	---	73.96	53.96	-9.10
10916.67	1.00	245	22.08	---	22.22	44.30	---	73.96	53.96	-9.66
22108.33	1.00	216	47.12	---	3.05	50.17	---	73.96	53.96	-3.79
24364.37	1.00	47	46.99	---	3.23	50.22	---	73.96	53.96	-3.74

Note:

1. Margin = Corrected - Limit.
2. The EUT utilizes a *permanently attached antenna*. In addition the spurious RF radiated emissions levels do comply with the *20dBc limit* both at its bandedges and other spurious emissions.
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

Test mode: IEEE 802.11b CH01 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	35.00	1.00	73	-3.56	31.44	43.50	-12.06
369.50	36.15	1.00	67	-2.11	34.04	46.00	-11.96
436.19	35.84	1.00	107	0.28	36.12	46.00	-9.88
461.65	34.65	1.00	277	1.18	35.83	46.00	-10.17
504.09	34.15	1.00	50	2.47	36.62	46.00	-9.38
961.20	24.66	1.00	120	16.11	40.77	54.00	-13.23

Test mode: IEEE 802.11b CH01 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
168.22	33.37	1.00	23	-3.76	29.61	43.50	-13.89
371.71	29.97	1.00	157	-2.08	27.89	46.00	-18.11
438.61	34.34	1.00	167	0.38	34.72	46.00	-11.28
501.66	35.28	1.00	150	2.36	37.64	46.00	-8.36
567.14	27.00	1.00	102	5.16	32.16	46.00	-13.84
670.20	28.14	1.00	234	8.57	36.71	46.00	-9.29

Test mode: IEEE 802.11b CH01 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2345.83	1.00	240	40.00	---	9.06	49.06	---	73.96	53.96	-4.90
2829.17	1.00	254	35.83	---	10.11	45.94	---	73.96	53.96	-8.02
3216.67	1.00	170	38.50	---	11.47	49.97	---	73.96	53.96	-3.99
9650.42	1.00	211	35.94	---	11.47	47.41	---	73.96	53.96	-6.55
12061.04	1.00	127	36.94	---	9.81	46.75	---	73.96	53.96	-7.21
21708.12	1.00	25	47.04	---	2.87	49.91	---	73.96	53.96	-4.05

Test mode: IEEE 802.11b CH01 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2152.08	1.00	25	37.00	---	8.52	45.52	---	73.96	53.96	-8.44
2356.25	1.00	19	37.83	---	9.09	46.92	---	73.96	53.96	-7.04
3216.67	1.00	25	36.17	---	11.47	47.64	---	73.96	53.96	-6.32
9650.42	1.00	26	35.27	---	11.47	46.74	---	73.96	53.96	-7.22
12061.04	1.00	276	37.60	---	9.81	47.41	---	73.96	53.96	-6.55
21708.12	1.00	34	47.49	---	2.87	50.36	---	73.96	53.96	-3.60

Test mode: IEEE 802.11b CH06 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
215.51	36.25	1.00	343	-3.98	32.27	43.50	-11.23
356.16	36.18	1.00	287	-2.52	33.66	46.00	-12.34
436.19	34.56	1.00	107	0.28	34.84	46.00	-11.16
459.22	34.42	1.00	287	1.11	35.53	46.00	-10.47
501.66	32.40	1.00	10	2.36	34.76	46.00	-11.24
961.20	24.62	1.00	168	16.11	40.73	54.00	-13.27

Test mode: IEEE 802.11b CH06 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
197.32	31.27	1.00	323	-3.52	27.75	43.50	-15.75
369.50	30.61	1.00	157	-2.11	28.50	46.00	-17.50
436.19	35.33	1.00	157	0.28	35.61	46.00	-10.39
502.87	35.43	1.00	180	2.41	37.84	46.00	-8.16
670.20	27.57	1.00	247	8.57	36.14	46.00	-9.86
765.99	23.74	1.00	82	10.76	34.50	46.00	-11.50

Test mode: IEEE 802.11b CH06 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2325.00	1.00	159	39.00	---	9.00	48.00	---	73.96	53.96	-5.96
2539.58	1.00	159	38.00	---	9.56	47.56	---	73.96	53.96	-6.40
3247.92	1.00	133	37.17	---	11.62	48.79	---	73.96	53.96	-5.17
9747.08	1.00	144	35.77	---	11.89	47.66	---	73.96	53.96	-6.30
12187.92	1.00	276	39.27	---	9.74	49.01	---	73.96	53.96	-4.95
24371.46	1.00	101	46.95	---	3.26	50.21	---	73.96	53.96	-3.75

Test mode: IEEE 802.11b CH06 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2152.08	1.00	101	37.00	---	8.52	45.52	---	73.96	53.96	-8.44
2341.67	1.00	342	37.66	---	9.05	46.71	---	73.96	53.96	-7.25
3247.92	1.00	342	36.00	---	11.62	47.62	---	73.96	53.96	-6.34
9747.08	1.00	9	35.94	---	11.89	47.83	---	73.96	53.96	-6.13
12187.92	1.00	0	38.94	---	9.74	48.68	---	73.96	53.96	-5.28
24371.46	1.00	100	46.60	---	3.26	49.86	---	73.96	53.96	-4.10

Test mode: IEEE 802.11b CH11 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
369.50	35.84	1.00	83	-2.11	33.73	46.00	-12.27
434.97	34.72	1.00	93	0.23	34.95	46.00	-11.05
461.65	34.18	1.00	243	1.18	35.36	46.00	-10.64
504.09	32.46	1.00	10	2.47	34.93	46.00	-11.07
567.14	29.01	1.00	24	5.16	34.17	46.00	-11.83
961.20	24.85	1.00	168	16.11	40.96	54.00	-13.04

Test mode: IEEE 802.11b CH11 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	30.90	1.00	273	-3.56	27.34	43.50	-16.16
288.26	31.43	1.00	17	-3.82	27.61	46.00	-18.39
370.71	31.28	1.00	147	-2.08	29.20	46.00	-16.80
436.19	33.79	1.00	167	0.28	34.07	46.00	-11.93
501.66	35.07	1.00	120	2.36	37.43	46.00	-8.57
670.20	27.22	1.00	232	8.57	35.79	46.00	-10.21

Test mode: IEEE 802.11b CH11 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
1535.41	1.00	349	35.66	---	15.34	51.00	---	73.96	53.96	-2.96
2354.17	1.00	190	41.50	---	9.08	50.58	---	73.96	53.96	-3.38
3283.33	1.00	101	39.17	---	11.79	50.96	---	73.96	53.96	-3.00
9849.79	1.00	13	35.78	---	11.93	47.71	---	73.96	53.96	-6.25
12308.75	1.00	148	36.77	---	9.56	46.33	---	73.96	53.96	-7.63
19696.46	1.00	336	48.41	---	1.81	50.22	---	73.96	53.96	-3.74

Test mode: IEEE 802.11b CH11 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2153.08	1.00	51	38.00	---	8.52	46.52	---	73.96	53.96	-7.44
2395.83	1.00	271	38.66	---	9.20	47.86	---	73.96	53.96	-6.10
3283.33	1.00	298	37.00	---	11.79	48.79	---	73.96	53.96	-5.17
9849.79	1.00	109	34.94	---	11.93	46.87	---	73.96	53.96	-7.09
12308.75	1.00	264	37.44	---	9.56	47.00	---	73.96	53.96	-6.96
19696.46	1.00	319	48.28	---	1.81	50.09	---	73.96	53.96	-3.87

Test mode: IEEE 802.11g CH01 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	34.53	1.00	241	-3.56	30.97	43.50	-12.53
370.71	35.57	1.00	66	-2.08	33.49	46.00	-12.51
434.97	34.44	1.00	116	0.23	34.67	46.00	-11.33
459.22	34.67	1.00	244	1.11	35.78	46.00	-10.22
502.87	33.49	1.00	40	2.41	35.90	46.00	-10.10
961.20	25.05	1.00	125	16.11	41.16	54.00	-12.84

Test mode: IEEE 802.11g CH01 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
168.22	35.29	1.00	336	-3.76	31.53	43.50	-11.97
288.26	31.22	1.00	77	-3.82	27.40	46.00	-18.60
369.50	29.57	1.00	158	-2.11	27.46	46.00	-18.54
436.19	33.27	1.00	249	0.28	33.55	46.00	-12.45
502.87	35.84	1.00	161	2.41	38.25	46.00	-7.75
670.20	28.35	1.00	247	8.57	36.92	46.00	-9.08

Test mode: IEEE 802.11g CH01 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2356.25	1.00	151	40.33	---	9.09	49.42	---	73.96	53.96	-4.54
2485.42	1.00	162	39.17	---	9.45	48.62	---	73.96	53.96	-5.34
3216.67	1.00	121	39.17	---	11.47	50.64	---	73.96	53.96	-3.32
9650.42	1.00	249	35.44	---	11.47	46.91	---	73.96	53.96	-7.05
12061.04	1.00	291	37.94	---	9.81	47.75	---	73.96	53.96	-6.21
21708.12	1.00	31	47.08	---	2.87	49.95	---	73.96	53.96	-4.01

Test mode: IEEE 802.11g CH01 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2152.08	1.00	334	37.50	---	8.52	46.02	---	73.96	53.96	-7.94
2327.08	1.00	75	36.50	---	9.01	45.51	---	73.96	53.96	-8.45
3216.67	1.00	13	36.67	---	11.47	48.14	---	73.96	53.96	-5.82
9650.42	1.00	130	35.27	---	11.47	46.74	---	73.96	53.96	-7.22
12061.04	1.00	229	36.94	---	9.81	46.75	---	73.96	53.96	-7.21
21708.12	1.00	38	47.53	---	2.87	50.40	---	73.96	53.96	-3.56

Test mode: IEEE 802.11g CH06 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	34.46	1.00	73	-3.56	30.90	43.50	-12.60
370.71	35.96	1.00	87	-2.08	33.88	46.00	-12.12
436.19	34.96	1.00	87	0.28	35.24	46.00	-10.76
461.65	34.98	1.00	287	1.18	36.16	46.00	-9.84
502.87	32.74	1.00	50	2.41	35.15	46.00	-10.85
700.51	24.89	1.00	48	9.31	34.20	46.00	-11.80

Test mode: IEEE 802.11g CH06 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
168.22	32.11	1.00	201	-3.76	28.35	43.50	-15.15
198.54	31.18	1.00	310	-3.49	27.69	43.50	-15.81
434.97	35.73	1.00	175	0.23	35.96	46.00	-10.04
502.87	36.12	1.00	168	2.41	38.53	46.00	-7.47
565.92	27.22	1.00	104	5.12	32.34	46.00	-13.66
670.20	26.50	1.00	239	8.57	35.07	46.00	-10.93

Test mode: IEEE 802.11g CH06 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2372.92	1.00	207	42.17	---	9.13	51.30	---	73.96	53.96	-2.66
2529.17	1.00	231	38.50	---	9.54	48.04	---	73.96	53.96	-5.92
3250.00	1.00	111	37.35	---	11.61	48.96	---	73.96	53.96	-5.00
9747.08	1.00	42	35.94	---	11.89	47.83	---	73.96	53.96	-6.13
12187.92	1.00	78	39.44	---	9.74	49.18	---	73.96	53.96	-4.78
24371.46	1.00	111	46.62	---	3.26	49.88	---	73.96	53.96	-4.08

Test mode: IEEE 802.11g CH06 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2152.08	1.00	34	38.83	---	8.52	47.35	---	73.96	53.96	-6.61
2377.08	1.00	241	38.50	---	9.15	47.65	---	73.96	53.96	-6.31
3250.00	1.00	250	35.67	---	11.63	47.30	---	73.96	53.96	-6.66
9747.08	1.00	132	35.77	---	11.89	47.66	---	73.96	53.96	-6.30
12187.92	1.00	193	39.27	---	9.74	49.01	---	73.96	53.96	-4.95
24371.46	1.00	126	46.73	---	3.26	49.99	---	73.96	53.96	-3.97

Test mode: IEEE 802.11g CH11 for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
202.17	34.65	1.00	263	-3.56	31.09	43.50	-12.41
314.94	36.02	1.00	47	-3.15	32.87	46.00	-13.13
370.71	37.03	1.00	107	-2.08	34.95	46.00	-11.05
433.76	34.30	1.00	87	0.18	34.48	46.00	-11.52
461.65	34.56	1.00	247	1.18	35.74	46.00	-10.26
501.66	33.43	1.00	10	2.36	35.79	46.00	-10.21

Test mode: IEEE 802.11g CH11 for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table ( )	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
170.65	32.91	1.00	183	-3.82	29.09	43.50	-14.41
203.39	31.00	1.00	273	-3.62	27.38	43.50	-16.12
436.19	33.09	1.00	167	0.28	33.37	46.00	-12.63
502.87	35.04	1.00	140	2.41	37.45	46.00	-8.55
567.14	26.66	1.00	106	5.16	31.82	46.00	-14.18
670.20	27.92	1.00	261	8.57	36.49	46.00	-9.51

Test mode: IEEE 802.11g CH11 for 1GHz to 26.5GHz [Horizontal]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2392.02	1.00	163	43.35	30.50	9.19	52.54	39.69	73.96	53.96	-14.27
2508.33	1.00	233	38.83	---	9.51	48.34	---	73.96	53.96	-5.62
3283.33	1.00	117	38.67	---	11.79	50.46	---	73.96	53.96	-3.50
9849.79	1.00	292	35.78	---	11.93	47.71	---	73.96	53.96	-6.25
12308.75	1.00	221	38.11	---	9.56	47.67	---	73.96	53.96	-6.29
19696.46	1.00	338	48.51	---	1.81	50.32	---	73.96	53.96	-3.64

Test mode: IEEE 802.11g CH11 for 1GHz to 26.5GHz [Vertical]

Frequency	*Ant. H.*	*Table*	*Amplitude Peak / Ave.*		*Correction Factor*	*Corrected Amplitude Peak / Ave.*		*Limit Peak / Ave.*		*Margin*
MHz	*m*	*degree*	*dBμV*		*dB/m*	*dBμV/m*		*dBμV/m*		*dB*
2152.08	1.00	149	37.83	---	8.52	46.35	---	73.96	53.96	-7.61
2397.92	1.00	301	38.67	---	9.20	47.87	---	73.96	53.96	-6.09
3283.33	1.00	320	36.67	---	11.79	48.46	---	73.96	53.96	-5.50
9849.79	1.00	229	34.78	---	11.93	46.71	---	73.96	53.96	-7.25
12187.75	1.00	199	37.11	---	9.56	46.67	---	73.96	53.96	-7.29
19696.46	1.00	319	48.14	---	1.81	49.95	---	73.96	53.96	-4.01

8.4 Test Result of the Bandedge

If any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either *at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified id §15.209(a)*,

We perform this section by the *radiated manner*, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 20dB below the highest emission level measured.* If the emissions fall in the restricted bands stated in the Part15.205(a) must also *comply with the radiated emission limits specified in Part15.209(a). (Peak mode: RBW=VBW=1MHz, Average mode: RBW=1MHz; VBW=10Hz)*

The following pages show our observations referring to the channel 1 and 11 respectively.
Test Condition & Setup: same as < 8.1 >

Channel 1 of IEEE 802.11b



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 1.

1. The lobe left by the fundamental side is already 20dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

Radiated Emission					*Corrected Amplitude (dBμV/m)*		*Class B (3m)*		
Frequency (MHz)	*Ant. P.*	*Ant. H. (m)*	*Table ( )*	*Factors (dB)*	*Peak*	*Average*	*Limit (dBμV/m)* *Peak*	*Ave.*	*Margin (dB)*
2361.20	Hor	1.00	243	9.10	51.27	---	73.96	53.96	-2.69
2390.02	Hor	1.00	171	9.18	51.68	---	73.96	53.96	-2.28
2370.57	Ver	1.00	94	9.13	49.46	---	73.96	53.96	-4.50
2390.02	Ver	1.00	90	9.18	47.18	---	73.96	53.96	-6.78

Channel 11 of IEEE 802.11b



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 11.

3. The lobe right by the fundamental side is already 20dB below the highest emission level.
4. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below

Radiated Emission					*Corrected Amplitude (dBμV/m)*		*Class B (3m)*		
Frequency (MHz)	*Ant. P.*	*Ant. H. (m)*	*Table (°)*	*Factors (dB)*	*Peak*	*Average*	*Limit (dBμV/m) Peak*	*Limit (dBμV/m) Ave.*	*Margin (dB)*
2483.50	Hor	1.00	187	9.44	50.28	---	73.96	53.96	-3.68
2490.73	Hor	1.00	190	9.46	50.63	---	73.96	53.96	-3.33
2500.01	Hor	1.00	190	9.49	49.16	---	73.96	53.96	-4.80
2516.28	Hor	1.00	147	9.52	50.19	---	73.96	53.96	-3.77
2483.50	Ver	1.00	106	9.44	46.28	---	73.96	53.96	-7.68
2488.28	Ver	1.00	114	9.46	47.46	---	73.96	53.96	-6.50
2500.01	Ver	1.00	358	9.49	46.49	---	73.96	53.96	-7.47
2514.07	Ver	1.00	352	9.52	47.18	---	73.96	53.96	-6.78

Channel 1 of IEEE 802.11g



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 1.

5. The lobe left by the fundamental side is already 20dB below the highest emission level.
6. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

Radiated Emission					*Corrected Amplitude (dBμV/m)*		*Class B (3m)*		
Frequency (MHz)	*Ant. P.*	*Ant. H. (m)*	*Table ( )*	*Factors (dB)*	*Peak*	*Average*	*Limit (dBμV/m)* *Peak*	*Ave.*	*Margin (dB)*
2363.69	Hor	1.00	138	9.11	51.11	---	73.96	53.96	-2.85
2390.02	Hor	1.00	204	9.18	50.52	---	73.96	53.96	-3.44
2359.57	Ver	1.00	61	9.10	48.93	---	73.96	53.96	-5.03
2390.02	Ver	1.00	80	9.18	46.68	---	73.96	53.96	-7.28

Channel 11 of IEEE 802.11g



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 11.

7. The lobe right by the fundamental side is already 20dB below the highest emission level.
8. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below

Radiated Emission					*Corrected Amplitude (dBμV/m)*		*Class B (3m)*		
Frequency (MHz)	*Ant. P.*	*Ant. H. (m)*	*Table (°)*	*Factors (dB)*	*Peak*	*Average*	*Limit (dBμV/m) Peak*	*Limit (dBμV/m) Ave.*	*Margin (dB)*
2483.50	Hor	1.00	243	9.44	47.78	---	73.96	53.96	-6.18
2485.66	Hor	1.00	315	9.45	49.45	---	73.96	53.96	-4.51
2500.01	Hor	1.00	245	9.49	46.66	---	73.96	53.96	-7.30
2518.50	Hor	1.00	103	9.52	48.86	---	73.96	53.96	-5.10
2483.50	Ver	1.00	92	9.44	46.28	---	73.96	53.96	-7.68
2488.17	Ver	1.00	92	9.46	47.12	---	73.96	53.96	-6.84
2500.01	Ver	1.00	92	9.49	45.49	---	73.96	53.96	-8.47
2522.93	Ver	1.00	264	9.53	46.53	---	73.96	53.96	-7.43

IX. Section 15.247(d): Power Spectral Density

9.1 Test Condition & Setup

The tests below are running with the EUT transmitter set at high power in TDD mode. The EUT is needed to force selection of output power level and channel number. While testing, the EUT was set to transmit continuously and to be tested by the contact manner with the spectrum analyzer.

9.2 Test Instruments Configuration



PC to control the EUT at maximal power output and channel number and set antenna kit

9.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	11/15/06

9.4 Test Result of Power spectral density

The following table shows a summary of the test results of the Power Spectral Density.

IEEE 802.11b

Channel	*Ppr (dBm)*	*Cable Loss (dB)*	*Ppq (dBm)*	*Limit (dB)*	*Margin (dB)*
CH 01	-17.02	1.00	-16.02	8.00	-24.02
CH 06	-16.11	1.00	-15.11	8.00	-23.11
CH 11	-16.68	1.00	-15.68	8.00	-23.68

IEEE 802.11g

Channel	*Ppr (dBm)*	*Cable Loss (dB)*	*Ppq (dBm)*	*Limit (dB)*	*Margin (dB)*
CH 01	-22.46	1.00	-21.46	8.00	-29.46
CH 06	-25.65	1.00	-24.65	8.00	-32.65
CH 11	-26.09	1.00	-25.09	8.00	-33.09

Note:

1. The following pages show the results of spectrum reading.
2. Ppr: spectrum read power density (using peak search mode),
   Ppq: actual peak power density in the spread spectrum band.
3. Ppq = Ppr + |Cable Loss|

Power Spectral Density for Channel 01

IEEE 802.11b



IEEE 802.11g



Power Spectral Density for Channel 06

IEEE 802.11b



IEEE 802.11g



Power Spectral Density for Channel 11

IEEE 802.11b

IEEE 802.11g