# FCC RF Test Report

| | | |
|---|---|---|
| APPLICANT | : | ASUSTeK COMPUTER INC. |
| EQUIPMENT | : | ASUS Phone(Mobile Phone) |
| BRAND NAME | : | ASUS |
| MODEL NAME | : | ASUS_X017DA |
| FCC ID | : | MSQX017DA |
| STANDARD | : | FCC 47 CFR Part 2, 22(H), 24(E), 27(L) |
| CLASSIFICATION | : | PCS Licensed Transmitter Held to Ear (PCE) |

**The product was received on Nov. 04, 2017 and testing was completed on Jan. 23, 2018. We, Sporton Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI/TIA-603-E and has been in compliance with the applicable technical standards.**

**The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.**

Eric Shih

**Approved by: Eric Shih / Manager**

TESTING
NVLAP LAB CODE 600156-0

***Sporton International (Shenzhen) Inc.***
***1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China***

# TABLE OF CONTENTS

**REVISION HISTORY** ..... **3**

**SUMMARY OF TEST RESULT** ..... **4**

**1 GENERAL DESCRIPTION** ..... **5**

1.1 Applicant ..... 5
1.2 Manufacturer ..... 5
1.3 Product Feature of Equipment Under Test ..... 5
1.4 Product Specification of Equipment Under Test ..... 6
1.5 Modification of EUT ..... 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator ..... 7
1.7 Testing Location ..... 8
1.8 Applicable Standards ..... 9

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST** ..... **10**

2.1 Test Mode ..... 10
2.2 Connection Diagram of Test System ..... 11
2.3 Support Unit used in test configuration ..... 11
2.4 Measurement Results Explanation Example ..... 11

**3 CONDUCTED TEST RESULT** ..... **12**

3.1 Measuring Instruments ..... 12
3.2 Test Setup ..... 12
3.3 Test Result of Conducted Test ..... 12
3.4 Conducted Output Power and ERP/EIRP ..... 13
3.5 Peak-to-Average Ratio ..... 14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement ..... 15
3.7 Conducted Band Edge ..... 16
3.8 Conducted Spurious Emission ..... 17
3.9 Frequency Stability ..... 18

**4 RADIATED TEST ITEMS** ..... **19**

4.1 Measuring Instruments ..... 19
4.2 Test Setup ..... 19
4.3 Test Result of Radiated Test ..... 19
4.4 Field Strength of Spurious Radiation Measurement ..... 20

**5 LIST OF MEASURING EQUIPMENT** ..... **21**

**6 UNCERTAINTY OF EVALUATION** ..... **22**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST**

**APPENDIX C. TEST SETUP PHOTOGRAPHS**

# REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|---|---|---|---|
| FG7N0402A | Rev. 01 | Initial issue of report | Mar. 22, 2018 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

# SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|---|---|---|---|---|---|
| 3.4 | §2.1046 | Conducted Output Power | Reporting Only | PASS | - |
| | §22.913(a)(2) | Effective Radiated Power | < 7 Watts | PASS | - |
| | §24.232(c) | Equivalent Isotropic Radiated Power | < 2 Watts | PASS | - |
| | §27.50(d)(4) | Equivalent Isotropic Radiated Power | < 1 Watts | PASS | - |
| 3.5 | §24.232(d) | Peak-to-Average Ratio | < 13 dB | PASS | - |
| 3.6 | §2.1049<br>§22.917(b)<br>§24.238(b)<br>§27.53(g) | Occupied Bandwidth | Reporting Only | PASS | - |
| 3.7 | §2.1051<br>§22.917(a)<br>§24.238(a)<br>§27.53(h) | Band Edge Measurement | < 43+10log10(P[Watts]) | PASS | - |
| 3.8 | §2.1051<br>§22.917(a)<br>§24.238(a)<br>§27.53(h) | Conducted Emission | < 43+10log10(P[Watts]) | PASS | - |
| 3.9 | §2.1055<br>§22.355 | Frequency Stability for Temperature & Voltage | < 2.5 ppm for Part 22H | PASS | - |
| | §2.1055<br>§24.235<br>§27.54 | | Within Authorized Band | | |
| 4.4 | §2.1053<br>§22.917(a)<br>§24.238(a)<br>§27.53(h) | Field Strength of Spurious Radiation | < 43+10log10(P[Watts]) | PASS | Under limit 16.65 dB at 1672.800 MHz |

# 1 General Description

## 1.1 Applicant

**ASUSTeK COMPUTER INC.**
4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN

## 1.2 Manufacturer

**Wingtech Mobile Communications Co, Ltd.**
Floor 1st-3rd, Yinfeng Building, No.5097 Luosha Road, Luohu District, Shenzhen

## 1.3 Product Feature of Equipment Under Test

| Product Feature | |
|---|---|
| **Equipment** | ASUS Phone(Mobile Phone) |
| **Brand Name** | ASUS |
| **Model Name** | ASUS_X017DA |
| **FCC ID** | MSQX017DA |
| **EUT supports Radios application** | GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/<br>HSPA+ (16QAM uplink is not supported)/LTE/NFC<br>WLAN 2.4GHz 802.11b/g/n HT20/HT40<br>WLAN 5GHz 802.11a/n HT20/HT40<br>WLAN 5GHz 802.11ac VHT20/VHT40/VHT80<br>Bluetooth v3.0 + EDR / Bluetooth v4.0 LE/<br>Bluetooth v4.1 LE / Bluetooth v4.2 LE |
| **IMEI Code** | Conducted: 353746090026288/353746090026296<br>Radiation: 353746090026742/353746090026759 |
| **HW Version** | 89199_1_XX |
| **SW Version** | NMF26X.WW_Phone-14.0400.1702.001-20171109 |
| **EUT Stage** | Production Unit |

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two samples, the two samples have different suppliers for eMCP/LCD/camera/Battery, except for the supplier of these components, all the other features are the same, the differences will not affect RF features, so we assessed sample 1 to perform full test.

## 1.4 Product Specification of Equipment Under Test

| Standards-related Product Specification | |
|---|---|
| **Tx Frequency** | **GSM/GPRS/EDGE:**<br>850: 824.2 MHz ~ 848.8 MHz<br>1900: 1850.2 MHz ~ 1909.8MHz<br>**WCDMA:**<br>Band V: 826.4 MHz ~ 846.6 MHz<br>Band II: 1852.4 MHz ~ 1907.6 MHz<br>Band IV: 1712.4 MHz ~ 1752.6 MHz |
| **Rx Frequency** | **GSM/GPRS/EDGE:**<br>850: 869.2 MHz ~ 893.8 MHz<br>1900: 1930.2 MHz ~ 1989.8 MHz<br>**WCDMA:**<br>Band V: 871.4 MHz ~ 891.6 MHz<br>Band II: 1932.4 MHz ~ 1987.6 MHz<br>Band IV: 2112.4 MHz ~ 2152.6 MHz |
| **Maximum Output Power** | **GSM/GPRS/EDGE:**<br>850: 33.72 dBm<br>1900: 30.63 dBm<br>**WCDMA:**<br>Band V: 23.31 dBm<br>Band II: 21.62 dBm<br>Band IV: 22.15 dBm |
| **Antenna Type** | PIFA Antenna |
| **Antenna Gain** | Cellular Band: -4.10 dBi<br>PCS Band: -1.40 dBi<br>AWS Band: -2.50 dBi |
| **Type of Modulation** | GSM: GMSK<br>GPRS: GMSK<br>EDGE: GMSK / 8PSK<br>WCDMA : BPSK (Uplink)<br>HSDPA/DC-HSDPA : QPSK (Uplink)<br>HSUPA : QPSK (Uplink)<br>HSPA+ : 16QAM (16QAM uplink is not supported)<br>DC-HSDPA : 64QAM |

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

| FCC Rule | System | Type of Modulation | Maximum ERP/EIRP (W) | Frequency Tolerance (ppm) | Emission Designator |
|---|---|---|---|---|---|
| Part 22H | GSM850 GSM | GMSK | 0.5585 | 0.0033 ppm | 242KGXW |
| Part 22H | GSM850 EDGE class 8 | 8PSK | 0.1236 | 0.0108 ppm | 242KG7W |
| Part 22H | WCDMA Band V RMC 12.2Kbps | BPSK | 0.0508 | 0.0075 ppm | 4M15F9W |
| Part 24E | GSM1900 GSM | GMSK | 0.8375 | 0.0138 ppm | 243KGXW |
| Part 24E | GSM1900 EDGE class 8 | 8PSK | 0.2924 | 0.0057 ppm | 244KG7W |
| Part 24E | WCDMA Band II RMC 12.2Kbps | BPSK | 0.1052 | 0.0035 ppm | 4M15F9W |
| Part 27L | WCDMA Band IV RMC 12.2Kbps | BPSK | 0.0923 | 0.0013 ppm | 4M13F9W |

## 1.7 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No are CN5018 and CN5019.

| | | |
|---|---|---|
| **Test Site** | Sporton International (Shenzhen) Inc. | |
| **Test Site Location** | 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China<br>TEL: +86-755-8637-9589<br>FAX: +86-755-8637-9595 | |
| **Test Site No.** | **Sporton Site No.** | **FCC Test Firm Registration No.** |
| | TH01-SZ | 251365 |

| | | |
|---|---|---|
| **Test Site** | Sporton International (Shenzhen) Inc. | |
| **Test Site Location** | No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China<br>TEL: +86-755-3320-2398 | |
| **Test Site No.** | **Sporton Site No.** | **FCC Test Firm Registration No.** |
| | 03CH03-SZ | 577730 |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI/TIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

# 2 Test Configuration of Equipment Under Test

## 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

| Test Modes | | |
|---|---|---|
| **Band** | **Radiated TCs** | **Conducted TCs** |
| **GSM 850** | ■ GSM Link<br>■ EDGE class 8 Link | ■ GSM Link<br>■ EDGE class 8 Link |
| **GSM 1900** | ■ GSM Link<br>■ EDGE class 8 Link | ■ GSM Link<br>■ EDGE class 8 Link |
| **WCDMA Band V** | ■ RMC 12.2Kbps Link | ■ RMC 12.2Kbps Link |
| **WCDMA Band II** | ■ RMC 12.2Kbps Link | ■ RMC 12.2Kbps Link |
| **WCDMA Band IV** | ■ RMC 12.2Kbps Link | ■ RMC 12.2Kbps Link |

## 2.2 Connection Diagram of Test System




## 2.3 Support Unit used in test configuration

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|---|---|---|---|---|---|---|
| 1. | System Simulator | R&S | CMU 200 | N/A | N/A | Unshielded, 1.8 m |
| 2. | DC Power Supply | GW INSTEK | GPS-3030D | N/A | N/A | Unshielded, 1.8 m |

## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

*Offset(dB) = RF cable loss(dB) + attenuator factor(dB).*

= 4.0 + 10 = 14.0 (dB)

# 3 Conducted Test Result

## 3.1 Measuring Instruments

See list of measuring instruments of this test report.

## 3.2 Test Setup

### 3.2.1 Conducted Output Power




### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission




### 3.2.3 Frequency Stability




## 3.3 Test Result of Conducted Test

Please refer to Appendix A.

## 3.4 Conducted Output Power and ERP/EIRP

### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

$P_T$ = transmitter output power in dBm

$G_T$ = gain of the transmitting antenna in dBi

$L_C$ = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.

Record the maximum PAPR level associated with a probability of 0.1%.

## 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

### 3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   =P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its $10^{th}$ harmonic.

### 3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

= P(W) - [43 + 10log(P)] (dB)

= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

= -13dBm.

## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

# 4 Radiated Test Items

## 4.1 Measuring Instruments

See list of measuring instruments of this test report.

## 4.2 Test Setup

### 4.2.1 For radiated test from 30MHz to 1GHz




### 4.2.2 For radiated test above 1GHz




## 4.3 Test Result of Radiated Test

Please refer to Appendix B.

## 4.4 Field Strength of Spurious Radiation Measurement

### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.8 and ANSI/TIA-603-E Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

    = P(W) - [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

# 5 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---|---|---|---|---|---|---|---|---|
| Spectrum Analyzer | R&S | FSV40 | 101078 | 9kHz~40GHz | Apr. 20, 2017 | Jan. 18, 2018~ Jan. 20, 2018 | Apr. 19, 2018 | Conducted (TH01-SZ) |
| DC Power Supply | GWINSTEK | AnritsuGPS-3030D | EM882636 | Max 30V | May 13, 2017 | Jan. 18, 2018~ Jan. 20, 2018 | May 12, 2018 | Conducted (TH01-SZ) |
| Thermal Chamber | Ten Billion Hongzhangroup | LP-150U | H2014081803 | -40~+150°C | Jul. 20, 2017 | Jan. 18, 2018~ Jan. 20, 2018 | Jul. 19, 2018 | Conducted (TH01-SZ) |
| EMI Test Receiver&SA | KEYSIGHT | N9038A | MY54450083 | 20Hz~8.4GHz | Apr. 20, 2017 | Jan. 23, 2018 | Apr. 19, 2018 | Radiation (03CH03-SZ) |
| EXA Spectrum Anaiyzer | KEYSIGHT | N9010A | MY55150246 | 10Hz~44GHz; | Apr. 20, 2017 | Jan. 23, 2018 | Apr. 19, 2018 | Radiation (03CH03-SZ |
| Bilog Antenna | TeseQ | CBL6112D | 35408 | 30MHz-2GHz | May 14, 2017 | Jan. 23, 2018 | May 13, 2018 | Radiation (03CH03-SZ) |
| Double Ridge Horn Antenna | SCHWARZBECK | BBHA9120 D | 9120D-1355 | 1GHz~18GHz | Jul. 09, 2017 | Jan. 23, 2018 | Jul. 08, 2018 | Radiation (03CH03-SZ) |
| SHF-EHF Horn | com-power | AH-840 | 101071 | 18Ghz-40GHz | Jun.16, 2017 | Jan. 23, 2018 | Jun.15, 2018 | Radiation (03CH03-SZ) |
| Amplifier | Burgeon | BPA-530 | 102210 | 0.01Hz ~3000MHz | Oct. 19, 2017 | Jan. 23, 2018 | Oct. 18, 2018 | Radiation (03CH03-SZ) |
| HF Amplifier | MITEQ | TTA1840-35 -HG | 1871923 | 18GHz~40GHz | Jul. 18, 2017 | Jan. 23, 2018 | Jul. 17, 2018 | Radiation (03CH03-SZ) |
| Amplifier | Agilent Technologies | 83017A | MY39501302 | 500MHz~26.5GHz | Dec. 27, 2017 | Jan. 23, 2018 | Dec. 26, 2018 | Radiation (03CH03-SZ) |
| AC Power Source | Chroma | 61601 | 61601000198 5 | N/A | NCR | Jan. 23, 2018 | NCR | Radiation (03CH03-SZ) |
| Turn Table | EM | EM1000 | N/A | 0~360 degree | NCR | Jan. 23, 2018 | NCR | Radiation (03CH03-SZ) |
| Antenna Mast | EM | EM1000 | N/A | 1 m~4 m | NCR | Jan. 23, 2018 | NCR | Radiation (03CH03-SZ) |

NCR: No Calibration Required

# 6 Uncertainty of Evaluation

**Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)**

| | |
|---|---|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.0dB |

**Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)**

| | |
|---|---|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.6dB |

**Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)**

| | |
|---|---|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.8dB |

# Appendix A. Test Results of Conducted Test

## Conducted Output Power (Average power)

| Conducted Power (*Unit: dBm) | | | | | | |
|---|---|---|---|---|---|---|
| Band | GSM850 | | | GSM1900 | | |
| Channel | 128 | 189 | 251 | 512 | 661 | 810 |
| Frequency | 824.2 | 836.4 | 848.8 | 1850.2 | 1880.0 | 1909.8 |
| GSM | 33.45 | 33.72 | 33.42 | 30.43 | 30.63 | 30.37 |
| GPRS class 8 | 33.44 | 33.70 | 33.40 | 30.41 | 30.61 | 30.36 |
| GPRS class 10 | 30.20 | 30.50 | 30.10 | 27.60 | 27.58 | 27.45 |
| GPRS class 11 | 28.15 | 28.20 | 28.05 | 25.55 | 25.57 | 25.39 |
| GPRS class 12 | 26.77 | 26.88 | 26.70 | 24.60 | 24.61 | 24.42 |
| EGPRS class 8 | 27.14 | 27.17 | 27.12 | 26.05 | 26.06 | 25.96 |
| EGPRS class 10 | 24.09 | 24.16 | 23.91 | 23.02 | 23.14 | 22.88 |
| EGPRS class 11 | 22.08 | 22.17 | 22.04 | 20.96 | 20.91 | 20.76 |
| EGPRS class 12 | 21.67 | 21.75 | 21.55 | 20.45 | 20.42 | 20.20 |

| Conducted Power (*Unit: dBm) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Band | WCDMA Band V | | | WCDMA Band II | | | WCDMA Band IV | | |
| Channel | 4132 | 4182 | 4233 | 9262 | 9400 | 9538 | 1312 | 1413 | 1513 |
| Frequency | 826.4 | 836.4 | 846.6 | 1852.4 | 1880 | 1907.6 | 1712.4 | 1732.6 | 1752.6 |
| AMR 12.2K | 23.29 | 23.27 | 23.13 | 21.60 | 21.58 | 21.50 | 21.90 | 22.12 | 22.14 |
| RMC 12.2K | 23.31 | 23.30 | 23.15 | 21.62 | 21.59 | 21.51 | 21.91 | 22.14 | 22.15 |
| HSDPA Subtest-1 | 22.75 | 22.81 | 22.80 | 20.55 | 20.63 | 20.59 | 20.95 | 21.10 | 21.16 |
| HSDPA Subtest-2 | 22.69 | 21.86 | 22.79 | 20.59 | 20.62 | 20.66 | 20.70 | 21.15 | 21.15 |
| HSDPA Subtest-3 | 22.18 | 22.33 | 22.34 | 20.08 | 20.13 | 20.16 | 20.49 | 20.63 | 20.64 |
| HSDPA Subtest-4 | 22.26 | 21.51 | 22.33 | 20.11 | 20.12 | 20.19 | 20.47 | 20.65 | 20.62 |
| DC-HSDPA Subtest-1 | 22.31 | 22.36 | 22.37 | 20.49 | 20.54 | 20.56 | 20.82 | 20.91 | 20.95 |
| DC-HSDPA Subtest-2 | 22.30 | 22.34 | 22.35 | 20.45 | 20.51 | 20.53 | 20.76 | 20.85 | 20.87 |
| DC-HSDPA Subtest-3 | 21.81 | 21.85 | 21.90 | 20.07 | 20.10 | 20.12 | 20.38 | 20.43 | 20.46 |
| DC-HSDPA Subtest-4 | 21.79 | 21.83 | 21.85 | 20.04 | 20.07 | 20.08 | 20.36 | 20.39 | 20.45 |
| HSUPA Subtest-1 | 22.77 | 22.64 | 22.56 | 20.59 | 20.46 | 20.42 | 20.61 | 20.72 | 20.74 |
| HSUPA Subtest-2 | 20.74 | 20.83 | 20.81 | 18.57 | 18.52 | 18.55 | 18.69 | 18.88 | 18.89 |
| HSUPA Subtest-3 | 21.59 | 21.63 | 21.60 | 19.60 | 19.56 | 19.61 | 19.65 | 19.73 | 19.77 |
| HSUPA Subtest-4 | 20.75 | 20.73 | 20.68 | 18.58 | 18.61 | 18.51 | 18.61 | 18.65 | 18.66 |
| HSUPA Subtest-5 | 22.70 | 22.80 | 22.60 | 20.50 | 20.40 | 20.60 | 20.60 | 20.64 | 20.66 |

# ERP/EIRP

| GSM850 ($G_T$ - $L_C$= -4.10dB) | | | |
|---|---|---|---|
| Channel | 128 | 189 | 251 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 |
| Conducted Power (dBm) | 33.45 | 33.72 | 33.42 |
| Conducted Power (Watts) | 2.2131 | 2.3550 | 2.1979 |
| ERP(dBm) | 27.20 | 27.47 | 27.17 |
| ERP(Watts) | 0.5248 | 0.5585 | 0.5212 |

| EDGE850 ($G_T$ - $L_C$= -4.10dB) | | | |
|---|---|---|---|
| Channel | 128 | 189 | 251 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 824.2 | 836.4 | 848.8 |
| Conducted Power (dBm) | 27.14 | 27.17 | 27.12 |
| Conducted Power (Watts) | 0.5176 | 0.5212 | 0.5152 |
| ERP(dBm) | 20.89 | 20.92 | 20.87 |
| ERP(Watts) | 0.1227 | 0.1236 | 0.1222 |

| GSM1900 ($G_T$ - $L_C$= -1.40dB) | | | |
|---|---|---|---|
| Channel | 512 | 661 | 810 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 |
| Conducted Power (dBm) | 30.43 | 30.63 | 30.37 |
| Conducted Power (Watts) | 1.1041 | 1.1561 | 1.0889 |
| EIRP(dBm) | 29.03 | 29.23 | 28.97 |
| EIRP(Watts) | 0.7998 | 0.8375 | 0.7889 |

| EDGE1900 ($G_T$ - $L_C$= -1.40dB) | | | |
|---|---|---|---|
| Channel | 512 | 661 | 810 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 1850.2 | 1880 | 1909.8 |
| Conducted Power (dBm) | 26.05 | 26.06 | 25.96 |
| Conducted Power (Watts) | 0.4027 | 0.4036 | 0.3945 |
| EIRP(dBm) | 24.65 | 24.66 | 24.56 |
| EIRP(Watts) | 0.2917 | 0.2924 | 0.2858 |

| WCDMA Band V ($G_T$ - $L_C$ = -4.10dB) | | | |
|---|---|---|---|
| Channel | 4132 | 4182 | 4233 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 826.4 | 836.4 | 846.6 |
| Conducted Power (dBm) | 23.31 | 23.30 | 23.15 |
| Conducted Power (Watts) | 0.2143 | 0.2138 | 0.2065 |
| ERP(dBm) | 17.06 | 17.05 | 16.90 |
| ERP(Watts) | 0.0508 | 0.0507 | 0.0490 |

| WCDMA Band II ($G_T$ - $L_C$ = -1.40dB) | | | |
|---|---|---|---|
| Channel | 9262 | 9400 | 9538 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 1852.4 | 1880 | 1907.6 |
| Conducted Power (dBm) | 21.62 | 21.59 | 21.51 |
| Conducted Power (Watts) | 0.1452 | 0.1442 | 0.1416 |
| EIRP(dBm) | 20.22 | 20.19 | 20.11 |
| EIRP(Watts) | 0.1052 | 0.1045 | 0.1026 |

| WCDMA Band IV ($G_T$ - $L_C$ = -2.50dB) | | | |
|---|---|---|---|
| Channel | 1312 | 1413 | 1513 |
| | (Low) | (Mid) | (High) |
| Frequency (MHz) | 1712.4 | 1732.6 | 1752.6 |
| Conducted Power (dBm) | 21.91 | 22.14 | 22.15 |
| Conducted Power (Watts) | 0.1552 | 0.1637 | 0.1641 |
| EIRP(dBm) | 19.41 | 19.64 | 19.65 |
| EIRP(Watts) | 0.0873 | 0.0920 | 0.0923 |

# Peak-to-Average Ratio

| Mode | GSM850(dB) | | Limit: 13dB |
|---|---|---|---|
| Mod. | GSM | EDGE class 8 | Result |
| Lowest CH | 0.78 | 3.80 | PASS |
| Middle CH | 0.29 | 3.30 | |
| Highest CH | 0.81 | 3.65 | |

| Mode | GSM1900(dB) | | Limit: 13dB |
|---|---|---|---|
| Mod. | GSM | EDGE class 8 | Result |
| Lowest CH | 0.23 | 3.80 | PASS |
| Middle CH | 0.72 | 3.97 | |
| Highest CH | 0.23 | 3.97 | |

| Mode | WCDMA Band V(dB) | WCDMA Band II(dB) | WCDMA Band IV(dB) | Limit: 13dB |
|---|---|---|---|---|
| Mod. | RMC 12.2Kbps | RMC 12.2Kbps | RMC 12.2Kbps | Result |
| Lowest CH | 3.36 | 2.43 | 3.39 | PASS |
| Middle CH | 3.13 | 2.64 | 2.96 | |
| Highest CH | 3.33 | 2.58 | 3.25 | |

| GSM850 (GSM) | GSM850 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

| GSM1900 (GSM) | GSM1900 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

| WCDMA Band V (RMC 12.2Kbps) | WCDMA Band II (RMC 12.2Kbps) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

| WCDMA Band IV (RMC 12.2Kbps) | |
|---|---|
| **Lowest Channel** | |
|  | |
| **Middle Channel** | |
|  | |
| **Highest Channel** | |
|  | |

# 26dB Bandwidth

| Mode | GSM850(MHz) | |
|---|---|---|
| Mod. | GSM | EDGE class 8 |
| Lowest CH | 0.313 | 0.311 |
| Middle CH | 0.314 | 0.314 |
| Highest CH | 0.314 | 0.313 |

| Mode | GSM1900(MHz) | |
|---|---|---|
| Mod. | GSM | EDGE class 8 |
| Lowest CH | 0.316 | 0.316 |
| Middle CH | 0.313 | 0.321 |
| Highest CH | 0.315 | 0.318 |

| Mode | WCDMA Band V(MHz) | WCDMA Band II(MHz) | WCDMA Band IV(MHz) |
|---|---|---|---|
| Mod. | RMC 12.2Kbps | RMC 12.2Kbps | RMC 12.2Kbps |
| Lowest CH | 4.71 | 4.75 | 4.71 |
| Middle CH | 4.73 | 4.74 | 4.74 |
| Highest CH | 4.70 | 4.76 | 4.71 |

| GSM850 (GSM) | GSM850 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

| GSM1900 (GSM) | GSM1900 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

## WCDMA Band V (RMC 12.2Kbps)

### Lowest Channel




## WCDMA Band II (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Middle Channel




### Highest Channel




### Highest Channel



| WCDMA Band IV (RMC 12.2Kbps) | |
|---|---|
| **Lowest Channel** | |
|  | |
| **Middle Channel** | |
|  | |
| **Highest Channel** | |
|  | |

# Occupied Bandwidth

| Mode | GSM850(MHz) | |
|---|---|---|
| Mod. | GSM | EDGE class 8 |
| Lowest CH | 0.242 | 0.242 |
| Middle CH | 0.242 | 0.242 |
| Highest CH | 0.241 | 0.242 |

| Mode | GSM1900(MHz) | |
|---|---|---|
| Mod. | GSM | EDGE class 8 |
| Lowest CH | 0.242 | 0.244 |
| Middle CH | 0.243 | 0.242 |
| Highest CH | 0.242 | 0.242 |

| Mode | WCDMA Band V(MHz) | WCDMA Band II(MHz) | WCDMA Band IV(MHz) |
|---|---|---|---|
| Mod. | RMC 12.2Kbps | RMC 12.2Kbps | RMC 12.2Kbps |
| Lowest CH | 4.13 | 4.15 | 4.13 |
| Middle CH | 4.14 | 4.14 | 4.13 |
| Highest CH | 4.15 | 4.14 | 4.13 |

| GSM850 (GSM) | GSM850 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

| GSM1900 (GSM) | GSM1900 (EDGE class 8) |
|---|---|
| **Lowest Channel** | **Lowest Channel** |
|  |  |
| **Middle Channel** | **Middle Channel** |
|  |  |
| **Highest Channel** | **Highest Channel** |
|  |  |

## WCDMA Band V (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel




## WCDMA Band II (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel



## WCDMA Band IV (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel



# Conducted Band Edge

## GSM850 (GSM)

### Lowest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 820.000 MHz | 823.000 MHz | 100.000 kHz | 822.49500 MHz | -46.41 dBm | -33.41 dB |
| 823.000 MHz | 824.000 MHz | 3.000 kHz | 823.98303 MHz | -16.22 dBm | -3.22 dB |
| 824.000 MHz | 824.500 MHz | 10.000 kHz | 824.20110 MHz | 23.41 dBm | -11.59 dB |

Date: 19.JAN.2018 16:10:38

### Highest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 848.500 MHz | 849.000 MHz | 10.000 kHz | 848.86976 MHz | 22.98 dBm | -12.02 dB |
| 849.000 MHz | 850.000 MHz | 3.000 kHz | 849.02495 MHz | -18.14 dBm | -5.14 dB |
| 850.000 MHz | 855.000 MHz | 100.000 kHz | 850.54196 MHz | -46.36 dBm | -33.36 dB |

Date: 19.JAN.2018 16:12:13

## GSM850 (EDGE class 8)

### Lowest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 820.000 MHz | 823.000 MHz | 100.000 kHz | 822.45904 MHz | -49.34 dBm | -36.34 dB |
| 823.000 MHz | 824.000 MHz | 3.000 kHz | 823.98703 MHz | -23.32 dBm | -10.32 dB |
| 824.000 MHz | 824.500 MHz | 10.000 kHz | 824.22804 MHz | 16.44 dBm | -18.56 dB |

Date: 19.JAN.2018 15:30:24

### Highest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 848.500 MHz | 849.000 MHz | 10.000 kHz | 848.74301 MHz | 17.53 dBm | -17.47 dB |
| 849.000 MHz | 850.000 MHz | 3.000 kHz | 849.01297 MHz | -26.12 dBm | -13.12 dB |
| 850.000 MHz | 855.000 MHz | 100.000 kHz | 850.03247 MHz | -50.01 dBm | -37.01 dB |

Date: 19.JAN.2018 15:32:27

## GSM1900 (GSM)

### Lowest Band Edge




### Highest Band Edge




## GSM1900 (EDGE class 8)

### Lowest Band Edge




### Highest Band Edge



## WCDMA Band V (RMC 12.2Kbps)

### Lowest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 820.000 MHz | 823.000 MHz | 100.000 kHz | 822.83067 MHz | -34.51 dBm | -21.51 dB |
| 823.000 MHz | 824.000 MHz | 50.000 kHz | 823.85729 MHz | -26.74 dBm | -13.74 dB |
| 824.000 MHz | 829.000 MHz | 100.000 kHz | 825.69580 MHz | 7.87 dBm | -27.13 dB |

Date: 19.JAN.2018 17:29:37

### Highest Band Edge




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 844.000 MHz | 849.000 MHz | 100.000 kHz | 845.22128 MHz | 7.81 dBm | -27.19 dB |
| 849.000 MHz | 850.000 MHz | 50.000 kHz | 849.15070 MHz | -26.17 dBm | -13.17 dB |
| 850.000 MHz | 855.000 MHz | 100.000 kHz | 850.17233 MHz | -32.93 dBm | -19.93 dB |

Date: 19.JAN.2018 17:32:54

| WCDMA Band II (RMC 12.2Kbps) | |
|---|---|
| **Lowest Band Edge** | **Highest Band Edge** |




| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 1.845 GHz | 1.849 GHz | 1.000 MHz | 1.84883 GHz | -18.63 dBm | -5.63 dB |
| 1.849 GHz | 1.850 GHz | 50.000 kHz | 1.85000 GHz | -22.05 dBm | -9.05 dB |
| 1.850 GHz | 1.855 GHz | 100.000 kHz | 1.85263 GHz | 8.82 dBm | -26.18 dB |




| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 1.905 GHz | 1.910 GHz | 100.000 kHz | 1.90676 GHz | 8.07 dBm | -26.93 dB |
| 1.910 GHz | 1.911 GHz | 50.000 kHz | 1.91000 GHz | -24.39 dBm | -11.39 dB |
| 1.911 GHz | 1.915 GHz | 1.000 MHz | 1.91113 GHz | -18.17 dBm | -5.17 dB |

| WCDMA Band IV (RMC 12.2Kbps) | |
|---|---|
| **Lowest Band Edge** | **Highest Band Edge** |




| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 1.705 GHz | 1.709 GHz | 1.000 MHz | 1.70873 GHz | -24.39 dBm | -11.39 dB |
| 1.709 GHz | 1.710 GHz | 50.000 kHz | 1.70984 GHz | -27.41 dBm | -14.41 dB |
| 1.710 GHz | 1.715 GHz | 100.000 kHz | 1.71306 GHz | 7.50 dBm | -27.50 dB |




| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 1.750 GHz | 1.755 GHz | 100.000 kHz | 1.75175 GHz | 7.79 dBm | -27.21 dB |
| 1.755 GHz | 1.756 GHz | 50.000 kHz | 1.75515 GHz | -26.82 dBm | -13.82 dB |
| 1.756 GHz | 1.760 GHz | 1.000 MHz | 1.75622 GHz | -21.99 dBm | -8.99 dB |

# Conducted Spurious Emission

## GSM850 (GSM)

### Lowest Channel




### Middle Channel




### Highest Channel




## GSM850 (EDGE class 8)

### Lowest Channel




### Middle Channel




### Highest Channel



## GSM1900 (GSM)

### Lowest Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 666.24438 MHz | -35.13 dBm | -22.13 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.72021 GHz | -33.55 dBm | -20.55 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.75977 GHz | -32.03 dBm | -19.03 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.97125 GHz | -28.71 dBm | -15.71 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 12.90823 GHz | -27.41 dBm | -14.41 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 16.53109 GHz | -25.50 dBm | -12.50 dB |

Date: 18.JAN.2018 16:08:32

### Middle Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 883.90055 MHz | -34.40 dBm | -21.40 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.15519 GHz | -32.99 dBm | -19.99 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.75828 GHz | -32.51 dBm | -19.51 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.04037 GHz | -28.27 dBm | -15.27 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 10.87604 GHz | -28.95 dBm | -15.95 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 18.94267 GHz | -24.95 dBm | -11.95 dB |

Date: 18.JAN.2018 16:16:41

### Highest Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 971.15692 MHz | -34.49 dBm | -21.49 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.61549 GHz | -33.86 dBm | -20.86 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.82771 GHz | -32.24 dBm | -19.24 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.99525 GHz | -27.64 dBm | -14.64 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 13.18211 GHz | -29.16 dBm | -16.16 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 18.23637 GHz | -25.72 dBm | -12.72 dB |

Date: 18.JAN.2018 16:19:54

## GSM1900 (EDGE class 8)

### Lowest Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 968.73313 MHz | -33.72 dBm | -20.72 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.82452 GHz | -33.24 dBm | -20.24 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.90392 GHz | -31.22 dBm | -18.22 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.96575 GHz | -28.35 dBm | -15.35 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 10.61489 GHz | -29.08 dBm | -16.08 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 14.89025 GHz | -25.20 dBm | -12.20 dB |

Date: 18.JAN.2018 16:42:33

### Middle Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 849.96752 MHz | -33.71 dBm | -20.71 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.40856 GHz | -32.89 dBm | -19.89 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.98379 GHz | -31.80 dBm | -18.80 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.12186 GHz | -27.90 dBm | -14.90 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 11.49404 GHz | -27.92 dBm | -14.92 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 16.89603 GHz | -25.57 dBm | -12.57 dB |

Date: 18.JAN.2018 16:43:58

### Highest Channel




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 1.000 GHz | 1.000 MHz | 975.03498 MHz | -34.40 dBm | -21.40 dB |
| 1.000 GHz | 1.845 GHz | 1.000 MHz | 1.84014 GHz | -33.76 dBm | -20.76 dB |
| 1.915 GHz | 3.000 GHz | 1.000 MHz | 2.85049 GHz | -31.44 dBm | -18.44 dB |
| 3.000 GHz | 7.000 GHz | 1.000 MHz | 6.98075 GHz | -26.56 dBm | -13.56 dB |
| 7.000 GHz | 13.600 GHz | 1.000 MHz | 10.58425 GHz | -27.91 dBm | -14.91 dB |
| 13.600 GHz | 19.100 GHz | 1.000 MHz | 16.94278 GHz | -25.40 dBm | -12.40 dB |

Date: 18.JAN.2018 16:46:01

## WCDMA Band V (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel




## WCDMA Band II (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel



## WCDMA Band IV (RMC 12.2Kbps)

### Lowest Channel




### Middle Channel




### Highest Channel



# Frequency Stability

| Test Conditions | Middle Channel | GSM850 (GSM) | GSM850 (EDGE class 8) | Limit 2.5ppm |
|---|---|---|---|---|
| Temperature (°C) | Voltage (Volt) | Deviation (ppm) | | Result |
| 50 | Normal Voltage | 0.0004 | 0.0009 | PASS |
| 40 | Normal Voltage | 0.0030 | 0.0013 | |
| 30 | Normal Voltage | 0.0033 | 0.0037 | |
| 20(Ref.) | Normal Voltage | 0.0000 | 0.0000 | |
| 10 | Normal Voltage | 0.0016 | 0.0090 | |
| 0 | Normal Voltage | 0.0000 | 0.0009 | |
| -10 | Normal Voltage | 0.0016 | 0.0012 | |
| -20 | Normal Voltage | 0.0025 | 0.0024 | |
| -30 | Normal Voltage | 0.0012 | 0.0108 | |
| 20 | Maximum Voltage | 0.0011 | 0.0090 | |
| 20 | Normal Voltage | 0.0000 | 0.0000 | |
| 20 | Battery End Point | 0.0030 | 0.0092 | |

**Note:** Normal Voltage = 3.85V；Battery End Point (BEP) = 3.45 V；Maximum Voltage =4.4 V

| Test Conditions | Middle Channel | GSM1900 (GSM) | GSM1900 (EDGE class 8) | Limit Note 2. |
|---|---|---|---|---|
| Temperature (°C) | Voltage (Volt) | Deviation (ppm) | | Result |
| 50 | Normal Voltage | 0.0119 | 0.0046 | PASS |
| 40 | Normal Voltage | 0.0092 | 0.0006 | |
| 30 | Normal Voltage | 0.0034 | 0.0016 | |
| 20(Ref.) | Normal Voltage | 0.0000 | 0.0000 | |
| 10 | Normal Voltage | 0.0119 | 0.0057 | |
| 0 | Normal Voltage | 0.0009 | 0.0031 | |
| -10 | Normal Voltage | 0.0009 | 0.0027 | |
| -20 | Normal Voltage | 0.0138 | 0.0016 | |
| -30 | Normal Voltage | 0.0007 | 0.0005 | |
| 20 | Maximum Voltage | 0.0121 | 0.0022 | |
| 20 | Normal Voltage | 0.0000 | 0.0000 | |
| 20 | Battery End Point | 0.0114 | 0.0033 | |

**Note:**

1. Normal Voltage = 3.85V；Battery End Point (BEP) = 3.45 V；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

| Test Conditions | Middle Channel | WCDMA Band V (RMC 12.2Kbps) | Limit 2.5ppm |
|---|---|---|---|
| Temperature (°C) | Voltage (Volt) | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0003 | PASS |
| 40 | Normal Voltage | 0.0008 | |
| 30 | Normal Voltage | 0.0025 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0006 | |
| 0 | Normal Voltage | 0.0002 | |
| -10 | Normal Voltage | 0.0008 | |
| -20 | Normal Voltage | 0.0035 | |
| -30 | Normal Voltage | 0.0075 | |
| 20 | Maximum Voltage | 0.0023 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0052 | |

**Note:** Normal Voltage = 3.85V；Battery End Point (BEP) = 3.45 V；Maximum Voltage =4.4 V

| Test Conditions | Middle Channel | WCDMA Band II (RMC 12.2Kbps) | Limit Note 2. |
|---|---|---|---|
| Temperature (°C) | Voltage (Volt) | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0004 | PASS |
| 40 | Normal Voltage | 0.0001 | |
| 30 | Normal Voltage | 0.0009 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0016 | |
| 0 | Normal Voltage | 0.0002 | |
| -10 | Normal Voltage | 0.0012 | |
| -20 | Normal Voltage | 0.0001 | |
| -30 | Normal Voltage | 0.0035 | |
| 20 | Maximum Voltage | 0.0013 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0004 | |

**Note:**

1. Normal Voltage = 3.85V；Battery End Point (BEP) = 3.45 V；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

| Test Conditions | Middle Channel | WCDMA Band IV (RMC 12.2Kbps) | Limit Note 2. |
|---|---|---|---|
| Temperature (°C) | Voltage (Volt) | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0009 | PASS |
| 40 | Normal Voltage | 0.0008 | |
| 30 | Normal Voltage | 0.0010 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0003 | |
| 0 | Normal Voltage | 0.0002 | |
| -10 | Normal Voltage | 0.0008 | |
| -20 | Normal Voltage | 0.0007 | |
| -30 | Normal Voltage | 0.0013 | |
| 20 | Maximum Voltage | 0.0002 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0001 | |

**Note:**

1. Normal Voltage = 3.85V；Battery End Point (BEP) = 3.45 V；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

# Appendix B. Test Results of Radiated Test

## Radiated Spurious Emission

| GSM850 (GSM) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 1648.4 | -35.46 | -13 | -22.46 | -40.88 | -39.80 | 2.89 | 9.38 | H |
| | 2472.6 | -51.02 | -13 | -38.02 | -57.08 | -56.84 | 2.6 | 10.57 | H |
| | 3296.8 | -68.67 | -13 | -55.67 | -76.67 | -74.39 | 4.71 | 12.58 | H |
| | 4121 | -64.66 | -13 | -51.66 | -76.74 | -69.00 | 5.08 | 11.57 | H |
| | 1648.4 | -39.95 | -13 | -26.95 | -44.98 | -44.29 | 2.89 | 9.38 | V |
| | 2472.6 | -57.99 | -13 | -44.99 | -63.94 | -63.81 | 2.60 | 10.57 | V |
| | 3296.8 | -69.43 | -13 | -56.43 | -77.46 | -75.15 | 4.71 | 12.58 | V |
| | 4121 | -64.52 | -13 | -51.52 | -76.48 | -68.86 | 5.08 | 11.57 | V |
| Middle | 1672.8 | -29.65 | -13 | -16.65 | -35.43 | -33.98 | 2.92 | 9.40 | H |
| | 2509.2 | -61.07 | -13 | -48.07 | -67.13 | -66.89 | 2.63 | 10.60 | H |
| | 3345.6 | -68.86 | -13 | -55.86 | -76.86 | -74.57 | 4.74 | 12.60 | H |
| | 4182 | -62.97 | -13 | -49.97 | -75.05 | -67.31 | 5.11 | 11.60 | H |
| | 1672.8 | -32.60 | -13 | -19.60 | -38.00 | -36.93 | 2.92 | 9.40 | V |
| | 2509.2 | -62.19 | -13 | -49.19 | -68.14 | -68.01 | 2.63 | 10.60 | V |
| | 3345.6 | -69.45 | -13 | -56.45 | -77.48 | -75.16 | 4.74 | 12.60 | V |
| | 4182 | -63.11 | -13 | -50.11 | -75.07 | -67.45 | 5.11 | 11.60 | V |
| Highest | 1697.6 | -36.05 | -13 | -23.05 | -41.45 | -40.37 | 2.95 | 9.42 | H |
| | 2546.4 | -57.15 | -13 | -44.15 | -63.21 | -62.97 | 2.66 | 10.63 | H |
| | 3395.2 | -67.09 | -13 | -54.09 | -75.09 | -72.81 | 4.77 | 12.64 | H |
| | 4244 | -66.02 | -13 | -53.02 | -78.10 | -70.36 | 5.14 | 11.63 | H |
| | 1697.6 | -43.97 | -13 | -30.97 | -48.38 | -48.29 | 2.95 | 9.42 | V |
| | 2546.4 | -63.68 | -13 | -50.68 | -69.63 | -69.50 | 2.66 | 10.63 | V |
| | 3395.2 | -69.66 | -13 | -56.66 | -77.69 | -75.38 | 4.77 | 12.64 | V |
| | 4244 | -65.93 | -13 | -52.93 | -77.89 | -70.27 | 5.14 | 11.63 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| GSM850 (EDGE class 8) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 1648.4 | -44.07 | -13 | -31.07 | -48.60 | -48.38 | 2.92 | 9.38 | H |
| | 2472.6 | -65.49 | -13 | -52.49 | -71.55 | -71.28 | 2.63 | 10.57 | H |
| | 3296.8 | -69.56 | -13 | -56.56 | -77.56 | -75.25 | 4.74 | 12.58 | H |
| | 4121 | -67.49 | -13 | -54.49 | -79.57 | -71.80 | 5.11 | 11.57 | H |
| | 1648.4 | -52.73 | -13 | -39.73 | -55.34 | -57.04 | 2.92 | 9.38 | V |
| | 2472.6 | -68.76 | -13 | -55.76 | -74.71 | -74.55 | 2.63 | 10.57 | V |
| | 3296.8 | -69.35 | -13 | -56.35 | -77.38 | -75.04 | 4.74 | 12.58 | V |
| | 4121 | -67.56 | -13 | -54.56 | -79.52 | -71.87 | 5.11 | 11.57 | V |
| Middle | 1672.8 | -48.00 | -13 | -35.00 | -51.82 | -52.33 | 2.92 | 9.40 | H |
| | 2509.2 | -69.81 | -13 | -56.81 | -75.87 | -75.63 | 2.63 | 10.60 | H |
| | 3345.6 | -69.55 | -13 | -56.55 | -77.55 | -75.26 | 4.74 | 12.60 | H |
| | 4182 | -67.61 | -13 | -54.61 | -79.69 | -71.95 | 5.11 | 11.60 | H |
| | 1672.8 | -53.38 | -13 | -40.38 | -55.77 | -57.71 | 2.92 | 9.40 | V |
| | 2509.2 | -70.82 | -13 | -57.82 | -76.77 | -76.64 | 2.63 | 10.60 | V |
| | 3345.6 | -69.46 | -13 | -56.46 | -77.49 | -75.17 | 4.74 | 12.60 | V |
| | 4182 | -67.75 | -13 | -54.75 | -79.71 | -72.09 | 5.11 | 11.60 | V |
| Highest | 1697.6 | -44.25 | -13 | -31.25 | -48.78 | -48.60 | 2.92 | 9.42 | H |
| | 2546.4 | -70.04 | -13 | -57.04 | -76.10 | -75.89 | 2.63 | 10.63 | H |
| | 3395.2 | -69.67 | -13 | -56.67 | -77.67 | -75.42 | 4.74 | 12.64 | H |
| | 4244 | -67.92 | -13 | -54.92 | -80.00 | -72.29 | 5.11 | 11.63 | H |
| | 1697.6 | -52.20 | -13 | -39.20 | -54.97 | -56.55 | 2.92 | 9.42 | V |
| | 2546.4 | -71.01 | -13 | -58.01 | -76.96 | -76.86 | 2.63 | 10.63 | V |
| | 3395.2 | -69.77 | -13 | -56.77 | -77.80 | -75.52 | 4.74 | 12.64 | V |
| | 4244 | -67.90 | -13 | -54.90 | -79.86 | -72.27 | 5.11 | 11.63 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| GSM1900 (GSM) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | EIRP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 3700.4 | -48.86 | -13 | -35.86 | -60.11 | -56.08 | 5.33 | 12.55 | H |
| | 5550.6 | -53.23 | -13 | -40.23 | -69.11 | -58.76 | 7.49 | 13.02 | H |
| | 7400.8 | -61.62 | -13 | -48.62 | -79.94 | -65.12 | 7.82 | 11.32 | H |
| | 3700.4 | -46.40 | -13 | -33.40 | -58.87 | -53.62 | 5.33 | 12.55 | V |
| | 5550.6 | -53.83 | -13 | -40.83 | -70.15 | -59.36 | 7.49 | 13.02 | V |
| | 7400.8 | -61.78 | -13 | -48.78 | -80 | -65.28 | 7.82 | 11.32 | V |
| Middle | 3760 | -48.09 | -13 | -35.09 | -59.34 | -55.33 | 5.36 | 12.60 | H |
| | 5640 | -54.90 | -13 | -41.90 | -70.78 | -60.48 | 7.52 | 13.10 | H |
| | 7520 | -61.36 | -13 | -48.36 | -79.68 | -64.85 | 7.85 | 11.34 | H |
| | 3760 | -51.36 | -13 | -38.36 | -63.83 | -58.60 | 5.36 | 12.60 | V |
| | 5640 | -62.66 | -13 | -49.66 | -78.98 | -68.24 | 7.52 | 13.10 | V |
| | 7520 | -61.72 | -13 | -48.72 | -79.94 | -65.21 | 7.85 | 11.34 | V |
| Highest | 3819.6 | -63.12 | -13 | -50.12 | -74.37 | -70.38 | 5.39 | 12.65 | H |
| | 5729.4 | -53.59 | -13 | -40.59 | -69.47 | -59.24 | 7.55 | 13.20 | H |
| | 7639.2 | -61.40 | -13 | -48.40 | -79.72 | -64.88 | 7.88 | 11.36 | H |
| | 3819.6 | -54.94 | -13 | -41.94 | -67.41 | -62.20 | 5.39 | 12.65 | V |
| | 5729.4 | -54.43 | -13 | -41.43 | -70.75 | -60.08 | 7.55 | 13.20 | V |
| | 7639.2 | -61.59 | -13 | -48.59 | -79.81 | -65.07 | 7.88 | 11.36 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| GSM1900 (EDGE class 8) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | EIRP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 3700.4 | -56.82 | -13 | -43.82 | -68.07 | -64.01 | 5.36 | 12.55 | H |
| | 5550.6 | -61.56 | -13 | -48.56 | -77.44 | -67.06 | 7.52 | 13.02 | H |
| | 7400.8 | -61.23 | -13 | -48.23 | -79.55 | -64.70 | 7.85 | 11.32 | H |
| | 3700.4 | -55.08 | -13 | -42.08 | -67.55 | -62.27 | 5.36 | 12.55 | V |
| | 5550.6 | -63.64 | -13 | -50.64 | -79.96 | -69.14 | 7.52 | 13.02 | V |
| | 7400.8 | -61.69 | -13 | -48.69 | -79.91 | -65.16 | 7.85 | 11.32 | V |
| Middle | 3760 | -58.83 | -13 | -45.83 | -70.08 | -66.07 | 5.36 | 12.60 | H |
| | 5640 | -59.15 | -13 | -46.15 | -75.03 | -64.73 | 7.52 | 13.10 | H |
| | 7520 | -61.60 | -13 | -48.60 | -79.92 | -65.09 | 7.85 | 11.34 | H |
| | 3760 | -56.35 | -13 | -43.35 | -68.82 | -63.59 | 5.36 | 12.60 | V |
| | 5640 | -60.87 | -13 | -47.87 | -77.19 | -66.45 | 7.52 | 13.10 | V |
| | 7520 | -61.80 | -13 | -48.80 | -80.02 | -65.29 | 7.85 | 11.34 | V |
| Highest | 3819.6 | -60.76 | -13 | -47.76 | -72.01 | -68.05 | 5.36 | 12.65 | H |
| | 5729.4 | -64.14 | -13 | -51.14 | -80.02 | -69.82 | 7.52 | 13.20 | H |
| | 7639.2 | -61.48 | -13 | -48.48 | -79.80 | -64.99 | 7.85 | 11.36 | H |
| | 3819.6 | -61.62 | -13 | -48.62 | -74.09 | -68.91 | 5.36 | 12.65 | V |
| | 5729.4 | -63.74 | -13 | -50.74 | -80.06 | -69.42 | 7.52 | 13.20 | V |
| | 7639.2 | -61.56 | -13 | -48.56 | -79.78 | -65.07 | 7.85 | 11.36 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| WCDMA Band V(RMC 12.2Kbps) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 1649.4 | -58.82 | -13 | -45.82 | -60.53 | -63.13 | 2.92 | 9.38 | H |
| | 2474.1 | -70.58 | -13 | -57.58 | -76.64 | -76.37 | 2.63 | 10.57 | H |
| | 3298.8 | -69.54 | -13 | -56.54 | -77.54 | -75.23 | 4.74 | 12.58 | H |
| | 4132 | -67.18 | -13 | -54.18 | -79.26 | -71.49 | 5.11 | 11.57 | H |
| | 1649.4 | -62.86 | -13 | -49.86 | -64.70 | -67.17 | 2.92 | 9.38 | V |
| | 2474.1 | -70.89 | -13 | -57.89 | -76.84 | -76.68 | 2.63 | 10.57 | V |
| | 3298.8 | -69.50 | -13 | -56.50 | -77.53 | -75.19 | 4.74 | 12.58 | V |
| | 4132 | -67.32 | -13 | -54.32 | -79.28 | -71.63 | 5.11 | 11.57 | V |
| Middle | 1673.04 | -56.48 | -13 | -43.48 | -58.19 | -60.81 | 2.92 | 9.40 | H |
| | 2509.56 | -71.05 | -13 | -58.05 | -77.11 | -76.87 | 2.63 | 10.60 | H |
| | 3346.08 | -69.82 | -13 | -56.82 | -77.82 | -75.53 | 4.74 | 12.60 | H |
| | 4182 | -67.63 | -13 | -54.63 | -79.71 | -71.97 | 5.11 | 11.60 | H |
| | 1673.04 | -60.31 | -13 | -47.31 | -62.15 | -64.64 | 2.92 | 9.40 | V |
| | 2509.56 | -71.47 | -13 | -58.47 | -77.42 | -77.29 | 2.63 | 10.60 | V |
| | 3346.08 | -69.63 | -13 | -56.63 | -77.66 | -75.34 | 4.74 | 12.60 | V |
| | 4182 | -67.92 | -13 | -54.92 | -79.88 | -72.26 | 5.11 | 11.60 | V |
| Highest | 1696.62 | -58.72 | -13 | -45.72 | -60.43 | -63.07 | 2.92 | 9.42 | H |
| | 2544.93 | -71.30 | -13 | -58.30 | -77.36 | -77.15 | 2.63 | 10.63 | H |
| | 3393.24 | -69.70 | -13 | -56.70 | -77.70 | -75.45 | 4.74 | 12.64 | H |
| | 4233 | -67.94 | -13 | -54.94 | -80.02 | -72.31 | 5.11 | 11.63 | H |
| | 1696.62 | -62.32 | -13 | -49.32 | -64.16 | -66.67 | 2.92 | 9.42 | V |
| | 2544.93 | -71.42 | -13 | -58.42 | -77.37 | -77.27 | 2.63 | 10.63 | V |
| | 3393.24 | -69.77 | -13 | -56.77 | -77.80 | -75.52 | 4.74 | 12.64 | V |
| | 4233 | -68.22 | -13 | -55.22 | -80.18 | -72.59 | 5.11 | 11.63 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| WCDMA Band II(RMC 12.2Kbps) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | EIRP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 3704.8 | -63.24 | -13 | -50.24 | -74.49 | -70.43 | 5.36 | 12.55 | H |
| | 5557.2 | -63.19 | -13 | -50.19 | -79.07 | -68.69 | 7.52 | 13.02 | H |
| | 7409.6 | -61.63 | -13 | -48.63 | -79.95 | -65.10 | 7.85 | 11.32 | H |
| | 3704.8 | -60.21 | -13 | -47.21 | -72.68 | -67.40 | 5.36 | 12.55 | V |
| | 5557.2 | -63.90 | -13 | -50.90 | -80.22 | -69.40 | 7.52 | 13.02 | V |
| | 7409.6 | -61.94 | -13 | -48.94 | -80.16 | -65.41 | 7.85 | 11.32 | V |
| Middle | 3760 | -63.52 | -13 | -50.52 | -74.77 | -70.76 | 5.36 | 12.60 | H |
| | 5640 | -62.98 | -13 | -49.98 | -78.86 | -68.56 | 7.52 | 13.10 | H |
| | 7520 | -61.68 | -13 | -48.68 | -80.00 | -65.17 | 7.85 | 11.34 | H |
| | 3760 | -61.39 | -13 | -48.39 | -73.86 | -68.63 | 5.36 | 12.60 | V |
| | 5640 | -63.66 | -13 | -50.66 | -79.98 | -69.24 | 7.52 | 13.10 | V |
| | 7520 | -61.75 | -13 | -48.75 | -79.97 | -65.24 | 7.85 | 11.34 | V |
| Highest | 3815.2 | -66.06 | -13 | -53.06 | -77.31 | -73.35 | 5.36 | 12.65 | H |
| | 5722.8 | -60.90 | -13 | -47.90 | -76.78 | -66.58 | 7.52 | 13.20 | H |
| | 7630.4 | -61.41 | -13 | -48.41 | -79.73 | -64.92 | 7.85 | 11.36 | H |
| | 3815.2 | -64.77 | -13 | -51.77 | -77.24 | -72.06 | 5.36 | 12.65 | V |
| | 5722.8 | -63.06 | -13 | -50.06 | -79.38 | -68.74 | 7.52 | 13.20 | V |
| | 7630.4 | -61.74 | -13 | -48.74 | -79.96 | -65.25 | 7.85 | 11.36 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| WCDMA Band IV(RMC 12.2Kbps) | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | Frequency ( MHz ) | EIRP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest | 3424.8 | -44.65 | -13 | -31.65 | -58.35 | -52.60 | 4.63 | 12.58 | H |
| | 5137.2 | -62.62 | -13 | -49.62 | -80.55 | -69.01 | 6.28 | 12.67 | H |
| | 6849.6 | -59.74 | -13 | -46.74 | -79.36 | -64.37 | 8.32 | 12.95 | H |
| | 3424.8 | -43.70 | -13 | -30.70 | -56.58 | -51.65 | 4.63 | 12.58 | V |
| | 5137.2 | -66.80 | -13 | -53.80 | -80.41 | -73.19 | 6.28 | 12.67 | V |
| | 6849.6 | -60.49 | -13 | -47.49 | -79.61 | -65.12 | 8.32 | 12.95 | V |
| Middle | 3465.2 | -44.76 | -13 | -31.76 | -58.46 | -52.73 | 4.63 | 12.60 | H |
| | 5197.8 | -62.84 | -13 | -49.84 | -80.77 | -69.29 | 6.25 | 12.70 | H |
| | 6930.4 | -60.06 | -13 | -47.06 | -79.68 | -64.83 | 8.23 | 13.00 | H |
| | 3465.2 | -47.12 | -13 | -34.12 | -58.53 | -55.09 | 4.63 | 12.6 | V |
| | 5197.8 | -67.23 | -13 | -54.23 | -80.84 | -73.68 | 6.25 | 12.7 | V |
| | 6930.4 | -60.82 | -13 | -47.82 | -79.94 | -65.59 | 8.23 | 13 | V |
| Highest | 3505.2 | -47.25 | -13 | -34.25 | -60.95 | -55.22 | 4.69 | 12.66 | H |
| | 5257.8 | -62.69 | -13 | -49.69 | -80.62 | -69.10 | 6.34 | 12.75 | H |
| | 7010.4 | -60.50 | -13 | -47.50 | -80.12 | -65.24 | 8.38 | 13.12 | H |
| | 3505.2 | -49.87 | -13 | -36.87 | -61.28 | -57.84 | 4.69 | 12.66 | V |
| | 5257.8 | -67.06 | -13 | -54.06 | -80.67 | -73.47 | 6.34 | 12.75 | V |
| | 7010.4 | -61.05 | -13 | -48.05 | -80.17 | -65.79 | 8.38 | 13.12 | V |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

# Appendix C. Test Setup Photographs