FCC RF Test Report

APPLICANT	:	ASUSTeK COMPUTER INC.
EQUIPMENT	:	ASUS Phone (Mobile Phone)
BRAND NAME	:	ASUS
MODEL NAME	:	ASUS_X01AD
FCC ID	:	MSQX01AD
STANDARD	:	FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jul. 20, 2018 and completely tested on Oct. 30, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang

Approved by: James Huang / Manager

TESTING
NVLAP LAB CODE 600155-0

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 8
1.8 Applicable Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**
2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration 10
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 11
3 CONDUCTED TEST RESULT **12**
3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power and ERP/EIRP 13
3.5 Peak-to-Average Ratio 14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 15
3.7 Conducted Band Edge 16
3.8 Conducted Spurious Emission 17
3.9 Frequency Stability 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 19
4.4 Field Strength of Spurious Radiation Measurement 20
5 LIST OF MEASURING EQUIPMENT **21**
6 UNCERTAINTY OF EVALUATION **22**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG872010A	Rev. 01	Initial issue of report	Nov. 07, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 37.45 dB at 1648.00 MHz

1 General Description

1.1 Applicant

ASUSTeK COMPUTER INC.
4F, No.150, Li-Te Rd., Peitou, Taipei 112, Taiwan

1.2 Manufacturer

ASUSTeK COMPUTER INC.
4F, No.150, Li-Te Rd., Peitou, Taipei 112, Taiwan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	ASUS Phone (Mobile Phone)
Brand Name	ASUS
Model Name	ASUS_X01AD
FCC ID	MSQX01AD
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR/EDR/LE
IMEI Code	Conducted: 352203100056807/352203100056815 Radiation: 352203100056922/352203100056930
HW Version	A8r8a
SW Version	DailyBuildOPM1.WW_Phone-15.2016.1805.000-20180913
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz **WCDMA:** Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz **WCDMA:** Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	**GSM/GPRS/EDGE:** 850: 32.73 dBm 1900: 30.50 dBm **WCDMA:** Band V: 23.54 dBm Band II: 23.89 dBm Band IV: 23.62 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: -7.00 dBi PCS Band: -6.00 dBi AWS Band: -6.00 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.2280	0.0407 ppm	242KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.0667	0.0335 ppm	236KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.0275	0.0514 ppm	4M11F9W
Part 24	GSM1900 GSM	GMSK	0.2818	0.0176 ppm	244KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.1107	0.0186 ppm	242KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.0615	0.0112 ppm	4M11F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.0578	0.0144 ppm	4M12F9W

1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH06-KS	CN5013	630927

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to10th harmonic for WCDMA Band IV.
3. 30 MHz to10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.3 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.3 + 10 = 14.3 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power

3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 19, 2018	Oct. 17, 2018	Apr. 18, 2019	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 11, 2018	Oct. 17, 2018	Oct. 10, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471084	10Hz-44GHz	Jun. 25, 2018	Oct. 30, 2018	Jun. 24, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Jan. 29, 2018	Oct. 30, 2018	Jan. 28, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Oct. 30, 2018	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Oct. 30, 2018	Feb. 06, 2019	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Oct. 30, 2018	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35 -HG	2014749	18~40GHz	Feb. 08, 2018	Oct. 30, 2018	Feb. 07, 2019	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Oct. 30, 2018	Apr. 16, 2019	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Dec. 16, 2017	Oct. 30, 2018	Dec. 15, 2018	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 30, 2018	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 30, 2018	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 30, 2018	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.0dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.0dB

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.53	32.34	32.73	29.89	30.50	29.94
GPRS class 8	32.52	32.66	32.72	29.90	30.49	29.93
GPRS class 10	32.23	32.34	32.10	29.30	29.69	29.38
GPRS class 11	30.31	30.39	30.36	27.31	28.04	27.39
GPRS class 12	28.57	28.58	28.62	25.66	26.36	25.78
EGPRS class 8	27.39	27.30	27.16	25.90	26.44	25.82
EGPRS class 10	26.18	26.07	25.93	25.78	26.28	25.64
EGPRS class 11	24.49	24.41	24.16	24.10	24.55	23.89
EGPRS class 12	22.91	22.72	22.59	22.41	22.89	22.26

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.53	23.45	23.38	23.67	23.88	23.52	23.48	23.60	23.54
RMC 12.2K	23.54	23.46	23.38	23.68	23.89	23.54	23.49	23.62	23.55
HSDPA Subtest-1	22.20	22.41	22.47	22.63	22.61	22.56	22.42	22.24	22.39
HSDPA Subtest-2	22.23	22.41	22.49	22.59	22.66	22.59	22.44	22.25	22.42
HSDPA Subtest-3	21.72	21.93	21.94	22.08	22.13	22.16	21.91	21.73	21.89
HSDPA Subtest-4	21.73	21.94	21.94	22.08	22.14	22.11	21.91	21.77	21.93
DC-HSDPA Subtest-1	22.20	22.41	22.47	22.48	22.63	22.59	22.23	22.09	22.15
DC-HSDPA Subtest-2	22.23	22.41	22.49	22.51	22.62	22.48	22.20	22.05	22.15
DC-HSDPA Subtest-3	21.72	21.93	21.94	22.05	22.08	22.08	21.78	21.59	21.65
DC-HSDPA Subtest-4	21.73	21.94	21.94	22.01	22.01	22.15	21.80	21.58	21.62
HSUPA Subtest-1	22.17	22.31	22.47	22.60	22.60	22.56	22.43	22.22	22.33
HSUPA Subtest-2	20.19	20.34	20.44	20.58	20.59	20.55	20.38	20.23	20.37
HSUPA Subtest-3	21.16	21.38	21.36	21.57	21.54	21.58	21.38	21.24	21.35
HSUPA Subtest-4	20.19	20.34	20.37	20.56	20.57	20.57	20.40	20.25	20.34
HSUPA Subtest-5	22.20	22.40	22.40	22.60	22.60	22.50	22.40	22.20	22.40
HSPA+ (16QAM) Subtest-1	20.60	20.50	20.70	21.00	20.87	20.80	20.90	21.10	21.20

ERP/EIRP

GSM850 (G_T - L_C= -7.00 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.53	32.34	32.73
Conducted Power (Watts)	1.7906	1.7140	1.8750
ERP(dBm)	23.38	23.19	23.58
ERP(Watts)	0.2178	0.2084	0.2280

EDGE850 (G_T - L_C= -7.00 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	27.39	27.30	27.16
Conducted Power (Watts)	0.5483	0.5370	0.5200
ERP(dBm)	18.24	18.15	18.01
ERP(Watts)	0.0667	0.0653	0.0632

GSM1900 (G_T - L_C= -6.00 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	29.89	30.50	29.94
Conducted Power (Watts)	0.9750	1.1220	0.9863
EIRP(dBm)	23.89	24.50	23.94
EIRP(Watts)	0.2449	0.2818	0.2477

EDGE1900 (G_T - L_C= -6.00 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	25.90	26.44	25.82
Conducted Power (Watts)	0.3890	0.4406	0.3819
EIRP(dBm)	19.90	20.44	19.82
EIRP(Watts)	0.0977	0.1107	0.0959

WCDMA Band V (G_T - L_C = -7.00 dB)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.4	846.6
Conducted Power (dBm)	23.54	23.46	23.38
Conducted Power (Watts)	0.2259	0.2218	0.2178
ERP(dBm)	14.39	14.31	14.23
ERP(Watts)	0.0275	0.0270	0.0265

WCDMA Band II (G_T - L_C = -6.00 dB)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Conducted Power (dBm)	23.68	23.89	23.54
Conducted Power (Watts)	0.2333	0.2449	0.2259
EIRP(dBm)	17.68	17.89	17.54
EIRP(Watts)	0.0586	0.0615	0.0568

WCDMA Band IV (G_T - L_C = -6.00 dB)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	23.49	23.62	23.55
Conducted Power (Watts)	0.2234	0.2301	0.2265
EIRP(dBm)	17.49	17.62	17.55
EIRP(Watts)	0.0561	0.0578	0.0569

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	3.51	PASS
Middle CH	0.20	3.30	
Highest CH	0.17	3.19	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.20	3.28	PASS
Middle CH	0.14	3.28	
Highest CH	0.17	3.30	

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.25	2.96	2.41	PASS
Middle CH	3.13	3.01	3.28	
Highest CH	3.33	2.96	2.72	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.315	0.314
Middle CH	0.316	0.314
Highest CH	0.318	0.316

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.318	0.314
Middle CH	0.315	0.310
Highest CH	0.317	0.314

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.675	4.705	4.735
Middle CH	4.685	4.705	4.685
Highest CH	4.685	4.715	4.715

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Lowest Channel



Middle Channel



Middle Channel



Highest Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.235
Middle CH	0.242	0.236
Highest CH	0.242	0.235

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.241	0.240
Middle CH	0.244	0.242
Highest CH	0.242	0.241

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.11	4.10	4.12
Middle CH	4.11	4.11	4.11
Highest CH	4.11	4.11	4.11

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.99550 MHz	-37.57 dBm	-24.57 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.98104 MHz	-17.73 dBm	-4.73 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.21208 MHz	22.59 dBm	-12.41 dB

Date: 17.OCT.2018 21:28:09

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.86776 MHz	22.47 dBm	-12.53 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01896 MHz	-18.23 dBm	-5.23 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.01249 MHz	-37.95 dBm	-24.95 dB

Date: 17.OCT.2018 21:29:37

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.97453 MHz	-44.07 dBm	-31.07 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.96707 MHz	-23.21 dBm	-10.21 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.13922 MHz	18.03 dBm	-16.97 dB

Date: 17.OCT.2018 21:43:39

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.77894 MHz	17.72 dBm	-17.28 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.00898 MHz	-26.65 dBm	-13.65 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.04246 MHz	-44.58 dBm	-31.58 dB

Date: 17.OCT.2018 21:45:12

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84896 GHz	-37.31 dBm	-24.31 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-18.15 dBm	-5.15 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85018 GHz	22.04 dBm	-12.96 dB

Date: 17.OCT.2018 22:07:52

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90987 GHz	21.87 dBm	-13.13 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-20.09 dBm	-7.09 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91103 GHz	-35.98 dBm	-22.98 dB

Date: 17.OCT.2018 22:09:24

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-38.67 dBm	-25.67 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84997 GHz	-24.12 dBm	-11.12 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85019 GHz	18.21 dBm	-16.79 dB

Date: 17.OCT.2018 22:22:27

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90984 GHz	17.44 dBm	-17.56 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91003 GHz	-28.22 dBm	-15.22 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-38.61 dBm	-25.61 dB

Date: 17.OCT.2018 22:23:57

WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.82767 MHz	-27.95 dBm	-14.95 dB
823.000 MHz	824.000 MHz	50.000 kHz	823.85130 MHz	-25.39 dBm	-12.39 dB
824.000 MHz	829.000 MHz	100.000 kHz	826.40010 MHz	8.27 dBm	-26.73 dB

Date: 17.OCT.2018 22:40:25

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
844.000 MHz	849.000 MHz	100.000 kHz	845.69580 MHz	7.83 dBm	-27.17 dB
849.000 MHz	850.000 MHz	50.000 kHz	849.15669 MHz	-27.33 dBm	-14.33 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.14735 MHz	-31.88 dBm	-18.88 dB

Date: 17.OCT.2018 22:43:09

WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84900 GHz	-26.84 dBm	-13.84 dB
1.849 GHz	1.850 GHz	50.000 kHz	1.85000 GHz	-28.52 dBm	-15.52 dB
1.850 GHz	1.855 GHz	100.000 kHz	1.85263 GHz	8.43 dBm	-26.57 dB

Date: 17.OCT.2018 22:57:48

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.905 GHz	1.910 GHz	100.000 kHz	1.90672 GHz	8.31 dBm	-26.69 dB
1.910 GHz	1.911 GHz	50.000 kHz	1.91000 GHz	-27.39 dBm	-14.39 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91114 GHz	-22.22 dBm	-9.22 dB

Date: 17.OCT.2018 23:00:32

WCDMA Band IV (RMC 12.2Kbps)	
Lowest Band Edge	**Highest Band Edge**



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.705 GHz	1.709 GHz	1.000 MHz	1.70893 GHz	-20.57 dBm	-7.57 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.71000 GHz	-25.01 dBm	-12.01 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71238 GHz	8.31 dBm	-26.69 dB

Date: 17.OCT.2018 23:15:52



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75175 GHz	8.09 dBm	-26.91 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75500 GHz	-27.39 dBm	-14.39 dB
1.756 GHz	1.760 GHz	1.000 MHz	1.75602 GHz	-22.80 dBm	-9.80 dB

Date: 17.OCT.2018 23:18:38