FCC RF Test Report

APPLICANT	:	ASUSTeK COMPUTER INC.
EQUIPMENT	:	ASUS Phone(Mobile phone)
BRAND NAME	:	ASUS
MODEL NAME	:	ASUS_Z01GS
FCC ID	:	MSQZ01GS
STANDARD	:	FCC 47 CFR Part 2, and 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 08, 2017 and testing was completed on Sep. 29, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA-603-E-2016 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Modification of EUT 6
1.5 Testing Site 7
1.6 Applied Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration and system 10
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 11

3 TEST RESULT **12**

3.1 Conducted Output Power Measurement 12
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement 13
3.3 Emissions Mask Measurement 14
3.4 Emissions Mask – Out Of Band Emissions Measurement 16
3.5 Field Strength of Spurious Radiation Measurement 17
3.6 Frequency Stability Measurement 19

4 LIST OF MEASURING EQUIPMENT **21**

5 UNCERTAINTY OF EVALUATION **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG740843D	Rev. 01	Initial issue of report	Oct. 03, 2017
FG740843D	Rev. 02	Revising ANSI / TIA / EIA-603-C-2004 information.	Oct. 13, 2017
FG740843D	Rev. 03	Revising ANSI / TIA-603-E-2016 information.	Oct. 17, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< $50+10\log_{10}$(P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< $43+10\log_{10}$(P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 19.98 dB at 1632.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

ASUSTeK COMPUTER INC.
4F, No. 150, LI-TE RD., PEITOU, TAIPEI, TAIWAN

1.2 Manufacturer

COTEK ELECTRONICS (SUZHOU) CO., LTD.
No.288, Mayun Road, Suzhou Hi-and-New Tech Park, Jiangsu, PRC

1.3 Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, FM Receiver, NFC, and GPS.

Product Specification subjective to this standard	
Sample 1	EUT with SKU 1
Sample 2	EUT with SKU 2
Sample 3	EUT with SKU 3
Sample 4	EUT with SKU 4
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo : PIFA Antenna NFC: Loop Antenna FM: Integral Antenna (Earphone acting as FM antenna deemed as an integral antenna)

<Sample Information>

SKU MB	SKU1	SKU2
DDR4X	6G/ Hynix	6G/ Hynix
UFS 2.1	128G/ Toshiba	64G/ Toshiba
CPU	MSM-8998	
TP Module	TIANMA//TA055VVHM09-03 ON CELL	TIANMA/TA055VVHM09-05 ON CELL
Front Camera	CHICONY/CBAH81120003870LH	CHICONY/CBAH81120003871LH
Rear Camera	12M+16M/SEMCO/MOMDM82PG3A	
Battery	ATL POLY/C11P1701/SMP	

SKU MB	SKU3	SKU4
DDR4X	6G/ Samsung	6G/ Hynix
UFS 2.1	256G/ Samsung	64G/ Samsung
CPU	MSM-8998	MSM-8998
TP Module	TIANMA//TA055VVHM08-05	TIANMA//TA055VVHM09-05
Front Camera	CHICONY/CBAH81120003871LH	
Rear Camera	12M+16M/SEMCO/MOMDM82PG3A	
Battery	ATL POLY/C11P1701/SMP	

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Site

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA-603-E-2016
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v	v			v	v	v
Frequency Stability	26				v	v	-	v					v		v	
E.R.P.	26	v	v	v	v	v	-	v	v	v	v			v		
Radiated Spurious Emission	26	v	v	v	v	v	-	v			v			v	v	v
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log_{10}(f/6.1) decibels or 50 + 10 Log_{10}(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log_{10}(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E-2016. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 11, 2016	Aug. 01, 2017 ~ Sep. 29, 2017	Oct. 10, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 04, 2016	Aug. 01, 2017 ~ Sep. 29, 2017	Nov. 03, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30℃~70℃	Sep. 01, 2016	Aug. 01, 2017 ~ Aug. 16, 2017	Aug. 31, 2017	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30℃~70℃	Aug. 28, 2017	Aug. 28, 2017 ~ Sep. 29, 2017	Aug. 27, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~5A	Oct. 03, 2016	Aug. 01, 2017 ~ Sep. 29, 2017	Oct. 02, 2017	Conducted (TH05-HY)
Coupler	Warison	1-18GHz 20dB 25WSMA Directional Coupler	#B	1G~18GHz	Feb. 20, 2017	Aug. 01, 2017 ~ Sep. 29, 2017	Feb. 19, 2018	Conducted (TH05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Jul. 17, 2018	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 15, 2016	Sep. 01, 2017 ~ Sep. 18, 2017	Oct. 14, 2017	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 23, 2016	Sep. 01, 2017 ~ Sep. 18, 2017	Dec. 22, 2017	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 25, 2016	Sep. 01, 2017 ~ Sep. 18, 2017	Oct. 24, 2017	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 23, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Mar. 22, 2018	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 01, 2016	Sep. 01, 2017 ~ Sep. 18, 2017	Nov. 30, 2017	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Sep. 01, 2017 ~ Sep. 18, 2017	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Sep. 01, 2017 ~ Sep. 18, 2017	N/A	Radiation (03CH12-HY)
Attenuator	Fairview Microwave	SA18S5W-10	n/a	10db	Mar. 24, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Mar. 23, 2018	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Apr. 26, 2018	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1212	1GHz ~ 18GHz	Mar. 17, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Mar. 16, 2018	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	Sep. 01, 2017 ~ Sep. 18, 2017	Nov. 07, 2017	Radiation (03CH12-HY)
Signal Generator	Anritsu	MG3694C	163401	0.1Hz~40GHz	Jan. 04, 2017	Sep. 01, 2017 ~ Sep. 18, 2017	Jan. 03, 2018	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.36

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.70

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.98

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.62	-	-
15	1	37		22.60	-	-
15	1	74		22.50	-	-
15	36	0		21.63	-	-
15	36	20		21.62	-	-
15	36	39		21.53	-	-
15	75	0		21.63	-	-
15	1	0	16-QAM	21.92	-	-
15	1	37		21.85	-	-
15	1	74		21.95	-	-
15	36	0		20.66	-	-
15	36	20		20.74	-	-
15	36	39		20.60	-	-
15	75	0		20.68	-	-
15	1	0	64-QAM	20.70	-	-
15	1	37		20.74	-	-
15	1	74		20.61	-	-
15	36	0		19.59	-	-
15	36	20		19.65	-	-
15	36	39		19.57	-	-
15	75	0		19.65	-	-
10	1	0	QPSK	-	22.57	-
10	1	25		-	22.61	-
10	1	49		-	22.60	-
10	25	0		-	21.65	-
10	25	12		-	21.63	-
10	25	25		-	21.57	-
10	50	0		-	21.58	-
10	1	0	16-QAM	-	21.63	-
10	1	25		-	21.64	-
10	1	49		-	21.66	-
10	25	0		-	20.65	-
10	25	12		-	20.66	-
10	25	25		-	20.52	-
10	50	0		-	20.63	-
10	1	0	64-QAM	-	20.80	-
10	1	25		-	20.79	-
10	1	49		-	20.90	-
10	25	0		-	19.60	-
10	25	12		-	19.57	-
10	25	25		-	19.52	-
10	50	0		-	19.65	-

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.51	22.56	22.66
5	1	12		22.46	22.59	22.57
5	1	24		22.54	22.54	22.53
5	12	0		21.64	21.62	21.63
5	12	7		21.58	21.60	21.62
5	12	13		21.57	21.59	21.57
5	25	0		21.59	21.61	21.63
5	1	0	16-QAM	21.75	21.87	21.75
5	1	12		21.73	21.85	21.71
5	1	24		21.83	21.83	21.69
5	12	0		20.54	20.60	20.68
5	12	7		20.56	20.59	20.66
5	12	13		20.49	20.56	20.61
5	25	0		20.58	20.58	20.71
5	1	0	64-QAM	20.69	20.77	20.91
5	1	12		20.63	20.67	20.83
5	1	24		20.69	20.66	20.83
5	12	0		19.61	19.65	19.76
5	12	7		19.62	19.66	19.76
5	12	13		19.56	19.64	19.71
5	25	0		19.60	19.63	19.58
3	1	0	QPSK	22.48	22.55	**22.68**
3	1	8		22.44	22.54	22.60
3	1	14		22.47	22.51	22.50
3	8	0		21.56	21.58	21.58
3	8	4		21.58	21.59	21.61
3	8	7		21.54	21.59	21.55
3	15	0		21.55	21.59	21.55
3	1	0	16-QAM	21.87	21.98	21.49
3	1	8		21.89	21.97	21.45
3	1	14		21.85	21.87	21.47
3	8	0		20.64	20.68	20.67
3	8	4		20.67	20.72	20.70
3	8	7		20.61	20.70	20.69
3	15	0		20.49	20.70	20.62
3	1	0	64-QAM	20.87	20.79	20.75
3	1	8		20.90	20.77	20.58
3	1	14		20.89	20.74	20.56
3	8	0		19.63	19.77	19.65
3	8	4		19.69	19.79	19.66
3	8	7		19.58	19.76	19.63
3	15	0		19.61	19.56	19.61

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.46	22.41	22.46
1.4	1	3		22.54	22.48	22.53
1.4	1	5		22.43	22.38	22.45
1.4	3	0		22.45	22.47	22.51
1.4	3	1		22.50	22.50	22.59
1.4	3	3		22.48	22.48	22.52
1.4	6	0		21.52	21.51	21.53
1.4	1	0	16-QAM	21.93	21.44	21.51
1.4	1	3		21.99	21.39	21.58
1.4	1	5		21.92	21.31	21.50
1.4	3	0		21.50	21.55	21.40
1.4	3	1		21.55	21.57	21.50
1.4	3	3		21.52	21.51	21.57
1.4	6	0		20.54	20.46	20.58
1.4	1	0	64-QAM	20.65	20.77	20.76
1.4	1	3		20.72	20.81	20.79
1.4	1	5		20.70	20.73	20.70
1.4	3	0		20.65	20.69	20.61
1.4	3	1		20.66	20.73	20.63
1.4	3	3		20.63	20.68	20.57
1.4	6	0		19.51	19.49	19.62

LTE Band 26_Part 90S

Peak-to-Average Ratio

Mode	LTE Band 26 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	4	5.16	4.75	6.06	
Highest CH	-	-	-	-	
Mode	LTE Band 26 / 10MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH			-	-	PASS
Middle CH	6.23	6.78	-	-	
Highest CH			-	-	

LTE Band 26 / 10MHz / QPSK

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 26 / 10MHz / 16QAM

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 26 / 10MHz / 64QAM	
Middle Channel / 1RB	Middle Channel / Full RB
	

26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.22	1.23	3.00	2.96	4.94	4.90	-	-	14.42	14.18	-	-
Middle CH	1.22	1.23	3.04	3.03	4.92	4.87	9.69	9.81	-	-	-	-
Highest CH	1.22	1.23	3.02	3.05	4.88	4.96	-	-	-	-	-	-
Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.22	-	3.02	-	4.9	-	-	-	14.27	-	-	-
Middle CH	1.23	-	3.03	-	4.91	-	9.87	-	-	-	-	-
Highest CH	1.23	-	2.98	-	4.89	-	-	-	-	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / 64QAM



Lowest Channel / 3MHz / 64QAM



Middle Channel / 1.4MHz / 64QAM



Middle Channel / 3MHz / 64QAM



Highest Channel / 1.4MHz / 64QAM



Highest Channel / 3MHz / 64QAM



LTE Band 26

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



LTE Band 26	
Middle Channel / 15MHz / 64QAM	
	

Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.08	2.72	2.72	4.5	4.47	-	-	13.43	13.43	-	-
Middle CH	1.09	1.08	2.7	2.72	4.49	4.49	9.03	9.05	-	-	-	-
Highest CH	1.09	1.09	2.72	2.72	4.51	4.49	-	-	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	1.1	-	2.72	-	4.48	-	-	-	13.43	-	-	-
Middle CH	1.09	-	2.73	-	4.49	-	9.03	-	-	-	-	-
Highest CH	1.09	-	2.72	-	4.49	-	-	-	-	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Date: 12.SEP.2017 23:49:51

Lowest Channel / 1.4MHz / 16QAM



Date: 12.SEP.2017 23:50:01

Middle Channel / 1.4MHz / QPSK



Date: 12.SEP.2017 23:52:21

Middle Channel / 1.4MHz / 16QAM



Date: 12.SEP.2017 23:52:31

Highest Channel / 1.4MHz / QPSK



Date: 12.SEP.2017 23:54:51

Highest Channel / 1.4MHz / 16QAM



Date: 12.SEP.2017 23:55:01

LTE Band 26

Lowest Channel / 3MHz / QPSK



Date: 12.SEP.2017 23:25:45

Lowest Channel / 3MHz / 16QAM



Date: 12.SEP.2017 23:25:55

Middle Channel / 3MHz / QPSK



Date: 12.SEP.2017 23:28:15

Middle Channel / 3MHz / 16QAM



Date: 12.SEP.2017 23:28:25

Highest Channel / 3MHz / QPSK



Date: 12.SEP.2017 23:30:45

Highest Channel / 3MHz / 16QAM



Date: 12.SEP.2017 23:30:55

LTE Band 26

Lowest Channel / 5MHz / QPSK



Date: 12.SEP.2017 23:33:16

Lowest Channel / 5MHz / 16QAM



Date: 12.SEP.2017 23:33:26

Middle Channel / 5MHz / QPSK



Date: 12.SEP.2017 23:35:46

Middle Channel / 5MHz / 16QAM



Date: 12.SEP.2017 23:35:56

Highest Channel / 5MHz / QPSK



Date: 12.SEP.2017 23:38:16

Highest Channel / 5MHz / 16QAM



Date: 12.SEP.2017 23:38:26

LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 26

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / 64QAM



Date: 29.SEP.2017 14:58:57

Lowest Channel / 3MHz / 64QAM



Date: 29.SEP.2017 14:55:40

Middle Channel / 1.4MHz / 64QAM



Date: 29.SEP.2017 14:59:17

Middle Channel / 3MHz / 64QAM



Date: 29.SEP.2017 14:56:00

Highest Channel / 1.4MHz / 64QAM



Date: 29.SEP.2017 14:59:37

Highest Channel / 3MHz / 64QAM



Date: 29.SEP.2017 14:56:20

LTE Band 26

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



LTE Band 26	
Middle Channel / 15MHz / 64QAM	
	

Conducted Band Edge

LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 22.53 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-24.66 dBm	-47.19 dB	-11.66 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-27.84 dBm	-50.37 dB	-6.84 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.41406 MHz	-54.65 dBm	-77.18 dB	-33.65 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.58978 MHz	-47.68 dBm	-70.22 dB	-34.68 dB

Date: 12.SEP.2017 22:45:18

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 22.46 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.36671 MHz	-49.03 dBm	-71.49 dB	-36.03 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.56719 MHz	-55.07 dBm	-77.53 dB	-34.07 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-29.68 dBm	-52.14 dB	-8.68 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-24.74 dBm	-47.20 dB	-11.74 dB

Date: 12.SEP.2017 22:49:53

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.74 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-30.22 dBm	-51.96 dB	-17.22 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.96719 MHz	-37.22 dBm	-58.96 dB	-16.22 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.42344 MHz	-38.82 dBm	-60.56 dB	-17.82 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44185 MHz	-33.30 dBm	-55.04 dB	-20.30 dB

Date: 12.SEP.2017 22:47:36

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.27 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55815 MHz	-30.04 dBm	-51.31 dB	-17.04 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-35.59 dBm	-56.85 dB	-14.59 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-34.14 dBm	-55.40 dB	-13.14 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-29.09 dBm	-50.35 dB	-16.09 dB

Date: 12.SEP.2017 22:52:12

LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-25.19 dBm	-47.19 dB	-12.19 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-29.46 dBm	-51.45 dB	-8.46 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.42344 MHz	-55.36 dBm	-77.36 dB	-34.36 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.58978 MHz	-48.50 dBm	-70.49 dB	-35.50 dB

Date: 12.SEP.2017 22:46:27

Highest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.52334 MHz	-48.75 dBm	-70.20 dB	-35.75 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.58594 MHz	-55.69 dBm	-77.14 dB	-34.69 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-31.79 dBm	-53.25 dB	-10.79 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-26.90 dBm	-48.36 dB	-13.90 dB

Date: 12.SEP.2017 22:51:03

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.91464 MHz	-30.90 dBm	-51.84 dB	-17.90 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-37.97 dBm	-58.91 dB	-16.97 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-38.83 dBm	-59.77 dB	-17.83 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44185 MHz	-32.41 dBm	-53.35 dB	-19.41 dB

Date: 12.SEP.2017 22:48:45

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55815 MHz	-31.42 dBm	-51.96 dB	-18.42 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-36.41 dBm	-56.95 dB	-15.41 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-34.74 dBm	-55.28 dB	-13.74 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.05055 MHz	-29.97 dBm	-50.51 dB	-16.97 dB

Date: 12.SEP.2017 22:53:21

LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.36 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-27.66 dBm	-48.02 dB	-14.66 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-34.23 dBm	-54.59 dB	-13.23 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.41406 MHz	-55.94 dBm	-76.30 dB	-34.94 dB
737.500 kHz	3.000 MHz	100.000 kHz	816.41647 MHz	-53.22 dBm	-73.58 dB	-40.22 dB

Date: 29.SEP.2017 17:38:21

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.52 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.34930 MHz	-52.34 dBm	-72.86 dB	-39.34 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-58.26 dBm	-78.78 dB	-37.26 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-31.70 dBm	-52.22 dB	-10.70 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-26.10 dBm	-46.62 dB	-13.10 dB

Date: 29.SEP.2017 09:41:36

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.16 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.94945 MHz	-33.06 dBm	-52.22 dB	-20.06 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-37.84 dBm	-57.00 dB	-16.84 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-37.30 dBm	-56.46 dB	-16.30 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44185 MHz	-31.75 dBm	-50.92 dB	-18.75 dB

Date: 29.SEP.2017 15:10:56

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.46 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55815 MHz	-29.91 dBm	-49.38 dB	-16.91 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-35.26 dBm	-54.73 dB	-14.26 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.01406 MHz	-33.35 dBm	-52.81 dB	-12.35 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-27.75 dBm	-47.21 dB	-14.75 dB

Date: 29.SEP.2017 09:42:45

LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-18.30 dBm	-40.71 dB	-5.30 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-21.44 dBm	-43.85 dB	-0.44 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-56.42 dBm	-78.83 dB	-35.42 dB
1.538 MHz	5.000 MHz	100.000 kHz	818.01540 MHz	-49.26 dBm	-71.66 dB	-36.26 dB

Date: 12.SEP.2017 22:54:30

Highest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.01357 MHz	-49.86 dBm	-71.65 dB	-36.86 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-54.29 dBm	-76.09 dB	-33.29 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-22.97 dBm	-44.77 dB	-1.97 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-18.66 dBm	-40.46 dB	-5.66 dB

Date: 12.SEP.2017 22:59:07

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-25.82 dBm	-47.60 dB	-12.82 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-29.76 dBm	-51.54 dB	-8.76 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-29.67 dBm	-51.45 dB	-8.67 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04474 MHz	-25.99 dBm	-47.77 dB	-12.99 dB

Date: 12.SEP.2017 22:56:48

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-29.73 dBm	-51.24 dB	-16.73 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-30.82 dBm	-52.34 dB	-9.82 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-29.58 dBm	-51.10 dB	-8.58 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-24.90 dBm	-46.41 dB	-11.90 dB

Date: 12.SEP.2017 23:01:25

LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-18.17 dBm	-39.77 dB	-5.17 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-21.64 dBm	-43.24 dB	-0.64 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-56.44 dBm	-78.04 dB	-35.44 dB
1.538 MHz	5.000 MHz	100.000 kHz	818.02989 MHz	-48.60 dBm	-70.21 dB	-35.60 dB

Date: 12.SEP.2017 22:55:39

Highest Band Edge /1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.05703 MHz	-49.73 dBm	-71.16 dB	-36.73 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-53.69 dBm	-75.13 dB	-32.69 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-22.97 dBm	-44.41 dB	-1.97 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-18.40 dBm	-39.83 dB	-5.40 dB

Date: 12.SEP.2017 23:00:16

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-27.07 dBm	-47.84 dB	-14.07 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-30.77 dBm	-51.54 dB	-9.77 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-30.53 dBm	-51.30 dB	-9.53 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04474 MHz	-26.25 dBm	-47.02 dB	-13.25 dB

Date: 12.SEP.2017 22:57:58

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-28.13 dBm	-48.71 dB	-15.13 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-31.43 dBm	-52.01 dB	-10.43 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-30.63 dBm	-51.21 dB	-9.63 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-28.98 dBm	-49.57 dB	-15.98 dB

Date: 12.SEP.2017 23:02:35

LTE Band 26 / 3MHz / 64QAM

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-20.21 dBm	-40.41 dB	-7.21 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-25.89 dBm	-46.10 dB	-4.89 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-59.75 dBm	-79.96 dB	-38.75 dB
1.538 MHz	5.000 MHz	100.000 kHz	818.07335 MHz	-53.52 dBm	-73.73 dB	-40.52 dB

Date: 29.SEP.2017 09:43:53

Highest Band Edge /1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-54.11 dBm	-74.67 dB	-41.11 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-59.24 dBm	-79.80 dB	-38.24 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-25.42 dBm	-45.98 dB	-4.42 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-20.91 dBm	-41.47 dB	-7.91 dB

Date: 29.SEP.2017 09:46:10

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-27.90 dBm	-47.36 dB	-14.90 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-31.85 dBm	-51.31 dB	-10.85 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-32.13 dBm	-51.59 dB	-11.13 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.05923 MHz	-29.94 dBm	-49.40 dB	-16.94 dB

Date: 29.SEP.2017 09:45:01

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-29.35 dBm	-48.75 dB	-16.35 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-32.73 dBm	-52.14 dB	-11.73 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-31.47 dBm	-50.88 dB	-10.47 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-27.15 dBm	-46.55 dB	-14.15 dB

Date: 29.SEP.2017 09:47:18

LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 22.39 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-24.96 dBm	-47.34 dB	-11.96 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-29.32 dBm	-51.70 dB	-8.32 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-61.27 dBm	-83.66 dB	-40.27 dB
2.538 MHz	7.500 MHz	100.000 kHz	820.89844 MHz	-51.52 dBm	-73.90 dB	-38.52 dB

Date: 12.SEP.2017 23:03:44

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 22.01 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	817.14509 MHz	-52.69 dBm	-74.69 dB	-39.69 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-61.46 dBm	-83.47 dB	-40.46 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-29.25 dBm	-51.26 dB	-8.25 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-25.54 dBm	-47.54 dB	-12.54 dB

Date: 12.SEP.2017 23:08:20

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.64 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.90809 MHz	-32.90 dBm	-54.54 dB	-19.90 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-35.61 dBm	-57.25 dB	-14.61 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-36.05 dBm	-57.70 dB	-15.05 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.04838 MHz	-35.51 dBm	-57.15 dB	-22.51 dB

Date: 12.SEP.2017 23:06:02

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.62 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95162 MHz	-32.12 dBm	-53.74 dB	-19.12 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-36.09 dBm	-57.71 dB	-15.09 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-35.11 dBm	-56.73 dB	-14.11 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-31.58 dBm	-53.20 dB	-18.58 dB

Date: 12.SEP.2017 23:10:38

LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 21.43 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-24.76 dBm	-46.19 dB	-11.76 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-29.16 dBm	-50.58 dB	-8.16 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-61.01 dBm	-82.43 dB	-40.01 dB
2.538 MHz	7.500 MHz	100.000 kHz	820.76785 MHz	-51.18 dBm	-72.60 dB	-38.18 dB

Date: 12.SEP.2017 23:04:53

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.27 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	817.27569 MHz	-51.52 dBm	-72.79 dB	-38.52 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-61.58 dBm	-82.86 dB	-40.58 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-30.57 dBm	-51.84 dB	-9.57 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-27.15 dBm	-48.43 dB	-14.15 dB

Date: 12.SEP.2017 23:09:29

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.62 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-32.73 dBm	-53.35 dB	-19.73 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-36.95 dBm	-57.57 dB	-15.95 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-38.11 dBm	-58.73 dB	-17.11 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.04838 MHz	-33.94 dBm	-54.57 dB	-20.94 dB

Date: 12.SEP.2017 23:07:11

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.56 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95162 MHz	-33.67 dBm	-54.23 dB	-20.67 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-37.47 dBm	-58.03 dB	-16.47 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-36.83 dBm	-57.39 dB	-15.83 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-33.15 dBm	-53.72 dB	-20.15 dB

Date: 12.SEP.2017 23:11:47