FCC Test Report

Report No.:	RF180207C11-4
FCC ID:	MSQZ01RD
Test Model:	ASUS_Z01RD / ASUS_Z01RS
Received Date:	Feb. 07, 2018
Test Date:	Feb. 27, 2018 ~ Mar. 30, 2018
Issued Date:	May 02, 2018
Applicant:	ASUSTek COMPUTER INC.
Address:	4F, No. 150, LI-TE Rd., PEITOU, TAIPEI 112, TAIWAN
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lab Address:	No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)
Test Location (1):	No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.
FCC Registration / Designation Number:	788550 / TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record **3**

1 Certificate of Conformity **4**

2 Summary of Test Results **5**

2.1 Measurement Uncertainty 5
2.2 Modification Record 5

3 General Information **6**

3.1 General Description of EUT 6
3.2 Description of Test Modes 7
3.2.1 Test Mode Applicability and Tested Channel Detail 7
3.3 Description of Support Units 9
3.3.1 Configuration of System under Test 9
3.4 General Description of Applied Standards 9

4 Test Types and Results **10**

4.1 Radiated Emission Measurement 10
4.1.1 Limits of Radiated Emission Measurement 10
4.1.2 Test Instruments 11
4.1.3 Test Procedures 13
4.1.4 Deviation from Test Standard 13
4.1.5 Test Set Up 14
4.1.6 EUT Operating Conditions 14
4.1.7 Test Results 15
4.2 Conducted Emission Measurement 26
4.2.1 Limits of Conducted Emission Measurement 26
4.2.2 Test Instruments 26
4.2.3 Test Procedures 27
4.2.4 Deviation from Test Standard 27
4.2.5 Test Setup 27
4.2.6 EUT Operating Conditions 27
4.2.7 Test Results 28
4.3 Frequency Stability 30
4.3.1 Limits of Frequency Stability Measurement 30
4.3.2 Test Setup 30
4.3.3 Test Instruments 30
4.3.4 Test Procedure 30
4.3.5 Deviation fromTest Standard 30
4.3.6 EUT Operating Conditions 30
4.3.7 Test Result 31
4.4 20 dB Bandwidth 32
4.4.1 Limits of 20 dB Bandwidth Measurement 32
4.4.2 Test Setup 32
4.4.3 Test Instruments 32
4.4.4 Test Procedures 32
4.4.5 Deviation from Test Standard 32
4.4.6 EUT Operating Conditions 32
4.4.7 Test Results 33

5 Pictures of Test Arrangements **34**

Appendix – Information on the Testing Laboratories **35**

Release Control Record

Issue No.	Description	Date Issued
RF180207C11-4	Original Release	May 02, 2018

1 Certificate of Conformity

Product: ASUS Phone

Brand: ASUS

Test Model: ASUS_Z01RD / ASUS_Z01RS

Sample Status: Production Unit

Applicant: ASUSTek COMPUTER INC.

Test Date: Feb. 27, 2018 ~ Mar. 30, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.225)
47 CFR FCC Part 15, Subpart C (Section 15.215)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : _____ , **Date:** May 02, 2018
Ivonne Wu / Supervisor

Approved by : _____ , **Date:** May 02, 2018
Dylan Chiou / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.225, 15.215)			
FCC Clause	**Test Item**	**Result**	**Remarks**
15.207	Conducted emission test	Pass	Meet the requirement of limit. Minimum passing margin is -2.40 dB at 13.56130 MHz.
15.225 (a)	The field strength of any emissions within the band 13.553-13.567 MHz	Pass	Meet the requirement of limit. Minimum passing margin is -72.31 dB at 13.56 MHz.
15.225 (b)	The field strength of any emissions within the bands 13.410-13.553 MHz and 13.567-13.710 MHz	Pass	Meet the requirement of limit.
15.225 (c)	The field strength of any emissions within the bands 13.110-13.410 MHz and 13.710-14.010 MHz	Pass	Meet the requirement of limit.
15.225 (d)	The field strength of any emissions appearing outside of the 13.110-14.010 MHz band	Pass	Meet the requirement of limit. Minimum passing margin is -1.03 dB at 40.67 MHz.
15.225 (e)	The frequency tolerance	Pass	Meet the requirement of limit.
15.215 (c)	20 dB Bandwidth	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	ASUS Phone
Brand	ASUS
Test Model	ASUS_Z01RD / ASUS_Z01RS
Status of EUT	Production Unit
Power Supply Rating	5.0 Vdc or 9.0 Vdc (adapter) 5.0 Vdc (host equipment) 3.85 Vdc (battery)
Modulation Type	ASK
Operating Frequency	13.56 MHz
Antenna Type	Loop Antenna
Accessory Device	Refer to Note
Data Cable Supplied	Refer to Note

Note:

1. All models are listed as below.

Brand	SKU	Model	Difference
ASUS	WW-5CA	ASUS_Z01RD	Dual SIM
	WW Operator-5CA	ASUS_Z01RS	Single SIM
* The models have the same layout, circuit, and components, but different SIM card slot, therefore, only ASUS_Z01RD was chosen for the final test.			

2. There're 2 configurations for the EUT listed as below.
   Main Sample: EUT + CPU 1 + Rear Camera 1 + Front Camera 1 + UFS 3 + DDR 3
   2nd Sample: EUT + CPU 2 + Rear Camera 2 + Front Camera 2 + UFS 3 + DDR 3
   ✧ Only the worst test data was presented in the report.
3. The EUT's accessories list refers to Ext. Pho.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

One channel was provided to this EUT:

Channel	Frequency (MHz)
1	13.56

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable To				Description
	RE	PLC	FS	EB	
A	√	√	√	√	Main Sample
B	√	-	-	-	2nd Sample

Where **RE:** Radiated Emission **PLC:** Power Line Conducted Emission
FS: Frequency Stability **EB:** 20 dB Bandwidth measurement

Radiated Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Axis
A, B	1	1	ASK	Z

Note: Only 30 MHz ~ 1 GHz test was performed for 2nd sample.

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Axis
A	1	1	ASK	Z

Frequency Stability:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Axis
A	1	1	ASK	Z

20 dB Bandwidth:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Axis
A	1	1	ASK	Z

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested By
RE	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
FS	25 deg. C, 65 % RH	3.85 Vdc	Wayne Lin
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Getaz Yang
EB	25 deg. C, 68 % RH	3.85 Vdc	Wayne Lin

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.225)
FCC Part 15, Subpart C (15.215)
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission Measurement

4.1.1 Limits of Radiated Emission Measurement

a. The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
b. Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
c. Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
d. The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209 as below table:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manaufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY52260177	Jul. 05, 2017	Jul. 04, 2018
Spectrum Analyzer Agilent	N9010A	MY52220314	Nov. 24, 2017	Nov. 23, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	100115	Nov. 23, 2017	Nov. 22, 2018
Double Ridge Guide Horn Antenna EMCO	3115	5619	Nov. 30, 2017	Nov. 29, 2018
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 06, 2017	Dec. 05, 2018
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-400)	Jun. 23, 2017	Jun. 22, 2018
Loop Antenna	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier EMCI	EMC001340	980201	Nov. 01, 2017	Oct. 30, 2018
Preamplifier EMCI	EMC 012645	980115	Oct. 20, 2017	Oct. 19, 2018
Preamplifier EMCI	EMC 184045	980116	Oct. 20, 2017	Oct. 19, 2018
Preamplifier EMCI	EMC 330H	980112	Oct. 13, 2017	Oct. 12, 2018
Power Meter Anritsu	ML2495A	1012010	Aug. 15, 2017	Aug. 14, 2018
Power Sensor Anritsu	MA2411B	1315050	Aug. 15, 2017	Aug. 14, 2018
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM-8000&3000	140811+170717	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM-1000(140807)	Oct. 20, 2017	Oct. 19, 2018
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Oct. 20, 2017	Oct. 19, 2018
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 08, 2017	Sep. 07, 2018
DC Power Supply Topward	33010D	807748	Oct. 25, 2016	Oct. 24, 2018
Digital Multimeter Fluke	87-III	70360742	Jun. 30, 2017	Jun. 29, 2018

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
4. The IC Site Registration No. is IC7450F-10.

4.1.3 Test Procedures

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. Both Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Set Up

<Radiated Emission below 30 MHz>



<Radiated Emission 30 MHz to 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

No non-compliance noted:

KDB 937606 OATS and Chamber Correlation Justification

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

- OATs and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	13.553 ~ 13.567 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Open at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
13.56	51.69	31.19	124	-72.31	20.5	0	0	100	0	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

13.56 MHz = 15848 uV/m 30m

= 84 dBuV/m 30m

= $84+20\log(30/3)^2$ 3m

= 124 dBuV/m

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	13.553 ~ 13.567 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Close at 3 m										
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Factor (dB/m)**	**Cable Loss (dB)**	**Preamp Factor (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
13.56	48.65	28.15	124	-75.35	20.5	0	0	100	360	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

13.56 MHz = 15848 uV/m 30m
= 84 dBuV/m 30m
= $84+20\log(30/3)^2$ 3m
= 124 dBuV/m

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	13.553 ~ 13.567 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Ground at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
13.56	47.04	26.54	124	-76.96	20.5	0	0	100	360	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. Above limits have been translated by the formula

The measured field strength was extrapolated to distance 30 meters, using the formula that the limit of field strength varies as the inverse distance square (40dB per decade of distance)

Example:

13.56 MHz =	15848 uV/m	30m
=	84 dBuV/m	30m
=	$84+20\log(30/3)^2$	3m
=	124 dBuV/m	

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	Below 30 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Open at 3 m										
Frequency (MHz)	**Emission Level (dBuV/m)**	**Read Level (dBuV)**	**Limit (dBuV/m)**	**Margin (dB)**	**Antenna Factor (dB/m)**	**Cable Loss (dB)**	**Preamp Factor (dB)**	**Antenna Height (cm)**	**Table Angle (Degree)**	**Remark**
27.12	37.66	17	69.54	-31.88	20.66	0	0	100	360	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	Below 30 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Close at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
27.12	35.95	15.29	69.54	-33.59	20.66	0	0	100	0	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	Below 30 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang



Antenna Polarity & Test Distance: Loop Antenna Ground at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
27.12	36.92	16.26	69.54	-32.62	20.66	0	0	100	0	QP

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

<Mode A>

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	Below 1000 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang

Horizontal



Vertical



Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
40.67	26.47	43.45	40	-13.53	13.55	0.49	31.02	149	319	Peak
67.83	27.17	47.27	40	-12.83	11	0.63	31.73	133	32	Peak
122.15	32.49	52.39	43.5	-11.01	11.15	0.85	31.9	127	153	Peak
187.14	28.53	48.83	43.5	-14.97	10.26	1.16	31.72	106	194	Peak
296.75	25.89	43.19	46	-20.11	12.85	1.64	31.79	140	155	Peak
774.96	27.12	33.02	46	-18.88	21.87	3.59	31.36	132	74	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
40.67	38.97	55.95	40	-1.03	13.55	0.49	31.02	108	236	QP
67.83	27.57	47.67	40	-12.43	11	0.63	31.73	146	210	Peak
115.36	27.67	48.17	43.5	-15.83	10.55	0.82	31.87	135	279	Peak
220.12	23.4	43.56	46	-22.6	10.22	1.33	31.71	109	312	Peak
297.72	21.58	38.87	46	-24.42	12.88	1.64	31.81	141	126	Peak
487.84	23.54	35.81	46	-22.46	17.08	2.44	31.79	145	259	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value.

<Mode B>

EUT Test Condition		Measurement Detail	
Channel	Channel 1	**Frequency Range**	Below 1000 MHz
Input Power	120 Vac, 60 Hz	**Detector Function**	Quasi-Peak
Environmental Conditions	25 deg. C, 65 % RH	**Tested By**	Getaz Yang

Horizontal



Vertical



Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
60.07	23.01	41.85	40	-16.99	11.94	0.58	31.36	122	22	Peak
119.24	31.72	51.84	43.5	-11.78	10.93	0.84	31.89	122	77	Peak
220.12	26.91	47.07	46	-19.09	10.22	1.33	31.71	143	56	Peak
296.75	26.47	43.77	46	-19.53	12.85	1.64	31.79	117	17	Peak
527.61	22.17	33.27	46	-23.83	17.95	2.62	31.67	106	126	Peak
789.51	27.37	33.06	46	-18.63	22.08	3.63	31.4	118	332	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
39.7	27.97	44.93	40	-12.03	13.54	0.49	30.99	108	340	Peak
119.24	26.87	46.99	43.5	-16.63	10.93	0.84	31.89	119	149	Peak
221.09	22.46	42.58	46	-23.54	10.26	1.34	31.72	148	243	Peak
298.69	21.91	39.18	46	-24.09	12.91	1.64	31.82	136	200	Peak
486.87	24.28	36.57	46	-21.72	17.06	2.44	31.79	106	227	Peak
789.51	27.93	33.62	46	-18.07	22.08	3.63	31.4	100	36	Peak

Remarks:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value.

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 23, 2017	Nov. 22, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN/AMN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 06, 2018	Mar. 05, 2019
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Getaz Yang	Test Date	2018/2/27

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.10	37.51	24.87	47.61	34.97	66.00	56.00	-18.39	-21.03
2	0.23216	10.11	25.06	14.74	35.17	24.85	62.37	52.37	-27.20	-27.52
3	0.53318	10.12	16.45	12.42	26.57	22.54	56.00	46.00	-29.43	-23.46
4	1.84694	10.18	11.81	7.79	21.99	17.97	56.00	46.00	-34.01	-28.03
5	4.40017	10.31	16.92	11.47	27.23	21.78	56.00	46.00	-28.77	-24.22
6	13.56130	10.83	36.74	36.61	47.57	47.44	60.00	50.00	-12.43	-2.56

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Getaz Yang	Test Date	2018/2/27

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.10	37.88	23.53	47.98	33.63	65.79	55.79	-17.81	-22.16
2	0.19692	10.10	29.63	16.18	39.73	26.28	63.74	53.74	-24.01	-27.46
3	0.58401	10.12	14.57	10.00	24.69	20.12	56.00	46.00	-31.31	-25.88
4	1.58106	10.16	12.96	8.98	23.12	19.14	56.00	46.00	-32.88	-26.86
5	4.13038	10.27	15.47	8.25	25.74	18.52	56.00	46.00	-30.26	-27.48
6	13.56130	10.67	37.02	36.93	47.69	47.60	60.00	50.00	-12.31	-2.40

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 Frequency Stability

4.3.1 Limits of Frequency Stability Measurement

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01 % of the operating frequency over a temperature variation of –20 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85 % to 115% of the rated supply voltage at a temperature of 20 degrees C.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
b. Turned the EUT on and coupled its output to a spectrum analyzer.
c. Turned the EUT off and set the chamber to the highest temperature specified.
d. Allowed sufficient time (approximately 30 min) for the temperature of the chamber to stabilize then turned the EUT on and measured the operating frequency after 2, 5, and 10 minutes.
e. Repeated step 2 and 3 with the temperature chamber set to the lowest temperature.
f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85 % to 115 % and the frequency record.

4.3.5 Deviation fromTest Standard

No deviation.

4.3.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.3.7 Test Result

Frequency Stability Versus Temperature									
Temp. (℃)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
50	3.85	13.560079	0.00058	13.560071	0.00052	13.560065	0.00048	13.560077	0.00057
40	3.85	13.559984	-0.00012	13.560001	0.00001	13.559997	-0.00002	13.559994	-0.00004
30	3.85	13.560069	0.00051	13.560073	0.00054	13.560057	0.00042	13.560048	0.00035
20	3.85	13.560003	0.00002	13.560001	0.00001	13.559987	-0.00010	13.559998	-0.00001
10	3.85	13.560046	0.00034	13.560053	0.00039	13.560041	0.00030	13.560035	0.00026
0	3.85	13.560055	0.00041	13.560044	0.00032	13.560046	0.00034	13.560039	0.00029
-10	3.85	13.560064	0.00047	13.560071	0.00052	13.560051	0.00038	13.560065	0.00048
-20	3.85	13.560064	0.00047	13.560046	0.00034	13.560049	0.00036	13.560042	0.00031
-30	3.85	13.559993	-0.00005	13.559996	-0.00003	13.560009	0.00007	13.560007	0.00005

Frequency Stability Versus Voltage									
Temp. (℃)	Power Supply (Vdc)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift	Measured Frequency	Frequency Drift
		(MHz)	%	(MHz)	%	(MHz)	%	(MHz)	%
20	4.38	13.560006	0.00004	13.559997	-0.00002	13.559986	-0.00010	13.559996	-0.00003
	3.85	13.560003	0.00002	13.560001	0.00001	13.559987	-0.00010	13.559998	-0.00001
	3.6	13.560007	0.00005	13.559996	-0.00003	13.559987	-0.00010	13.559996	-0.00003

4.4 20 dB Bandwidth

4.4.1 Limits of 20 dB Bandwidth Measurement

The 20 dB bandwidth shall be specified in operating frequency band.

4.4.2 Test Setup

Refer to section 4.1.5.

4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1 kHz RBW and 3 kHz VBW. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

a. Placed the EUT on the testing table.
b. Set the EUT under transmission condition continuously at specific channel frequency.

4.4.7 Test Results

20 dBc Point (Low)	20 dBc Point (High)	Operating Frequency Band (MHz)	Pass / Fail
13.558429487 MHz	13.561025641 MHz	13.553~13.567	Pass

Spectrum Plot Of Value



Date: 26.FEB.2018 23:04:03

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---