



Operational Description

The transmitter of the EUT (Dual Radio 2.4GHz/5GHz Access Point) is powered by AC adapter or POE. The antenna type used in this product is Dualband Built-in directional antenna with UFL antenna connector. Under normal use condition, the user has to keep at least 20cm separation distance between radiator and the body of the user.

For more detailed instruction, please take a look at the user's manual.

FCC 15.407(c) states: The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met"

Data transmission is always initiated by software, which is then pass down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets (ACKs, CTS, PSpoll, etc...) are initiated by the MAC. There are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets are being transmitted.

NOTE: 1. Both of the 2.4GHz and 5GHz can transmit simultaneously.

2. Two radios are under firmware controlled not to use the same channel or a channel which are separated less than 4 channels and is not user changeable.