

FCC TEST REPORT

REPORT NO.: RF910606R01B

MODEL NO.: WL-683D

RECEIVED: Sept. 18, 2002

TESTED: Sept. 20 ~ Sept. 24, 2002

APPLICANT: GEMTEK TECHNOLOGY CO., LTD.

ADDRESS: No. 1, Jen Ai Road, Hsinchu Industrial Park
Hukou, Hsin Chu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 49 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0

Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
4	TEST TYPES AND RESULTS	9
4.1	CONDUCTED EMISSION MEASUREMENT	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	9
4.1.2	TEST INSTRUMENTS	9
4.1.3	TEST PROCEDURES	10
4.1.4	DEVIATION FROM TEST STANDARD	10
4.1.5	TEST SETUP	11
4.1.6	EUT OPERATING CONDITIONS.....	11
4.1.7	TEST RESULTS	12
4.2	RADIATED EMISSION MEASUREMENT	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	18
4.2.2	TEST INSTRUMENTS	19
4.2.3	TEST PROCEDURES	20
4.2.4	TEST SETUP	21
4.2.5	DEVIATION FROM TEST STANDARD	21
4.2.6	EUT OPERATING CONDITIONS.....	21
4.2.7	TEST RESULTS (A)	22
4.2.8	TEST RESULTS (B)	23
4.2.9	TEST RESULT	24
4.3	6dB BANDWIDTH MEASUREMENT	27
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	27
4.3.2	TEST INSTRUMENTS	27
4.3.3	TEST PROCEDURE	28
4.3.4	DEVIATION FROM TEST STANDARD	28
4.3.5	TEST SETUP	28
4.3.6	EUT OPERATING CONDITIONS.....	28
4.3.7	TEST RESULTS	29
4.4	MAXIMUM PEAK OUTPUT POWER.....	33
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	33
4.4.2	INSTRUMENTS.....	33
4.4.3	TEST PROCEDURES	34
4.4.4	DEVIATION FROM TEST STANDARD	34



4.4.5	TEST SETUP	34
4.4.6	EUT OPERATING CONDITIONS.....	34
4.4.7	TEST RESULTS	35
4.5	POWER SPECTRAL DENSITY MEASUREMENT	36
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	36
4.5.2	TEST INSTRUMENTS	36
4.5.3	TEST PROCEDURE	37
4.5.4	DEVIATION FROM TEST STANDARD	37
4.5.5	TEST SETUP	37
4.5.6	EUT OPERATING CONDITION	37
4.5.7	TEST RESULTS	38
4.6	BAND EDGES MEASUREMENT	42
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	42
4.6.2	TEST INSTRUMENTS	42
4.6.3	TEST PROCEDURE	42
4.6.4	DEVIATION FROM TEST STANDARD	42
4.6.5	EUT OPERATING CONDITION	43
4.6.6	TEST RESULTS	43
4.7	ANTENNA REQUIREMENT	46
4.7.1	STANDARD APPLICABLE	46
4.7.2	ANTENNA CONNECTED CONSTRUCTION	46
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	47
6	INFORMATION ON THE TESTING LABORATORIES.....	49



1 CERTIFICATION

PRODUCT : DELL TrueMobile 1180 Wireless USB Adapter
BRAND NAME : DELL
MODEL NO. : WL-683D
APPLICANT : GEMTEK TECHNOLOGY CO., LTD.
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Sept. 20, 2002 to Sept. 24, 2002. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY : Emily Lu , DATE : Sep. 25, 2002
Emily Lu

APPROVED BY : Alan Lane , DATE : Sep. 25, 2002
Dr. Alan Lane, Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -14.94dBuV at 15.551MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -2.00dBuV at 4874.0MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	DELL TrueMobile 1180 Wireless USB Adapter
MODEL NO.	WL-683D
POWER SUPPLY	5.0VDC from Notebook
MODULATION TYPE	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	13.86dBm
ANTENNA TYPE	Inverted F Antenna
DATA CABLE	0.3m, 1.8m (Shielded with ferrite core) *see Note 1
I/O PORTS	mini USB port
ASSOCIATED DEVICES	NA

NOTE:

- 1.Two USB cables are provided and considered as part of this EUT.
- 2.This report is prepared for FCC class II permissive change. The differences compared with the original design are antenna type and outer appearance.
- 3.For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

- NOTE:** 1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. For conducted emission measurement, the length of USB cable = 1.8m was chosen for final test. For radiated emission measurement below 1GHz, test result (A) is for the length of USB cable =1.8m and test result (B) is for the length of USB cable 0.3m.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a DELL TrueMobile 1180 Wireless USB Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR 47 Part 15, Subpart C. (15.247)
ANSI C63.4 : 1992

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK PC	DELL	PPX	99125	FCC DoC APPROVED
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED
3	MODEM	ACEEX	1414	980020503	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	847793/022	Mar. 12, 2003
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	Jul. 23, 2003
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 25, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 2, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 2, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	Jul. 23, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	Jul. 23, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. “*”: These equipment are used for conducted telecom port test only (if tested).
 4. The test was performed in ADT Open Site No. 5.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.

4.1.7 TEST RESULTS

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.10	46.58	-	46.68	-	64.08	54.08	-17.40	-
2	0.568	0.13	39.21	-	39.34	-	56.00	46.00	-16.66	-
3	0.920	0.19	32.51	-	32.70	-	56.00	46.00	-23.30	-
4	1.488	0.20	34.65	-	34.85	-	56.00	46.00	-21.15	-
5	2.871	0.29	35.81	-	36.10	-	56.00	46.00	-19.90	-
6	5.234	0.44	35.21	-	35.65	-	60.00	50.00	-24.35	-
7	15.551	0.73	42.09	-	42.82	-	60.00	50.00	-17.18	-
8	17.117	0.83	30.49	-	31.32	-	60.00	50.00	-28.68	-


- REMARKS : 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.10	45.04	-	45.14	-	64.08	54.08	-18.94	-
2	0.568	0.13	38.90	-	39.03	-	56.00	46.00	-16.97	-
3	0.713	0.15	32.34	-	32.49	-	56.00	46.00	-23.51	-
4	3.758	0.29	32.87	-	33.16	-	56.00	46.00	-22.84	-
5	13.773	0.48	23.48	-	23.96	-	60.00	50.00	-36.04	-
6	15.551	0.53	44.53	-	45.06	-	60.00	50.00	-14.94	-
7	17.563	0.65	30.99	-	31.64	-	60.00	50.00	-28.36	-


- REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.10	46.36	-	46.46	-	63.91	53.91	-17.45	-
2	0.564	0.13	40.92	-	41.05	-	56.00	46.00	-14.95	-
3	0.662	0.14	35.69	-	35.83	-	56.00	46.00	-20.17	-
4	0.713	0.15	34.49	-	34.64	-	56.00	46.00	-21.36	-
5	4.941	0.43	35.54	-	35.97	-	56.00	46.00	-20.03	-
6	15.613	0.74	39.44	-	40.18	-	60.00	50.00	-19.82	-
7	17.625	0.86	29.94	-	30.80	-	60.00	50.00	-29.20	-


- REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.10	44.82	-	44.92	-	63.91	53.91	-18.99	-
2	0.584	0.13	37.52	-	37.65	-	56.00	46.00	-18.35	-
3	0.713	0.15	34.49	-	34.64	-	56.00	46.00	-21.36	-
4	1.121	0.20	33.87	-	34.07	-	56.00	46.00	-21.93	-
5	2.086	0.20	33.40	-	33.60	-	56.00	46.00	-22.40	-
6	4.328	0.31	33.71	-	34.02	-	56.00	46.00	-21.98	-
7	12.270	0.45	22.85	-	23.30	-	60.00	50.00	-36.70	-


- REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.10	46.62	-	46.72	-	63.91	53.91	-17.19	-
2	0.568	0.13	39.73	-	39.86	-	56.00	46.00	-16.14	-
3	1.121	0.20	34.45	-	34.65	-	56.00	46.00	-21.35	-
4	2.340	0.23	34.75	-	34.98	-	56.00	46.00	-21.02	-
5	3.434	0.34	35.45	-	35.79	-	56.00	46.00	-20.21	-
6	5.832	0.46	32.70	-	33.16	-	60.00	50.00	-26.84	-
7	17.566	0.85	25.87	-	26.72	-	60.00	50.00	-33.28	-


- REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 75%RH, 1005 hPa	TESTED BY: Bunny Yao	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.193	0.10	45.69	-	45.79	-	63.91	53.91	-18.12	-
2	0.884	0.18	30.51	-	30.69	-	56.00	46.00	-25.31	-
3	1.852	0.20	36.29	-	36.49	-	56.00	46.00	-19.51	-
4	2.574	0.23	36.67	-	36.90	-	56.00	46.00	-19.10	-
5	5.270	0.32	34.59	-	34.91	-	60.00	50.00	-25.09	-
6	15.879	0.55	44.33	-	44.88	-	60.00	50.00	-15.12	-
7	17.625	0.66	34.26	-	34.92	-	60.00	50.00	-25.08	-

- REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Oct. 30, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 7, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 3, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 9, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:** 1. The measurement uncertainty is less than $\pm 3.0\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
3. "*" = These equipment are used for the final measurement.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The test was performed in ADT Open Site No. 5.


4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS (A)

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 85%RH, 1005 hPa	TESTED BY: Eric Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	220.00	33.0 QP	46.00	-13.00	1.27H	264	21.52	10.12	1.36	0.00	-11.48
2	240.60	39.0 QP	46.00	-7.00	1.30H	5	26.28	11.41	1.31	0.00	-12.72
3	336.00	33.5 QP	46.00	-12.50	1.09H	248	18.12	13.92	1.45	0.00	-15.37
4	340.00	38.0 QP	46.00	-8.00	1.30H	189	22.53	14.02	1.45	0.00	-15.48
5	352.00	34.2 QP	46.00	-11.80	1.29H	264	18.47	14.31	1.46	0.00	-15.76
6	441.00	32.8 QP	46.00	-13.20	1.17H	51	14.90	16.32	1.59	0.00	-17.91
7	528.00	33.0 QP	46.00	-13.00	1.36H	95	13.58	17.62	1.79	0.00	-19.43
8	620.00	32.9 QP	46.00	-13.10	1.57H	77	12.09	18.85	1.96	0.00	-20.82
9	746.00	34.0 QP	46.00	-12.00	1.64H	3	11.73	20.10	2.17	0.00	-22.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	220.00	33.5 QP	46.00	-12.50	1.67V	320	22.02	10.12	1.36	0.00	-11.48
2	240.00	30.0 QP	46.00	-16.00	1.68V	184	17.28	11.41	1.31	0.00	-12.72
3	260.00	38.8 QP	46.00	-7.20	1.26V	25	24.47	13.03	1.30	0.00	-14.34
4	336.00	30.2 QP	46.00	-15.80	1.19V	178	14.83	13.92	1.45	0.00	-15.37
5	340.00	34.5 QP	46.00	-11.50	1.35V	302	19.03	14.02	1.45	0.00	-15.47
6	361.00	36.6 QP	46.00	-9.40	1.57V	101	20.55	14.58	1.47	0.00	-16.06
7	441.00	39.3 QP	46.00	-6.70	1.01V	90	21.40	16.32	1.59	0.00	-17.91
8	528.00	34.5 QP	46.00	-11.50	1.10V	280	15.08	17.62	1.79	0.00	-19.42
9	624.00	33.0 QP	46.00	-13.00	1.39V	131	12.12	18.91	1.97	0.00	-20.88
10	746.00	28.9 QP	46.00	-17.10	1.35V	239	6.63	20.10	2.17	0.00	-22.28

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.

4.2.8 TEST RESULTS (B)

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25 deg. C, 85%RH, 1005 hPa	TESTED BY: Eric Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	220.00	34.0 QP	46.00	-12.00	1.07H	257	22.52	10.12	1.36	0.00	-11.48
2	240.00	32.1 QP	46.00	-13.90	1.21H	322	19.38	11.41	1.31	0.00	-12.72
3	260.00	39.0 QP	46.00	-7.00	1.43H	3	24.67	13.03	1.30	0.00	-14.33
4	336.00	26.9 QP	46.00	-19.10	1.72H	294	11.53	13.92	1.45	0.00	-15.37
5	341.00	36.0 QP	46.00	-10.00	1.62H	223	20.53	14.02	1.45	0.00	-15.47
6	361.50	34.8 QP	46.00	-11.20	1.42H	91	18.65	14.67	1.47	0.00	-16.16
7	441.60	39.5 QP	46.00	-6.50	1.32H	150	21.58	16.33	1.59	0.00	-17.93
8	528.00	36.0 QP	46.00	-10.00	1.31H	155	16.58	17.62	1.79	0.00	-19.42
9	624.00	33.0 QP	46.00	-13.00	1.18H	50	12.12	18.91	1.97	0.00	-20.88
10	746.00	33.0 QP	46.00	-13.00	1.10H	73	10.73	20.10	2.17	0.00	-22.27

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	220.00	28.5 QP	46.00	-17.50	1.18V	175	17.02	10.12	1.36	0.00	-11.48
2	240.50	33.0 QP	46.00	-13.00	1.25V	264	20.28	11.41	1.31	0.00	-12.72
3	260.10	35.0 QP	46.00	-11.00	1.52V	352	20.67	13.03	1.30	0.00	-14.33
4	336.00	34.0 QP	46.00	-12.00	1.45V	233	18.63	13.92	1.45	0.00	-15.37
5	361.00	32.3 QP	46.00	-13.70	1.25V	113	16.25	14.58	1.47	0.00	-16.05
6	441.00	34.8 QP	46.00	-11.20	1.13V	145	16.90	16.32	1.59	0.00	-17.90
7	528.00	36.0 QP	46.00	-10.00	1.38V	225	16.58	17.62	1.79	0.00	-19.42
8	624.00	36.0 QP	46.00	-10.00	1.22V	341	15.12	18.91	1.97	0.00	-20.88
9	746.00	32.3 QP	46.00	-13.70	1.03V	264	10.03	20.10	2.17	0.00	-22.27

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.

4.2.9 TEST RESULT

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 85%RH, 1005 hPa	TESTED BY: Eric Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2363.00	38.3 AV	54.00	-15.70	1.73H	8	45.10	27.52	2.40	36.73	6.80
2	2363.00	42.1 PK	74.00	-31.90	1.73H	8	48.90	27.52	2.40	36.73	6.80
3	*2412.00	94.9 AV			1.73H	189	101.40	27.67	2.53	36.72	6.52
4	*2412.00	101.3 PK			1.73H	189	107.80	27.67	2.53	36.72	6.52
5	4824.00	47.9 AV	54.00	-6.10	1.37H	27	49.10	31.52	4.01	36.70	1.18
6	4824.00	50.3 PK	74.00	-23.70	1.37H	27	51.50	31.52	4.01	36.70	1.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2363.00	38.2 AV	54.00	-15.80	1.21V	111	45.00	27.52	2.40	36.73	6.80
2	2363.00	41.7 PK	74.00	-32.30	1.21V	111	48.50	27.52	2.40	36.73	6.80
3	*2412.00	102.5 AV			1.00V	91	109.00	27.67	2.53	36.72	6.52
4	*2412.00	107.4 PK			1.00V	92	113.90	27.67	2.53	36.72	6.52
5	4824.00	51.4 AV	54.00	-2.60	1.39V	131	52.60	31.52	4.01	36.70	1.18
6	4824.00	52.8 PK	74.00	-21.20	1.39V	131	54.00	31.52	4.01	36.70	1.18

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 85%RH, 1005 hPa	TESTED BY: Eric Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2365.00	36.4 AV	54.00	-17.60	1.25H	123	43.20	27.52	2.40	36.73	6.80
2	2365.00	39.0 PK	74.00	-35.00	1.25H	123	45.80	27.52	2.40	36.73	6.80
3	*2437.00	96.2 AV			1.12H	36	102.40	27.81	2.66	36.71	6.24
4	*2437.00	102.7 PK			1.12H	36	108.90	27.81	2.66	36.71	6.24
5	4874.00	48.6 AV	54.00	-5.40	1.35H	15	49.70	31.59	4.03	36.70	1.09
6	4874.00	50.9 PK	74.00	-23.10	1.35H	15	52.00	31.59	4.03	36.70	1.09

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2318.00	31.8 AV	54.00	-22.20	1.06V	106	38.90	27.38	2.27	36.74	7.08
2	2318.00	32.9 PK	74.00	-41.10	1.06V	106	40.00	27.38	2.27	36.74	7.08
3	*2437.00	100.6 AV			1.00V	115	106.80	27.81	2.66	36.71	6.24
4	*2437.00	105.9 PK			1.00V	115	112.10	27.81	2.66	36.71	6.24
5	4874.00	52.0 AV	54.00	-2.00	1.04V	72	53.10	31.59	4.03	36.70	1.08
6	4874.00	53.3 PK	74.00	-20.70	1.04V	72	54.40	31.59	4.03	36.70	1.08
7	7311.00	46.1 AV	54.00	-7.90	1.00V	39	41.20	36.26	5.65	37.02	-4.91
8	7311.00	48.7 PK	74.00	-25.30	1.00V	39	43.80	36.26	5.65	37.02	-4.91

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency



EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25 deg. C, 85%RH, 1005 hPa	TESTED BY: Eric Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2438.00	31.8 AV	54.00	-22.20	1.35H	1	38.00	27.81	2.66	36.71	6.24
2	2438.00	34.3 PK	74.00	-39.70	1.35H	1	40.50	27.81	2.66	36.71	6.24
3	*2462.00	96.1 AV			1.44H	148	102.30	27.81	2.66	36.71	6.24
4	*2462.00	103.0 PK			1.44H	148	109.20	27.81	2.66	36.71	6.24
5	4924.00	48.1 AV	54.00	-5.90	1.08H	67	49.10	31.66	4.06	36.70	0.99
6	4924.00	50.2 PK	74.00	-23.80	1.08H	67	51.20	31.66	4.06	36.70	0.99

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2317.00	32.6 AV	54.00	-21.40	1.12V	103	39.70	27.38	2.27	36.74	7.08
2	2317.00	34.0 PK	74.00	-40.00	1.12V	103	41.10	27.38	2.27	36.74	7.08
3	*2462.00	98.7 AV			1.63V	81	104.90	27.81	2.66	36.71	6.24
4	*2462.00	105.0 PK			1.63V	81	111.20	27.81	2.66	36.71	6.24
5	4924.00	51.7 AV	54.00	-2.30	1.32V	129	52.70	31.66	4.06	36.70	1.00
6	4924.00	53.9 PK	74.00	-20.10	1.32V	129	54.90	31.66	4.06	36.70	1.00

- REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
 2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
 3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
 4. The other emission levels were very low against the limit.
 5. Margin value = Emission level – Limit value.
 6. “ * ” = Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

Notes:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS


EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	27 deg. C, 60%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.72	0.5	PASS
6	2437	11.68	0.5	PASS
11	2462	11.68	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
PEAK POWER SENSOR	NRV-Z32	100013	Feb. 23, 2003
POWER METER	NRVS	100026	Feb. 23, 2003

- NOTE:** 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

The transmitter output was connected to the peak power meter.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	27 deg. C, 60%RH, 1005 hPa
TESTED BY: Steven Lu			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	13.86	30	PASS
6	2437	13.47	30	PASS
11	2462	13.49	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION


Same as Item 4.3.6.

4.5.7 TEST RESULTS

EUT	DELL TrueMobile 1180 Wireless USB Adapter	MODEL	WL-683D
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	27 deg. C, 60 %RH, 1005 hPa
TESTED BY: Steven Lu			


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.50	8	PASS
6	2437	-11.64	8	PASS
11	2462	-11.72	8	PASS

CH1






1 PK
VIEW



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation




4.6.5 EUT OPERATING CONDITION


Same as Item 4.3.6.

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 51.51dB delta between carrier maximum power and local maximum emission in restrict band (2.4864GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 (Page 26) is 98.7dBuV/m, so the maximum field strength in restrict band is $98.7 - 51.51 = 47.19$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION


The antenna used in this product is Inverted F Antenna. There is no antenna connector. The maximum Gain of the antenna is -1dBi only.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.