




FOR CHAIN 1: CH 1



CH 4



CH 7



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP 40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

For Single TX:

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 10Hz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz) are attached on the following pages.

For Dual TX:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW = VBW = 100kHz; Average RBW = 1MHz, VBW = 10Hz)

NOTE: The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following 24 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

802.11b DSSS MODULATION:

NOTE 1:



The band edge emission plot on the next page shows 49.73dBc between carrier maximum power and local maximum emission in restrict band (2.38748GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 110.95dBuV/m (Peak), so the maximum field strength in restrict band is $110.95 - 49.73 = 61.22$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 52.85dBc between carrier maximum power and local maximum emission in restrict band (2.38748GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 106.37dBuV/m (Average), so the maximum field strength in restrict band is $106.37 - 52.85 = 53.52$ dBuV/m which is under 54dBuV/m limit.



NOTE 2:

The band edge emission plot on the next second page shows 51.15dBc between carrier maximum power and local maximum emission in restrict band (2.48626GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 110.98dBuV/m (Peak), so the maximum field strength in restrict band is $110.98 - 51.15 = 59.83$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 54.23dBc between carrier maximum power and local maximum emission in restrict band (2.48646GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.39dBuV/m (Average), so the maximum field strength in restrict band is $106.39 - 54.23 = 52.16$ dBuV/m which is under 54dBuV/m limit.







802.11g OFDM MODULATION:

NOTE 1:



The band edge emission plot on the next page shows 44.04dBc between carrier maximum power and local maximum emission in restrict band (2.38880GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 110.56dBuV/m (Peak), so the maximum field strength in restrict band is $110.56 - 44.04 = 66.52$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 46.61dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 97.79dBuV/m (Average), so the maximum field strength in restrict band is $97.79 - 46.61 = 51.18$ dBuV/m which is under 54dBuV/m limit.



NOTE 2:

The band edge emission plot on the next second page shows 45.40dBc between carrier maximum power and local maximum emission in restrict band (2.48850GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 110.01dBuV/m (Peak), so the maximum field strength in restrict band is $110.01 - 45.40 = 64.61$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 47.73dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.28dBuV/m (Average), so the maximum field strength in restrict band is $97.28 - 47.73 = 49.55$ dBuV/m which is under 54dBuV/m limit.







DRAFT 802.11n (20MHz) OFDM MODULATION: DUAL TX

NOTE 1:



The band edge emission plot on the next page shows 50.21dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 112.28dBuV/m (Peak), so the maximum field strength in restrict band is $112.28 - 50.21 = 62.07$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 50.01dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.59dBuV/m (Average), so the maximum field strength in restrict band is $101.59 - 50.01 = 51.58$ dBuV/m which is under 54dBuV/m limit.



NOTE 2:

The band edge emission plot on the next second page shows 47.76dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz) is 111.73dBuV/m (Peak), so the maximum field strength in restrict band is $111.73 - 47.76 = 63.97$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 49.43dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 101.08dBuV/m (Average), so the maximum field strength in restrict band is $101.08 - 49.43 = 51.65$ dBuV/m which is under 54dBuV/m limit.







DRAFT 802.11n (40MHz) OFDM MODULATION: DUAL TX

NOTE 1:



The band edge emission plot on the next page shows 41.65dBc between carrier maximum power and local maximum emission in restrict band (2.38840GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 110.01dBuV/m (Peak), so the maximum field strength in restrict band is $110.01 - 41.65 = 68.36$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on the next page shows 45.52dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 97.82dBuV/m (Average), so the maximum field strength in restrict band is $97.82 - 45.52 = 52.30$ dBuV/m which is under 54dBuV/m limit.



NOTE 2:

The band edge emission plot on the next second page shows 43.93dBc between carrier maximum power and local maximum emission in restrict band (2.48712GHz). The emission of carrier strength list in the test result of channel 7 at the item 4.2.7 is 109.35dBuV/m (Peak), so the maximum field strength in restrict band is $109.35 - 43.93 = 65.42$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the next third page shows 46.96dBc between carrier maximum power and local maximum emission in restrict band (2.48712GHz). The emission of carrier strength list in the test result of channel 7 at the item 4.2.7 is 97.72dBuV/m (Average), so the maximum field strength in restrict band is $97.72 - 46.96 = 50.76$ dBuV/m which is under 54dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole antenna with RSMA connector. The maximum Gain of the antenna is 2dBi.

6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, NCC
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.