

ENGINEERING TEST REPORT

PCMCIA WIRELESS LAN CARD

Model No: WL-201

FCC ID: MXF-WL201

**FCC PART 15, SUBPART C, PARA. 15.247
DIRECT SEQUENCE SPREAD SPECTRUM (DSSS) TRANSMITTERS
OPERATING IN THE FREQUENCY BAND FROM 2412 - 2462 MHz**

UltraTech's FILE NO.: GGT-001FTX

TESTED FOR:

GEMTEK TECHNOLOGY CO., LTD.
11 Fl., 181 Tatung Rd., Sec. 1, Hsi-chih
Taipei Hsien, Taiwan, R.O.C.

TESTED BY:

UltraTech Engineering Labs Inc.
4181 Sladeview Crescent, Unit 33
Mississauga, Ontario
Canada L5L 5R2

PREPARED BY: Tri M. Luu, P.Eng.

DATE: May 20, 1998

TABLE OF CONTENTS

1. EXHIBIT 1 - SUMMARY OF TEST RESULTS & GENERAL STATEMENT OF CERTIFICATION	3
2. EXHIBIT 2 - GENERAL INFORMATION.....	5
2.1 APPLICANT.....	5
2.2 MANUFACTURER	5
2.3 DESCRIPTION OF EQUIPMENT UNDER TEST	5
2.4 RELATED SUBMITTAL(S)/GRANT	6
2.5 TEST METHODOLOGY	6
2.6 TEST FACILITY	6
2.7 UNITS OF MEASUREMENTS	6
3. EXHIBIT 3 - SYSTEM TEST CONFIGURATION	7
3.1 TEST SYSTEM DETAILS	7
3.2 BLOCK DIAGRAMS RADIATED EMISSION MEASUREMENTS.....	7
3.3 PHOTOGRAPH FOR RF EMISSION MEASUREMENTS	8
3.4 JUSTIFICATION.....	14
3.5 EUT OPERATING CONDITION.....	14
3.6 SPECIAL ACCESSORIES	14
3.7 EQUIPMENT MODIFICATIONS.....	14
4. EXHIBIT 4 - TEST DATA	15
4.1 6 DB BANDWIDTH @ FCC CFR 47, PARA 15.247(A)(2)	15
4.2 MAXIMUM PEAK OUTPUT POWER @ FCC 15.247(B) AND RF EXPOSURE LIMIT FCC 1.1310	22
4.3 RF CONDUCTED EMISSIONS AT THE TRANSMITTER ANTENNA TERMINAL, FCC CFR 47, PARA. 15.247(C).....	26
4.4 TRANSMITTER RADIATED EMISSIONS @ 3 METERS, FCC CFR 47, PARA. 15.247(C), 15.209 & 15.205.....	48
4.5 TRANSMITTED POWER DENSITY OF A DIRECT SEQUENCE SPREAD SPECTRUM SYSTEM, FCC CFR 47, PARA. 15.247(D).....	75
4.6 PROCESSING GAIN OF A DIRECT SEQUENCE SPREAD SPECTRUM, FCC CFR 47, PARA. 15.247(E)	83
4.7 AC POWERLINE CONDUCTED EMISSIONS, FCC CFR 47, PARA. 15.107(A)	99
5. EXHIBIT 5 - GENERAL TEST PROCEDURES	103
5.1 AC POWERLINE CONDUCTED EMISSIONS MEASUREMENTS - GENERAL TEST METHOD.....	103
5.2 ELECTRICAL FIELD RADIATED EMISSIONS MEASUREMENTS - GENERAL TEST METHOD	105
6. EXHIBIT 6 - INFORMATION RELATED TO EQUIPMENT UNDER TESTS.....	108
6.1 FCC ID LABELING AND SKETCH OF FCC LABEL LOCATION	108
6.2 PHOTOGRAPHS OF EQUIPMENT UNDER TEST	108
6.3 SYSTEM BLOCK DIAGRAM(S).....	108
6.4 SCHEMATIC DIAGRAMS AND PART LISTS.....	108
6.5 USER'S MANUAL WITH "FCC INFORMATION TO USER STATEMENTS"	108

1. EXHIBIT 1 - SUMMARY OF TEST RESULTS & GENERAL STATEMENT OF CERTIFICATION

FCC PARAGRAPH.	TEST REQUIREMENTS	COMPLIANCE (YES/NO)
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System	Yes
15.247(b)	Maximum Peak Power	Yes
15.247(c)	RF Conducted Spurious Emissions at the Transmitter Antenna Terminal	Yes
15.247(c), 15.209 & 15.205	Transmitter Radiated Emissions	Yes
15.247(d)	Transmitted Power Density of a Direct Sequence Spread Spectrum System	Yes
15.247(e)	Processing Gain of Direct Sequence Spread Spectrum System	Yes
15.107, 15.109	AC Power Conducted Emissions & Radiated Emissions Digital Circuit Portions	Yes (Note 1)

Note 1: The digital circuits and receiver portion of the EUT has been tested and verified to comply with FCC Part 15, Subpart B, Class B – Computing Devices (FCC DoC). The engineering test report can be provided upon FCC requests.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

TESTIMONIAL AND STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY:

- 1) *THAT the application was prepared either by, or under the direct supervision of the undersigned.*
- 2) *THAT the measurement data supplied with the application was taken under my direction and supervision.*
- 3) *THAT the data was obtained on representative production units, representative.*
- 4) *THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.*

Certified by:

***Tri Minh Luu, P. Eng.
V.P., Engineering***

DATE: May 20, 1998

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

2. EXHIBIT 2 - GENERAL INFORMATION

2.1 *Applicant*

GEMTEK TECHNOLOGY CO., LTD.
11 Fl., 181 Tatung Rd., Sec. 1, Hsi-chih
Taipei Hsien, Taiwan, R.O.C.

Applicant's Representative: Mr. Howard Chen

2.2 *Manufacturer*

GEMTEK TECHNOLOGY CO., LTD.
11 Fl., 181 Tatung Rd., Sec. 1, Hsi-chih
Taipei Hsien, Taiwan, R.O.C.

Applicant's Representative: Mr. Howard Chen

2.3 *Description of Equipment under Test*

PRODUCT NAME:	PCMCIA WIRELESS LAN CARD
SERIAL NUMBER:	Pre-production
TYPE OF EQUIPMENT:	DSSS Transmitters
MODULATION:	1 Mb/s BPSK or 2 Mb/s QPSK
CHIP RATE:	5.5 Mchips/s (BPSK) or 11 Mchips/s (QPSK)
OPERATING FREQ.:	2412 – 2462 MHz
NUMBER OF CHANNEL:	11
CHANNEL SPACING:	5 MHz
BANDWIDTH (6 dB OBW):	10 MHz minimum
POWER RATING:	39 mW max. (direct) or 44.6 mW EIRP
ANTENNA GAIN:	2.4 GHz Disk Antenna, P/N: ERJ2RKF7150J, pcb mount type, Gain: 0 dBi typical and 2.15 dBi max. (permanently attached inside the case, on the pcb.)
EMISSION DESIGNATION:	Direct Sequence Spread Spectrum
DUTY CYCLE:	Continuous
OSC. FREQUENCY(IES):	32.768 KHz, 22 MHz, 40MHz, 560 MHz (VCO), 2450 MHz (IF), 280 MHz (IF), Tx Local Osc.: Tx freq. – IF freq. (280 MHz)

PCMCIA WIRELESS LAN CARD, Model WL-201**FCC ID: MXF-WL201**

INPUT SUPPLY: Using DC Power from a laptop computer

ASSOCIATED DEVICES: Not applicable

FCC ID: MXF-WL201

INTERFACE PORTS: Not applicable

2.4 Related Submittal(s)/Grant

Not applicable.

2.5 Test Methodology

These tests were conducted on a sample of the equipment for the purpose of certification compliance with Code of Federal Regulations (CFR47-1991), Part 15, Subpart C, Para. 15.247, Direct Sequence Spread Spectrum Transmitters operating in the Frequency Band 2412 - 2462 MHz.

Both conducted and radiated emissions measurements were conducted in accordance with American National Standards Institute ANSI C63.4-1992 - American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 KHz to 40 GHz.

2.6 Test Facility

AC Powerline Conducted Emissions were performed in UltraTech's shielded room, 16'(L) by 12'(W) by 12'(H).

Radiated Emissions were performed at the UltraTech's 3-to-10 Meter Open Field Test Site (OFTS) situated in the Town of Oakville, province of Ontario.

The above sites have been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec. 2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville Open Field Test Site has been filed with FCC office (FCC File No.: 31040/SIT 1300B3) and Industry Canada office (Industry Canada File No.: IC2049). Last Date of Site Calibration: July 16, 1997.

The above test site is also filed with Interference Technology International Ltd (ITI - An EC Directive on EMC).

2.7 Units of Measurements

Measurements of conducted emissions are reported in units of dB referenced to one microvolt [dB(uV)].

Measurements of radiated emissions are reported in units of dB referenced to one microvolt per meter [dB(uV)/m] at the distance specified in the report, wherever it is applicable.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


3. EXHIBIT 3 - SYSTEM TEST CONFIGURATION

3.1 Test System Details

The following peripherals, FCC identifiers and types interconnecting cables were used with the EUT for testing:

- (1) **EUT**: GEMTEK TECHNOLOGY CO., LTD., PCMCIA WIRELESS LAN CARD, Model : WL-201, S/N: Pre-production
Power & I/O Cable: Not applicable.
- (2) **PERIPHERAL**: HP OmniBook Laptop Computer, Model HP OmniBook 5500 CS, FCC ID: B945500, S/N: TW63403246
I/O Cable: All I/O Cables were shielded
Power Supply Cable: Non-shielded
- (3) **PERIPHERAL**: Digital DEC Writer 100I Parallel Printer, Model LJ100-AZ, S/N: OV44352056, FCC ID: EP8JP150
I/O CABLE: Shielded
POWER CABLE: Unshielded
- (5) **PERIPHERAL**: GVC Fax Modem, Model FM-144VR1, FCC ID: DK4FM144VR1
I/O Cable: Shielded
Power Supply Cable: Non-shielded

3.2 Block Diagrams Radiated Emission Measurements




- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

3.3 Photograph for RF Emission Measurements

Please refer to appendix the attached photos.

**TEST SETUP FOR
AC POWER LINE CONDUCTED EMISSIONS MEASUREMENTS
(tests were performed in the screen room)**

FRONT VIEW



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

SIDE & REAR VIEWS



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

TEST SETUP FOR RADIATED EMISSIONS MEASUREMENTS
(tests were performed at the Open Field test Site located in Oakville, Ontario, Canada)

***** TESTED WITH PERIPHERAL DEVICES ON THE TABLE *****



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

*** TESTED WITH PERIPHERAL DEVICES ON THE TABLE ***



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

*** TESTED WITH PERIPHERAL DEVICES OFF THE TABLE ***



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

*** TESTED WITH PERIPHERAL DEVICES OFF THE TABLE ***



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

3.4 Justification

No deviation, in both configuration and operation manners, different from normal operation were required.

3.5 EUT Operating Condition

Software provided by GEMTEK TECHNOLOGY CO., LTD. to set the EUT to transmit at lowest, middle and highest channel frequencies.

3.6 Special Accessories

No special accessories were required.

3.7 Equipment Modifications

To achieve compliance, the following change(s) were made by UltraTech's test house during compliance testing:

Not required.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4. EXHIBIT 4 - TEST DATA**4.1 6 dB Bandwidth @ FCC CFR 47, Para 15.247(a)(2)****PRODUCT NAME:** PCMCIA WIRELESS LAN CARD, Model No.: WL-201**FCC REQUIREMENTS:**

For a direct sequence spread spectrum system, the minimum 6 dB bandwidth shall be at least 500 KHz.

CLIMATE CONDITION:


Standard Temperature and Humidity: 23°C and 53%

TEST EQUIPMENT:

- Advantest Spectrum Analyzer, Model R3271, S/N: 15050203

METHOD OF MEASUREMENTS:

The transmitter output was connected to the spectrum analyzer through an attenuator. the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 100 KHz RBW, VBW = 100 KHz,. The 6 dB bandwidth was measured and recorded.


TEST ARRANGEMENT**TEST RESULTS:** Conforms.**TEST PERSONNEL:** Tri M. Luu, P.Eng.**DATE:** May 04, 1998**MEASUREMENT DATA:**

CHANNEL FREQUENCY (MHz)	DATA RATE / MODULATION	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
2412	2 Mb/s QPSK	9.9	0.5	PASS
2437	2 Mb/s QPSK	10.1	0.5	PASS
2462	2 Mb/s QPSK	9.9	0.5	PASS
2412	1 Mb/s BPSK	10.0	0.5	PASS
2437	1 Mb/s BPSK	9.9	0.5	PASS
2462	1 Mb/s BPSK	9.9	0.5	PASS

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 Mbps QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.2 Maximum Peak Output Power @ FCC 15.247(b) and RF Exposure Limit FCC 1.1310**PRODUCT NAME:** PCMCIA WIRELESS LAN CARD, Model No.: WL-201**FCC REQUIREMENTS:**

FCC 15.247(b):- Maximum peak output power of the transmitter shall not exceed 1 Watt. If the antenna of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC 1.1310:- The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	...	...	F/1500	6
1500-100,000	...	...	1.0	30

F = Frequency in MHz

* = Plane-wave equivalent power density

CLIMATE CONDITION:

- Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- HP RF Peak Power Meter, Model 8900, S/N: 2131A00124, Measuring Freq. Range: 01 - 18 GHz, 50 Ohm IN.
- HP RF Peak Power Sensor, Model 8481A, S/N: 2551A01965, Measuring Freq. Range: 0.1 - 18 GHz, 50 Ohm IN/OUT
- Bird 20 dB Attenuator, 50 Ohm IN/OUT

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

METHOD OF MEASUREMENTS:

FCC @ 1.1310 & OST Bulletin No. 65-October 1985

$$S = PG/4\pi r^2 = EIRP/4\pi r^2$$

Where:

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm²


G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{PG/4\pi S}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

TEST ARRANGEMENT

TEST RESULTS: Conforms.

TEST PERSONNEL: Tri M. Luu, P.Eng.

DATE: May 04, 1998

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

MEASUREMENT DATA:

PEAK POWER MEASUREMENT

ANTENNA GAIN: 0 dBi typical, 2.15 max. or 1.65 numeric

**DIRECT PEAK POWER MEASUREMENTS AT THE ANTENNA TERMINAL
WITH THE ANTENNA REPLACED BY A SMA CONNECTOR**

TRANSMITTER CHANNEL OUTPUT	FUNDAMENTAL FREQUENCY (MHz)	DATA RATE / MODULATION	MEASURED PEAK TOTAL POWER (mW)	PEAK POWER LIMIT (mW)
1	2412	2 Mb/s QPSK	38.8	1000.0
6	2437	2 Mb/s QPSK	38.1	1000.0
11	2462	2 Mb/s QPSK	34.4	1000.0
1	2412	1 Mb/s BPSK	38.8	1000.0
6	2437	1 Mb/s BPSK	38.1	1000.0
11	2462	1 Mb/s BPSK	34.4	1000.0

**EFFECTIVE ISOTROPIC RADIATED POWER (EIRP) MEASURED AT 3 METER DISTANCE
(Substitution Method)**

TX CHANNEL OUTPUT	FUNDAMENTAL FREQUENCY (MHz)	DATA RATE / MODULATION	Rx Antenna Gain (Numeric)	Max. Field Strength Level At 3 m (dBuV/m)	(1) Max. EIRP POWER @ 1 MHz BW (mW)	(2) Max. EIRP POWER In a full BW (mW)	PEAK POWER LIMIT (mW)
1	2412	2 Mb/s QPSK	4.3	102.3	3.1	17.4	1000.0
6	2437	2 Mb/s QPSK	4.3	106.4	7.9	44.6	1000.0
11	2462	2 Mb/s QPSK	4.3	91.8	0.3	1.5	1000.0
1	2412	1 Mb/s BPSK	4.3	101.6	2.6	14.8	1000.0
6	2437	1 Mb/s BPSK	4.3	106.3	7.8	43.6	1000.0
11	2462	1 Mb/s BPSK	4.3	92.1	0.3	1.7	1000.0

Remarks:

- (1) EIRP power measured in 1 MHz BW
- (2) Conversion of power measured in 1MHz BW using the EMI receiver to power in full BW using HP8900 peak power meter:
1MHz BW-Full BW power conversion factor = peak power level measured using the HP peak power meter - peak power level measured using EMI receiver in 1 MHz BW = 38.8 dBm – 31.3 dBm = 7.5 dB
- (3) The discrepancies between the EIRP power and direct power measurements are due to the non-linear characteristics of the transmitter antenna gain of the device under test (0 dBi typical, 2.15 dBi max.)

RF EXPOSURE DISTANCE LIMITS: $r = (PG/4\pi S)^{1/2}$
 $S=1\text{mW}/\text{cm}^2$, $G= 0 \text{ dBi}$ typical or 2.15 dBi max or 1.65 max

TRANSMITTER CHANNEL OUTPUT	FUNDAMENTAL FREQUENCY (MHz)	DATA RATE / MODULATION	MESURED EIRP FULL POWER (mWatts)	MINIMUM ALLOWABLE DISTANCE (r) FROM SKIN (Centi-Meter)
1	2412	2 Mb/s QPSK	17.4	1.5
6	2437	2 Mb/s QPSK	44.6	2.4
11	2462	2 Mb/s QPSK	1.5	0.5
1	2412	1 Mb/s BPSK	14.8	1.4
6	2437	1 Mb/s BPSK	43.6	2.4
11	2462	1 Mb/s BPSK	1.7	0.5

Since the power density of $1 \text{ mW}/\text{cm}^2$ is at a very short distance from the radiating antenna integrated on the printed circuit board which is completely enclosure in the case, RF exposure limit warning or SAR tests are not required.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.3 RF Conducted Emissions at the Transmitter Antenna Terminal, FCC CFR 47, Para. 15.247(c)

PRODUCT NAME: PCMCIA WIRELESS LAN CARD, Model No.: WL-201

FCC REQUIREMENTS:

In any 100 KHz bandwidth outside the operating frequency band, the radio frequency power that is produced by modulation products of the spreading sequence, the information sequence and the carrier frequency shall be at least 20 dB below that in any 100 KHz bandwidth within the band that contains the highest level of the desired power.

CLIMATE CONDITION:

Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- Advantest Spectrum Analyzer, Model R3271, S/N: 15050203

METHOD OF MEASUREMENT:

A scan was made by using a spectrum analyzer with the detector function set to PEAK mode.

Set RBW = 100 KHz, VBW = 100 KHz.

FCC CFR 47, Para. 2.997 - Frequency spectrum to be investigated


The spectrum was investigated from the lowest radio generated in the equipment up to at least the 10th harmonic of the carrier frequency or to the highest frequency practicable in the present state of the art of measuring techniques, whichever is lower. Particular attention should be paid to harmonics and subharmonics of the carrier frequency. Radiation at the frequencies of multiplier stages should be checked. The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

FCC CFR 47, Para. 2.991 - Spurious Emissions at Antenna Terminal

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of the harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in 2.989 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

TEST ARRANGEMENT



TEST RESULTS: Conforms.

TEST PERSONNEL: Tri M. Luu, P.Eng.

DATE: May 04, 1998

MEASUREMENT DATA

**SPURIOUS & HARMONIC EMISSIONS
AT THE TRANSMITTER ANTENNA TERMINAL**

TEST CONFIGURATION

- The transmitter was coupled to the Spectrum Analyzer.
- The channel frequencies were established on the extreme edges (both upper and lower) and middle of the 2412 - 2462 MHz band at its full rated output power. The emissions were investigated up to the tenth harmonic of the fundamental emissions in each case. The measured level of the carrier was recorded and compared to the level of the emissions as required in Part 15.247(c)

Channel #1, Channel Frequency: 2412 MHz Full Peak Rated Power: 38.8 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK			Power Level in 100 KHz BW: 6.2 dBm Limit = 6.2 dBm - 20 dB = -13.8 dBm	
FREQUENCY (MHz)	RF LEVEL 100 kHz BW (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2412.0	6.2	--	--	--
281.0	-46.5	-13.8	-32.7	PASS
1480.0	-62.8	-13.8	-49.0	PASS
4805.0	-62.3	-13.8	-48.5	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				

Channel #6, Channel Frequency: 2437 MHz Full Rated Peak Power: 38.1 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK			Power Level in 100 KHz BW: 4.4 dBm Limit = 4.4 dBm - 20 dB = -15.6 dBm	
FREQUENCY (MHz)	RF LEVEL 100 kHz BW (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2437.0	4.4	--	--	--
280.0	-46.7	-15.6	-31.1	PASS
1523.0	-62.5	-15.6	-46.9	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				

Channel #11, Channel Frequency: 2462 MHz Full Rated Peak Power: 34.4 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK			Power Level in 100 KHz BW: 3.6 dBm Limit = 3.6 dBm - 20 dB = -16.4 dBm	
FREQUENCY (MHz)	RF LEVEL (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2462.0	3.6	--	--	--
280.0	-49.5	-16.4	-33.1	PASS
1566.0	-60.8	-16.4	-44.4	PASS
2165.0	-60.8	-16.4	-44.4	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				

Channel #1, Channel Frequency: 2412 MHz Full Rated Peak Power: 38.8 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK			Power Level in 100 KHz BW: 5.8 dBm Limit = 5.8 dBm - 20 dB = -14.2 dBm	
FREQUENCY (MHz)	RF LEVEL (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2412.0	5.8	--	--	--
281.0	-46.5	-14.2	-32.3	PASS
1480.0	-62.0	-14.2	-47.8	PASS
4805.0	-60.1	-14.2	-45.9	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				

Channel #6, Channel Frequency: 2437 MHz Full Rated Peak Power: 38.1 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK			Power Level in 100 KHz BW: 4.1 dBm Limit = 4.1 dBm - 20 dB = -15.9 dBm	
FREQUENCY (MHz)	RF LEVEL (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2437.0	4.1	--	--	--
280.0	-47.3	-15.9	-31.4	PASS
1523.0	-63.6	-15.9	-47.7	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				


- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Channel #11, Channel Frequency: 2462 MHz Full Rated Peak Power: 34.4 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK			Power Level in 100 KHz BW: 3.9 dBm Limit = 3.9 dBm - 20 dB = -16.1 dBm	
FREQUENCY (MHz)	RF LEVEL (dBm)	LIMIT (dBm)	MARGIN (dB)	PASS/ FAIL
2462.0	3.9	--	--	--
280.0	-50.0	-16.1	-33.9	PASS
1566.0	-62.1	-16.1	-46.0	PASS
2165.0	-61.6	-16.1	-45.5	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details				

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1 1: Tx Frequency: 2412 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK




*** Multi Marker List ***
310 MHz -46.66 dBm
1.523 GHz -62.53 dBm
2.422 GHz 3.72 dBm

No. 1:
No. 2:
No. 3:
No. 4:
No. 5:
No. 6:
No. 7:
No. 8:
Δ:

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WLR-201
Channel #: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WVR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK



*** Multi Marker List ***


No.	Frequency (MHz)	Power (dBm)
1	338 MHz	-49.47 dBm
2	1.566 GHz	-60.84 dBm
3	2.436 GHz	3.03 dBm
4	2.165 GHz	-60.84 dBm

No. 1: Δ
No. 2: Δ
No. 3: Δ
No. 4: Δ
No. 5: Δ
No. 6: Δ
No. 7: Δ
No. 8: Δ

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WLR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1 1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Truh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DSSS



*** Multi Marker List ***


No.	Marker	Frequency (MHz)	Power (dBm)
1	281 MHz	281 MHz	-46.50 dBm
2	1.480 GHz	1.480 GHz	-62.03 dBm
3	2.393 GHz	2.393 GHz	5.84 dBm
4	4.805 GHz	4.805 GHz	-60.06 dBm

No. 1:
No. 2:
No. 3:
No. 4:
No. 5:
No. 6:
No. 7:
No. 8:
Δ:

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Triah


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK



*** Multi Marker List ***


No.	Freq (MHz)	Power (dBm)
1	310	-47.31
2	1.523	-63.56
3	2.422	3.34

No. 1: A
No. 2: A
No. 3: A
No. 4: A
No. 5: A
No. 6: A
No. 7: A
No. 8: A

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DSSS



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh


TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK



*** Multi Marker List ***

No.	Frequency (MHz)	Power (dBm)
1	338	-50.00
2	1.566	-62.13
3	2.436	-2.66
4	2.165	-61.59


No. 1:
No. 2:
No. 3:
No. 4:
No. 5:
No. 6:
No. 7:
No. 8:
Δ:

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

UltraTech
Engineering Labs Inc.

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK

Date: May 04, 1998
Tested by: Hung Trinh



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.4 Transmitter Radiated Emissions @ 3 Meters, FCC CFR 47, Para. 15.247(c), 15.209 & 15.205**PRODUCT NAME:** PCMCIA WIRELESS LAN CARD, Model No.: WL-201**FCC REQUIREMENTS:**

In any 100 KHz bandwidth outside the operating frequency band, the radio frequency power that is produced by modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 KHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in @ 15.209(a), which lesser attenuation.

All other emissions inside restricted bands specified in @ 15.205(a) shall not exceed the general radiated emission limits specified in @ 15.209(a)

Remarks:

- Applies to harmonics/spurious emissions that fall in the restricted bands listed in Section 15.205. The maximum permitted average field strength is listed in Section 15.209.
- @ FCC CFR 47, Para. 15.237(c) - The emission limits as specified above are based on measurement instrument employing an average detector. The provisions in @15.35 for limiting peak emissions apply.

FCC CFR 47, Part 15, Subpart C, Para. 15.205(a) - Restricted Frequency Bands

MHz	MHz	MHz	GHz
0.090 - 0.110	162.0125 - 167.17	2310 - 2390	9.3 - 9.5
0.49 - 0.51	167.72 - 173.2	2483.5 - 2500	10.6 - 12.7
2.1735 - 2.1905	240 - 285	2655 - 2900	13.25 - 13.4
8.362 - 8.366	322 - 335.4	3260 - 3267	14.47 - 14.5
13.36 - 13.41	399.9 - 410	3332 - 3339	14.35 - 16.2
25.5 - 25.67	608 - 614	3345.8 - 3358	17.7 - 21.4
37.5 - 38.25	960 - 1240	3600 - 4400	22.01 - 23.12
73 - 75.4	1300 - 1427	4500 - 5250	23.6 - 24.0
108 - 121.94	1435 - 1626.5	5350 - 5460	31.2 - 31.8
123 - 138	1660 - 1710	7250 - 7750	36.43 - 36.5
149.9 - 150.05	1718.8 - 1722.2	8025 - 8500	Above 38.6
156.7 - 156.9	2200 - 2300	9000 - 9200	

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

FCC CFR 47, Part 15, Subpart C, Para. 15.209(a)

-- Field Strength Limits within Restricted Frequency Bands --

FREQUENCY (MHz)	FIELD STRENGTH LIMITS (microvolts/m)	DISTANCE (Meters)
0.009 - 0.490	2,400 / F (KHz)	300
0.490 - 1.705	24,000 / F (KHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

CLIMATE CONDITION:

Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- **Spectrum Analyzer**, Advantest, Model R3271, S/N: 15050203, 100 Hz to 32 GHz)
- **Microwave Amplifier**, HP, Model 83017A, Frequency Range 1 to 26.5 GHz, 34-38 dBdB gain nominal.
- **Active Loop Antenna**, Emco, Model 6507, SN 8906-1167, Frequency Range 1 KHz - 30 MHz, @ 50 Ohms
- **Log Periodic/Bow-Tie Antenna**, Emco, Model 3143, SN 1029, 20 - 1000 MHz, @ 50 ohms.
- **Horn Antenna**, Emco, Model 3115, SN 9701-5061, Frequency Range: 1 - 18 GHz, @ 50 Ohms.
- **Horn Antenna**, Emco, Model 3160-09, 18-26.5GHz
- **Horn Antenna**, Emco, Model 3160-09, 18-26.5GHz
- **Horn Antenna**, Emco, Model 3160-10, 26.5-40GHz
- **Mixer**, Tektronix, P/N 118-0098-00, 18-26.5GHz
- **Mixer**, Tektronix, P/N 119-0098-00, 26.5-40GHz

METHOD OF MEASUREMENTS:

Refer to **ANSI 63.4-1992, Para. 8** for detailed radiated emissions measurement procedures.

Applies to harmonics/spurious that fall in the restricted bands listed in Section 15.205. the maximum permitted average field strength is listed in Section 15.209. A Pre-Amp and highpass filter are used for this measurement.

For measurement below 1 GHz, set RBW = 100 KHz, VBW $\geq$ 100 KHz, SWEEP=AUTO.

For measurement above 1 GHz, set RBW = 1 MHz, VBW = 1 MHz (Peak) & VBW = 10 Hz (Average), SWEEP=AUTO.

If the emission is pulsed, modified the unit for continuous operation, then use the settings above for measurements, then correct the reading by subtracting the peak-average correction factor derived from the appropriate duty cycle calculation. See Section 15.35(b) and (c).

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

FCC CFR 47, Para. 2.997 - Frequency spectrum to be investigated

The spectrum was investigated from the lowest radio generated in the equipment up to at least the 10th harmonic of the carrier frequency or to the highest frequency practicable in the present state of the art of measuring techniques, whichever is lower. Particular attention should be paid to harmonics and subharmonics of the carrier frequency. Radiation at the frequencies of multiplier stages should be checked. The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

FCC CFR 47, Para. 2.993 - Field Strength Spurious Emissions

- (a) Measurements was made to detect spurious emissions radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data were supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph 2.989(c) as appropriate. For equipment operating on frequencies below 1 GHz, an Open Field Test is normally required, with the measuring instrument antenna located in the far field at all test frequencies. In event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurement will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with the reference to the rated power output of the transmitter, assuming all emissions are radiated from half-wave dipole antennas.
- (b) Measurements specified in paragraph (a) of this section shall be made for the following equipment:
- (1) Those in which the spurious emission are required to be 60 dB or more below the mean power of the transmitter.
 - (2) All equipment operating on frequencies higher than 25 MHz
 - (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
 - (4) Other types of equipment as required, when deemed necessary by the Commission.

TEST RESULTS: Conforms.

TEST PERSONNEL: Hung Trinh, EMI Technician

DATE: May 07 & 09, 1998

MEASUREMENT DATA**RADIATED EMISSIONS MEASUREMENTS @ 3 METERS****TEST CONFIGURATION**


- This lowest, middle and highest channels were established at its full rated output power. The emissions were investigated from the lowest frequency generated by the transmitter up to the 10th harmonic of the fundamental emissions in each case. the measured level of the carrier was recorded and compared to the level of the emissions as required in Parts 15.247(c) or 15.209(a) whichever was applicable.
- For measuring radiated emissions at frequencies below 1 GHz, the Spectrum Analyzer was set as 100 KHz RBW, VBW $\geq$ RBW, SWEEP TIME: AUTO, PEAK DETECTOR.
- For measuring radiated emissions at frequencies above 1 GHz, the Spectrum Analyzer was set as 1 MHz RBW, 1 MHz VBW, SWEEP TIME: AUTO for PEAK measurements and 1 MHz RBW, 10 Hz VBW, SWEEP TIME: AUTO for AVERAGE measurements.
- The following measurements were the worst cases when the radiating antenna was placed in both horizontal and vertical polarization.
- The following **AVERAGE** rf levels were obtained from either Peak or Average readings added by the duty cycle correction factor. **DUTY CYCLE FACTOR = N/A (continuous)**

Channel #1, Channel Frequency: 2412 MHz Full Rated Peak Power: 38.8 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK				Power Level in 1 MHz BW: 102.3 dBuV/m Limit = 82.3 dBuV/m			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	33.6	25.1	V	46.0	82.3	-20.9	PASS
280.00	29.8	20.0	H	46.0	82.3	-26.0	PASS
560.00	48.2	46.9	V	46.0	82.3	-35.4	PASS
560.00	51.7	50.3	H	46.0	82.3	-32.0	PASS
840.00	28.9	17.2	V	46.0	82.3	-65.1	PASS
840.00	30.0	18.6	H	46.0	82.3	-63.7	PASS
1120.00	58.3	52.3	V	54.0	82.3	-1.7	PASS
1120.00	57.1	48.9	H	54.0	82.3	-5.1	PASS
1400.00	37.3	21.8	V	54.0	82.3	-32.2	PASS
1400.00	37.3	26.1	H	54.0	82.3	-27.9	PASS
1680.00	43.3	38.6	V	54.0	82.3	-15.4	PASS
1680.00	37.7	28.6	H	54.0	82.3	-25.4	PASS
2132.00	67.9	66.0	V	54.0	82.3	-16.3	PASS
2132.00	70.0	68.3	H	54.0	82.3	-14.0	PASS
2240.00	52.6	50.8	V	54.0	82.3	-3.2	PASS
2240.00	52.6	51.0	H	54.0	82.3	-3.0	PASS
2412.00	98.4	--	V	54.0	82.3	--	--
2412.00	102.3	--	H	54.0	82.3	--	--
2520.00	43.7	31.9	V	54.0	82.3	-50.4	PASS
2800.00	46.5	42.1	V	54.0	82.3	-11.9	PASS
2800.00	48.8	44.6	H	54.0	82.3	-9.4	PASS
4264.00	46.3	33.2	V	54.0	82.3	-20.8	PASS
4264.00	46.6	33.0	H	54.0	82.3	-21.0	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh


TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 mb/s QPSK
Antenna polarization: VERTICAL [✓], HORIZONTAL []



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 Mbps QPSK
Antenna polarization: VERTICAL [] , HORIZONTAL [✓]



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OFTS
 GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
 TRANSMIT FREQ.: 2412 MHz, 2 Mb/s QPSK




- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Channel #6, Channel Frequency: 2437 MHz Full Rated Peak Power: 38.1 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK				Power Level in 1 MHz BW: 106.3 dBuV/m Limit = 86.3 dBuV/m			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	33.6	25.1	V	46.0	86.3	-20.9	PASS
280.00	29.8	20.0	H	46.0	86.3	-26.0	PASS
560.00	48.2	46.9	V	46.0	86.3	-39.4	PASS
560.00	51.7	50.3	H	46.0	86.3	-36.0	PASS
840.00	28.9	17.2	V	46.0	86.3	-69.1	PASS
840.00	30.0	18.6	H	46.0	86.3	-67.7	PASS
1120.00	58.3	52.3	V	54.0	86.3	-1.7	PASS
1120.00	57.1	48.9	H	54.0	86.3	-5.1	PASS
1400.00	37.3	21.8	V	54.0	86.3	-32.2	PASS
1400.00	37.3	26.1	H	54.0	86.3	-27.9	PASS
1680.00	43.3	38.6	V	54.0	86.3	-15.4	PASS
1680.00	37.7	28.6	H	54.0	86.3	-25.4	PASS
2157.00	69.8	68.4	V	54.0	86.3	-17.9	PASS
2157.00	70.4	68.4	H	54.0	86.3	-17.9	PASS
2240.00	52.6	50.8	V	54.0	86.3	-3.2	PASS
2240.00	52.6	51.0	H	54.0	86.3	-3.0	PASS
2437.00	105.8	--	V	54.0	86.3	--	--
2437.00	106.3	--	H	54.0	86.3	--	--
2520.00	43.7	31.9	V	54.0	86.3	-54.4	PASS
2800.00	46.5	42.1	V	54.0	86.3	-11.9	PASS
2800.00	48.8	44.6	H	54.0	86.3	-9.4	PASS
4314.00	48.5	40.1	V	54.0	86.3	-13.9	PASS
4314.00	46.8	34.8	H	54.0	86.3	-19.2	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK
Antenna polarization: VERTICAL ☒ HORIZONTAL ☐



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201

Channel #6: Tx Frequency: 2437 MHz


Modulation: 2 Mb/s QPSK

Antenna polarization: VERTICAL [], HORIZONTAL [✓]



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OFTS
 GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
 TRANSMIT FREQ.: 2437 MHz, 2 Mb/s QPSK




- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Channel #11, Channel Frequency: 2462 MHz Full Rated Peak Power: 34.4.0 mW Modulation: DSSS, 2Mb/s Data Rate, QPSK				Power Level in 1 MHz BW: dBuV/m Limit = dBuV/m			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	33.6	25.1	V	46.0	72.1	-20.9	PASS
280.00	29.8	20.0	H	46.0	72.1	-26.0	PASS
560.00	48.2	46.9	V	46.0	72.1	-25.2	PASS
560.00	51.7	50.3	H	46.0	72.1	-21.8	PASS
840.00	28.9	17.2	V	46.0	72.1	-54.9	PASS
840.00	30.0	18.6	H	46.0	72.1	-53.5	PASS
1120.00	58.3	52.3	V	54.0	72.1	-1.7	PASS
1120.00	57.1	48.9	H	54.0	72.1	-5.1	PASS
1400.00	37.3	21.8	V	54.0	72.1	-32.2	PASS
1400.00	37.3	26.1	H	54.0	72.1	-27.9	PASS
1680.00	43.3	38.6	V	54.0	72.1	-15.4	PASS
1680.00	37.7	28.6	H	54.0	72.1	-25.4	PASS
2182.00	68.1	65.8	V	54.0	72.1	-6.3	PASS
2182.00	71.3	69.4	H	54.0	72.1	-2.7	PASS
2240.00	52.6	50.8	V	54.0	72.1	-3.2	PASS
2240.00	52.6	51.0	H	54.0	72.1	-3.0	PASS
2462.00	91.8	--	V	54.0	72.1	--	--
2462.00	91.8	--	H	54.0	72.1	--	--
2520.00	43.7	31.9	V	54.0	72.1	-40.2	PASS
2800.00	46.5	42.1	V	54.0	72.1	-11.9	PASS
2800.00	48.8	44.6	H	54.0	72.1	-9.4	PASS
4364.00	47.5	37.4	V	54.0	72.1	-16.6	PASS
4364.00	46.8	33.9	H	54.0	72.1	-20.1	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh


TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2482 MHz
Modulation: 2 Mbps QPSK
Antenna polarization: VERTICAL [✓], HORIZONTAL []



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK
Antenna polarization: VERTICAL [] HORIZONTAL [X]



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OETS
 GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
 TRANSMIT FREQ.: 2462 MHz, 2 Mb/s QPSK




Channel #1, Channel Frequency: 2412 MHz Full Rated Peak Power: 38.8 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK				Power Level in 1 MHz BW: 101.6 dBuV/m Limit = 81.6 dBuV/m.			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	34.4	26.5	V	46.0	81.6	-19.5	PASS
280.00	29.7	20.5	H	46.0	81.6	-25.5	PASS
560.00	48.9	47.8	V	46.0	81.6	-33.8	PASS
560.00	48.9	47.8	H	46.0	81.6	-33.8	PASS
840.00	26.3	15.0	V	46.0	81.6	-66.6	PASS
840.00	31.8	22.5	H	46.0	81.6	-59.1	PASS
1120.00	58.3	51.6	V	54.0	81.6	-2.4	PASS
1120.00	57.6	49.9	H	54.0	81.6	-4.1	PASS
1400.00	37.5	24.4	V	54.0	81.6	-29.6	PASS
1680.00	40.1	32.1	V	54.0	81.6	-21.9	PASS
1680.00	38.8	30.8	H	54.0	81.6	-23.2	PASS
2132.00	68.3	65.3	V	54.0	81.6	-16.3	PASS
2132.00	70.4	68.1	H	54.0	81.6	-13.5	PASS
2240.00	53.6	51.7	V	54.0	81.6	-2.3	PASS
2240.00	50.8	48.2	H	54.0	81.6	-5.8	PASS
2412.00	98.4	98.4	V	54.0	81.6	--	--
2412.00	101.6	101.6	H	54.0	81.6	--	--
2520.00	42.4	31.3	V	54.0	81.6	-50.3	PASS
2800.00	47.6	42.5	V	54.0	81.6	-11.5	PASS
2800.00	47.3	41.0	H	54.0	81.6	-13.0	PASS
4264.00	48.9	40.3	V	54.0	81.6	-13.7	PASS
4264.00	46.0	34.6	H	54.0	81.6	-19.4	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh


TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DSSS
Antenna polarization: VERTICAL [✓] HORIZONTAL []



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DPSK
Antenna polarization: VERTICAL [] HORIZONTAL [x]



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OFTS
 GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
 TRANSMIT FREQ.: 2412 MHz, 1 Mb/s BPSK




- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Channel #6, Channel Frequency: 2437 MHz Full Rated Peak Power: 38.1 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK				Power Level in 1 MHz BW: 106.4 dBuV/m Limit = 86.4 dBuV/m			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	34.4	26.5	V	46.0	86.4	-19.5	PASS
280.00	29.7	20.5	H	46.0	86.4	-25.5	PASS
560.00	48.9	47.8	V	46.0	86.4	-38.6	PASS
560.00	48.9	47.8	H	46.0	86.4	-38.6	PASS
840.00	26.3	15.0	V	46.0	86.4	-71.4	PASS
840.00	31.8	22.5	H	46.0	86.4	-63.9	PASS
1120.00	58.3	51.6	V	54.0	86.4	-2.4	PASS
1120.00	57.6	49.9	H	54.0	86.4	-4.1	PASS
1400.00	37.5	24.4	V	54.0	86.4	-29.6	PASS
1680.00	40.1	32.1	V	54.0	86.4	-21.9	PASS
1680.00	38.8	30.8	H	54.0	86.4	-23.2	PASS
2157.00	69.9	68.0	V	54.0	86.4	-18.4	PASS
2157.00	70.2	68.4	H	54.0	86.4	-18.0	PASS
2240.00	53.6	51.7	V	54.0	86.4	-2.3	PASS
2240.00	50.8	48.2	H	54.0	86.4	-5.8	PASS
2437.00	105.8	105.8	V	54.0	86.4	--	--
2437.00	106.4	106.3	H	54.0	86.4	--	--
2520.00	42.4	31.3	V	54.0	86.4	-55.1	PASS
2800.00	47.6	42.5	V	54.0	86.4	-11.5	PASS
2800.00	47.3	41.0	H	54.0	86.4	-13.0	PASS
4314.00	48.5	40.1	V	54.0	86.4	-13.9	PASS
4314.00	46.8	34.8	H	54.0	86.4	-19.2	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh


TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK
Antenna polarization: VERTICAL ☒ HORIZONTAL ☐



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK
Antenna polarization: VERTICAL [] HORIZONTAL [✓]



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OETS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
TRANSMIT FREQ.: 2437 MHz, 1 Mb/s BPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)


Channel #11, Channel Frequency: 2462 MHz Full Rated Peak Power: 34.4 mW Modulation: DSSS, 1Mb/s Data Rate, BPSK				Power Level in 1 MHz BW: 92.1 dBuV/m Limit = 72.1 dBuV/m			
FREQUENCY (MHz)	RF PEAK LEVEL (dBuV/m)	RF AVG LEVEL (dBuV/m)	ANTENNA PLANE (H/V)	LIMIT 15.209 (dBuV/m)	LIMIT 15.247 (dBuV/m)	MARGIN (dB)	PASS/ FAIL
280.00	34.4	26.5	V	46.0	72.1	-19.5	PASS
280.00	29.7	20.5	H	46.0	72.1	-25.5	PASS
560.00	48.9	47.8	V	46.0	72.1	-24.3	PASS
560.00	48.9	47.8	H	46.0	72.1	-24.3	PASS
840.00	26.3	15.0	V	46.0	72.1	-57.1	PASS
840.00	31.8	22.5	H	46.0	72.1	-49.6	PASS
1120.00	58.3	51.6	V	54.0	72.1	-2.4	PASS
1120.00	57.6	49.9	H	54.0	72.1	-4.1	PASS
1400.00	37.5	24.4	V	54.0	72.1	-29.6	PASS
1680.00	40.1	32.1	V	54.0	72.1	-21.9	PASS
1680.00	38.8	30.8	H	54.0	72.1	-23.2	PASS
2182.00	68.2	66.4	V	54.0	72.1	-5.7	PASS
2182.00	70.8	69.4	H	54.0	72.1	-2.7	PASS
2240.00	53.6	51.7	V	54.0	72.1	-2.3	PASS
2240.00	50.8	48.2	H	54.0	72.1	-5.8	PASS
2462.00	91.8	92.1	V	54.0	72.1	--	--
2462.00	91.8	91.7	H	54.0	72.1	--	--
2520.00	42.4	31.3	V	54.0	72.1	-40.8	PASS
2800.00	47.6	42.5	V	54.0	72.1	-11.5	PASS
2800.00	47.3	41.0	H	54.0	72.1	-13.0	PASS
4364.00	47.3	35.0	V	54.0	72.1	-19.0	PASS
4364.00	46.8	33.9	H	54.0	72.1	-20.1	PASS
No other significant emissions were found in the frequency range from 10 MHz to 25 GHz. Refer to attached plots for details							

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

UltraTech
Engineering Labs Inc.

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK
Antenna polarization: VERTICAL [✓] HORIZONTAL []

Date: May 05, 1998
Tested by: Hung Trinh



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 05, 1998
Tested by: Hung Trinh

TRANSMITTER RADIATED EMISSIONS @ 3 Meters
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201

Channel #1: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DPSK
Antenna polarization: VERTICAL [].



E3115+HP83017+SMA7
REF 107.0 dB μ /m
10dB/

Mon May 4 15: 55: 48 1998

ATT 10 dB A write&max B blank

[illegible]

91.69 dB/V/m

A hand-drawn diagram consisting of a vertical line intersected by a horizontal line. Below the intersection, there are two wavy lines, one above the other, both starting from the vertical line and extending to the right.

amplitude

[illegible]

[illegible][illegible]


--	--	--	--	--	--	--

SPAN 200.0 MHz

2005

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Transmitter Radiated Emissions Measurements at 3 Meter OFTS
 GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
 TRANSMIT FREQ.: 2462 MHz, 1 Mb/s BPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.5 Transmitted Power Density of a Direct Sequence Spread Spectrum System, FCC CFR 47, Para. 15.247(d)

PRODUCT NAME: PCMCIA WIRELESS LAN CARD, Model No.: WL-201

FCC REQUIREMENTS:

For a direct sequence system, the transmitted power density average over any 1 second interval shall not be greater than 8 dBm in any 3 KHz bandwidth within this band.

CLIMATE CONDITION:

Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- Advantest Spectrum Analyzer, Model R3271, S/N: 15050203
- Bird 20 dB Attenuator, 50 Ohm IN/OUT

METHOD OF MEASUREMENT:


A scan was made by using a spectrum analyzer with the detector function set to NORMAL mode.

Locate and zoom in on emission peak(s) within the passband. Set RBW = 3 KHz, VBW $\geq$ RBW, Sweep = SPAN/3 KHz. For example, a span of 1.5 MHz, the sweep should be $1.6 \times 10^6 / 3.0 \times 10^3 = 500$ seconds. The measured peak level must be no greater than +8 dBm.

- For devices with spectrum line spacing greater than 3 KHz no change is required.
- For devices with spectrum line spacing equal to or less than 3 KHz, the resolution bandwidth must be reduced below 3 KHz until the individual lines in the spectrum are resolved. The measurement data must then be normalized to 3 KHz by summing the power of all the individual spectral lines within 3 KHz band (in linear power units) to determine compliance.
- If the spectrum line spacing cannot be resolved on the available spectrum analyzer, the noise density function on most modern conventional spectrum analyzer will directly measure the noise power density normalized to 1 Hz noise power bandwidth. Add 30 dB for correction to 3 KHz.
- Should all the above fail or any controversy develop regarding accuracy of measurement, the Laboratory will use HP 89440A Vector Signal Analyzer for final measurement unless a clear showing can be made for a further alternate.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

TEST ARRANGEMENT



TEST RESULTS: Conforms.

TEST PERSONNEL: Tri M. Luu, P.Eng.

DATE: May 04, 1998

MEASUREMENT DATA:

TEST CONFIGURATION



- The transmitter was coupled to the Spectrum Analyzer.
- The channel frequencies were established on the extreme edges (both upper and lower) and middle of the 2412 - 2462 MHz band at its full rated output power. The emissions was investigated up to the tenth harmonic of the fundamental emissions in each case. the measured level of the carrier was recorded and compared to the level of the emissions as required in Part 15.247(d)

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	DATA RATE / MODULATION	RF POWER LEVEL IN 3 KHz BW (dBm)	LIMIT (dBm)	MARGIN (dB)	COMMENTS (PASS/FAIL)
1	2412	2 Mb/s QPSK	-9.0	8.0	-17.0	PASS
6	2437	2 Mb/s QPSK	-10.9	8.0	-18.9	PASS
11	2462	2 Mb/s QPSK	-11.7	8.0	-19.7	PASS
1	2412	1 Mb/s BPSK	-9.3	8.0	-17.3	PASS
6	2437	1 Mb/s BPSK	-11.1	8.0	-19.1	PASS
11	2462	1 Mb/s BPSK	-11.4	8.0	-19.4	PASS

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh



TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh



TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
Channel #: Tx Frequency: 2437 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Triah



TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 2 Mb/s QPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh



TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #1: Tx Frequency: 2412 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh



TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WL-201
Channel #6: Tx Frequency: 2437 MHz
Modulation: 1 Mb/s DPSK



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Date: May 04, 1998
Tested by: Hung Trinh

TRANSMITTER ANTENNA POWER CONDUCTED EMISSIONS
GEMTEK PCMCIA WIRELESS LAN CARD, MODEL WR-201
Channel #11: Tx Frequency: 2462 MHz
Modulation: 1 Mb/s DSSS



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.6 Processing Gain of A Direct Sequence Spread Spectrum, FCC CFR 47, Para. 15.247(e)

PRODUCT NAME: PCMCIA WIRELESS LAN CARD, Model No.: WL-201

FCC REQUIREMENTS:

The processing gain of a direct sequence system shall be at least 10 dB. The processing gain shall be determined from the ratio in dB of the signal-to-noise ratio with the system spreading code turned off to the signal-to-noise ratio with the system spreading code turned on, as measured at the demodulated output of the receiver.

CLIMATE CONDITION:

Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- Advantest Spectrum Analyzer, Model R3271, S/N: 15050203
- 3dB & 40 dB Attenuators, 50 Ohm IN/OUT
- Fluke RF Signal Generator, Model 6061A, Freq. range: 10 KHz - 1050 MHz.
- HP 8900 RF Peak Power Meter, Measuring Frequency Range: 100 MHz - 18 GHz.
- Bert Fireberd 4000 Communication Analyzer

METHOD OF MEASUREMENT:- Jamming Margin Method

The processing gain may be measured using the CW jamming margin method. Figure 1 shows the test configuration. The test consists of stepping a signal generator in 50 KHZ increments across the passband of the system. At each point, the generator level required to produce the recommended Bit Error Rate (BER) is recorded. This level is jammer level. The output power of the transmitting unit is measured at the same point. The Jammer to Signal (J/S) ratio is then calculated. Discard the worst 20% of the J/S data points. The lowest remaining J/S ratio is used when calculating the Process Gain.

The signal to noise ratio for an ideal differentially coherent detection of a differentially encoded BPSK receiver can be derived from the Bit Error Probability (Pb) versus Signal-to-Noise ratio. See attached plot for detailed information.

For measurement of the $(S/N)_o$ we use the Pb of 1.0×10^{-5} minimum.

Ref.: Viterbi, A.J. Principles of Coherent Communications (New York: McGraw-HILL 1966), Pg. 207

Using equation (1) shown above, calculate the signal to noise ratio required for your chosen BER. This value and the measured J/S ratio are used in the following equation to calculate the Process Gain (Gp) of the system.

$$G_p = (S/N)_o + M_j + L_{sys}$$

Where:

- (S/N)_o: Theoretical signal to noise ratio required to maintain the normal operation just before the BER appears. In real measurements the maximum error of 0.001 is allowed in an ideal system using their modulation scheme with all codes turned off (i.e. no spreading or processing gain).
- M_j: Maximum jammer to Signal Ratio that recorded at the detected BER.
- L_{sys}: System losses such as non-ideal synchronization, tracking circuitry, non-optimal baseband receiver filtering and etc... These losses can be in excess of 3 dB for each transmitter and receiver pair. For the purpose of this processing gain calculation we assume a L_{sys} at its minimum value of 2 dB.

Ref.: Dixon, R, Spread Spectrum Systems. (New York: Wiley, 1984), Chapter 1.

TEST RESULTS: Conforms.


TEST PERSONNEL: Tri M. Luu, P.Eng.

DATE: May 12, 1998

MEASUREMENT DATA:

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

- Processing gain $G_p = (S/N)_o + L_{sys} + M_j = (S/N)_o + 2 + M_j$



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.5 Definitions and Performance of Spectral and Power Efficiency

211




Figure 4.5.1 Theoretical $P_e = f(E_b/N_0)$ performance in a stationary additive white Gaussian noise (AWGN) environment. Ideal, linearly amplified coherent BPSK, QPSK, and differentially demodulated DBPSK systems are illustrated. The performance of non-linearly amplified FQPSK and GMSK is compared to ideal linearly amplified QPSK in Figures 4.3.33 and 4.3.34. (From Proakis, 1989.) See Appendix A.3.

tically equivalent term bit-error rate (BER) is used in applied references and specifications.

Power efficiency of modulated systems is defined as being inversely proportional to the

$$\text{BER} = f(C/N)$$

and/or

$$\text{BER} = f(E_b/N_0)$$

equations and performance curves, where E_b is the average energy of a modulated bit and N_0 is the noise power spectral density (the noise power in a normalized 1-Hz bandwidth) at the demodulator input. The higher the probability of error, the lower the power efficiency, since transmitted power is "wasted" on more bad data.

Test Method Employed: Jamming Margin
Test Configuration Mode: QPSK MODULATION, 2 Mb/s Data Rate

$$\text{Theoretical Process Gain} = \frac{11 \text{ MHz}}{(2\text{Mb/s})/(2\text{bits/symbol})} = 11 \text{ numeric or } 10.4 \text{ dB}$$

Measured The Transmitter's Peak RF Power @ Receiver Input Terminal:: -23.7 dBm

THEORETICAL PROCESS GAIN : 10.4dB				MIN. MEASURED PROCESSING GAIN: 12.1dB after discarding 18.9% of the worst readings			
Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
1	-5.00	0.1	9.6	2.0	1.6	13.2	
2	-4.95	4.2	9.1	2.0	3.7	14.8	
3	-4.90	2.4	9.3	2.0	2.7	14.0	
4	-4.85	1.3	9.5	2.0	3.2	14.7	
5	-4.80	1.4	9.4	2.0	3.0	14.4	
6	-4.75	1.8	9.4	2.0	2.6	14.0	
7	-4.70	1.1	9.5	2.0	3.1	14.6	
8	-4.65	2.3	9.3	2.0	3.5	14.8	
9	-4.60	4.1	9.1	2.0	3.4	14.5	
10	-4.55	2.1	9.4	2.0	3.8	15.2	
11	-4.50	1.9	9.4	2.0	2.7	14.1	
12	-4.45	2.3	9.3	2.0	3.8	15.1	
13	-4.40	1.4	9.4	2.0	2.9	14.3	
14	-4.35	1.5	9.4	2.0	2.7	14.1	
15	-4.30	2.3	9.3	2.0	2.9	14.2	
16	-4.25	2.2	9.4	2.0	2.6	14.0	
17	-4.20	3.1	9.2	2.0	2.8	14.0	
18	-4.15	1.8	9.4	2.0	2.5	13.9	
19	-4.10	2.0	9.4	2.0	2.4	13.8	
20	-4.05	3.2	9.2	2.0	2.9	14.1	
21	-4.00	4.3	9.1	2.0	1.6	12.7	
22	-3.95	3.2	9.2	2.0	2.8	14.0	
23	-3.90	2.3	9.3	2.0	1.9	13.2	
24	-3.85	2.1	9.4	2.0	1.7	13.1	
25	-3.80	2.8	9.3	2.0	0.9	12.2	
26	-3.75	1.9	9.4	2.0	0.8	12.2	
27	-3.70	1.0	9.5	2.0	0.2	11.7	29
28	-3.65	2.1	9.4	2.0	0.1	11.5	27
29	-3.60	2.1	9.4	2.0	0.5	11.9	33
30	-3.55	1.9	9.4	2.0	0.3	11.7	28

Continued ...

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
31	-3.50	1.2	9.5	2.0	-1.5	10.0	8
32	-3.45	1.5	9.4	2.0	-0.8	10.6	16
33	-3.40	2.6	9.3	2.0	-0.2	11.1	23
34	-3.35	2.4	9.3	2.0	-0.7	10.6	15
35	-3.30	2.1	9.4	2.0	-0.5	10.9	19
36	-3.25	1.4	9.4	2.0	-0.8	10.6	17
37	-3.20	1.9	9.4	2.0	-0.4	11.0	20
38	-3.15	2.4	9.3	2.0	-0.3	11.0	22
39	-3.10	2.1	9.4	2.0	-0.8	10.6	14
40	-3.05	1.3	9.5	2.0	-0.1	11.4	26
41	-3.00	3.2	9.2	2.0	-0.9	10.3	12
42	-2.95	1.5	9.4	2.0	-0.1	11.3	25
43	-2.90	3.2	9.2	2.0	0.7	11.9	36
44	-2.85	1.7	9.4	2.0	0.9	12.3	
45	-2.80	2.4	9.3	2.0	0.6	11.9	35
46	-2.75	2.5	9.3	2.0	0.7	12.0	38
47	-2.70	2.6	9.3	2.0	1.0	12.3	
48	-2.65	2.7	9.3	2.0	1.5	12.8	
49	-2.60	1.8	9.4	2.0	1.5	12.9	
50	-2.55	2.1	9.4	2.0	1.8	13.2	
51	-2.50	3.8	9.2	2.0	1.4	12.6	
52	-2.45	2.4	9.3	2.0	2.7	14.0	
53	-2.40	1.9	9.4	2.0	3.1	14.5	
54	-2.35	3.2	9.2	2.0	3.6	14.8	
55	-2.30	3.2	9.2	2.0	3.5	14.7	
56	-2.25	3.9	9.1	2.0	3.1	14.2	
57	-2.20	3.4	9.2	2.0	3.0	14.2	
58	-2.15	2.4	9.3	2.0	3.2	14.5	
59	-2.10	1.9	9.4	2.0	4.1	15.5	
60	-2.05	1.0	9.5	2.0	3.4	14.9	
61	-2.00	1.3	9.5	2.0	2.7	14.2	
62	-1.95	1.3	9.5	2.0	3.1	14.6	
62	-1.90	2.4	9.3	2.0	3.5	14.8	
64	-1.85	1.8	9.4	2.0	2.4	13.8	
65	-1.80	3.2	9.2	2.0	2.6	13.8	
66	-1.75	3.2	9.2	2.0	3.1	14.3	
67	-1.70	1.7	9.4	2.0	2.8	14.2	
68	-1.65	1.9	9.4	2.0	2.9	14.3	
69	-1.60	1.4	9.4	2.0	2.6	14.0	

Continued ...

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
70	-1.55	1.2	9.5	2.0	3.6	15.1	
71	-1.50	2.5	9.3	2.0	2.4	13.7	
72	-1.45	2.7	9.3	2.0	3.8	15.1	
73	-1.40	2.1	9.4	2.0	3.9	15.3	
74	-1.35	2.7	9.3	2.0	3.6	14.9	
75	-1.30	2.1	9.4	2.0	3.5	14.9	
76	-1.25	2.1	9.4	2.0	2.6	14.0	
77	-1.20	2.4	9.3	2.0	2.5	13.8	
78	-1.15	3.2	9.2	2.0	2.8	14.0	
79	-1.10	2.7	9.3	2.0	2.8	14.1	
80	-1.05	2.9	9.3	2.0	2.9	14.2	
81	-1.00	3.4	9.2	2.0	2.1	13.3	
82	-0.95	4.2	9.1	2.0	1.9	13.0	
83	-0.90	2.1	9.4	2.0	1.4	12.8	
84	-0.85	2.3	9.3	2.0	1.6	12.9	
85	-0.80	2.4	9.3	2.0	1.1	12.4	
86	-0.75	3.5	9.2	2.0	-0.9	10.3	11
87	-0.70	5.1	9.0	2.0	-1.6	9.4	2
88	-0.65	3.4	9.2	2.0	-1.7	9.5	3
89	-0.65	3.6	9.2	2.0	-1.8	9.4	1
90	-0.60	2.1	9.4	2.0	-0.1	11.3	24
91	-0.55	2.4	9.3	2.0	-1.7	9.6	4
92	-0.50	1.0	9.5	2.0	-1.1	10.4	13
93	-0.45	0.9	9.5	2.0	-0.5	11.0	21
94	-0.40	2.3	9.3	2.0	0.5	11.8	32
95	-0.35	3.2	9.2	2.0	-1.4	9.8	5
96	-0.30	2.7	9.3	2.0	-1.4	9.9	6
97	-0.25	1.1	9.5	2.0	-0.8	10.7	18
98	-0.20	1.4	9.4	2.0	-1.5	9.9	7
99	-0.15	1.3	9.5	2.0	-1.4	10.1	9
100	-0.10	1.3	9.5	2.0	-1.3	10.2	10
101	-0.05	1.2	9.5	2.0	0.9	12.4	
102	0.00	2.5	9.3	2.0	0.6	11.9	34
103	0.05	4.3	9.1	2.0	1.5	12.6	
104	0.10	3.1	9.2	2.0	1.2	12.4	
105	0.15	2.7	9.3	2.0	1.9	13.2	
106	0.20	2.3	9.3	2.0	1.6	12.9	
107	0.25	1.9	9.4	2.0	2.8	14.2	
108	0.30	2.1	9.4	2.0	2.9	14.3	
109	0.35	1.0	9.5	2.0	3.8	15.3	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
110	0.40	1.0	9.5	2.0	4.9	16.4	
111	0.45	1.7	9.4	2.0	4.2	15.6	
112	0.50	1.6	9.4	2.0	5.9	17.3	
114	0.55	2.1	9.4	2.0	4.8	16.2	
115	0.60	1.2	9.5	2.0	5.3	16.8	
116	0.65	3.6	9.2	2.0	5.9	17.1	
117	0.70	2.1	9.4	2.0	5.3	16.7	
118	0.75	2.8	9.3	2.0	5.1	16.4	
119	0.80	3.4	9.2	2.0	6.9	18.1	
120	0.85	2.1	9.4	2.0	8.1	19.5	
121	0.90	2.1	9.4	2.0	7.2	18.6	
122	0.95	1.5	9.4	2.0	7.9	19.3	
123	1.00	1.3	9.5	2.0	4.7	16.2	
123	1.05	2.7	9.3	2.0	7.3	18.6	
124	1.10	3.2	9.2	2.0	7.6	18.8	
125	1.15	0.9	9.5	2.0	7.5	19.0	
126	1.20	1.7	9.4	2.0	7.1	18.5	
127	1.25	2.8	9.3	2.0	7.3	18.6	
128	1.30	3.2	9.2	2.0	6.9	18.1	
129	1.35	2.1	9.4	2.0	7.2	18.6	
130	1.40	1.0	9.5	2.0	7.2	18.7	
131	1.45	1.4	9.4	2.0	7.1	18.5	
132	1.50	1.0	9.5	2.0	6.9	18.4	
133	1.55	2.1	9.4	2.0	6.8	18.2	
134	1.60	2.7	9.3	2.0	6.7	18.0	
135	1.65	1.7	9.4	2.0	7.9	19.3	
136	1.70	1.6	9.4	2.0	4.5	15.9	
137	1.75	1.0	9.5	2.0	3.2	14.7	
138	1.80	3.2	9.2	2.0	2.9	14.1	
139	1.85	3.1	9.2	2.0	2.7	13.9	
140	1.90	2.1	9.4	2.0	2.9	14.3	
141	1.95	2.1	9.4	2.0	2.5	13.9	
142	2.00	1.2	9.5	2.0	2.1	13.6	
143	2.05	1.7	9.4	2.0	1.5	12.9	
144	2.10	1.9	9.4	2.0	1.9	13.3	
145	2.15	1.2	9.5	2.0	1.8	13.3	
146	2.20	2.3	9.3	2.0	0.8	12.1	
147	2.25	4.3	9.1	2.0	0.7	11.8	30
148	2.30	4.5	9.1	2.0	1.8	12.9	
149	2.35	2.1	9.4	2.0	1.9	13.3	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
150	2.40	1.9	9.4	2.0	2.6	14.0	
151	2.45	2.3	9.3	2.0	0.6	11.9	37
152	2.50	2.4	9.3	2.0	0.8	12.1	
153	2.55	4.2	9.1	2.0	2.7	13.8	
154	2.60	2.0	9.4	2.0	1.9	13.3	
155	2.65	1.3	9.5	2.0	2.3	13.8	
156	2.70	1.0	9.5	2.0	2.4	13.9	
157	2.75	1.2	9.5	2.0	2.5	14.0	
158	2.80	2.3	9.3	2.0	2.7	14.0	
159	2.85	2.6	9.3	2.0	3.4	14.7	
160	2.90	1.3	9.5	2.0	2.1	13.6	
161	3.00	1.8	9.4	2.0	2.8	14.2	
162	3.05	1.4	9.4	2.0	2.8	14.2	
163	3.10	1.6	9.4	2.0	2.8	14.2	
164	3.15	1.3	9.5	2.0	3.6	15.1	
165	3.20	1.8	9.4	2.0	3.8	15.2	
166	3.25	1.7	9.4	2.0	3.1	14.5	
167	3.30	1.5	9.4	2.0	3.2	14.6	
168	3.35	1.7	9.4	2.0	2.9	14.3	
169	3.40	1.0	9.5	2.0	2.7	14.2	
170	3.45	1.9	9.4	2.0	3.8	15.2	
171	3.50	2.4	9.3	2.0	2.7	14.0	
172	3.55	3.7	9.2	2.0	3.5	14.7	
173	3.60	1.7	9.4	2.0	3.9	15.3	
174	3.65	2.4	9.3	2.0	3.7	15.0	
175	3.70	2.8	9.3	2.0	2.6	13.9	
176	3.75	1.3	9.5	2.0	2.9	14.4	
177	3.80	1.3	9.5	2.0	2.8	14.3	
178	3.85	3.9	9.1	2.0	2.6	13.7	
179	3.90	0.8	9.5	2.0	2.8	14.3	
180	3.95	0.7	9.5	2.0	3.1	14.6	
181	4.00	1.9	9.4	2.0	2.5	13.9	
182	4.05	1.3	9.5	2.0	4.1	15.6	
183	4.10	1.0	9.5	2.0	3.7	15.2	
184	4.15	3.8	9.2	2.0	3.2	14.4	
185	4.20	1.0	9.5	2.0	2.9	14.4	
186	4.25	1.5	9.4	2.0	3.8	15.2	
187	4.30	1.0	9.5	2.0	3.7	15.2	
188	4.35	3.1	9.2	2.0	3.5	14.7	
189	4.40	3.6	9.2	2.0	3.7	14.9	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (QPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
190	4.45	1.3	9.5	2.0	3.1	14.6	
191	4.50	1.9	9.4	2.0	0.7	12.1	
192	4.55	2.8	9.3	2.0	0.9	12.2	
193	4.60	3.1	9.2	2.0	0.9	12.1	
194	4.65	1.8	9.4	2.0	0.8	12.2	
195	4.70	1.0	9.5	2.0	1.6	13.1	
196	4.75	1.1	9.5	2.0	0.8	12.3	
197	4.80	1.1	9.5	2.0	0.8	12.3	
198	4.85	2.0	9.4	2.0	0.9	12.3	
199	4.90	2.0	9.4	2.0	1.2	12.6	
200	4.95	1.0	9.5	2.0	1.9	13.4	
201	5.00	4.3	9.1	2.0	0.7	11.8	31

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Method Employed: Jamming Margin

Test Configuration Mode: BPSK MODULATION, 1 Mb/s Data Rate

Theoretical Process Gain = $\frac{5.5 \text{ Mchips/symbol}}{(1\text{Mb/s})/(2\text{bits/symbol})}$ = 11 numeric or 10.4 dB

Measured The Transmitter's Peak RF Power @ Receiver Input Terminal:: -23.7 dBm

THEORETICAL PROCESS GAIN : 10.4dB				MIN. MEASURED PROCESSING GAIN: 12.1 dB after discarding 19.4% of the worst readings			
Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
1	-5.00	1.3	9.5	2.0	1.6	13.1	
2	-4.95	2.6	9.3	2.0	3.7	15.0	
3	-4.90	2.1	9.4	2.0	2.7	14.1	
4	-4.85	2.3	9.3	2.0	3.2	14.5	
5	-4.80	1.2	9.5	2.0	3.0	14.5	
6	-4.75	2.0	9.4	2.0	2.6	14.0	
7	-4.70	1.5	9.4	2.0	3.1	14.5	
8	-4.65	3.8	9.2	2.0	3.5	14.7	
9	-4.60	3.4	9.2	2.0	3.4	14.6	
10	-4.55	1.6	9.4	2.0	3.8	15.2	
11	-4.50	2.0	9.4	2.0	2.7	14.1	
12	-4.45	2.1	9.4	2.0	3.8	15.2	
13	-4.40	1.2	9.5	2.0	2.9	14.4	
14	-4.35	3.3	9.2	2.0	2.7	13.9	
15	-4.30	1.7	9.4	2.0	2.9	14.3	
16	-4.25	2.0	9.4	2.0	2.6	14.0	
17	-4.20	2.1	9.4	2.0	2.8	14.2	
18	-4.15	1.8	9.4	2.0	2.5	13.9	
19	-4.10	2.4	9.3	2.0	2.4	13.7	
20	-4.05	2.1	9.4	2.0	2.9	14.3	
21	-4.00	3.0	9.3	2.0	1.6	12.9	
22	-3.95	3.3	9.2	2.0	2.8	14.0	
23	-3.90	1.6	9.4	2.0	1.9	13.3	
24	-3.85	2.4	9.3	2.0	1.7	13.0	
25	-3.80	1.9	9.4	2.0	0.9	12.3	
26	-3.75	2.6	9.3	2.0	0.8	12.1	
27	-3.70	1.0	9.5	2.0	0.2	11.7	28
28	-3.65	3.2	9.2	2.0	0.1	11.3	26
29	-3.60	3.0	9.3	2.0	0.5	11.8	30
30	-3.55	1.5	9.4	2.0	0.3	11.7	29
31	-3.50	1.1	9.5	2.0	-1.5	10.0	8
32	-3.45	1.9	9.4	2.0	-0.8	10.6	17

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) X10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
33	-3.40	2.2	9.4	2.0	-0.2	11.2	23
34	-3.35	2.0	9.4	2.0	-0.7	10.7	18
35	-3.30	1.7	9.4	2.0	-0.5	10.9	19
36	-3.25	2.1	9.4	2.0	-0.8	10.6	15
37	-3.20	2.2	9.4	2.0	-0.4	11.0	20
38	-3.15	2.2	9.4	2.0	-0.3	11.1	22
39	-3.10	3.5	9.2	2.0	-0.8	10.4	14
40	-3.05	1.2	9.5	2.0	-0.1	11.4	27
41	-3.00	3.8	9.2	2.0	-0.9	10.3	12
42	-2.95	1.7	9.4	2.0	-0.1	11.3	25
43	-2.90	2.1	9.4	2.0	0.7	12.1	
44	-2.85	2.1	9.4	2.0	0.9	12.3	
45	-2.80	3.2	9.2	2.0	0.6	11.8	31
46	-2.75	3.0	9.3	2.0	0.7	12.0	35
47	-2.70	3.4	9.2	2.0	1.0	12.2	
48	-2.65	1.8	9.4	2.0	1.5	12.9	
49	-2.60	1.4	9.4	2.0	1.5	12.9	
50	-2.55	1.6	9.4	2.0	1.8	13.2	
51	-2.50	3.3	9.2	2.0	1.4	12.6	
52	-2.45	3.3	9.2	2.0	2.7	13.9	
53	-2.40	1.5	9.4	2.0	3.1	14.5	
54	-2.35	2.7	9.3	2.0	3.6	14.9	
55	-2.30	2.1	9.4	2.0	3.5	14.9	
56	-2.25	3.0	9.3	2.0	3.1	14.4	
57	-2.20	3.4	9.2	2.0	3.0	14.2	
58	-2.15	2.2	9.4	2.0	3.2	14.6	
59	-2.10	1.8	9.4	2.0	4.1	15.5	
60	-2.05	1.4	9.4	2.0	3.4	14.8	
61	-2.00	1.1	9.5	2.0	2.7	14.2	
62	-1.95	1.3	9.5	2.0	3.1	14.6	
62	-1.90	2.7	9.3	2.0	3.5	14.8	
64	-1.85	3.0	9.3	2.0	2.4	13.7	
65	-1.80	3.2	9.2	2.0	2.6	13.8	
66	-1.75	2.0	9.4	2.0	3.1	14.5	
67	-1.70	3.0	9.3	2.0	2.8	14.1	
68	-1.65	1.9	9.4	2.0	2.9	14.3	
69	-1.60	2.0	9.4	2.0	2.6	14.0	
70	-1.55	1.1	9.5	2.0	3.6	15.1	
71	-1.50	1.8	9.4	2.0	2.4	13.8	
72	-1.45	1.9	9.4	2.0	3.8	15.2	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
73	-1.40	1.5	9.4	2.0	3.9	15.3	
74	-1.35	3.5	9.2	2.0	3.6	14.8	
75	-1.30	1.9	9.4	2.0	3.5	14.9	
76	-1.25	3.5	9.2	2.0	2.6	13.8	
77	-1.20	2.7	9.3	2.0	2.5	13.8	
78	-1.15	2.4	9.3	2.0	2.8	14.1	
79	-1.10	1.9	9.4	2.0	2.8	14.2	
80	-1.05	2.3	9.3	2.0	2.9	14.2	
81	-1.00	4.2	9.1	2.0	2.1	13.2	
82	-0.95	2.6	9.3	2.0	1.9	13.2	
83	-0.90	3.3	9.2	2.0	1.4	12.6	
84	-0.85	1.9	9.4	2.0	1.6	13.0	
85	-0.80	1.7	9.4	2.0	1.1	12.5	
86	-0.75	3.6	9.2	2.0	-0.9	10.3	13
87	-0.70	3.1	9.2	2.0	-1.6	9.6	2
88	-0.65	2.2	9.4	2.0	-1.7	9.7	3
89	-0.65	2.3	9.3	2.0	-1.8	9.5	1
90	-0.60	2.1	9.4	2.0	-0.1	11.3	24
91	-0.55	1.6	9.4	2.0	-1.7	9.7	4
92	-0.50	2.3	9.3	2.0	-1.1	10.2	11
93	-0.45	1.1	9.5	2.0	-0.5	11.0	21
94	-0.40	2.1	9.4	2.0	0.5	11.9	32
95	-0.35	2.1	9.4	2.0	-1.4	10.0	6
96	-0.30	1.9	9.4	2.0	-1.4	10.0	7
97	-0.25	2.0	9.4	2.0	-0.8	10.6	16
98	-0.20	1.5	9.4	2.0	-1.5	9.9	5
99	-0.15	1.0	9.5	2.0	-1.4	10.1	10
100	-0.10	2.1	9.4	2.0	-1.3	10.1	9
101	-0.05	1.2	9.5	2.0	0.9	12.4	
102	0.00	2.3	9.3	2.0	0.6	11.9	34
103	0.05	3.2	9.2	2.0	1.5	12.7	
104	0.10	2.0	9.4	2.0	1.2	12.6	
105	0.15	3.7	9.2	2.0	1.9	13.1	
106	0.20	3.3	9.2	2.0	1.6	12.8	
107	0.25	3.0	9.3	2.0	2.8	14.1	
108	0.30	1.8	9.4	2.0	2.9	14.3	
109	0.35	1.7	9.4	2.0	3.8	15.2	
110	0.40	1.7	9.4	2.0	4.9	16.3	
111	0.45	2.6	9.3	2.0	4.2	15.5	
112	0.50	1.3	9.5	2.0	5.9	17.4	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
114	0.55	1.6	9.4	2.0	4.8	16.2	
115	0.60	1.5	9.4	2.0	5.3	16.7	
116	0.65	3.1	9.2	2.0	5.9	17.1	
117	0.70	3.0	9.3	2.0	5.3	16.6	
118	0.75	1.8	9.4	2.0	5.1	16.5	
119	0.80	2.2	9.4	2.0	6.9	18.3	
120	0.85	2.0	9.4	2.0	8.1	19.5	
121	0.90	3.4	9.2	2.0	7.2	18.4	
122	0.95	2.4	9.3	2.0	7.9	19.2	
123	1.00	1.1	9.5	2.0	4.7	16.2	
123	1.05	1.8	9.4	2.0	7.3	18.7	
124	1.10	3.5	9.2	2.0	7.6	18.8	
125	1.15	1.3	9.5	2.0	7.5	19.0	
126	1.20	1.4	9.5	2.0	7.1	18.6	
127	1.25	1.7	9.4	2.0	7.3	18.7	
128	1.30	2.1	9.4	2.0	6.9	18.3	
129	1.35	1.6	9.4	2.0	7.2	18.6	
130	1.40	1.0	9.5	2.0	7.2	18.7	
131	1.45	1.7	9.4	2.0	7.1	18.5	
132	1.50	2.5	9.3	2.0	6.9	18.2	
133	1.55	2.9	9.3	2.0	6.8	18.1	
134	1.60	2.4	9.3	2.0	6.7	18.0	
135	1.65	1.6	9.4	2.0	7.9	19.3	
136	1.70	2.2	9.4	2.0	4.5	15.9	
137	1.75	1.3	9.5	2.0	3.2	14.7	
138	1.80	2.1	9.4	2.0	2.9	14.3	
139	1.85	2.1	9.4	2.0	2.7	14.1	
140	1.90	1.8	9.4	2.0	2.9	14.3	
141	1.95	1.6	9.4	2.0	2.5	13.9	
142	2.00	1.8	9.4	2.0	2.1	13.5	
143	2.05	1.5	9.4	2.0	1.5	12.9	
144	2.10	1.5	9.4	2.0	1.9	13.3	
145	2.15	3.6	9.2	2.0	1.8	13.0	
146	2.20	1.9	9.4	2.0	0.8	12.2	
147	2.25	3.6	9.2	2.0	0.7	11.9	33
148	2.30	4.1	9.1	2.0	1.8	12.9	
149	2.35	2.0	9.4	2.0	1.9	13.3	
150	2.40	1.5	9.4	2.0	2.6	14.0	
151	2.45	1.8	9.4	2.0	0.6	12.0	37
152	2.50	1.7	9.4	2.0	0.8	12.2	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
153	2.55	4.4	9.1	2.0	2.7	13.8	
154	2.60	1.4	9.4	2.0	1.9	13.3	
155	2.65	1.8	9.4	2.0	2.3	13.7	
156	2.70	2.2	9.4	2.0	2.4	13.8	
157	2.75	2.2	9.4	2.0	2.5	13.9	
158	2.80	4.3	9.1	2.0	2.7	13.8	
159	2.85	1.8	9.4	2.0	3.4	14.8	
160	2.90	1.2	9.5	2.0	2.1	13.6	
161	3.00	1.4	9.4	2.0	2.8	14.2	
162	3.05	3.0	9.3	2.0	2.8	14.1	
163	3.10	1.5	9.4	2.0	2.8	14.2	
164	3.15	3.0	9.3	2.0	3.6	14.9	
165	3.20	1.9	9.4	2.0	3.8	15.2	
166	3.25	1.4	9.5	2.0	3.1	14.6	
167	3.30	1.6	9.4	2.0	3.2	14.6	
168	3.35	1.4	9.5	2.0	2.9	14.4	
169	3.40	0.9	9.5	2.0	2.7	14.2	
170	3.45	3.3	9.2	2.0	3.8	15.0	
171	3.50	2.0	9.4	2.0	2.7	14.1	
172	3.55	2.2	9.4	2.0	3.5	14.9	
173	3.60	1.9	9.4	2.0	3.9	15.3	
174	3.65	3.6	9.2	2.0	3.7	14.9	
175	3.70	3.2	9.2	2.0	2.6	13.8	
176	3.75	1.1	9.5	2.0	2.9	14.4	
177	3.80	1.2	9.5	2.0	2.8	14.3	
178	3.85	2.8	9.3	2.0	2.6	13.9	
179	3.90	2.9	9.3	2.0	2.8	14.1	
180	3.95	1.6	9.4	2.0	3.1	14.5	
181	4.00	2.6	9.3	2.0	2.5	13.8	
182	4.05	2.2	9.4	2.0	4.1	15.5	
183	4.10	1.1	9.5	2.0	3.7	15.2	
184	4.15	2.4	9.3	2.0	3.2	14.5	
185	4.20	1.0	9.5	2.0	2.9	14.4	
186	4.25	1.3	9.5	2.0	3.8	15.3	
187	4.30	2.0	9.4	2.0	3.7	15.1	
188	4.35	3.6	9.2	2.0	3.5	14.7	
189	4.40	4.3	9.1	2.0	3.7	14.8	
190	4.45	2.6	9.3	2.0	3.1	14.4	
191	4.50	2.7	9.3	2.0	0.7	12.0	36
192	4.55	1.9	9.4	2.0	0.9	12.3	

Continued

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Test Point	Jammer Signal Freq. +/- Fc (MHz)	(BER) (BPSK) x10-5	(S/N)o (dB)	System Loss Lsys (dB)	Jammer to Signal Ratio Mj (dB)	Measured Processing Gain (dB)	Number of Discard Reading
193	4.60	2.0	9.4	2.0	0.9	12.3	
194	4.65	2.5	9.3	2.0	0.8	12.1	
195	4.70	0.9	9.5	2.0	1.6	13.1	
196	4.75	2.7	9.3	2.0	0.8	12.1	
197	4.80	3.2	9.2	2.0	0.8	12.0	39
198	4.85	1.5	9.4	2.0	0.9	12.3	
199	4.90	1.5	9.4	2.0	1.2	12.6	
200	4.95	1.0	9.5	2.0	1.9	13.4	
201	5.00	2.5	9.3	2.0	0.7	12.0	38

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

4.7 AC Powerline Conducted Emissions, FCC CFR 47, Para. 15.107(a)

PRODUCT NAME: PCMCIA WIRELESS LAN CARD, Model No.: WL-201

NAME OF TEST: AC Powerline Conducted Emissions.

FCC LIMIT:

The RF voltage conducted back onto the public utility lines shall not exceed 250 uV or 48.0 dBuV measured from 450 KHz to 30 MHz.

CLIMATE CONDITION:

Standard Temperature and Humidity: 23°C and 53%

POWER INPUT:

Using DC Power from a laptop computer.

TEST EQUIPMENT:

- Advantest R3271 Spectrum Analyzer, Frequency Range: 100Hz-26.5GHz, with built-in Peak, Quasi-Peak and Average Detectors.
- HP 11947A Transient Limiter, HP, Model 11947A, Frequency Range: 9KHz-200MHz, Attenuation: 10dB.
- HP 7475 Plotter
- EMCO 3825/2 LISN, Frequency Range: 9KHz-200MHz
- RF Shielded Enclosure (12x16x12 feet)

METHOD OF MEASUREMENTS:

Refer to ANSI C63.4-1992.

TEST RESULTS: Conforms.

TEST PERSONNEL: Hung Trinh, EMI Technician

DATE: May 7, 1998

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

MEASUREMENT DATAAC POWER-LINE CONDUCTED EMISSIONSREMARKS

- All rf emissions from 450 KHz to 30 MHz were scanned, and eight highest emission levels were recorded. See attached plots.
- P: Peak Detector, 10 KHz RBW, VBW $\geq$ RBW
- Q: CISPR QUASI-PEAK, 9 KHz RBW, VBW $\geq$ RBW
- QP/BB: for broadband emission (QP level - AVG level $>$ 6 dB); the recorded level was QP level less 13 dB.

FREQUENCY (MHz)	RF LEVEL (dBuV)	RECEIVER DETECTOR (P/QP/AVG)	QP/NB LIMIT (dBuV)	QP/BB LIMIT (dBuV)	MARGIN (dB)	PASS/ FAIL	LINE TESTED (L1/L2)
10.800	38.2	QP	48.0	61.0	-9.8	PASS	L1
16.600	40.9	QP	48.0	61.0	-7.1	PASS	L1
11.500	38.1	QP	48.0	61.0	-9.9	PASS	L2
16.200	40.5	QP	48.0	61.0	-7.5	PASS	L2

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)



APPLICANT:
PRODUCT:
MODEL:

GENTILE TECHNOLOGY CO., LTD.
PCMCIA WIRELESS LAN CARD
802-11B

POWER-LINE CONDUCTED EMISSIONS MEASUREMENTS

EMI Detector: [V] Peak [V] Quasi Peak [V] Average Temp.: 24 °C, Humidity: 46 %
Line Tested: [F] Input Voltage: 120, Tested by: VEEH Test Date: MAY 7/98
Comments:

Signal Freq (MHz) PK Amp QP Amp AV Amp QPΔ1
1 10.818840 40.4 38.2 34.4 -9.8
2 16.559475 44.2 40.9 36.4 -7.1

CLEAR
WRITE A

MAX
HOLD A

VIEW A


ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 10.77 MHz
38.64 dBμV

SIGNAL NUMBER
1

BLANK A

Trace
A B C

More
1 of 4



- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)



APPLICANT: GENTEK TECHNOLOGY CO., LTD.
 PRODUCT: PCMCIA WIRELESS LAN CARD
 MODEL: WL-201

POWER-LINE CONDUCTED EMISSIONS MEASUREMENTS

EMI Detector: M Peak N Quasi Peak N Average Temp.: 24 °C, Humidity: 46 %
 Line Tested: 1-2, Input Voltage: 120, Tested by: VENH Test Date: May 7/98
 Comments:

Signal Freq (MHz)	PK Amp	QP Amp	AV Amp	QPA1
1 11.525145	40.8	38.1	33.6	-9.9
2 16.225813	43.2	40.5	35.9	-7.4


MARKER
→ HIGH

MARKER
→ CF

NEXT
PEAK

ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 11.48 MHz
 39.08 dBμV

START
450 KHz



NEXT PK
RIGHT

NEXT PK
LEFT

More
1 of 3

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

5. EXHIBIT 5 - GENERAL TEST PROCEDURES

5.1 AC Powerline Conducted Emissions Measurements - General Test Method

- AC Powerline Conducted Emissions were performed in the shielded room, 16'(L) by 12'(W) by 12'(H).
- Conducted power-line measurements were made over the frequency range from 450 KHz to 30 MHz to determine the line-to-ground radio noise voltage which was conducted from the EUT power-input terminals that were directly connected to a public power network.
- The EUT normally received power from another device that connects to the public utility ac power lines, measurements would be made on that device with the EUT in operation to ensure that the device continues to comply with the appropriate limits while providing the EUT with power.
- If the EUT was operates only from internal or dedicated batteries, with no provisions for connection to the public utility ac power lines, ac power-line conducted measurements are not required.
- Table-top devices were placed on a platform of nominal size 1 m by 1.5m raised 80 cm above the conducting ground plane.
- The EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN to the power source. All unused 50-Ohm connectors of the LISN was terminated in 50-ohm when not connected to the measuring instruments.
- The line cord of the EUT connected to one LISN which was connected to the measuring instrument. Those power cords for the units of devices not under measurement were connected to a separate multiple ac outlets. Drawings and photographs of typically conducted emission test setups were shown in the Test Report. Each current-carrying conductor of the EUT shall be individually tested.
- The EUT was normally operated with a ground (safety) connection, the EUT was connected to the ground at the LISN through a conductor provided in the lead from the ac power mains to the LISN.
- The excess length of the power cord was folded back and forth in an 8-shape on a wooden strip with a vertical prong located on the top of the LISN case.
- The EUT was set-up in its typical configuration and operated in its various modes as described in 3.2 of the test report.
- A preliminary scan was made by using spectrum analyzer system with the detector function set to PEAK mode (10 KHz RBW, VBW $\geq$ RBW), frequency span 450KHz-30MHz.
- The maximum conducted emission for a given mode of operation was found by using the following step-by-step procedure:
 - Step1. Monitor the frequency range of interest at a fixed EUT azimuth.
 - Step2. Manipulate the system cables and peripheral devices to produce highest amplitude signal relative to the limit. Note the amplitude and frequency of the suspect signal.
 - Step3. The effects of various modes of operation is examined. This is done by varying equipment operation modes as step 2 is being performed.
 - Step4. After completing step 1 through 3, record EUT and peripheral device configuration, mode of operation, cable configuration, signal levels and frequencies for final test.

- Each highest signal level at the maximized test configuration was zoomed in a small frequency span on the spectrum analyzer's display (the manipulation of cables and peripheral devices and EUT operation modes might have to be repeated to obtain the highest signal level with the spectrum analyzer set to PEAK detector mode 10 KHz RBW and VBW $\geq$ RBW). The spectrum analyzer was then set to CISPR QUASI-PEAK detector mode (9 KHz RBW, 1 MHz VBW) and the final highest RF signal level and frequency was record.
- **Broad-band ac Powerline conducted emissions:-** If the EUT exhibits ac Powerline conducted emissions that exceed the limit with the instrument set to the quasi-peak mode, then measurements should be made in the average mode. If the amplitude measured in the quasi-peak mode is at least 6 dB higher than the amplitude measured in the average mode, the level measured in quasi peak mode may be reduced by 13 dB before comparing it to the limit.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

5.2 Electrical Field Radiated Emissions Measurements - General Test Method

- The radiated emission measurements were performed at the UltraTech's 3 Meter Open Field Test Site (OFTS) situated in the Town of Oakville, province of Ontario. The Attenuation Characteristics of OFTS have been filed to FCC.
- Radiated emissions measurements were made using the following test instruments:
 - 1) Calibrated EMCO active loop antenna in the frequency range from 10 KHz to 1 MHz
 - 2) Calibrated EMCO biconilog antenna in the frequency range from 30 MHz to 2000 MHz.
 - 3) Calibrated A.H. Systems log periodic antenna in the frequency range above 1000 MHz (1GHz - 18 GHz).
 - 4) Horn Antennas:
 - a) Horn Antenna, Emco, Model 3160-09, 18-26.5GHz
 - b) Horn Antenna, Emco, Model 3160-10, 26.5-40GHz
 - c) Mixer, Tektronix, P/N 118-0098-00, 18-26.5GHz
 - d) Mixer, Tektronix, P/N 119-0098-00, 26.5-40GHz
 - e) Mixer, HP, P/N R3434A, 12.4-18GHz
 - f) Mixer, HP, P/N R3434B, 18-26.5GHz
 - g) Mixer, HP, P/N R3434C, 26.5-40GHz
 - 5) Calibrated Advantest spectrum analyzer and pre-selector/pre-amplifier. In general, the spectrum analyzer would be used as follows:
 - The rf electric field levels were measured with the spectrum analyzer set to PEAK detector (1 KHz RBW and 1 KHz VBW for frequency below 30 MHz, 100 KHz RBW and VBW $\geq$ RBW for Frequency below 1 GHz and 1 MHz RBW and 1 MHz VBW for frequency greater than 1 GHz).
 - If any rf emission was observed to be a broadband noise, the spectrum analyzer's CISPR QUASI-PEAK detector (120 KHz RBW and 1MHz VBW) was then set to measure the signal level.
 - If the signal being measured was narrowband and the ambient field was broadband, the bandwidth of the spectrum analyzer was reduced.
- The EUT was set-up in its typical configuration and operated in its various modes as described in 3.2 of the test report.
- The frequencies of emissions was first detected. Then the amplitude of the emissions was measured at the specified measurement distance using required antenna height, polarization, and detector characteristics.
- During this process, cables and peripheral devices were manipulated within the range of likely configuration.
- For each mode of operation required to be tested, the frequency spectrum was monitored. Variations in antenna heights (from 1 meter to 4 meters above the ground plane), antenna polarization (horizontal plane and vertical plane), cable placement and peripheral placement (each variable within bounds specified elsewhere) were explored to produce the highest amplitude signal relative to the limit.

The maximum radiated emission for a given mode of operation was found by using the following step-by-step procedure:

Step1: Monitor the frequency range of interest at a fixed antenna height and EUT azimuth.

Step2: Manipulate the system cables to produce highest amplitude signal relative to the limit. Note the amplitude and frequency of the suspect signal.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

PCMCIA WIRELESS LAN CARD, Model WL-201**FCC ID: MXF-WL201**

- Step3: Rotate the EUT 360 degrees to maximize the suspected highest amplitude signal. If the signal or another at a different frequency is observed to exceed the previously noted highest amplitude signal by 1 dB or more, go back to the azimuth and repeat Step 2. Otherwise, orient the EUT azimuth to repeat the highest amplitude observation and proceed.
- Step4: Move the antenna over its full allowed range of travel (1 to 4 meters) to maximize the suspected highest amplitude signal. If the signal or another at a different frequency is observed to exceed the previously noted highest amplitude signal by 1 dB or more, return to Step 2 with the highest amplitude observation and proceed.
- Step5: Change the polarization of the antenna and repeat Step 2 through 4. Compare the resulting suspected highest amplitude signal with that found for the other polarization. Select and note the higher of the two signals. This signal is termed the highest observed signal with respect to the limit for this EUT operational mode.
- Step6: The effects of various modes of operation is examined. This is done by varying the equipment modes as steps 2 through 5 are being performed.
- Step7: After completing steps 1 through 6, record the final highest emission level, frequency, antenna polarization and detector mode of the measuring instrument.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

Calculation of Field Strength:

The field strength is calculated by adding the calibrated antenna factor and cable factor, and subtracting the Amplifier gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where	FS	=	Field Strength
	RA	=	Receiver/Analyzer Reading
	AF	=	Antenna Factor
	CF	=	Cable Attenuation Factor
	AG	=	Amplifier Gain

Example: If a receiver reading of 60.0 dBuV is obtained, the antenna factor of 7.0 dB/m and cable factor of 1.0 dB are added, and the amplifier gain of 30 dB is subtracted. The actual field strength will be:.

Field Level in dBuV/m = $60 + 7.0 + 1.0 - 30 = 38.0$ dBuV/m.

Field Level in uV/m = $10^{(38/20)} = 79.43$ uV/m.

Notes: The frequency and amplitude of at least six highest conducted emissions relative to the limit are recorded unless such emissions are more than 20 dB below the limit. If less than six emissions are within 20dB of the limit, the background or receiver noise level shall be reported at representative frequencies.

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)

6. EXHIBIT 6 - INFORMATION RELATED TO EQUIPMENT UNDER TESTS**6.1 *FCC ID Labeling and Sketch of FCC Label Location***

Refer to the attached file "fccform.doc"

6.2 *Photographs of Equipment under Test*

External photos, refer to the attached files: pic00002.jpg, pic00003.jpg

Internal photos, refer to the attached files: pic00004.jpg, pic00005.jpg, pic00006.jpg, pic00007.jpg

6.3 *System Block Diagram(s)*

Refer to the attached file "blockd.doc"

6.4 *Schematic Diagrams and Part Lists*

Refer to the attached files schem1.jpg, schem2.jpg, schem3.jpg, schem4.jpg

6.5 *User's Manual with "FCC Information to User Statements"*

Refer to the attached file wl201men.doc

- Accredited by **ITI** (UK) Competent Body & **NVLAP** (USA) Accreditation Body
- Recognized/Listed by **FCC** (USA), **Industry Canada** (Canada), **Austel** (Australia)
- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (**NIST**)