







Mode LTE Band 41, CB: 20MHz


QPSK, Low Channel, 1RB



QPSK, Low Channel, Full RB














Mode LTE Band 41, CB: 20MHz


16QAM, Low Channel, 1RB



16QAM, Low Channel, Full RB








3.5 Emission and Occupied Bandwidth

3.5.1 Test Procedures


1. Set resolution bandwidth (RBW) = 62~220 kHz, Video bandwidth = 200 ~ 680 kHz for 5 ~ 20 MHz channel bandwidth
2. Set Detector = Peak, Trace mode = max hold, Sweep = auto couple, Allow the trace to stabilize.
3. Using 26dB and occupied bandwidth measurement function of spectrum analyzer to measure bandwidth

3.5.2 Test Setup




3.5.3 Test Result of Occupied Bandwidth


Channel Bandwidth (MHz)	Modulation	Frequency (MHz)	26dB BW (MHz)	99% OBW (MHz)
5	QPSK	2498.5	5.7970	4.5104
5	QPSK	2593.0	5.7270	4.5104
5	QPSK	2687.5	5.7660	4.5104
5	16QAM	2498.5	5.6270	4.5037
5	16QAM	2593.0	5.5480	4.4981
5	16QAM	2687.5	5.5340	4.4992




Channel Bandwidth (MHz)	Modulation	Frequency (MHz)	26dB BW (MHz)	99% OBW (MHz)
10	QPSK	2501.0	10.8800	8.9433
10	QPSK	2593.0	10.8300	8.9445
10	QPSK	2685.0	10.8000	8.9416
10	16QAM	2501.0	11.4400	9.0304
10	16QAM	2593.0	11.1500	9.0183
10	16QAM	2685.0	11.1400	9.0206



Channel Bandwidth (MHz)	Modulation	Frequency (MHz)	26dB BW (MHz)	99% OBW (MHz)
15	QPSK	2503.5	15.8000	13.4270
15	QPSK	2593.0	15.7300	13.3980
15	QPSK	2682.5	15.7000	13.4230
15	16QAM	2503.5	15.4700	13.4010
15	16QAM	2593.0	15.4400	13.3860
15	16QAM	2682.5	15.4700	13.3960



Channel Bandwidth (MHz)	Modulation	Frequency (MHz)	26dB BW (MHz)	99% OBW (MHz)
20	QPSK	2506.0	20.2000	17.9140
20	QPSK	2593.0	20.4400	17.9070
20	QPSK	2680.0	20.4600	17.9260
20	16QAM	2506.0	20.3700	17.9410
20	16QAM	2593.0	20.2200	17.9400
20	16QAM	2680.0	20.1000	17.9330



3.6 Frequency Stability


3.6.1 Limit of Frequency Stability

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation

3.6.2 Test Procedures

1. EUT was placed at temperature chamber and connected to an external power supply.
2. Temperature and voltage condition shall be tested to confirm frequency stability.
3. Temperature range is from -30~55°C and voltage range is from lowest to highest working voltage.
4. Tem Link up EUT and simulator. Confirm frequency drift value of simulator and record it.

3.6.3 Test Setup



3.6.4 Test Result of Frequency Stability

Channel Bandwidth: 5MHz

Frequency: 2593.0MHz	Frequency Drift (ppm)	
Temperature (°C)	Frequency Error (ppm)	Limit (ppm)
T20°C Vmax	-0.007	2.5
T20°C Vmin	-0.003	2.5
T50°C Vnom	-0.003	2.5
T40°C Vnom	-0.005	2.5
T30°C Vnom	-0.009	2.5
T20°C Vnom	-0.004	2.5
T10°C Vnom	-0.006	2.5
T0°C Vnom	-0.006	2.5
T-10°C Vnom	-0.008	2.5
T-20°C Vnom	-0.005	2.5
T-30°C Vnom	-0.008	2.5
Vnom [Vac]: 120	Vmax [Vac]: 138	Vmin [Vac]: 102
Tnom [°C]: 20	Tmax [°C]: 50	Tmin [°C]: -30

Channel Bandwidth: 10MHz

Frequency: 2593.0MHz	Frequency Drift (ppm)	
Temperature (°C)	Frequency Error (ppm)	Limit (ppm)
T20°C Vmax	-0.007	2.5
T20°C Vmin	-0.005	2.5
T50°C Vnom	-0.004	2.5
T40°C Vnom	-0.009	2.5
T30°C Vnom	-0.005	2.5
T20°C Vnom	-0.005	2.5
T10°C Vnom	-0.003	2.5
T0°C Vnom	-0.007	2.5
T-10°C Vnom	-0.005	2.5
T-20°C Vnom	-0.004	2.5
T-30°C Vnom	-0.002	2.5
Vnom [Vac]: 120	Vmax [Vac]: 138	Vmin [Vac]: 102
Tnom [°C]: 20	Tmax [°C]: 50	Tmin [°C]: -30

Channel Bandwidth: 15MHz

Frequency: 2593.0MHz	Frequency Drift (ppm)	
Temperature (°C)	Frequency Error (ppm)	Limit (ppm)
T20°C _{Vmax}	-0.005	2.5
T20°C _{Vmin}	-0.006	2.5
T50°C _{Vnom}	-0.008	2.5
T40°C _{Vnom}	-0.005	2.5
T30°C _{Vnom}	-0.005	2.5
T20°C _{Vnom}	-0.003	2.5
T10°C _{Vnom}	-0.007	2.5
T0°C _{Vnom}	-0.008	2.5
T-10°C _{Vnom}	-0.004	2.5
T-20°C _{Vnom}	-0.004	2.5
T-30°C _{Vnom}	-0.003	2.5
Vnom [Vac]: 120	Vmax [Vac]: 138	Vmin [Vac]: 102
Tnom [°C]: 20	Tmax [°C]: 50	Tmin [°C]: -30

Channel Bandwidth: 20MHz

Frequency: 2593.0MHz	Frequency Drift (ppm)	
Temperature (°C)	Frequency Error (ppm)	Limit (ppm)
T20°C _{Vmax}	-0.007	2.5
T20°C _{Vmin}	-0.005	2.5
T50°C _{Vnom}	-0.006	2.5
T40°C _{Vnom}	-0.008	2.5
T30°C _{Vnom}	-0.007	2.5
T20°C _{Vnom}	-0.008	2.5
T10°C _{Vnom}	-0.006	2.5
T0°C _{Vnom}	-0.004	2.5
T-10°C _{Vnom}	-0.008	2.5
T-20°C _{Vnom}	-0.006	2.5
T-30°C _{Vnom}	-0.008	2.5
Vnom [Vac]: 120	Vmax [Vac]: 138	Vmin [Vac]: 102
Tnom [°C]: 20	Tmax [°C]: 50	Tmin [°C]: -30

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==