

FCC Part 15D – APPLICATION FORM & SELF-DECLARATION

Applicant Name	Telefield Ltd.		
Address	Flat D,2/F,Valiant Industrial Centre, 2-12 Au Pui Wan Street,Fo Tan,N.T.,Hong Kong.		
Contact person	Ho Wing Cheong		
Telephone No.	852 26052811	FaX No.	852 30078968
Manufacturer Name	Skymotion Technology (Hong Kong) Limited		
Address	Flat 10, 17/F, Fo Tan Industrial Centre,26-28 Au Pui Wan Street, Fo Tan, Shatin, N.T., Hong Kong		

	PP		FP	
FCC ID	MZVIP-162		MZVIP-162	
Model Number(s)	IP162,IP162S,IPxxx,IPxxxx, IPxxxxx,IP062,IP062S, IPDT-0150,IPDT-0xxx, IPDT-0xxxx, IPDT-0xxxxx, IPDT-50,IPDT-xx,IPDT-xxx, IPDT-xxxx, Note: "x" shall consist of a series of Arabic numerals, capital letters or a combination thereof.		IP162,IP162S,IPxxx,IPxxxx, IPxxxxx,IP100,IP100S,IP1xx, IP1xxx,IP1xxxx, IPDT-0150,IPDT-0xxx, IPDT-0xxxx, IPDT-0xxxxx, IPDT-0100,IPDT-01xx, IPDT-01xxx, IPDT-01xxxx Note: "x" shall consist of a series Arabic numerals, capital letters or a combination thereof.	
HW version				
SW version				
Antenna Type	Monopole Antenna		Monopole Antenna	
Max, Antenna Gain(dBi)	0dBi		0dBi	
Mains Power Voltage	Adapter Input	AC 100-240V	Adapter Input	AC 100-240V
	Adapter Output	DC6V	Adapter Output	DC5V
	PP Inport	DC6V	FP Inport	DC5V
Battery Voltage	DC 2.4V			

Number of channels	5				
Carrier frequency(MHz)	1921.536	1923.264	1924.992	1926.720	1928.448
Nominal Receive Bandwidth	+/-500kHz				
Frame period(ms)	24time slots within 10 seconds .First 12 slots for PP transmit and neXt 12 slots for FP transmit				
Timeslot Plan	24 timeslots per frame. First 12 timeslots used for PP transmissions and other 12 timeslots used for FP transmissions.				
Operating Temperature Range(° C)	Min	-10°C	Max	40°C	

Does a system built with the EUT that implement the provisions of 47CFR 15.323(c) (5) enabling the use of the upper threshold for deferral?	☒ Yes	☐ No
---	---	-----------------------------

