

**Telefield Limited**

Application  
For  
Certification  
**(FCC ID: MZVWT-1)**

Transmitter

WO# 0010480  
WL/at  
November 3, 2000

## LIST OF EXHIBITS

### *INTRODUCTION*

|                   |                           |
|-------------------|---------------------------|
| <i>EXHIBIT 1:</i> | General Description       |
| <i>EXHIBIT 2:</i> | System Test Configuration |
| <i>EXHIBIT 3:</i> | Emission Results          |
| <i>EXHIBIT 4:</i> | Equipment Photographs     |
| <i>EXHIBIT 5:</i> | Product Labelling         |
| <i>EXHIBIT 6:</i> | Technical Specifications  |
| <i>EXHIBIT 7:</i> | Instruction Manual        |
| <i>EXHIBIT 8:</i> | Miscellaneous Information |

# INTERTEK TESTING SERVICES

## MEASUREMENT/TECHNICAL REPORT

**Telefield Limited - MODEL: UMP Wireless Sentry WT-1**  
**FCC ID: MZVWT-1**

**November 3, 2000**

This report concerns (check one:)    Original Grant   X      Class II Change \_\_\_\_\_

Equipment Type: Low Power Transmitter (example: computer, printer, modem, etc.)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?    Yes \_\_\_\_\_    No   X  

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?    Yes \_\_\_\_\_    No   X  

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-1-96 Edition] provision.

Report prepared by:

Wilson Loke  
Intertek Testing Services  
2/F., Garment Center,  
576, Castle Peak Road,  
HONG KONG  
Phone: 852-2173-8575  
Fax: 852-2745-8306

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

|                                                      |    |
|------------------------------------------------------|----|
| 1.0 <b><u>General Description</u></b> .....          | 2  |
| 1.1 Product Description .....                        | 2  |
| 1.2 Related Submittal(s) Grants .....                | 2  |
| 1.3 Test Methodology .....                           | 3  |
| 1.4 Test Facility .....                              | 3  |
| 2.0 <b><u>System Test Configuration</u></b> .....    | 5  |
| 2.1 Justification .....                              | 5  |
| 2.2 EUT Exercising Software .....                    | 5  |
| 2.3 Special Accessories .....                        | 5  |
| 2.4 Equipment Modification .....                     | 6  |
| 2.5 Support Equipment List and Description .....     | 6  |
| 3.0 <b><u>Emission Results</u></b> .....             | 8  |
| 3.1 Field Strength Calculation .....                 | 9  |
| 3.2 Radiated Emission Configuration Photograph ..... | 11 |
| 3.3 Radiated Emission Data .....                     | 12 |
| 3.4 Line Conducted Configuration Photograph .....    | 15 |
| 3.5 Line Conducted Emission Configuration Data ..... | 16 |
| 4.0 <b><u>Equipment Photographs</u></b> .....        | 17 |
| 5.0 <b><u>Product Labelling</u></b> .....            | 19 |
| 6.0 <b><u>Technical Specifications</u></b> .....     | 21 |
| 7.0 <b><u>Instruction Manual</u></b> .....           | 23 |
| 8.0 <b><u>Miscellaneous Information</u></b> .....    | 25 |
| 8.1 Discussion of Pulse Desensitization .....        | 27 |
| 8.2 Calculation of Average Factor .....              | 28 |
| 8.3 Emissions Test Procedures .....                  | 29 |

---

## INTERTEK TESTING SERVICES

---

### List of attached file

| Exhibit type          | File Description               | filename                       |
|-----------------------|--------------------------------|--------------------------------|
| Cover Letter          | Letter of Agency               | letter.pdf                     |
| Test Report           | Test Report                    | report.doc                     |
| Operation Description | Technical Description          | descri.pdf                     |
| Test Setup Photo      | Radiated Emission              | radiated1.jpg to radiated2.jpg |
| Test Setup Photo      | Conducted Emission             | conduct1.jpg to conduct3.jpg   |
| Test Report           | Conducted Emission Test Result | conduct.pdf                    |
| External Photo        | External Photo                 | ophoto1.jpg to ophoto2.jpg     |
| Internal Photo        | Internal Photo                 | iphoto1.jpg to iphoto4.jpg     |
| Block Diagram         | Block Diagram                  | block.pdf                      |
| Schematics            | Circuit Diagram                | circuit.pdf                    |
| ID Label/Location     | Label Artwork and Location     | label.pdf                      |
| User Manual           | User Manual                    | manual.pdf                     |

**EXHIBIT 1**

**GENERAL DESCRIPTION**

## INTERTEK TESTING SERVICES

---

### 1.0 **General Description**

#### 1.1 Product Description

The Equipment Under Test (EUT) is a transmitter operating between 924.875 and 927.725MHz. The EUT is powered by 3.6V d.c. (1 x 3.6V 300mAh GP30AAK 3BMX rechargeable battery). Before the transmitter was used, it should be programmed with the receiver and one of the channel was selected. There are 2 band of channels and there are 10 channels in each band. It transmits alert signal to the receiver if the contact inside the chair sentry mat is open, low battery or out of range is detected. Alarm can be reset by pressing the “alarm reset” button. Also, there is a charging base for recharging the rechargeable battery inside the EUT.

For electronic filing, the brief circuit description is saved with filename: descri.pdf

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transmitter. The receiver with FCC ID: MZVWR-1 associated with the transmitter has been filed.

## INTERTEK TESTING SERVICES

---

### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**EXHIBIT 2**  
**SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in C63.4 (1992.)

The EUT was powered from 1 x fully charged 3.6V 300mAh rechargeable battery.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes. The worst case bit sequence was applied during test.

For simplicity of testing, the unit was wired to transmit continuously.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the button is depressed, the unit transmits the typical signal. For simplicity of testing, the unit was wired to transmit continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

## INTERTEK TESTING SERVICES

---

### 2.4 Equipment Modification

Any modifications installed previous to testing by Telefield Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services.

### 2.5 Support Equipment List and Description

This product was tested in a standalone configuration.

All the items listed under section 2.0 of this report are

*Confirmed by:*

*Wilson Loke  
Manager  
Intertek Testing Services Hong Kong Ltd.  
Agent for Telefield Limited*

\_\_\_\_\_  
Signature

\_\_\_\_\_  
November 3, 2000

\_\_\_\_\_  
Date

**EXHIBIT 3**  
**EMISSION RESULTS**

### 3.0 **Emission Results**

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

### 3.1 Field Strength Calculation (cont'd)

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

## **INTERTEK TESTING SERVICES**

---

### 3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
at  
2776.565 MHz

For electronic filing, the front view and back view of test configuration photograph is saved with filename: radiated1.jpg and radiated2.jpg respectively.

## INTERTEK TESTING SERVICES

---

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 3.0 dB

#### ***TEST PERSONNEL:***

\_\_\_\_\_  
*Signature*

Ben W. K. Ho, Compliance Engineer  
*Typed/Printed Name*

November 3, 2000  
*Date*

---

## INTERTEK TESTING SERVICES

---

Company: Telefield Limited  
Model: UMP Wireless Sentry WT-1  
Mode: Band 1 TX

Date of Test: October 25, 2000

Table 1

### Radiated Emissions

| Polarity | Frequency<br>(M Hz) | Reading<br>(dB $\mu$ V ) | Antenna<br>Factor<br>(dB ) | Pre-<br>Am p<br>Gain<br>(dB ) | Average<br>Factor<br>(-dB ) | Net<br>at 3m<br>(dB $\mu$ V /m ) | Limit<br>at 3m<br>(dB $\mu$ V /m ) | Margin<br>(dB ) |
|----------|---------------------|--------------------------|----------------------------|-------------------------------|-----------------------------|----------------------------------|------------------------------------|-----------------|
| H        | 925.516             | 87.0                     | 22.8                       | 16                            | 4.0                         | 89.8                             | 94                                 | -4.2            |
| V        | 1851.043            | 55.0                     | 26.5                       | 34                            | 4.0                         | 43.5                             | 54                                 | -10.5           |
| H        | 2776.565            | 59.9                     | 29.1                       | 34                            | 4.0                         | 51.0                             | 54                                 | -3.0            |
| H        | 3702.087            | 48.4                     | 32.8                       | 34                            | 4.0                         | 43.2                             | 54                                 | -10.8           |
| V        | 4627.609            | 42.8                     | 34.0                       | 34                            | 4.0                         | 38.8                             | 54                                 | -15.2           |
| H        | 5553.131            | 37.6                     | 36.0                       | 34                            | 4.0                         | 35.6                             | 54                                 | -18.4           |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna and average detector are used for the emission over 1000MHz.

\*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Ben W. K. Ho

---

## INTERTEK TESTING SERVICES

---

Company: Telefield Limited  
Model: UMP Wireless Sentry WT-1  
Mode: Band 2 TX

Date of Test: October 25, 2000

Table 2

### Radiated Emissions

| Polarity | Frequency<br>(M Hz) | Reading<br>(dB $\mu$ V ) | Antenna<br>Factor<br>(dB ) | Pre-<br>Am p<br>Gain<br>(dB ) | A verage<br>Factor<br>(-dB ) | Net<br>at 3m<br>(dB $\mu$ V /m ) | L im it<br>at 3m<br>(dB $\mu$ V /m ) | M argin<br>(dB ) |
|----------|---------------------|--------------------------|----------------------------|-------------------------------|------------------------------|----------------------------------|--------------------------------------|------------------|
| H        | 927.019             | 87.2                     | 22.8                       | 16                            | 4.0                          | 90.0                             | 94                                   | -4.0             |
| V        | 1854.043            | 56.1                     | 26.5                       | 34                            | 4.0                          | 44.6                             | 54                                   | -9.4             |
| H        | 2781.067            | 59.9                     | 29.1                       | 34                            | 4.0                          | 51.0                             | 54                                   | -3.0             |
| H        | 3708.090            | 49.3                     | 32.8                       | 34                            | 4.0                          | 44.1                             | 54                                   | -9.9             |
| V        | 4635.136            | 43.5                     | 34.0                       | 34                            | 4.0                          | 39.5                             | 54                                   | -14.5            |
| H        | 5562.136            | 36.1                     | 36.0                       | 34                            | 4.0                          | 34.1                             | 54                                   | -19.9            |

- Notes:
1. Peak Detector Data unless otherwise stated.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna and average detector are used for the emission over 1000MHz.

\*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Ben W. K. Ho

### 3.4 Line Conducted Configuration Photograph

#### Worst Case Line-Conducted Configuration

For electronic filing, the worst case line-conducted configuration photograph are saved with filename: conduct1.jpg , conduct 2.jpg and conduct3.jpg respectively.

## INTERTEK TESTING SERVICES

---

### 3.5 Line Conducted Emission Configuration Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

#### **TEST PERSONNEL:**

---

*Signature*

Ben W. K. Ho, Compliance Engineer  
*Typed/Printed Name*

November 3, 2000  
*Date*

**EXHIBIT 4**  
**EQUIPMENT PHOTOGRAPHS**

### 4.0 **Equipment Photographs**

For electronic filing, the photographs of the tested EUT are saved with filename: ophoto1.jpg to ophoto2.jpg for external photo and iphoto1.jpg to iphoto4.jpg for internal photo.

**EXHIBIT 5**  
**PRODUCT LABELLING**

### 5.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf

**EXHIBIT 6**  
**TECHNICAL SPECIFICATIONS**

### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematics of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 7**  
**INSTRUCTION MANUAL**

### 7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

This manual will be provided to the end-user with each unit sold/leased in the United States.

**EXHIBIT 8**

**MISCELLANEOUS INFORMATION**

### 8.0 **Miscellaneous Information**

This miscellaneous information includes details of the test procedure and calculation of factors such as pulse desensitization and averaging factor.

### 8.1 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity was not applicable for this device. The effective period ( $T_{\text{eff}}$ ) was approximately 63 ms for a digital "1" bit, as shown in Exhibit 8.2. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

### 8.2 Calculation of Average Factor

Averaging factor in dB =  $20 \log (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specify measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100 ms

Effective period of the cycle = 63 ms

$$DC = 63 \text{ ms} / 100 \text{ ms} = 0.63$$

Therefore, the averaging factor is found by  $20 \log_{10} 0.63 = -4.0 \text{ dB}$

### 8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 1992.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.1.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 450 kHz to 30 MHz.

### 8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.4 - 1992.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.