

TEST REPORT

Reference No..... : WTS17S0681214-2E
FCC ID : N2GSL505
Applicant..... : DOPPIO MOBILE INTERNATIONAL LIMITED
Address..... : ROOM 1708, 17/f HART AVENUE PLAZA, 5-9 HART AVENUE
TISM SHA TSUI, Kowloon, Hongkong
Manufacturer : The same as above
Address..... : The same as above
Product Name..... : Mobile Phone
Model No..... : Doppio SL505
Brand..... : doppio
Standards..... : FCC CFR47 Part 15.247:2016
Date of Receipt sample : Jun. 06, 2017
Date of Test : Jun. 07 ~ 20, 2017
Date of Issue..... : Jun. 21, 2017
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Ford Wang

Ford Wang / Project Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services Test Group Ltd is a professional third-party testing and certification organization with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by CNAS (China National Accreditation Service for Conformity Assessment) AQSIIQ, CMA and IECEE for CBTL. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CPSC(Consumer Product Safety Commission), CEC(California energy efficiency), IC(Industry Canada) and ELI(Efficient Lighting Initiative). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as UL, Intertek(ETL-SEMKO), CSA, TÜV Rheinland, TÜV SÜD, etc.



Waltek Services Test Group Ltd. is one of the largest and the most comprehensive third party testing organizations in China, our headquarter located in Shenzhen and have branches in Foshan, Dongguan, Zhongshan, Suzhou, Ningbo and Hong Kong, Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), reliability and energy performance, Chemical test. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

3 Contents

	Page
1 COVER PAGE.....	1
2 LABORATORIES INTRODUCTION.....	2
3 CONTENTS	3
4 REVISION HISTORY	5
5 GENERAL INFORMATION.....	6
5.1 GENERAL DESCRIPTION OF E.U.T.	6
5.2 DETAILS OF E.U.T.	6
5.3 CHANNEL LIST.....	8
5.4 TEST MODE	9
5.5 TEST FACILITY.....	10
6 TEST SUMMARY	11
7 EQUIPMENT USED DURING TEST	12
7.1 EQUIPMENTS LIST	12
7.2 DESCRIPTION OF SUPPORT UNITS	13
7.3 MEASUREMENT UNCERTAINTY	13
7.4 TEST EQUIPMENT CALIBRATION	13
8 CONDUCTED EMISSION	14
8.1 E.U.T. OPERATION	14
8.2 EUT SETUP.....	14
8.3 MEASUREMENT DESCRIPTION	14
8.4 CONDUCTED EMISSION TEST RESULT	15
9 RADIATED EMISSIONS.....	19
9.1 EUT OPERATION.....	19
9.2 TEST SETUP	20
9.3 SPECTRUM ANALYZER SETUP	21
9.4 TEST PROCEDURE	22
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	22
9.6 SUMMARY OF TEST RESULTS	23
10 CONDUCTED SPURIOUS EMISSIONS.....	41
10.1 TEST PROCEDURE.....	41
10.2 TEST RESULT	42
11 BAND EDGE MEASUREMENT	58
11.1 TEST PRODUCE	58
11.2 TEST RESULT	59
12 6 DB BANDWIDTH MEASUREMENT	64
12.1 TEST PROCEDURE:.....	64
12.2 TEST RESULT:	64
13 MAXIMUM PEAK OUTPUT POWER	73
13.1 TEST PROCEDURE:.....	73
13.2 TEST RESULT:	74
14 POWER SPECTRAL DENSITY	83
14.1 TEST PROCEDURE:.....	83
14.2 TEST RESULT:	83
15 ANTENNA REQUIREMENT	92
16 RF EXPOSURE.....	93

17	PHOTOGRAPHS OF TEST SETUP AND EUT.....	94
-----------	---	-----------

4 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTS17S0681214-2E	Jun. 06, 2017	Jun. 07 ~ 20, 2017	Jun. 21, 2017	original	-	Valid

5 General Information

5.1 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	Doppio SL505
Model Description:	N/A
GSM Band(s):	GSM 850/900/1800/1900MHz
GPRS/EGPRS Class:	12
WCDMA Band(s):	FDD Band I/II/V
LTE Band(s):	FDD Band 2/4/7
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Bluetooth Version:	Bluetooth v4.0 with BLE
GPS:	Support
NFC:	N/A
Hardware Version:	SWW1631_0301_V5156
Software Version:	SWW1631_Mainboard_P2
Highest frequency (Exclude Radio):	1.25GHz
Storage Location:	Internal Storage
Note:	N/A

5.2 Details of E.U.T.

Operation Frequency:	GSM/GPRS/EDGE 850: 824~849MHz PCS/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz LTE Band 2: 1850~1910MHz LTE Band 4: 1710~1755MHz LTE Band 7: 2500-2570MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz Bluetooth: 2402~2480MHz
Max. RF output power:	GSM 850: 32.94dBm PCS1900: 29.99dBm WCDMA Band II: 22.72dBm WCDMA Band V: 22.85dBm LTE Band 2: 22.99dBm LTE Band 4: 24.82dBm

Type of Modulation:	LTE Band 7: 23.85dBm WiFi(2.4G): 9.46dBm Bluetooth: 3.89dBm GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK, 16QAM LTE: QPSK, 16QAM WiFi: CCK, OFDM Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK
Antenna installation:	GSM/WCDMA/LTE: internal permanent antenna WiFi/Bluetooth: internal permanent antenna
Antenna Gain:	GSM 850: -2.0dBi PCS1900: -1.1dBi WCDMA Band II: -1.1dBi WCDMA Band V: -2.0dBi LTE Band 2: -1.1dBi LTE Band 4: -1.4dBi LTE Band 7: -1.2dBi WiFi(2.4G): 1.9dBi Bluetooth: 1.9dBi
Technical Data:	Battery DC 3.85V, 3000mAh DC 5V, 2.0A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.35A)
Adapter:	Manufacture: Dongguan Aohai Power Technology Co.,Ltd Model No.: A8A-050200U-US1

5.3 Channel List

WIFI

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

Remark: 11n(HT40) channel: 3/4/5/6/7/8/9

BT BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Table 2 Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

5.5 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

6 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Equipment Used during Test

7.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	Sep.12,2016	Sep.11,2017
2.	LISN	R&S	ENV216	101215	Sep.12,2016	Sep.11,2017
3.	Cable	Top	TYPE16(3.5M)	-	Sep.12,2016	Sep.11,2017
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	101155	Sep.12,2016	Sep.11,2017
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	Sep.12,2016	Sep.11,2017
3.	Limiter	York	MTS-IMP-136	261115-001-0024	Sep.12,2016	Sep.11,2017
4.	Cable	LARGE	RF300	-	Sep.12,2016	Sep.11,2017
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	Apr.29, 2017	Apr.28, 2018
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	Apr.09,2017	Apr.08,2018
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	Apr.09,2017	Apr.08,2018
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	Sep.12,2016	Sep.11,2017
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	Apr.09,2017	Apr.08,2018
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	Apr.09,2017	Apr.08,2018
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	Apr.13,2017	Apr.12,2018
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	Apr.13,2017	Apr.12,2018
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	Apr.13,2017	Apr.12,2018
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	Apr.09,2017	Apr.08,2018
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	Apr.13,2017	Apr.12,2018
4	Cable	HUBER+SUHNER	CBL2	525178	Apr.13,2017	Apr.12,2018

RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	Sep.12,2016	Sep.11,2017
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	Sep.12,2016	Sep.11,2017
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	Sep.12,2016	Sep.11,2017

7.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

7.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Conducted Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)
Conducted Spurious Emissions test	± 3.12 dB (9kHz~30MHz)
	± 4.21 dB (30M~1000MHz)
	± 5.14 dB (1000M~26500MHz)
Confidence interval: 95%. Confidence factor:k=2	

7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207
Test Method: ANSI C63.10:2013
Test Result: PASS
Frequency Range: 150kHz to 30MHz
Class/Severity: Class B
Limit:

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	60
5 to 30	60	50


8.1 E.U.T. Operation

Operating Environment :
Temperature: 21.5 °C
Humidity: 51.9 % RH
Atmospheric Pressure: 101.2kPa

EUT Operation :
The test was performed in TX transmitting mode, the worst data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result


An initial pre-scan was performed on the live and neutral lines.

Worst Mode: WIFI mode (b mode low channel)

Live line:




Neutral line:




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1780	39.32	9.87	49.19	64.57	-15.38	QP	
2	0.1780	24.40	9.87	34.27	54.57	-20.30	AVG	
3	0.2620	36.87	10.00	46.87	61.36	-14.49	QP	
4	0.2620	23.71	10.00	33.71	51.36	-17.65	AVG	
5	0.6380	30.07	10.08	40.15	56.00	-15.85	QP	
6	0.6380	17.57	10.08	27.65	46.00	-18.35	AVG	
7	1.5980	28.26	10.16	38.42	56.00	-17.58	QP	
8	1.5980	18.50	10.16	28.66	46.00	-17.34	AVG	
9	3.1420	27.38	10.24	37.62	56.00	-18.38	QP	
10	3.1420	16.46	10.24	26.70	46.00	-19.30	AVG	
11	14.0620	26.52	10.38	36.90	60.00	-23.10	QP	
12	14.0620	17.14	10.38	27.52	50.00	-22.48	AVG	

Worst Mode: BLE mode (low channel)

Live line:



Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1740	41.67	9.87	51.54	64.76	-13.22	QP	
2	0.1740	28.28	9.87	38.15	54.76	-16.61	AVG	
3	0.2580	35.40	10.01	45.41	61.49	-16.08	QP	
4	0.2580	22.48	10.01	32.49	51.49	-19.00	AVG	
5	0.3500	32.44	10.06	42.50	58.96	-16.46	QP	
6	0.3500	18.87	10.06	28.93	48.96	-20.03	AVG	
7	0.6460	29.29	10.08	39.37	56.00	-16.63	QP	
8	0.6460	16.03	10.08	26.11	46.00	-19.89	AVG	
9	1.8300	28.45	10.18	38.63	56.00	-17.37	QP	
10	1.8300	17.09	10.18	27.27	46.00	-18.73	AVG	
11	14.2220	26.45	10.38	36.83	60.00	-23.17	QP	
12	14.2220	16.91	10.38	27.29	50.00	-22.71	AVG	

9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth.....10kHz
 Video Bandwidth.....10kHz
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 DetectorPK
 Resolution Bandwidth.....100kHz
 Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
 DetectorPK
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....3MHz
 DetectorAve.
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
802.11b (low channel 2412)							
6.032	25.01	QP	21.84	40.00	6.85	29.54	-22.69
8.051	24.56	QP	21.02	40.00	5.58	29.54	-23.96
26.215	24.35	QP	20.55	40.00	4.90	29.54	-24.64
802.11b (middle channel 2437)							
6.021	25.34	QP	21.84	40.00	7.18	29.54	-22.36
8.304	26.13	QP	21.02	40.00	7.15	29.54	-22.39
26.127	24.02	QP	20.55	40.00	4.57	29.54	-24.97
802.11b (high channel 2462)							
6.022	25.34	QP	21.84	40.00	7.18	29.54	-22.36
8.303	26.13	QP	21.02	40.00	7.15	29.54	-22.39
26.126	24.02	QP	20.55	40.00	4.57	29.54	-24.97
802.11g (low channel 2412)							
6.032	24.53	QP	21.84	40.00	6.37	29.54	-23.17
8.051	24.71	QP	21.02	40.00	5.73	29.54	-23.81
26.215	25.06	QP	20.55	40.00	5.61	29.54	-23.93
802.11g (middle channel 2437)							
6.026	25.33	QP	21.84	40.00	7.17	29.54	-22.37
8.311	26.15	QP	21.02	40.00	7.17	29.54	-22.37
26.131	24.07	QP	20.55	40.00	4.62	29.54	-24.92
802.11g (high channel 2462)							
6.020	25.35	QP	21.84	40.00	7.19	29.54	-22.35
8.332	26.12	QP	21.02	40.00	7.14	29.54	-22.40
26.131	24.08	QP	20.55	40.00	4.63	29.54	-24.91

802.11n(HT20 low channel 2412)							
6.032	25.17	QP	21.84	40.00	7.01	29.54	-22.53
8.051	25.03	QP	21.02	40.00	6.05	29.54	-23.49
26.215	24.42	QP	20.55	40.00	4.97	29.54	-24.57
802.11n(HT20 middle channel 2437)							
6.037	25.36	QP	21.84	40.00	7.20	29.54	-22.34
8.341	26.17	QP	21.02	40.00	7.19	29.54	-22.35
26.141	24.21	QP	20.55	40.00	4.76	29.54	-24.78
802.11n(HT20 high channel 2462)							
6.037	25.38	QP	21.84	40.00	7.22	29.54	-22.32
8.341	26.23	QP	21.02	40.00	7.25	29.54	-22.29
26.141	24.45	QP	20.55	40.00	5.00	29.54	-24.54
802.11n(HT40 low channel 2412)							
6.032	25.11	QP	21.84	40.00	6.95	29.54	-22.59
8.051	25.23	QP	21.02	40.00	6.25	29.54	-23.29
26.215	24.57	QP	20.55	40.00	5.12	29.54	-24.42
802.11n(HT40 middle channel 2437)							
6.052	25.45	QP	21.84	40.00	7.29	29.54	-22.25
8.342	26.78	QP	21.02	40.00	7.80	29.54	-21.74
26.121	24.89	QP	20.55	40.00	5.44	29.54	-24.10
802.11n(HT40 high channel 2452)							
6.052	25.12	QP	21.84	40.00	6.96	29.54	-22.58
8.342	26.73	QP	21.02	40.00	7.75	29.54	-21.79
26.121	24.21	QP	20.55	40.00	4.76	29.54	-24.78

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.30	42.13	QP	111.06	1.75	H	11.02	31.11	46.00	-14.89
223.20	36.16	QP	294.19	1.11	V	11.02	25.14	46.00	-20.86
4824.00	50.16	PK	209.13	1.65	V	1.08	49.08	74.00	-24.92
4824.00	46.21	Ave	209.13	1.65	V	1.08	45.13	54.00	-8.87
7236.00	40.29	PK	291.76	1.52	H	1.33	41.62	74.00	-32.38
7236.00	40.09	Ave	291.76	1.52	H	1.33	41.42	54.00	-12.58
2342.90	46.86	PK	44.39	1.93	V	13.11	33.75	74.00	-40.25
2342.90	38.00	Ave	44.39	1.93	V	13.11	24.89	54.00	-29.11
2356.22	42.86	PK	311.09	1.58	H	13.06	29.80	74.00	-44.20
2356.22	38.68	Ave	311.09	1.58	H	13.04	25.64	54.00	-28.36
2495.04	44.57	PK	49.53	1.98	V	13.00	31.57	74.00	-42.43
2495.04	36.98	Ave	49.53	1.98	V	13.00	23.98	54.00	-30.02

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Middle Channel 2437MHz									
223.30	43.00	QP	126.48	1.07	H	11.02	31.98	46.00	-14.02
223.30	36.16	QP	101.50	1.71	V	11.02	25.14	46.00	-20.86
4874.00	50.57	PK	238.23	1.25	V	1.08	49.49	74.00	-24.51
4874.00	47.31	Ave	238.23	1.25	V	1.08	46.23	54.00	-7.77
7311.00	41.51	PK	311.41	1.22	H	2.21	43.72	74.00	-30.28
7311.00	40.77	Ave	311.41	1.22	H	2.21	42.98	54.00	-11.02
2315.31	46.29	PK	211.94	1.40	V	13.19	33.10	74.00	-40.90
2315.31	39.10	Ave	211.94	1.40	V	13.19	25.91	54.00	-28.09
2360.72	42.22	PK	208.43	1.92	H	13.14	29.08	74.00	-44.92
2360.72	36.86	Ave	208.43	1.92	H	13.14	23.72	54.00	-30.28
2499.71	42.05	PK	22.53	1.35	V	13.08	28.97	74.00	-45.03
2499.71	36.27	Ave	22.53	1.35	V	13.08	23.19	54.00	-30.81

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: High Channel 2462MHz									
223.30	42.63	QP	359.38	1.93	H	11.02	31.61	46.00	-14.39
223.30	36.11	QP	131.52	1.35	V	11.02	25.09	46.00	-20.91
4924.00	50.44	PK	140.99	1.49	V	1.08	49.36	74.00	-24.64
4924.00	48.47	Ave	140.99	1.49	V	1.08	47.39	54.00	-6.61
7386.00	41.43	PK	81.35	1.11	H	2.84	44.27	74.00	-29.73
7386.00	40.07	Ave	81.35	1.11	H	2.84	42.91	54.00	-11.09
2338.24	45.53	PK	40.29	1.30	V	13.11	32.42	74.00	-41.58
2338.24	37.01	Ave	40.29	1.30	V	13.11	23.90	54.00	-30.10
2377.98	43.86	PK	126.19	1.15	H	13.06	30.80	74.00	-43.20
2377.98	36.29	Ave	126.19	1.15	H	13.04	23.25	54.00	-30.75
2490.57	42.19	PK	146.29	1.67	V	13.00	29.19	74.00	-44.81
2490.57	37.70	Ave	146.29	1.67	V	13.00	24.70	54.00	-29.30

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Low Channel 2412MHz									
223.30	41.99	QP	348.52	1.01	H	11.02	30.97	46.00	-15.03
223.30	35.57	QP	96.75	1.98	V	11.02	24.55	46.00	-21.45
4824.00	50.92	PK	132.68	1.72	V	1.08	49.84	74.00	-24.16
4824.00	48.27	Ave	132.68	1.72	V	1.08	47.19	54.00	-6.81
7236.00	41.18	PK	299.12	1.57	H	1.33	42.51	74.00	-31.49
7236.00	40.33	Ave	299.12	1.57	H	1.33	41.66	54.00	-12.34
2318.77	46.61	PK	171.86	1.91	V	13.11	33.50	74.00	-40.50
2318.77	37.05	Ave	171.86	1.91	V	13.11	23.94	54.00	-30.06
2383.97	42.42	PK	116.91	1.78	H	13.06	29.36	74.00	-44.64
2383.97	38.62	Ave	116.91	1.78	H	13.04	25.58	54.00	-28.42
2494.71	43.32	PK	307.46	1.61	V	13.00	30.32	74.00	-43.68
2494.71	38.85	Ave	307.46	1.61	V	13.00	25.85	54.00	-28.15

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: Middle Channel 2437MHz									
223.30	41.85	QP	76.47	1.21	H	11.02	30.83	46.00	-15.17
223.30	35.80	QP	204.46	1.97	V	11.02	24.78	46.00	-21.22
4874.00	50.15	PK	45.69	1.17	V	1.08	49.07	74.00	-24.93
4874.00	49.59	Ave	45.69	1.17	V	1.08	48.51	54.00	-5.49
7311.00	40.38	PK	41.67	1.29	H	2.21	42.59	74.00	-31.41
7311.00	39.96	Ave	41.67	1.29	H	2.21	42.17	54.00	-11.83
2319.87	45.81	PK	306.17	1.35	V	13.11	32.70	74.00	-41.30
2319.87	38.09	Ave	306.17	1.35	V	13.11	24.98	54.00	-29.02
2389.38	42.33	PK	0.94	1.17	H	13.06	29.27	74.00	-44.73
2389.38	38.29	Ave	0.94	1.17	H	13.04	25.25	54.00	-28.75
2496.66	43.55	PK	246.37	1.50	V	13.00	30.55	74.00	-43.45
2496.66	36.27	Ave	246.37	1.50	V	13.00	23.27	54.00	-30.73

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11g: High Channel 2462MHz									
223.30	40.62	QP	45.31	1.24	H	11.02	29.60	46.00	-16.40
223.30	35.50	QP	43.75	1.07	V	11.02	24.48	46.00	-21.52
4924.00	51.17	PK	161.11	1.97	V	1.08	50.09	74.00	-23.91
4924.00	50.21	Ave	161.11	1.97	V	1.08	49.13	54.00	-4.87
7386.00	41.65	PK	15.92	1.08	H	2.84	44.49	74.00	-29.51
7386.00	38.47	Ave	15.92	1.08	H	2.84	41.31	54.00	-12.69
2331.56	46.18	PK	165.16	1.35	V	13.11	33.07	74.00	-40.93
2331.56	38.06	Ave	165.16	1.35	V	13.11	24.95	54.00	-29.05
2372.49	43.59	PK	25.24	1.09	H	13.06	30.53	74.00	-43.47
2372.49	38.55	Ave	25.24	1.09	H	13.04	25.51	54.00	-28.49
2485.82	44.75	PK	32.47	1.20	V	13.00	31.75	74.00	-42.25
2485.82	37.25	Ave	32.47	1.20	V	13.00	24.25	54.00	-29.75

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Low Channel 2412MHz									
223.30	41.57	QP	308.86	1.62	H	11.02	30.55	46.00	-15.45
223.30	35.19	QP	317.59	1.56	V	11.02	24.17	46.00	-21.83
4824.00	52.33	PK	174.96	1.82	V	1.08	51.25	74.00	-22.75
4824.00	49.87	Ave	174.96	1.82	V	1.08	48.79	54.00	-5.21
7236.00	41.32	PK	120.69	1.69	H	1.33	42.65	74.00	-31.35
7236.00	38.34	Ave	120.69	1.69	H	1.33	39.67	54.00	-14.33
2321.85	45.78	PK	279.82	1.95	V	13.11	32.67	74.00	-41.33
2321.85	39.74	Ave	279.82	1.95	V	13.11	26.63	54.00	-27.37
2369.69	42.47	PK	233.22	1.04	H	13.06	29.41	74.00	-44.59
2369.69	37.07	Ave	233.22	1.04	H	13.04	24.03	54.00	-29.97
2494.03	44.95	PK	126.60	1.37	V	13.00	31.95	74.00	-42.05
2494.03	36.40	Ave	126.60	1.37	V	13.00	23.40	54.00	-30.60

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: Middle Channel 2437MHz									
223.30	41.65	QP	246.22	1.16	H	11.02	30.63	46.00	-15.37
223.30	33.99	QP	272.81	1.58	V	11.02	22.97	46.00	-23.03
4874.00	52.38	PK	81.61	1.96	V	1.08	51.30	74.00	-22.70
4874.00	50.35	Ave	81.61	1.96	V	1.08	49.27	54.00	-4.73
7311.00	40.74	PK	249.86	1.06	H	2.21	42.95	74.00	-31.05
7311.00	38.17	Ave	249.86	1.06	H	2.21	40.38	54.00	-13.62
2315.74	46.93	PK	164.90	1.32	V	13.11	33.82	74.00	-40.18
2315.74	39.04	Ave	164.90	1.32	V	13.11	25.93	54.00	-28.07
2376.75	42.96	PK	116.40	1.09	H	13.06	29.90	74.00	-44.10
2376.75	38.97	Ave	116.40	1.09	H	13.04	25.93	54.00	-28.07
2494.92	43.95	PK	121.55	1.75	V	13.00	30.95	74.00	-43.05
2494.92	38.90	Ave	121.55	1.75	V	13.00	25.90	54.00	-28.10

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n20: High Channel 2462MHz									
223.30	42.26	QP	31.15	1.36	H	11.02	31.24	46.00	-14.76
223.30	32.55	QP	316.63	1.42	V	11.02	21.53	46.00	-24.47
4924.00	52.80	PK	62.43	1.85	V	1.08	51.72	74.00	-22.28
4924.00	49.21	Ave	62.43	1.85	V	1.08	48.13	54.00	-5.87
7386.00	40.11	PK	138.39	1.17	H	2.84	42.95	74.00	-31.05
7386.00	38.55	Ave	138.39	1.17	H	2.84	41.39	54.00	-12.61
2339.53	46.41	PK	125.81	1.83	V	13.11	33.30	74.00	-40.70
2339.53	39.68	Ave	125.81	1.83	V	13.11	26.57	54.00	-27.43
2356.16	44.91	PK	191.15	1.89	H	13.06	31.85	74.00	-42.15
2356.16	37.65	Ave	191.15	1.89	H	13.04	24.61	54.00	-29.39
2494.05	42.21	PK	312.36	1.37	V	13.00	29.21	74.00	-44.79
2494.05	36.86	Ave	312.36	1.37	V	13.00	23.86	54.00	-30.14

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Low Channel 2422MHz									
223.30	43.07	QP	310.64	1.75	H	11.02	32.05	46.00	-13.95
223.30	31.50	QP	322.09	1.55	V	11.02	20.48	46.00	-25.52
4844.00	51.77	PK	104.90	1.69	V	1.08	50.69	74.00	-23.31
4844.00	47.00	Ave	104.90	1.69	V	1.08	45.92	54.00	-8.08
7266.00	38.60	PK	108.75	1.81	H	1.33	39.93	74.00	-34.07
7266.00	36.04	Ave	108.75	1.81	H	1.33	37.37	54.00	-16.63
2315.73	46.58	PK	256.78	1.23	V	13.11	33.47	74.00	-40.53
2315.73	37.89	Ave	256.78	1.23	V	13.11	24.78	54.00	-29.22
2350.64	42.06	PK	168.79	1.18	H	13.06	29.00	74.00	-45.00
2350.64	38.35	Ave	168.79	1.18	H	13.04	25.31	54.00	-28.69
2491.72	43.63	PK	297.06	1.97	V	13.00	30.63	74.00	-43.37
2491.72	36.04	Ave	297.06	1.97	V	13.00	23.04	54.00	-30.96

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: Middle Channel 2437MHz									
223.30	43.23	QP	6.64	1.97	H	11.02	32.21	46.00	-13.79
223.30	30.85	QP	77.68	1.02	V	11.02	19.83	46.00	-26.17
4874.00	51.39	PK	151.06	1.93	V	1.08	50.31	74.00	-23.69
4874.00	47.23	Ave	151.06	1.93	V	1.08	46.15	54.00	-7.85
7311.00	37.70	PK	349.91	1.80	H	2.21	39.91	74.00	-34.09
7311.00	35.24	Ave	349.91	1.80	H	2.21	37.45	54.00	-16.55
2336.91	45.44	PK	32.41	1.38	V	13.11	32.33	74.00	-41.67
2336.91	38.39	Ave	32.41	1.38	V	13.11	25.28	54.00	-28.72
2387.20	44.67	PK	142.98	1.52	H	13.06	31.61	74.00	-42.39
2387.20	37.38	Ave	142.98	1.52	H	13.04	24.34	54.00	-29.66
2490.37	43.37	PK	64.26	1.14	V	13.00	30.37	74.00	-43.63
2490.37	36.00	Ave	64.26	1.14	V	13.00	23.00	54.00	-31.00

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.247/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11n40: High Channel 2452MHz									
223.30	44.19	QP	5.50	1.12	H	11.02	33.17	46.00	-12.83
223.30	31.72	QP	149.96	1.65	V	11.02	20.70	46.00	-25.30
4904.00	51.51	PK	290.39	1.90	V	1.08	50.43	74.00	-23.57
4904.00	46.71	Ave	290.39	1.90	V	1.08	45.63	54.00	-8.37
7356.00	36.90	PK	98.68	1.05	H	2.84	39.74	74.00	-34.26
7356.00	36.18	Ave	98.68	1.05	H	2.84	39.02	54.00	-14.98
2328.23	46.33	PK	245.46	1.77	V	13.11	33.22	74.00	-40.78
2328.23	38.89	Ave	245.46	1.77	V	13.11	25.78	54.00	-28.22
2365.71	43.86	PK	142.96	1.02	H	13.06	30.80	74.00	-43.20
2365.71	36.30	Ave	142.96	1.02	H	13.04	23.26	54.00	-30.74
2489.88	42.81	PK	142.34	1.23	V	13.00	29.81	74.00	-44.19
2489.88	37.37	Ave	142.34	1.23	V	13.00	24.37	54.00	-29.63

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:**Test Frequency: 9KHz~26MHz**

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
GFSK Low Channel 2402MHz							
6.032	24.03	QP	21.84	40.00	5.87	29.54	-23.67
8.051	25.62	QP	21.02	40.00	6.64	29.54	-22.90
25.215	24.27	QP	20.55	40.00	4.82	29.54	-24.72

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
GFSK Middle Channel 2440MHz							
6.124	25.29	QP	21.84	40.00	7.13	29.54	-22.41
8.227	26.35	QP	21.02	40.00	7.37	29.54	-22.17
25.069	24.26	QP	20.55	40.00	4.81	29.54	-24.73

Frequency	Measurement results dBμV @3m	Detector PK/QP	Correct factor dB/m	Extrapolation factor dB	Measurement results (calculated) dBμV/m @30m	Limits dBμV/m @30m	Margin dB
(MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
GFSK High Channel 2480MHz							
6.112	24.12	QP	21.84	40.00	5.96	29.54	-23.58
8.205	25.88	QP	21.02	40.00	6.90	29.54	-22.64
25.057	24.03	QP	20.55	40.00	4.58	29.54	-24.96

Test Frequency : 26MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2402MHz									
268.32	36.89	QP	247	1.1	H	-13.35	23.54	46.00	-22.46
268.32	41.33	QP	255	1.5	V	-13.35	27.98	46.00	-18.02
4804.00	46.15	PK	128	1.9	V	-1.06	45.09	74.00	-28.91
4804.00	43.52	Ave	128	1.9	V	-1.06	42.46	54.00	-11.54
7206.00	40.62	PK	55	1.0	H	1.33	41.95	74.00	-32.05
7206.00	35.37	Ave	55	1.0	H	1.33	36.70	54.00	-17.30
2345.10	45.49	PK	306	1.0	V	-13.19	32.30	74.00	-41.70
2345.10	39.83	Ave	306	1.0	V	-13.19	26.64	54.00	-27.36
2389.25	44.17	PK	268	1.6	H	-13.14	31.03	74.00	-42.97
2389.25	36.88	Ave	268	1.6	H	-13.14	23.74	54.00	-30.26
2486.48	44.36	PK	22	1.5	V	-13.08	31.28	74.00	-42.72
2486.48	36.68	Ave	22	1.5	V	-13.08	23.60	54.00	-30.40

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2440MHz									
268.32	35.70	QP	166	1.0	H	-13.35	22.35	46.00	-23.65
268.32	40.57	QP	212	1.7	V	-13.35	27.22	46.00	-18.78
4880.00	46.09	PK	212	1.8	V	-0.62	45.47	74.00	-28.53
4880.00	42.29	Ave	212	1.8	V	-0.62	41.67	54.00	-12.33
7320.00	40.25	PK	327	2.0	H	2.21	42.46	74.00	-31.54
7320.00	34.09	Ave	327	2.0	H	2.21	36.30	54.00	-17.70
2316.46	46.34	PK	60	1.2	V	-13.19	33.15	74.00	-40.85
2316.46	39.21	Ave	60	1.2	V	-13.19	26.02	54.00	-27.98
2385.10	44.21	PK	186	1.8	H	-13.14	31.07	74.00	-42.93
2385.10	37.81	Ave	186	1.8	H	-13.14	24.67	54.00	-29.33
2497.65	44.07	PK	84	1.6	V	-13.08	30.99	74.00	-43.01
2497.65	38.02	Ave	84	1.6	V	-13.08	24.94	54.00	-29.06

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel 2480MHz									
268.32	34.35	QP	265	1.7	H	-13.35	21.00	46.00	-25.00
268.32	39.58	QP	46	1.7	V	-13.35	26.23	46.00	-19.77
4960.00	47.56	PK	316	1.7	V	-0.24	47.32	74.00	-26.68
4960.00	42.75	Ave	316	1.7	V	-0.24	42.51	54.00	-11.49
7440.00	39.40	PK	275	1.1	H	2.84	42.24	74.00	-31.76
7440.00	32.61	Ave	275	1.1	H	2.84	35.45	54.00	-18.55
2340.11	45.38	PK	197	1.3	V	-13.19	32.19	74.00	-41.81
2340.11	39.13	Ave	197	1.3	V	-13.19	25.94	54.00	-28.06
2377.18	43.96	PK	234	1.2	H	-13.14	30.82	74.00	-43.18
2377.18	36.39	Ave	234	1.2	H	-13.14	23.25	54.00	-30.75
2497.11	43.49	PK	188	1.4	V	-13.08	30.41	74.00	-43.59
2497.11	37.88	Ave	188	1.4	V	-13.08	24.80	54.00	-29.20

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016
Test Result: PASS
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:

Below 1GHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 1GHz:

For WIFI mode

RBW = 100KHz, VBW = 300KHz, Sweep = auto

Detector function = peak, Trace = max hold

For BLE mode

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold

10.2 Test Result


9KHz – 30MHz



802.11b



Low Channel



Middle Channel











802.11n HT20



Low Channel



Middle Channel










BLE

Low Channel




Middle Channel






Above 30MHz
802.11b
Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11g


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT40


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



BLE


Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



11 Band Edge Measurement



Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016
Test Limit:	Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

11.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:







TX 11g: Band edge-left side





TX 11g: Band edge-right side









12 6 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016



12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



12.2 Test Result:



Operation mode	Test Channel	Bandwidth (MHz)	Limit (kHz)
TX 11b	Channel 1	10.060	500
	Channel 6	10.060	500
	Channel 11	10.060	500
TX 11g	Channel 1	16.267	500
	Channel 6	16.068	500
	Channel 11	16.068	500
TX 11n HT20	Channel 1	17.838	500
	Channel 6	17.623	500
	Channel 11	17.731	500
TX 11n HT40	Channel 3	35.890	500
	Channel 6	35.890	500
	Channel 9	35.890	500
BLE	Channel 0	0.773	500
	Channel 19	0.731	500
	Channel 39	0.743	500



Test result plot:






















13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq$ DTS bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1 \text{ MHz}$.
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the $span \geq 1.5 \times$ DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

13.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	9.38	1W/30dBm
	Middle-2437	9.34	1W/30dBm
	High-2462	9.20	1W/30dBm
TX 11g	Low-2412	9.46	1W/30dBm
	Middle-2437	9.35	1W/30dBm
	High-2462	9.36	1W/30dBm
TX 11n HT20	Low-2412	9.27	1W/30dBm
	Middle-2437	9.08	1W/30dBm
	High-2462	9.42	1W/30dBm
TX 11n HT40	Low-2422	9.29	1W/30dBm
	Middle-2437	9.21	1W/30dBm
	High-2452	9.31	1W/30dBm
BLE	Low-2402	1.69	1W/30dBm
	Middle-2440	3.64	1W/30dBm
	High-2480	2.37	1W/30dBm



Test Plot



Mode: TX 11b channel 1







Mode: TX 11b channel 6






















14 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016



14.1 Test Procedure:



KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016 section 10.2



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.



14.2 Test Result:



Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-15.90	8dBm per 3kHz
	Middle-2437	-16.13	8dBm per 3kHz
	High-2462	-13.97	8dBm per 3kHz
TX 11g	Low-2412	-22.36	8dBm per 3kHz
	Middle-2437	-19.75	8dBm per 3kHz
	High-2462	-20.09	8dBm per 3kHz
TX 11n HT20	Low-2412	-23.50	8dBm per 3kHz
	Middle-2437	-20.78	8dBm per 3kHz
	High-2462	-20.62	8dBm per 3kHz
TX 11n HT40	Low-2422	-27.23	8dBm per 3kHz
	Middle-2437	-27.32	8dBm per 3kHz
	High-2452	-26.81	8dBm per 3kHz
BLE	Low-2402	-14.38	8dBm per 3kHz
	Middle-2440	-12.13	8dBm per 3kHz
	High-2480	-13.54	8dBm per 3kHz






















15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

16 RF Exposure

Remark: refer to SAR test report: WWTS17S0681217E.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: WTS17S0681214E_Photo.

=====End of Report=====