



Electromagnetic Compatibility Test Report

Tests Performed on a Dane Industries, Inc.

Transmitter and Reciever, Model QuickKart SE3/HD3

Radiometrics Document RP-5678



Product Detail:

FCC ID: N2N600-044

Equipment type: 433.9 MHz Momentarily Operated Transmitter and Receiver

Test Standards:

US CFR Title 47, Chapter I, FCC Part 15 Subpart C

FCC Part 15 CFR Title 47: 2004

Industry Canada RSS-210, Issue 5 as required for Category I Equipment

This report concerns: Original Grant for Certification

FCC Part 15.231

RSS-210 section 6.1

Tests Performed For:

Dane Industries

7105 Northland Terrace
Brooklyn Park, MN 55428

Test Facility:

Radiometrics Midwest Corporation

12 East Devonwood
Romeoville, IL 60446
Phone: (815) 293-0772
e-mail: info@radiomet.com

Test Date(s): (Month-Day-Year)

October 13 to November 3, 2005

Document RP-5678 Revisions:

Rev.	Issue Date	Affected Pages	Revised By
0	November 7, 2005		
1	November 17, 2005		Joseph Strzelecki



Table of Contents

1 ADMINISTRATIVE DATA	3
2 TEST SUMMARY AND RESULTS	3
2.1 RF Exposure Compliance Requirements	3
3 EQUIPMENT UNDER TEST (EUT) DETAILS	4
3.1 EUT Description	4
3.1.1 FCC Section 15.203 & RSS-210 Section 5.5 Antenna Requirements	4
3.2 Related Submittals	4
4 TESTED SYSTEM DETAILS	4
4.1 Tested System Configuration	4
4.2 Special Accessories	4
5 TEST SPECIFICATIONS AND RELATED DOCUMENTS	4
6 RADIOMETRICS' TEST FACILITIES	5
7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS	5
8 CERTIFICATION	5
9 TEST EQUIPMENT TABLE	5
10 TEST SECTIONS	6
10.1 Radiated RF Emissions	6
10.1.1 Field Strength Calculation	7
10.1.2 Peak to average Correction	7
Figure 1. Plot of pulse train	8
10.1.3 Radiated Emissions Test Results (Transmitter)	9
10.1.4 Radiated Emissions Test Results (Receiver)	10
Figure 2. Drawing of Radiated Emissions Setup	11
10.2 Occupied Bandwidth Data	11
Figure 3. Occupied Bandwidth Plot	12
10.3 Transmitter Deactivation Delay	14

Notice: This report must not be reproduced (except in full) without the written approval of Radiometrics Midwest Corporation.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report
Testing of the Dane Industries, Inc., QuickKart SE3/HD3, Transmitter and Receiver

1 ADMINISTRATIVE DATA

<i>Equipment Under Test:</i> A Dane Industries, Transmitter Model 100-224 and Receiver Model 100-223 The system is a QuickKart SE3/HD3 will be referred to as the EUT in this Report	
<i>Date EUT Received at Radiometrics: (Month-Day-Year)</i> October 13, 2005	<i>Test Date(s): (Month-Day-Year)</i> October 13 to November 3, 2005
<i>Test Report Written By:</i> Joseph Strzelecki Senior EMC Engineer	<i>Test Witnessed By:</i> The tests were not witnessed by Dane Industries
<i>Radiometrics' Personnel Responsible for Test:</i>  Joseph Strzelecki Senior EMC Engineer NARTE EMC-000877-NE	<i>Test Report Approved By</i>  Chris W. Carlson Director of Engineering NARTE EMC-000921-NE

2 TEST SUMMARY AND RESULTS

The EUT (Equipment Under Test) is a Transmitter and Receiver, QuickKart SE3/HD3, manufactured by Dane Industries. The detailed test results are presented in a separate section. The following is a summary of the test results.

Emissions Tests Results

Environmental Phenomena	Frequency Range	Basic Standard	Test Result
RF Radiated Emissions Transmitter	30-4400 MHz	RSS-210 & FCC Part 15	Pass
RF Radiated Emissions Receiver	30-2000 MHz	RSS-210 & FCC Part 15	Pass
Occupied Bandwidth Test	Fundamental Freq.	RSS-210 & FCC Part 15	Pass

Since the EUT is battery powered, AC conducted emissions are not required.

2.1 RF Exposure Compliance Requirements

The power output is less than 10 mW; the EUT meets the FCC and Canada's RSS-210 requirements for RF exposure.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report
Testing of the Dane Industries, Inc., QuickKart SE3/HD3, Transmitter and Receiver

3 EQUIPMENT UNDER TEST (EUT) DETAILS

3.1 EUT Description

The EUT is a 433.9 MHz Transmitter, manufactured by Dane Industries. The EUT was in good working condition during the tests, with no known defects.

3.1.1 FCC Section 15.203 & RSS-210 Section 5.5 Antenna Requirements

There are no power level adjustments and the antenna is permanently attached.

3.2 Related Submittals

The associated receiver is subject to the IC requirements pursuant to the Certification equipment authorization under RSS-210. The associated receiver is subject to the IC requirements pursuant to the Certification equipment authorization under RSS-210.

4 TESTED SYSTEM DETAILS

4.1 Tested System Configuration

The system was configured for testing in a typical fashion. The EUT was placed on an 80-cm high, nonconductive test stand. The testing was performed in conditions as close as possible to installed conditions. Wiring was consistent with manufacturer's recommendations.

The EUT was tested as a stand-alone device. Power was supplied with a new battery. There are no external cables connected to the EUT.

4.2 Special Accessories

No special accessories were used during the tests in order to achieve compliance.

5 TEST SPECIFICATIONS AND RELATED DOCUMENTS

Document	Date	Title
FCC CFR Title 47	2004	Code of Federal Regulations Title 47, Chapter 1, Federal Communications Commission, Part 15 - Radio Frequency Devices
ANSI C63.4-2001	2001	Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
IC RSS-210 Issue 5	2001	Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)
IC RSS-212 Issue 1	1998	Test Methods For Radio Equipment

The test procedures used are in accordance with the Industry Canada RSS-212 and ANSI document C63.4-2001, "Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The specific procedures are described herein. Radiated testing was performed at an antenna to EUT distance of 3 meters. The antenna was raised and lowered from 1 to 4 meters.

6 RADIOMETRICS' TEST FACILITIES

The results of these tests were obtained at Radiometrics Midwest Corp. in Romeoville, Illinois, USA. Radiometrics is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025: 1999 "General Requirements for the Competence of Calibration and Testing Laboratories". Radiometrics' Lab Code is 121191 and Certification Number is 1495.01. Radiometrics' scope of accreditation includes all of the test methods listed herein. A copy of the accreditation can be accessed on our web site (www.radiomet.com). Radiometrics accreditation status can be verified at A2LA's web site (www.a2la2.net).

The following is a list of facilities used during the tests.

Chamber A: Is an anechoic chamber that measures 24' L X 12' W X 12' H. The walls and ceiling are fully lined with ferrite absorber tiles. The floor has a 10' x 10' section of ferrite absorber tiles in the located in the center. Panashield of Rowayton, Connecticut manufactured the chamber. The enclosure is NAMAS certified.

Chamber E: Is a custom made anechoic chamber that measures 52' L X 30' W X 18' H. The walls and ceiling are fully lined with RF absorber. Pro-shield of Collinsville, Oklahoma manufactured the chamber.

A separate ten-foot long, brass plated, steel ground rod attached via a 6 inch copper braid grounds each of the above chambers. Each enclosure is also equipped with low-pass power line filters.

Open Area Test Site (OATS): Is located on 8625 Helmar Road in Newark, Illinois, USA and measures 56' L X 24' W X 17' H. The entire open field test site has a metal ground screen. The FCC has accepted these sites as test site number 31040/SIT 1300F2. The FCC test site Registration Number is 90897. Details of the site characteristics are on file with the Industry Canada as file number IC3124.

A complete list of the test equipment is provided herein. The calibration due dates are indicated on the equipment list. The equipment is calibrated in accordance to ANSI/NCSL Z540-1 with traceability to the National Institute of Standards and Technology (NIST).

7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS

There were no deviations or exclusions from the test specifications.

8 CERTIFICATION

Radiometrics Midwest Corporation certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specification. The results relate only to the EUT listed herein. Any modifications made to the EUT subsequent to the indicated test date will invalidate the data and void this certification.

9 TEST EQUIPMENT TABLE

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
AMP-05	RMC/Celeritek	Pre-amplifier	MW110G	1001	1.0-12GHz	12 Mo.	12/07/04
AMP-12	MITEQ	Pre-amplifier	AM-1431	530935	0.01-1000MHz	12 Mo.	12/29/04
AMP-22	Anritsu	Pre-amplifier	MH648A	M23969	0.1-1200MHz	12 Mo.	12/07/04
ANT-06	EMCO	Log-Periodic Ant.	3146	1248	200-1000MHz	24 mo	11/17/03

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report							
Testing of the Dane Industries, Inc., QuicKart SE3/HD3, Transmitter and Receiver							

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
ANT-12	RMC	Dipole Antenna Set	HW1010	202	25-1000MHz	24 Mo.	07/12/04
ANT-13	EMCO	Horn Antenna	3115	2502	1.0-18GHz	24 Mo.	10/13/04
ANT-42	EMCO	Bicon Antenna	3104C	9512-4713	25-300MHz	24 Mo.	12/02/03
ANT-44	Impossible Machine	Super Log Antenna	SL-20M2G	1002	20-2000MHz	24 Mo.	06/15/04
REC-01	Hewlett Packard	Spectrum Analyzer	8566A	2106A02115, 2209A01349	30Hz-22GHz	12 Mo.	08/19/05
REC-03	Anritsu	Spectrum Analyzer	MS2601B	MT94589	0.01-2200MHz	12 Mo.	11/11/04
SCP-02	Tektronix	Oscilloscope	TDS 3054B	B030068	DC- 500 MHz	18 Mo.	06/02/04
THM-01	Extech Inst.	Temp/Humid Meter	4465CF	001106557	N/A	24 Mo.	01/28/04

Note: All calibrated equipment is subject to periodic checks.

10 TEST SECTIONS

10.1 Radiated RF Emissions

Radiated emission measurements were performed with linearly polarized broadband antennas. The results obtained with these antennas can be correlated with results obtained with a tuned dipole antenna. Below 1 GHz, when a radiated emission is detected approaching the specification limit, the measurement of the emission is repeated using a tuned dipole antenna with a Roberts Balun.

The radiated emission measurements were performed with a spectrum analyzer. The bandwidth used from 450 kHz to 30 MHz is 9 or 10 kHz and the bandwidth from 30 MHz to 1000 MHz is 100 or 120 kHz. Above 1 GHz, a 1 MHz bandwidth is used. A 10 dB linearity check is performed prior to start of testing in order to determine if an overload condition exists.

From 30 to 1000 MHz an Anritsu Spectrum analyzer and a MITEQ AM-1431 amplifier with a 10 dB attenuator connected to the input. The out of band emissions and the ambient emissions were below the level of input overload (80 dBuV).

For tests from 1 to 4.4 GHz, an HP8566A spectrum analyzer was used with a Celeritek uWave amplifier. The fundamental emission, out of band emissions and the ambient emissions were below the level of input overload (72 dBuV). In addition, a high pass filter was used to reduce the fundamental emission.

Preliminary radiated emission tests were performed inside of an anechoic enclosure. The frequency range from 30 to 4400 MHz was scanned and plotted using the peak detector function. The test antennas were positioned 3 meters from the EUT. The results of the preliminary scans were only used to identify the frequencies being emitted from the EUT and were not used to determine compliance with the test specification. Radiated emission measurements are performed with linearly polarized broadband antennas.

Final radiated emissions measurements were performed in the open area test site at a test distance of 3 meters. Measurements were performed using the peak or quasi-peak detector function. The detected emission levels were maximized by rotating the EUT, adjusting the positions of all cables, and by scanning the measurement antenna from 1 to 4 meters above the ground. The open area test site used to collect the radiated data is located on 8625 Helmar Road in Newark, Illinois. The open field test site has a metal ground screen. All other tests are performed at 12 East Devonwood Ave. Romeoville, Illinois EMI test lab.

The device was rotated through three orthogonal axes as per 13.1.4.1 of ANSI C63.4 during the prescans and during final radiated tests.

The entire frequency range from 30 to 4400 MHz was slowly scanned with particular attention paid to those frequency ranges which appeared high in the preliminary emission scan. Measurements were performed using two antenna polarizations, (vertical and horizontal). The worst case emissions were recorded.

The receiver was tested using the same procedures as above, except the frequency tested was 30 to 2000 MHz and since it is not hand held, it was rotated in one axis only.

10.1.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG + PKA$$

Where: FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

PKA = Peak to Average Factor

The Peak to average factor is used when average measurements are required. It is calculated by the highest duty cycle in percent over any 100mS transmission. The factor in dB is $20 * \log(\text{Duty cycle}/100)$.

10.1.2 Peak to average Correction


The transmitter has a maximum broadcast duty cycle of 12.044% within a 100mS window. This number was measured by recording the digital transmitter signal on a digital logic analyzer and looking at the high time (time when the transmitter carrier is on) vs. the low time (time when the transmitter carrier is off). This value could also be calculated from the following digital signal characteristics:

- Data bit rate = 8772 bits per second.
- Data is Manchester encoded.
- The transmitter uses On-Off-Keying (OOK) modulation.
- Two data bursts are sent within a 100mS window.
- A data burst consists of four "ID" bytes and one message packet.
- Each "ID" byte and the message packet are preceded by a preamble sequence and followed by an end-of-message sequence.
- The preamble consists of greater than two bit times (approx. 288µS) of carrier, followed by one Manchester encoded '0'.
- The end-of-message consists of greater than two bit times (approx. 288µS) of no transmission.
- The "ID" byte contains eight bits of data.
- There is approx. 288µS of non-transmission time between each "ID" byte and also before the message packet.
- The message packet contains 51 bits.
- There is 36.288mS of no carrier between data bursts.

The measured amount of carrier ON time was 12,044µS and carrier OFF time was 87,956µS per 100mS.

The peak to average factor is $20 \cdot \log(12.04/100) = -18.4 \text{ dB}$

Figure 1. Plot of pulse train



RADIOMETRICS MIDWEST CORPORATION - EMC Test Report	
Testing of the Dane Industries, Inc., QuickKart SE3/HD3, Transmitter and Receiver	

10.1.3 Radiated Emissions Test Results (Transmittter)

Test Date	10/18/2005 & 10/26/2005
Test Distance	3 Meters
Specification	FCC Part 15 Subpart C & RSS-210
Notes	Peak to Average factor is -18.4 dB; Correction factors are preamp and cable loss
Abbreviations	Pol = Antenna Polarization; V = Vertical; H = Horizontal; P = peak; Q = QP
Configuration	The following is the worst case reading for the 3 orthogonal axis

Hrm	Tx Freq	Emission Freq	Ant.	Max Peak	Peak to Ave	Ave	ANT	Cbl + Amp	Ave Field Strength dBuV/m		Margin under limit dB
#	MHz	MHz	Pol	dBuV	dB	dBuV	Fact.	dB	EUT	Limit	
1	433.9	433.9	V	92.6	-18.4	74.2	16.4	-14.3	76.3	80.8	4.5
1	433.9	433.9	H	93.5	-18.4	75.1	16.9	-14.3	77.7	80.8	3.1
2	433.9	867.8	V	46.2	-18.4	27.8	21.4	-10.9	38.3	60.8	22.5
2	433.9	867.8	H	43.1	-18.4	24.7	22.5	-10.9	36.3	60.8	24.5
3	433.9	1301.8	V	65.0	-18.4	46.6	24.8	-27.3	44.1	54.0	9.9
3	433.9	1301.8	H	61.5	-18.4	43.1	24.8	-27.3	40.6	54.0	13.4
4	433.9	1735.7	V	57.5	-18.4	39.1	26.3	-26.8	38.6	60.8	22.2
4	433.9	1735.7	H	59.9	-18.4	41.5	26.3	-26.8	41.0	60.8	19.8
5	433.9	2169.6	V	56.9	-18.4	38.5	27.9	-26.7	39.7	60.8	21.1
5	433.9	2169.6	H	60.5	-18.4	42.1	27.9	-26.7	43.3	60.8	17.5
6	433.9	2603.5	V	43.1	-18.4	24.7	28.9	-25.8	27.8	60.8	33.0
6	433.9	2603.5	H	45.6	-18.4	27.2	28.9	-25.8	30.3	60.8	30.5
7	433.9	3037.4	V	38.5	-18.4	20.1	30.1	-25.2	25.0	60.8	35.8
7	433.9	3037.4	H	42.6	-18.4	24.2	30.1	-25.2	29.1	60.8	31.7
8	433.9	3471.4	V	36.9	-18.4	18.5	31.1	-24.6	25.0	60.8	35.8
8	433.9	3471.4	H	38.2	-18.4	19.8	31.1	-24.6	26.3	60.8	34.5
9	433.9	3905.3	V	35.0	-18.4	16.6	32.5	-24.3	24.8	60.8	36.0
9	433.9	3905.3	H	34.5	-18.4	16.1	32.5	-24.3	24.3	60.8	36.5
10	433.9	4339.2	V	35.0	-18.4	16.6	33.1	-24.1	25.6	54.0	28.4
10	433.9	4339.2	H	34.0	-18.4	15.6	33.1	-24.1	24.6	54.0	29.4


Judgment: Passed by 3.1 dB

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report	
Testing of the Dane Industries, Inc., QuickKart SE3/HD3, Transmitter and Receiver	

10.1.4 Radiated Emissions Test Results (Receiver)

Test Date	10-26-05
Test Distance	3 Meters
Specification	FCC Part 15 Subpart C & RSS-210
Notes	Correction factors are preamp and cable loss
Abbreviations	Pol = Antenna Polarization; V = Vertical; H = Horizontal; P = peak; Q = QP
Configuration	

Tx Freq MHz	Emission Freq MHz	Ant. Pol	Max rdg	Det	ANT	Cbl + Amp	Field Strength dBuV/m		Margin under limit dB
			dBuV	Funt.	Fact.	dB	EUT	Limit	
433.9	77.1	H	36.4	P	6.6	-16.9	26.1	40.0	13.9
433.9	94.7	H	33.1	P	9.2	-16.7	25.6	43.5	17.9
433.9	90.1	H	32.7	P	8.4	-16.8	24.4	43.5	19.1
433.9	83.7	H	30.5	P	7.0	-16.8	20.7	40.0	19.3
433.9	43.2	H	29.5	P	19.1	-17.5	31.1	40.0	8.9
433.9	37.3	V	31.7	P	15.6	-17.6	29.7	40.0	10.3
433.9	30.9	V	30.0	P	16.5	-17.8	28.7	40.0	11.3
433.9	35.0	V	27.3	Q	15.8	-17.7	25.4	40.0	14.6
433.9	75.5	V	35.8	P	7.2	-16.9	26.0	40.0	14.0
433.9	75.0	V	32.5	Q	7.2	-16.9	22.8	40.0	17.2
433.9	150.6	V	31.4	P	7.8	-16.1	23.1	43.5	20.4
433.9	167.3	V	30.2	P	11.6	-15.9	25.8	43.5	17.7
433.9	204.7	V	32.7	P	10.5	-15.7	27.5	43.5	16.0
433.9	210.0	V	31.3	P	10.9	-15.6	26.6	43.5	16.9
433.9	238.2	V	28.8	P	12.8	-15.4	26.2	46.0	19.8
433.9	288.6	V	29.8	P	12.9	-15.1	27.6	46.0	18.4
433.9	75.6	V	36.5	P	7.2	-16.9	26.8	40.0	13.2
433.9	75.2	V	37.4	P	7.2	-16.9	27.6	40.0	12.4
433.9	93.6	V	32.4	P	8.8	-16.7	24.5	43.5	19.0
433.9	127.2	V	33.1	P	10.4	-16.3	27.2	43.5	16.3
433.9	214.4	V	28.8	P	11.4	-15.6	24.6	43.5	18.9
433.9	209.2	V	32.2	P	10.9	-15.6	27.5	43.5	16.0
433.9	206.6	V	31.5	P	10.6	-15.7	26.4	43.5	17.1
433.9	74.0	H	31.8	P	6.6	-17.0	21.5	40.0	18.5
433.9	96.8	H	36.9	P	9.7	-16.7	30.0	43.5	13.5
433.9	134.0	H	32.1	P	10.0	-16.2	25.9	43.5	17.6

Figure 2. Drawing of Radiated Emissions Setup

10.2 Occupied Bandwidth Data

The occupied bandwidth of the RF output was measured using a spectrum analyzer. The bandwidth was measured using the peak detector function and a narrow resolution bandwidth.


A broadband antenna was used to receive the modulated signal. The spectrum analyzer was set to the MAX HOLD mode to record the worst case of the modulation. The spectrum analyzer display was digitized and plotted. A limit was drawn on the plots based on the level of the modulated carrier. The plots of the occupied bandwidth for the EUT are supplied on the following page.


Figure 3. Occupied Bandwidth Plot

The maximum 20 dB bandwidth allowed is 0.25% of 433.9 MHz = 1.08 MHz. The measured 20 dB bandwidth is 62 kHz.

Judgment: Passed.

The 20 dB bandwidth is show on the following two plots.






COMPANY : Dane Industries	ITEM : 100-224	DATE : 11-03-2005
CENTER 433.962 MHz	REF 5.0 dBm	SPAN 100 kHz
RES BW 10 kHz	VBW 30 kHz	ATTEN 20 dB
10 dB/	TIME : 16:27	SWP 30.0 msec
NOTES : Occupied Bandwidth,		

10.3 Transmitter Deactivation Delay

Since this is a manually activated transmitter, it must meet the following requirement from RSS-210 6.1.1 (a) (1) and FCC 15.231 (a) (1):

“A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.”

The following plot shows the time it takes for the transmitter to deactivate after the on switch is released.



The upper trace is the RF signal measured with a crystal detector. The crystal detector provides a negative output proportional to the RF signal. The lower trace is the DC level at the on switch. When the switch is at 5 VDC the transmitter is off.

As can be seen by the delta marker the deactivation delay is 60 mSeconds.

Judgment: Passed.