

POWER DENSITY ESTIMATIONS BASED ON POWER OUTPUT, ANTENNA GAIN, AND DISTANCE FROM ANTENNA

$$(P G) / (4 R^2 \pi) = S$$

where: $S =$ maximum power density (mW/cm ²)		transmitter operating variables:		must be blank if dB values are entered	
$P =$	power input to the antenna ----->>	=	25.17 (dBm) - or -		(mW)
$G =$	gain of the antenna - worst case ----->>	=	6.01 (dBi) - or -		(numeric gain)
$R =$	distance to the center of the radiation of the antenna -->>	=	20		(cm)

$(P \quad G)$	$/$	$(4 * R^2 * \pi)$	$=$	S	(mW/cm ²)
---------------	-----	-------------------	-----	-----	-----------------------

$(\frac{328.8516309}{(mw)} \quad \frac{3.99025}{(gain)})$	$/$	$(4 * \frac{20}{(cm)}^2 * \pi)$	$=$	S	(mW/cm ²)
---	-----	---------------------------------	-----	-----	-----------------------

(1312.199899)	$/$	$(4 * 400 * \pi)$	$=$	S	(mW/cm ²)
-----------------	-----	-------------------	-----	-----	-----------------------

(1312.199899)	$/$	(5026.548246)	$=$	0.261054	(mW/cm ²)
-----------------	-----	-----------------	-----	----------	-----------------------

