

TEST REPORT

FCC MPE Test for ADXV-R-33BTF
Certification

APPLICANT
ADRF KOREA, Inc.

REPORT NO.
HCT-RF-2512-FC005-R1

DATE OF ISSUE
January 30, 2026

Tested by
Jae hyeon Chu



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2512-FC005-R1

DATE OF ISSUE

January 30, 2026

Applicant	ADRF KOREA, Inc. 196-16 IYEO-RO BAEKSA-MYEON ICHEON-SI, GYEONGGI-DO, 17316, KOREA
Product Name	DAS
Model Name	ADXV-R-33BTF
FCC ID	N52-ADXV-R-33BTFP
Output Power	Downlink: 33 dBm, Uplink: -35 dBm
Date of Test	November 27, 2025 ~ December 09, 2025
Location of Test	☒ Permanent Testing Lab ☐ On Site Testing (Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)
Test Standard Used	CFR 47 Part 2.1091
Test Results	PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 09, 2025	Initial Release
1	January 30, 2026	Revised the FCC ID.

Notice

Content

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

RF Exposure Statement

1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures				
Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	#)(100)	30
1.34 - 30.....	824/f	2.19/f	#)(180/f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

= Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

[Uplink]

- BRS/EBS –

Max output Power at antenna input terminal	-34.50	dBm
Max output Power at antenna input terminal	0.00035	mW
Prediction distance	25.00	cm
Prediction frequency	2 500.00	MHz
Antenna Gain(typical)	5.30	dBi
Antenna Gain(numeric)	3.39	-
Power density at prediction frequency (S)	0.00000015	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²

[Downlink]

- BRS/EBS –

Max output Power at antenna input terminal	33.50	dBm
Max output Power at antenna input terminal	2 238.72	mW
Prediction distance	25.00	cm
Prediction frequency	2 496.00	MHz
Antenna Gain(typical)	5.30	dBi
Antenna Gain(numeric)	3.39	-
Power density at prediction frequency (S)	0.9659	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.0000	mW/cm ²