

TEST REPORT

BNNetzA-CAB-02/21-102

Test report no.: 1-9420/19-03-05

Testing laboratory

CTC advanced GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://www.ctcadvanced.com>

e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate starting with the registration number: D-PL-12076-01.

Applicant

Valeo Comfort and Driving Assistance S.A.S.

76 rue Auguste Perret - ZI Europarc

94046 CRETEIL CEDEX / FRANCE

Phone: +33 1 48 84 54 00

Contact: Jerome Hugot

e-mail: jerome.hugot@valeo.com

Phone: +33 1 48 84 57 14

Manufacturer

Valeo Comfort and Driving Assistance S.A.S.

76 rue Auguste Perret - ZI Europarc

94046 CRETEIL CEDEX / FRANCE

Test standard/s

FCC - Title 47 CFR Part 15 FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

RSS - 210 Issue 10 Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: Smart Hub (BRT, VRR)

Model name: BLXH1A

FCC ID: N5F-BLXH1

IC: 3248A-BLXH1

Frequency: DTS band 2400 MHz to 2483.5 MHz

Technology tested: Proprietary RF transmitter

Antenna: Integrated PCB and external FAKRA antennas

Power supply: 12 V DC by vehicle battery

Temperature range: -40°C to +85°C

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:



Michael Dorongovski
Lab Manager
Radio Communications

Test performed:



René Oelmann
Lab Manager
Radio Communications

1 Table of contents

1	Table of contents	2
2	General information	3
2.1	Notes and disclaimer	3
2.2	Application details	3
2.3	Test laboratories sub-contracted	3
3	Test standard/s, references and accreditations	4
4	Reporting statements of conformity – decision rule	5
5	Test environment	6
6	Test item	6
6.1	General description	6
6.2	Additional information	6
7	Description of the test setup.....	7
7.1	Shielded semi anechoic chamber	8
7.2	Shielded fully anechoic chamber.....	9
7.3	Radiated measurements > 18 GHz.....	10
7.4	Conducted measurements	11
8	Sequence of testing	12
8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	12
8.2	Sequence of testing radiated spurious 30 MHz to 1 GHz	13
8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz	14
8.4	Sequence of testing radiated spurious above 18 GHz	15
9	Measurement uncertainty	16
10	Summary of measurement results.....	17
11	Additional information and comments	18
12	Measurement results.....	19
12.1	Timing of the transmitter.....	19
12.2	Maximum carrier field strength	22
12.3	Occupied bandwidth – 99% emission bandwidth	24
12.4	Band edge compliance radiated	25
12.5	Spurious emissions radiated below 30 MHz.....	33
12.6	Spurious emissions radiated 30 MHz to 1 GHz	46
12.7	Spurious emissions radiated above 1 GHz	53
13	Observations	74
14	Glossary	75
15	Document history	76
16	Accreditation Certificate – D-PL-12076-01-04	76
17	Accreditation Certificate – D-PL-12076-01-05	77

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2020-07-22
Date of receipt of test item:	2020-09-15
Start of test:	2021-01-26
End of test:	2021-03-19
Person(s) present during the test:	-/-

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations

Test standard	Date	Description
FCC - Title 47 CFR Part 15	-/-	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
RSS - 210 Issue 10	December 2019	Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment
RSS - Gen Issue 5 incl. Amendment 1	March 2019	Spectrum Management and Telecommunications Radio Standards Specification - General Requirements for Compliance of Radio Apparatus

Guidance	Version	Description
ANSI C63.4-2014	-/-	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10-2013	-/-	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices


Accreditation	Description
D-PL-12076-01-04	Telecommunication and EMC Canada https://www.dakks.de/as/ast/d/D-PL-12076-01-04e.pdf
D-PL-12076-01-05	Telecommunication FCC requirements https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf



4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."



5 Test environment

Temperature :	T_{nom} T_{max} T_{min}	+24 °C during room temperature tests No tests under extreme temperature conditions required. No tests under extreme temperature conditions required.
Relative humidity content :		42 %
Barometric pressure :		1021 hpa
Power supply :	V_{nom} V_{max} V_{min}	12 V DC by vehicle battery / external power supply (RF tests) No tests under extreme voltage conditions required. No tests under extreme voltage conditions required.

6 Test item

6.1 General description

Kind of test item :	Smart Hub (BRT, VRR)	
Model name :	BLXH1A	
HMN :	-/-	
PMN :	BRT , VRR	
HVIN :	BLXH1A	
FVIN :	-/-	
S/N serial number :	Radiated unit: Conducted unit:	Rad. Ant 1/2/3 internal PCB A1: internal PCB A2: external FAKRA A3:
Hardware status :	B156717-01-C	
Software status :	V3.27	
Firmware status :	n/a	
Frequency band :	DTS band 2400 MHz to 2483.5 MHz	
Type of radio transmission :	Single unmodulated carrier, DSSS	
Use of frequency spectrum :		
Type of modulation :	GFSK, CW	
Number of channels :	75	
Antenna :	Integrated PCB and external FAKRA antennas	
Power supply :	12 V DC by vehicle battery	
Temperature range :	-40°C to +85°C	

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report:

1-9420/19-03-01_AnnexA
 1-9420/19-03-01_AnnexB
 1-9420/19-03-01_AnnexD

7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).


In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter; EMC32 software version: 10.59.00

$FS = UR + CL + AF$

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

$FS [dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \mu V/m)$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
2	A	Spectrum-Analyzer	FSU26	R&S	200809	300003874	k	09.12.2020	08.12.2021
3	A	Meßkabine 1	HF-Absorberhalle	MWB AG 300023		300000551	ne	-/-	-/-
4	A	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
5	A	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
6	A	Turntable Interface-Box	Model 105637	ETS-Lindgren	44583	300003747	izw	-/-	-/-
7	A	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck Mess - Elektronik	01029	300005379	vKI!	02.07.2019	01.07.2021
8	A	EMI Test Receiver	ESR3	Rohde & Schwarz	102587	300005771	k	10.12.2020	09.06.2022
9	A	DC Power Supply	HMP2020	Rohde & Schwarz	102850	300005517	vKI!	12.12.2019	11.12.2021

7.2 Shielded fully anechoic chamber



Measurement distance: horn antenna 3 meter; loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)


Example calculation:

FS [dBμV/m] = 40.0 [dBμV/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dBμV/m] (71.61 μV/m)

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A, B, C	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2818A03450	300001040	vKI!	09.12.2020	08.12.2023
2	B	Active Loop Antenna 9 kHz to 30 MHz	6502	EMCO	2210	300001015	vKI!	13.06.2019	12.06.2021
3	A, B, C	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev	-/-	-/-
4	A, C	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9709-5289	300000213	vKI!	14.07.2020	13.07.2022
5	A, B, C	Switch / Control Unit	3488A	HP	*	300000199	ne	-/-	-/-
6	A	Band Reject filter	WRCG2400/2483-2375/2505-50/10SS	Wainwright	11	300003351	ev	-/-	-/-
7	A, B, C	EMI Test Receiver 20Hz- 26,5GHz	ESU26	R&S	100037	300003555	k	09.12.2020	08.12.2021
8	A	Highpass Filter	WHK1.1/15G-10SS	Wainwright	3	300003255	ev	-/-	-/-
9	A	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	19	300003790	ne	-/-	-/-
10	A	Broadband Amplifier 0.5-18 GHz	CBLU5184540	CERNEX	22049	300004481	ev	-/-	-/-
11	A, B, C	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000037	300004509	ne	-/-	-/-
12	A, B, C	NEXIO EMV-Software	BAT EMC V3.20.06	EMCO	-/-	300004682	ne	-/-	-/-
13	A, B, C	PC	ExOne	F+W	-/-	300004703	ne	-/-	-/-
14	A	RF-Amplifier	AMF-6F06001800-30-10P-R	NARDA-MITEQ Inc	2011572	300005241	ev	-/-	-/-

7.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)

Example calculation:


FS [dB μ V/m] = 40.0 [dB μ V/m] + (-60.1) [dB] + 36.74 [dB/m] = 16.64 [dB μ V/m] (6.79 μ V/m)

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP	00419	300002268	ev	-/-	-/-
2	A	Std. Gain Horn Antenna 18.0-26.5 GHz	638	Narda	01096	300000486	vIKI!	21.01.2020	20.01.2022
3	A	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	07.12.2020	06.12.2021
4	A	RF-Cable	ST18/SMAM/SMAM/48	Huber & Suhner	Batch no. 600918	400001182	ev	-/-	-/-
5	A	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-
6	A	DC Power Supply	HMP2020	Rohde & Schwarz	102850	300005517	vIKI!	12.12.2019	11.12.2021

7.4 Conducted measurements

Conducted measurements normal conditions



$$OP = AV + CA$$

(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

$$OP \text{ [dBm]} = 6.0 \text{ [dBm]} + 11.7 \text{ [dB]} = 17.7 \text{ [dBm]} \text{ (58.88 mW)}$$

Equipment table:

No.	Lab / Item	Equipment	Type	Manufacturer	Serial No.	INV. No.	Kind of Calibration	Last Calibration	Next Calibration
1	A	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	07.12.2020	06.12.2021
2	A	DC-Blocker 0.1-40 GHz	8141A	Inmet	-/-	400001185	ev	-/-	-/-
3	A	Hygro-Thermometer	-/-, 5-45°C, 20-100%rF	Thies Clima	-/-	400000108	ev	13.08.2020	12.08.2022
4	A	PC Tester R005	Intel Core i3 3220/3,3 GHz, Prozessor	-/-	2V2403033A4523	300004589	ne	-/-	-/-
5	A	RF-Cable	ST18/SMAm/SMAm /60	Huber & Suhner	Batch no. 606844	400001181	ev	-/-	-/-
6	A	Coax Attenuator 10 dB 2W 0-40 GHz	MCL BW-K10-2W44+	Mini Circuits	-/-	400001186	ev	-/-	-/-
7	A	Synchron Power Meter	SPM-4	CTC	1	300005580	ev	-/-	-/-
8	A	DC Power Supply	HMP2020	Rohde & Schwarz	102850	300005517	vIKI!	12.12.2019	11.12.2021
9	A	Tester Software RadioStar (C.BER2 for BT Conformance)	Version 1.0.0.X	CTC advanced GmbH	0001	400001380	ne	-/-	-/-

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

*Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

- The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

Final measurement

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.

9 Measurement uncertainty

Measurement uncertainty	
Test case	Uncertainty
Antenna gain	± 3 dB
Spectrum bandwidth	± 21.5 kHz absolute; ± 15.0 kHz relative
Maximum field strength	± 3 dB
Band edge compliance radiated	± 3 dB
Spurious emissions radiated below 30 MHz	± 3 dB
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB
Spurious emissions radiated above 12.75 GHz	± 4.5 dB
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB

10 Summary of measurement results

☒	No deviations from the technical specifications were ascertained
☐	There were deviations from the technical specifications ascertained
☐	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15 RSS 210, Issue 10	See table!	2021-03-24	-/-

Test specification clause	Test case	Guideline	Temperature & voltage conditions	Mode	C	NC	NA	NP	Remark
§ 15.35 RSS GEN	Timing of the transmitter	-/-	Nominal	TX modulated	-/-				-/-
§15.249 RSS 210	Maximum field strength	-/-	Nominal	TX modulated and CW	☒	☐	☐	☐	-/-
RSS Gen	OBW – 99% emission bandwidth	-/-	Nominal	TX modulated and CW	-/-				-/-
§15.249 RSS 210	Band edge compliance radiated	-/-	Nominal	TX modulated and CW	☒	☐	☐	☐	-/-
§15.249 RSS 210	Spurious emissions radiated below 30 MHz	-/-	Nominal	TX modulated and CW	☒	☐	☐	☐	-/-
§15.249 RSS 210	Spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	TX modulated and CW	☒	☐	☐	☐	-/-
§15.249 RSS 210	Spurious emissions radiated above 1 GHz	-/-	Nominal	TX modulated and CW	☒	☐	☐	☐	-/-
§15.107 §15.207 RSS-Gen	Spurious emissions conducted below 30 MHz (AC conducted)	-/-	Nominal	-/-	☐	☐	☒	☐	-/-

Note: C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed

11 Additional information and comments

Reference documents: CCC-CAR_Mc LAREN 【P16】 PEPS (BLR)_ RfQ (Compliance)

1-9420/19-03-05_log1_conducted.pdf

Special test descriptions: None

Configuration descriptions: None

Test mode: ☒ EUT is transmitting pseudo random data by itself

EUT selection: ☐ Only one device available

☒ Devices selected by the customer

☐ Devices selected by the laboratory (Randomly)

Antennas and transmit
operating modes:

☒ Operating mode 1 (single antenna)

- Equipment with 1 antenna,
- Equipment with 2 diversity antennas operating in switched diversity mode by which at any moment in time only 1 antenna is used,
- Smart antenna system with 2 or more transmit/receive chains, but operating in a mode where only 1 transmit/receive chain is used)

☐ Operating mode 2 (multiple antennas, no beamforming)

- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously but without beamforming.

☐ Operating mode 3 (multiple antennas, with beamforming)

- Equipment operating in this mode contains a smart antenna system using two or more transmit/receive chains simultaneously with beamforming.
In addition to the antenna assembly gain (G), the beamforming gain (Y) may have to be taken into account when performing the measurements.

12 Measurement results

12.1 Timing of the transmitter

Description:

Measurement of the transmitter timing behavior for duty cycle correction.


Measurement parameter	
Detector	Peak
Sweep time	See plot
Resolution bandwidth	See plot
Video bandwidth	See plot
Span	Zero
Trace mode	Single
Test setup	See sub clause 7.4 A
Measurement uncertainty	See sub clause 9

Limits:


FCC	IC
Timing of the transmitter	
(c) Unless otherwise specified, e.g. Section 15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.	

Result:

Plot 1:



6 emissions @ 100 ms

Plot 2:Tx_{on} 164 μs

6 x 164 μs @ 100 ms = 984 μs

DC Correction factor: $20 \log(0.00984) = -40.14 \text{ dB}$

The timing is similar to the transmitter KEY FOB (KFML1), tested in test report 1-9420_19-01-05.
 The plots and the calculation are representative for both devices.

12.2 Maximum carrier field strength

Description:

Measurement of the carrier field strength @ 3-meter distance with peak and average detector.

Measurement parameters	
Detector	Peak / AVG (RMS or duty cycle correction)
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	10 MHz
Span	5 MHz
Trace mode	Max hold
Test setup	See sub clause 7.2 C
Measurement uncertainty	See sub clause 9

Limits:

FCC	IC
The field strength of emissions of intentional radiators shall comply with the following: Field strength of fundamental: 50 mV/m / (94 dBµV/m) @ 3 m (AVG) 500 mV/m / (114 dBµV/m) @ 3 m (Peak)	

Results: internal PCB A1

Field strength @ 3 meter	Frequency		
	Lowest channel	Middle channel	Highest channel
Peak (GFSK / CW)	97.2 / 100.9	96.6 / 100.0	95.8 / 100.5
AVG (GFSK / CW) (corrected with duty cycle correction factor from chapter 12.1)	57.1 / 60.8	56.5 / 59.9	55.7 / 60.4

Results: internal PCB A2

Field strength @ 3 meter	Frequency		
	Lowest channel	Middle channel	Highest channel
Peak (GFSK / CW)	98.1 / 101.9	96.2 / 100.8	96.7 / 101.2
AVG (GFSK / CW) (corrected with duty cycle correction factor from chapter 12.1)	58.0 / 61.8	56.1 / 60.7	56.6 / 61.1

Results: external FAKRA A3

Field strength @ 3 meter	Frequency		
	Lowest channel	Middle channel	Highest channel
Peak (GFSK / CW)	100.3 / 103.9	99.9 / 104.8	99.1 / 103.4
AVG (GFSK / CW) (corrected with duty cycle correction factor from chapter 12.1)	60.2 / 63.8	59.8 / 64.7	59.0 / 63.3

12.3 Occupied bandwidth – 99% emission bandwidth

Description:

Measurement of the 99% bandwidth of the modulated signal acc. RSS-GEN.

Measurement parameter	
Reference document:	1-9420/19-03-05_log1_conducted.pdf
Test setup	See sub clause 7.4 A
Measurement uncertainty	See sub clause 9

Usage:

-/-	IC
Occupied bandwidth – 99% emission bandwidth	
OBW is necessary for emission designator	

Results:

	Frequency		
	Lowest channel	Middle channel	Highest channel
99% bandwidth (kHz) - GFSK	1041	1041	1041
99% bandwidth (kHz) - CW	78	78	79

12.4 Band edge compliance radiated

Description:

Measurement of the radiated band edge compliance.

Measurement parameters	
Detector	Peak / RMS
Sweep time	Auto
Resolution bandwidth	1 MHz
Video bandwidth	3 MHz
Span	Lower Band: 2310 – 2405 MHz higher Band: 2478 – 2500 MHz
Trace mode	Max hold
Test setup	See sub clause 7.2 C
Measurement uncertainty	See sub clause 9

Limits:

FCC	IC
Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209 / RSS GEN, whichever is the lesser attenuation.	
54 dBµV/m AVG 74 dBµV/m Peak	

Result: internal PCB A1



Scenario	Band edge compliance radiated [dBµV/m]
Lower restricted band (GFSK)	32.3 dBµV/m AVG 43.6 dBµV/m Peak
Upper restricted band (GFSK)	47.7 dBµV/m AVG 64.2 dBµV/m Peak
Lower restricted band (CW)	32.4 dBµV/m AVG 43.8 dBµV/m Peak
Upper restricted band (CW)	47.1 dBµV/m AVG 50.4 dBµV/m Peak

Result: internal PCB A2


Scenario	Band edge compliance radiated [dBµV/m]
Lower restricted band (GFSK)	32.4 dBµV/m AVG 43.4 dBµV/m Peak
Upper restricted band (GFSK)	49.0 dBµV/m AVG 66.2 dBµV/m Peak
Lower restricted band (CW)	32.4 dBµV/m AVG 43.6 dBµV/m Peak
Upper restricted band (CW)	48.1 dBµV/m AVG 51.3 dBµV/m Peak

Result: external FAKRA A3


Scenario	Band edge compliance radiated [dBµV/m]
Lower restricted band (GFSK)	32.6 dBµV/m AVG 43.5 dBµV/m Peak
Upper restricted band (GFSK)	50.0 dBµV/m AVG 59.3 dBµV/m Peak
Lower restricted band (CW)	32.6 dBµV/m AVG 43.6 dBµV/m Peak
Upper restricted band (CW)	49.3 dBµV/m AVG 52.3 dBµV/m Peak



Plots: internal PCB A1**Plot 1:** Lower restricted band, GFSK**Plot 2:** Upper restricted band, GFSK

Plot 3: Lower restricted band, CW




Plot 4: Upper restricted band, CW




Plots: internal PCB A2**Plot 1:** Lower restricted band, GFSK**Plot 2:** Upper restricted band, GFSK

Plot 3: Lower restricted band, CW




Plot 4: Upper restricted band, CW




Plots: external FAKRA A3


Plot 1: Lower restricted band, GFSK




Plot 2: Upper restricted band, GFSK



Plot 3: Lower restricted band, CW



Plot 4: Upper restricted band, CW



12.5 Spurious emissions radiated below 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The limits are recalculated to a measurement distance of 3 m according the ANSI C63.10.

Measurement parameters	
Detector	Peak / Quasi peak
Sweep time	Auto
Resolution bandwidth	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Video bandwidth	F < 150 kHz: 1 kHz F > 150 kHz: 30 kHz
Span	9 kHz to 30 MHz
Trace mode	Max hold
Test setup	See sub clause 7.2 B
Measurement uncertainty	See sub clause 9

Limits:


FCC		IC
TX spurious emissions radiated below 30 MHz		
Frequency (MHz)	Field strength (dB μ V/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Results:


TX spurious emissions radiated below 30 MHz [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
All detected emissions are more than 20 dB below the limit.		

Plots: internal PCB A1


Plot 1: 9 kHz to 30 MHz, low channel, GFSK



Plot 2: 9 kHz to 30 MHz, mid channel, GFSK




Plot 3: 9 kHz to 30 MHz, high channel, GFSK




Plots: internal PCB A2


Plot 1: 9 kHz to 30 MHz, low channel, GFSK



Plot 2: 9 kHz to 30 MHz, mid channel, GFSK




Plot 3: 9 kHz to 30 MHz, high channel, GFSK




Plots: external FAKRA A3


Plot 1: 9 kHz to 30 MHz, low channel, GFSK



Plot 2: 9 kHz to 30 MHz, mid channel, GFSK




Plot 3: 9 kHz to 30 MHz, high channel, GFSK




Plots: internal PCB A1


Plot 1: 9 kHz to 30 MHz, low channel, CW



Plot 2: 9 kHz to 30 MHz, mid channel, CW




Plot 3: 9 kHz to 30 MHz, high channel, CW




Plots: internal PCB A2


Plot 1: 9 kHz to 30 MHz, low channel, CW



Plot 2: 9 kHz to 30 MHz, mid channel, CW




Plot 3: 9 kHz to 30 MHz, high channel, CW




Plots: external FAKRA A3


Plot 1: 9 kHz to 30 MHz, low channel, CW



Plot 2: 9 kHz to 30 MHz, mid channel, CW



Plot 3: 9 kHz to 30 MHz, high channel, CW



12.6 Spurious emissions radiated 30 MHz to 1 GHz

Description:

Measurement of the radiated spurious emissions in transmit mode. The measurement is performed at lowest, middle and highest channel.

Measurement parameters	
Detector	Peak / Quasi Peak
Sweep time	Auto
Resolution bandwidth	120 kHz
Video bandwidth	3 x RBW
Span	30 MHz to 1 GHz
Trace mode	Max hold
Test setup	See sub clause 7.1 A
Measurement uncertainty	See sub clause 9

Limits:


FCC		IC
TX spurious emissions radiated		
Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209 / RSS GEN, whichever is the lesser attenuation.		
§15.209		
Frequency (MHz)	Field strength (dBμV/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10

NOTE: The plots are representative for all modes with all antennas and channels.

Results: internal PCB A1


Plots: Transmit mode, GFSK

Plot 1: 30 MHz to 1 GHz, low channel, vertical & horizontal polarization




Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
37.940	17.34	30.0	12.7	1000	120.0	122.0	H	265	13
55.895	16.64	30.0	13.4	1000	120.0	170.0	V	157	15
64.002	16.95	30.0	13.1	1000	120.0	110.0	V	247	12
510.034	22.21	36.0	13.8	1000	120.0	170.0	H	112	18
734.844	20.24	36.0	15.8	1000	120.0	170.0	V	247	22
943.724	28.45	36.0	7.6	1000	120.0	170.0	H	93	24

Plot 2: 30 MHz to 1 GHz, mid channel, vertical & horizontal polarization**Final results:**


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.041	17.95	30.0	12.1	1000	120.0	162.0	V	22	14
56.186	16.65	30.0	13.4	1000	120.0	105.0	V	186	15
63.993	17.22	30.0	12.8	1000	120.0	102.0	V	112	12
494.655	21.92	36.0	14.1	1000	120.0	166.0	H	67	18
734.393	25.17	36.0	10.8	1000	120.0	141.0	H	157	22
911.938	28.19	36.0	7.8	1000	120.0	170.0	V	67	24

Plot 3: 30 MHz to 1 GHz, high channel, vertical & horizontal polarization**Final results:**

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
38.204	12.40	30.0	17.6	1000	120.0	166.0	V	292	13
51.217	10.90	30.0	19.1	1000	120.0	170.0	H	-6	14
63.992	17.53	30.0	12.5	1000	120.0	119.0	V	-22	12
505.741	17.21	36.0	18.8	1000	120.0	170.0	H	202	18
732.878	25.04	36.0	11.0	1000	120.0	170.0	H	247	22
892.808	28.00	36.0	8.0	1000	120.0	163.0	V	247	24

Plots: Transmit mode, CW

Plot 1: 30 MHz to 1 GHz, mid channel, vertical & horizontal polarization




Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
42.161	13.05	30.0	17.0	1000	120.0	170.0	V	202	14
56.368	16.59	30.0	13.4	1000	120.0	122.0	V	247	15
64.002	16.93	30.0	13.1	1000	120.0	104.0	V	-22	12
99.514	16.80	33.5	16.7	1000	120.0	170.0	V	196	12
763.607	21.23	36.0	14.8	1000	120.0	163.0	V	249	22
938.721	28.52	36.0	7.5	1000	120.0	108.0	V	-22	24

Results: internal PCB A2

Plots: Transmit mode, GFSK

Plot 1: 30 MHz to 1 GHz, mid channel, vertical & horizontal polarization




Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
40.827	17.75	30.0	12.3	1000	120.0	170.0	H	247	14
56.421	11.71	30.0	18.3	1000	120.0	127.0	H	247	15
63.996	14.97	30.0	15.0	1000	120.0	116.0	V	67	12
514.813	22.38	36.0	13.6	1000	120.0	152.0	V	67	19
723.155	26.03	36.0	10.0	1000	120.0	170.0	V	157	21
884.023	27.98	36.0	8.0	1000	120.0	170.0	V	22	23

Results: external FAKRA A3

Plots: Transmit mode, GFSK

Plot 1: 30 MHz to 1 GHz, mid channel, vertical & horizontal polarization



Final results:

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
41.658	13.01	30.0	17.0	1000	120.0	123.0	V	-15	14
51.576	15.77	30.0	14.2	1000	120.0	170.0	H	112	14
63.993	20.43	30.0	9.6	1000	120.0	104.0	V	-22	12
344.809	19.00	36.0	17.0	1000	120.0	170.0	H	67	16
735.075	25.32	36.0	10.7	1000	120.0	170.0	H	-22	22
909.851	28.14	36.0	7.9	1000	120.0	170.0	V	202	24

12.7 Spurious emissions radiated above 1 GHz

Description:

Measurement of the radiated spurious emissions in transmit mode.

Measurement parameters	
Detector	Peak / RMS
Sweep time	Auto
Resolution bandwidth	1 MHz
Video bandwidth	3 x RBW
Span	1 GHz to 26 GHz
Trace mode	Max hold
Measured modulation	GFSK/CW
Test setup	See sub clause 7.2 A (1 GHz - 18 GHz) See sub clause 7.3 A (18 GHz - 26 GHz)
Measurement uncertainty	See sub clause 9

Limits:

FCC		IC
TX spurious emissions radiated		
Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209 / RSS GEN, whichever is the lesser attenuation.		
§15.209		
Frequency (MHz)	Field strength (dBµV/m)	Measurement distance
Above 960	54.0 (Average)	3
Above 960	74.0 (Peak)	3

Results: internal PCB A1**Results:** GFSK

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	-/-	Peak	-/-	-/-	Peak	-/-
	AVG	-/-		AVG	-/-		AVG	-/-

Results: CW

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	7319	Peak	49.1	7440	Peak	49.5
	AVG	-/-		AVG	41.4		AVG	42.7

Results: internal PCB A2**Results:** GFSK

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	7319	Peak	49.8	-/-	Peak	-/-
	AVG	-/-		AVG	39.3		AVG	-/-

Results: CW

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	7320	Peak	50.1	7440	Peak	49.6
	AVG	-/-		AVG	43.1		AVG	42.6

Results: external FAKRA A3

Results: GFSK

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	7319	Peak	51.4	7440	Peak	52.7
	AVG	-/-		AVG	42.9		AVG	45.6


Results: CW

TX spurious emissions radiated [dBµV/m]								
Lowest channel			Middle channel			Highest channel		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
-/-	Peak	-/-	7319	Peak	52.1	7440	Peak	52.7
	AVG	-/-		AVG	47.1		AVG	48.7

Results: internal PCB A1


Plots: Transmitter mode, GFSK


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, GFSK




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, GFSK




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, GFSK


Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, GFSK


Plots: Transmitter mode, CW


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, CW




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, CW




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, CW

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, CW

Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, CW


The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, CW

Results: internal PCB A2


Plots: Transmitter mode, GFSK


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, GFSK




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, GFSK




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, GFSK


Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, GFSK


Plots: Transmitter mode, CW


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, CW




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, CW




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, CW

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, CW

Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, CW


The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, CW

Results: external FAKRA A3


Plots: Transmitter mode, GFSK


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, GFSK




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, GFSK




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, GFSK


Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, GFSK

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, GFSK


Plots: Transmitter mode, CW


Plot 1: 1 GHz to 18 GHz, lowest channel, vertical & horizontal polarization, CW




The carrier signal is notched with a 2.4 GHz band rejection filter.


Plot 2: 18 GHz to 26 GHz, lowest channel, vertical & horizontal polarization, CW




Plot 3: 1 GHz to 18 GHz, mid channel, vertical & horizontal polarization, CW

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: 18 GHz to 26 GHz, mid channel, vertical & horizontal polarization, CW

Plot 5: 1 GHz to 18 GHz, high channel, vertical & horizontal polarization, CW

The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 6: 18 GHz to 26 GHz, high channel, vertical & horizontal polarization, CW

13 Observations

No observations except those reported with the single test cases have been made.


14 Glossary

EUT	Equipment under test
DUT	Device under test
UUT	Unit under test
GUE	GNSS User Equipment
ETSI	European Telecommunications Standards Institute
EN	European Standard
FCC	Federal Communications Commission
FCC ID	Company Identifier at FCC
IC	Industry Canada
PMN	Product marketing name
HMN	Host marketing name
HVIN	Hardware version identification number
FVIN	Firmware version identification number
EMC	Electromagnetic Compatibility
HW	Hardware
SW	Software
Inv. No.	Inventory number
S/N or SN	Serial number
C	Compliant
NC	Not compliant
NA	Not applicable
NP	Not performed
PP	Positive peak
QP	Quasi peak
AVG	Average
OC	Operating channel
OCW	Operating channel bandwidth
OBW	Occupied bandwidth
OOB	Out of band
DFS	Dynamic frequency selection
CAC	Channel availability check
OP	Occupancy period
NOP	Non occupancy period
DC	Duty cycle
PER	Packet error rate
CW	Clean wave
MC	Modulated carrier
WLAN	Wireless local area network
RLAN	Radio local area network
DSSS	Dynamic sequence spread spectrum
OFDM	Orthogonal frequency division multiplexing
FHSS	Frequency hopping spread spectrum
GNSS	Global Navigation Satellite System
C/N₀	Carrier to noise-density ratio, expressed in dB-Hz

15 Document history

Version	Applied changes	Date of release
-/-	Initial release	2021-03-24

16 Accreditation Certificate – D-PL-12076-01-04

first page	last page
 Deutsche Akkreditierungsstelle GmbH Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition Accreditation  The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (TC) and Electromagnetic Compatibility (EMC) for Canadian Standards The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 07 pages. Registration number of the certificate: D-PL-12076-01-04 Frankfurt am Main, 09.06.2020 by order:  Dr. Ing. (FH) Ralf Eigner Head of Division The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks See notes certified.	Deutsche Akkreditierungsstelle GmbH Office Berlin Spittelmarkt 10 10117 Berlin Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main Office Braunschweig Bundesallee 100 38116 Braunschweig The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkKS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf. No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkKS. The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkKS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations. The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkKS or may be received by CTC advanced GmbH on request

<https://www.dakks.de/as/ast/d/D-PL-12076-01-04e.pdf>

17 Accreditation Certificate – D-PL-12076-01-05

first page	last page
 Deutsche Akkreditierungsstelle GmbH Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition Accreditation  The Deutsche Akkreditierungsstelle GmbH attests that the testing laboratory CTC advanced GmbH Untertürkheimer Straße 6-10, 66117 Saarbrücken is competent under the terms of DIN EN ISO/IEC 17025:2018 to carry out tests in the following fields: Telecommunication (FCC Requirements) The accreditation certificate shall only apply in connection with the notice of accreditation of 09.06.2020 with the accreditation number D-PL-12076-01. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 05 pages. Registration number of the certificate: D-PL-12076-01-05 Frankfurt am Main, 09.06.2020 by order: Dipl.-Ing. (FH) Galf Egnier Head of Division The certificate together with its annex reflects the status at the time of the date of issue. The current status of the scope of accreditation can be found in the database of accredited bodies of Deutsche Akkreditierungsstelle GmbH. https://www.dakks.de/en/content/accredited-bodies-dakks See notes essential!	Deutsche Akkreditierungsstelle GmbH Office Berlin Spittelmarkt 10 10117 Berlin Office Frankfurt am Main Europa-Allee 52 60327 Frankfurt am Main Office Braunschweig Bundesallee 100 38116 Braunschweig The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkkS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf. No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkkS. The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products (Official Journal of the European Union L 218 of 9 July 2008, p. 30). DAkkS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations. The up-to-date state of membership can be retrieved from the following websites: EA: www.european-accreditation.org ILAC: www.ilac.org IAF: www.iaf.nu

Note: The current certificate annex is published on the website (link see below) of the Accreditation Body DAkkS or may be received by CTC advanced GmbH on request

<https://www.dakks.de/as/ast/d/D-PL-12076-01-05e.pdf>

END OF TEST REPORT