

January 31, 2024

FCC ID: N6C-SDMAH

To whom it may concern,

We, UL Japan, Inc, hereby declare that Embedded Wireless Module, model: SX-SDMAH (FCC ID: N6C-SDMAH) of Silex Technology, Inc is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances d (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

The SAR evaluation exemption threshold is calculated as below.

[SX-SDMAH]

900MHz Band

P_{th} (mW)	1890.1
f (GHz)	0.9265
$ERP_{20 \text{ cm}}$ (mW)	1890.1
d (cm)	20.0

Conducted Power	(dBm)	26.50
	(mW)	446.68
Antenna Gain	(dBi)	3.40
EIRP	(dBm)	29.90
	(dBm)	27.76
	(mW)	597.04

The Maximum time-averaged power or ERP whichever greater is 597.1 mW.
(Rounded up to two decimals place)

[SX-SDMAX]**[WLAN 2.4 GHz band part]**

<i>P_{th}</i> (mW)	3060
<i>f</i> (GHz)	2.462
<i>ERP</i> _{20 cm} (mW)	3060
<i>d</i> (cm)	20.0

Conducted Power *1)	(dBm)	18.50
	(mW)	70.79
Antenna Gain (dBi)		3.18
EIRP (dBm)		21.68
ERP	(dBm)	19.54
	(mW)	89.95

The Maximum time-averaged power or ERP whichever greater is 90 mW.
(Rounded up to two decimals place)

[Bluetooth (BR / EDR / LE) part]

<i>P_{th}</i> (mW)	3060
<i>f</i> (GHz)	2.48
<i>ERP</i> _{20 cm} (mW)	3060
<i>d</i> (cm)	20.0

Conducted Power *1)	(dBm)	6.50
	(mW)	4.47
Antenna Gain (dBi)		3.18
EIRP (dBm)		9.68
ERP	(dBm)	7.54
	(mW)	5.68

The Maximum time-averaged power or ERP whichever greater is 5.7 mW.
(Rounded up to two decimals place)

[WLAN 5 GHz band part]

<i>P_{th}</i> (mW)	3060
<i>f</i> (GHz)	5.825
<i>ERP</i> _{20 cm} (mW)	3060
<i>d</i> (cm)	20.0

Conducted Power *1)	(dBm)	16.50
	(mW)	44.67
Antenna Gain (dBi)		4.25
EIRP (dBm)		20.75
ERP	(dBm)	18.61
	(mW)	72.61

The Maximum time-averaged power or ERP whichever greater is 72.7 mW.
(Rounded up to two decimals place)

*1) The refereced conducted power is the maximum output power that the device can output by specification of SX-SDMAX (FCC ID: N6C-SDMAX).

Transmitters used in mobile exposure conditions for simultaneous transmission operations according to KDB447498 D04.

Value is calculated using the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(ii)(B).

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^a \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

[SDMAH: 900MHz Band and SDMAH: WLAN 2.4 GHz]

$$597.1 / 1890.1 + 90.0 / 3060 = 0.3159 + 0.0294 = 0.3453 < 1$$

[SDMAH: 900MHz Band, SDMAH: Bluetooth (BR/EDR/LE) and WLAN 5 GHz]

$$597.1 / 1890.1 + 5.7 / 3060 + 72.7 / 3060 = 0.3159 + 0.0019 + 0.0238 = 0.3416 < 1$$

Thank you for your attention to this matter.



Satofumi Matsuyama
Engineer