



The Hong Kong Standards and Testing Centre Ltd.

TEST REPORT

Date: 1998-08-31

Page 1 of 7

No.: KM0041/504

APPLICANT: (CODE : 021789)

QUICKSHOT LTD.

Unit 7, 7/F, Blk B, Hoplite Industrial Centre, 3-5 Wang Tai Road, Kowloon Bay, Kowloon.

DATE OF SAMPLES RECEIVED: 1998.08.21.

DATE OF TESTING: 1998.08.27. & 1998.08.28.

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: Speaker System

Manufacturer: Quickshot Ltd

Model Number: QS7900

Brand Name: Quickshot

Rating: 120V a.c. 0.429A 51.5W 60Hz

Origin: China

The AC/AC adaptor used for the tests was supplied by the applicant, the details of adaptor as follows:

GS AC power adaptor

Model Number: GS - 143000 adaptor.

Input: 120V AC 60Hz Output: 14V AC 3A

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part B - Unintentional Radiators. The results obtained are to compare with the class B digital device limit.

RESULTS: Please see attached sheet(s).

REMARK: This product was tested as a system using the Ancillary Equipment listed in Appendix B.

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have **COMPLIED** with the requirement for the relevant clauses of Federal Communications Commission Rules for Class B digital device.

TEST EQUIPMENT AUDIT: Please see Appendix A

Testing Engineer

Verify by

Patrick Wong
for Managing Director

Guidance on Use of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced without its authority or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it to a third party, provided that the Hong Kong Standards and Testing Centre Ltd. is notified in writing. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report.
2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report.
3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to accept any other remedies which may be appropriate.
4. Samples submitted for tests are accepted on the understanding that the Report issued does not form the basis of, or the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd.
5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage whatsoever arising from the use of information contained in any of its Reports or in any communication.



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31

TEST REPORT

Page 2 of 7

No.: KM0041/504

TEST SUMMARY

(A) Measurement of Radiated Emission

Result -- Satisfactory

Data -- See the attached data

(B) Measurement of Line-Conducted Voltage Test

Result -- Satisfactory

Data -- See the attached data



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31
No.: KM0041/504

TEST REPORT

Page 3 of 7

(A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B Section 15.109(a)
(Class B)

TEST CONDITION : Normal

TEST DATE : 1998.08.31.

Emission Frequency	Meter Reading	Polarization (including antenna factor)	Field Strength (at 3m)	FCC Limit
MHz	dB(μ V)		μ V/m	μ V/m
48.201	22.8	V	13.8	100
48.203	26.1	H	20.2	100
112.777	20.0	H	10.0	150
112.786	18.8	V	8.7	150

- End -

SUMMARY

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured.
polarizations at highest reading indicated as:
H -- Horizontal V -- Vertical



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31

TEST REPORT

Page 4 of 7

No.: KM0041/504

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane in compliance with the requirements of ANSI C63.4:1992.

(2) Test Equipment

HP 8572A EMI receiver was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100KHz or 1MHz depending on the type of signal. A biconical log-periodic antenna was used for frequency range from 30MHz to 1000MHz.

(3) Test Set-Up:

The EUT and support equipment are placed in accordance with ANSI C63.4.

(4) Measuring Procedure:

An initial pre-scan measurement was performed in a semi-anechoic chamber using a 25dB gain pre-amplifier. The receive antenna in the chamber was 1.5m above the groundplane and 3m from the sample. The sample was placed 0.8m above the groundplane. Measurements in both horizontal and vertical polarities were performed. All emissions recorded during the prescan were subsequently remeasured on the open field test site (described in 1 above) using the following procedure: The ambient noise scanning was made before powering on the EUT and support equipment to identify the emissions from the environment. During the test, each emission was maximized by: having the EUT continuously working, arranging, rotating turntable and manipulating interconnecting cables, rotating turntable and varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The frequency range tested is from 30MHz to 1000MHz and the worst-case emissions are shown in Test Results.

(5) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 200MHz = $\pm 3.7\text{dB}$, 200MHz to 1000MHz = $+ 3.0\text{dB}/-2.7\text{dB}$.



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31
No.: KM0041/504

TEST REPORT

Page 5 of 7

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)

TEST CONDITION : Normal

TEST DATE : 1998.08.27

(1) Between "Live" and "Ground"

Frequency	Range of Emission		Maximum Measured Radio Noise		FCC Limit (Class B)
	MHz		dB(μ V)	μ V	μ V
0.45	-	0.8	0.00	1.00	250.00
0.8	-	1.6	0.00	1.00	250.00
1.6	-	3.0	0.00	1.00	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	16.32	6.55	250.00
9.0	-	11.0	< 19.51	9.45	250.00
11.0	-	13.0	16.52	6.70	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	28.37	26.21	250.00
19.0	-	21.0	24.51	16.81	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

SUMMARY

All data is within limits



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31
No.: KM0041/504

TEST REPORT

Page 6 of 7

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)

TEST CONDITION : Normal

TEST DATE : 1998.08.27.

(1) Between "Neutral" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
MHz			dB(μV)	μV	μV
0.45	-	0.8	0.00	1.00	250.00
0.8	-	1.6	0.00	1.00	250.00
1.6	-	3.0	0.00	1.00	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	18.28	8.20	250.00
9.0	-	11.0	19.51	9.45	250.00
11.0	-	13.0	18.71	8.62	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	26.86	22.03	250.00
19.0	-	21.0	23.14	14.35	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

----- SUMMARY -----

All data is within limits



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31
No.: KM0041/504

TEST REPORT

Page 7 of 7

NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

(1) LISN (Line Impedance Stabilization Network) used :

50 μ H LISN in accordance with Section of ANSI C63.4:1992.

(2) Measurement Instrumentations:

CISPR quasi-peak type radio noise meter (9 KHz - 30 MHz), 6 dB bandwidth set at 9 KHz for measurement between 150 KHz & 30MHz.

(3) Frequency range scanned :

The frequency range from 450 KHz to 30 MHz had been searched. Reading of the highest emissions relating to the limit were reported as above.

(4) Configuration of EUT

Connection of equipment and operation conditions were same as those in the Radiation measurement.

(5) Measurement procedure :

In accordance with the relevant sections of ANSI C63.4:1992 "FCC Methods of measurement of Radio Noise Emissions from Computing Devices".

(6) Measuring Uncertainty:

The calculated uncertainty for conducted power-line measurement is = ± 2.3 dB.

**** End of document ****



The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-08-31
No.: KM0041/504

APPENDIX A

Page A1 of A1

TEST EQUIPMENT AUDIT

Pre-scan

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM001	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	27/10/97
EM006	ANTENNA	ARA INC	LPB-2513 A	1047	05/08/98
EM004	PREAMPLIFIER	HP	8447F OP1 1664	2944A04240	25/06/98
EM002	ANCHOFF CHAMBER	FELJAS & MASSON	N/A	N/A	05/06/98

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HP	HP85660B	3144A21192	29/05/98
EM008	SPECTRUM ANALYZER DISPLAY	HP	HP85662A	3144A20514	29/05/98
EM009	QUASI PEAK ADAPTOR	HP	HP85650A	3303A01702	29/05/98
EM010	RF PRESELECTOR	HP	HP85685A	3221A01410	29/05/98
EM011	ATTENUATOR SWITCH	HP	HP11713A	2508A10595	29/05/98
EM012	PREAMPLIFIER	HP	HP8449B	3008A00262	29/05/98
EM013	CONTROLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE, FLOPPY DRIVE	HP HP HP	HP9000 HPA1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM017	ANTENNA	ARA INC	LPB-2513 A	1069	31/12/97
EM072	SIGNAL GENERATOR	HP	8640B	1948A11892	30/03/98
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	16/02/98

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM003	SIGNAL GENERATOR	R & S	SMS	871603/529	CM
EM117	IMPULSE LIMITER	R & S	ESH3Z2	0357 8810/52	05/02/98
EM002	LISN	EMCO	3825-2	9005-1657	20/06/98
EM120	EMI TEST RECEIVER	R & S	ESLIS10	1004/0401/10	02/07/98
EM081	SMAALL SCREENED ROOM	MIKO INST HK	N/A	N/A	TBD

ABBREVIATIONS:

CM = Corrective Maintenance
N/A = Not Applicable
TBD = To Be Determined



The Hong Kong Standards and Testing Centre Ltd.

Date:1998-08-31

No.: KM0041/504

TEST REPORT APPENDIX B

Page B1 of B3

ANCILLARY EQUIPMENT

ITEM NO.	DESCRIPTION	MODEL NO.	FCC ID	REMARK
1	AST COMPUTER	AST PREMIUM II 486 33	DJKASTPII486-33	1.92m SVT SHIELDED CABLE
2	SVGA MONITOR	CM6P	GDRCM6P	RESOLUTION : 720*400 (DURING TESTING) 1.0M UNSHIELDED POWER CORD CONNECTED TO THE COMPUTER 1.8M SHIELDED CABLE CONNECTED TO THE COMPUTER
3	AST KEYBOARD	K13-101	AQ6MEMB-74004	1.8 SHIELDED COILED CABLE CONNECTED TO THE COMPUTER
4	MOUSE	PS12	ESUGMZC8	2.4M UNSHIELDED CABLE CONNECTED TO THE COMPUTER
5	SERIAL PROGRAM PAD (EUT)	SV-284	KY1SV-284	2.6M SHIELDED CABLE CONNECTED TO COMPUTER KEYBOARD SOCKET 2.3M SHIELDED CABLE CONNECTED TO SOUND CARD SOCKET OF THE COMPUTER
6	PARALLEL PRINTER	DMP3000	DE2850CDMP3000	1.8M UNSHIELDED POWER CORD 2.8M SHIELDED CABLE (BUNDLED TO 1M) CONNECTED TO THE COMPUTER
7	SERIAL PRINTER	N/A	N/A	SAME AS PARALLEL PRINTER