Test Report of FCC CFR 47 Part 15 Subpart C

On Behalf of

Mine Site Technologies Pty Ltd.

113, Wicks Road, North Ryde, NSW 2113, AUSTRALIA

Product Name:	**UT33 Tag**
Model/Type No.:	**PT33**
Trade Name:	**MST**
FCC ID:	**N73-PT33**
Prepared By:	**Shenzhen Hongcai Testing Technology Co., Ltd.** 1st-3rd Floor, Building C, Shuanghuan Xin Yi Dai Hi-Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen, Guangdong, China Tel: +86-755-86337020 Fax:+86-755-86337028
Report Number:	HCT16ER103E
Tested Date:	May 30~June 15, 2016
Issued Date:	June 15, 2016
Tested By:	Haiqing.Zhao/ Haiqing Zhao

Reviewed By: Owen Yang

Owen.Yang
EMC Technical Supervisor

Approved By: Tony Wu

Tony Wu
EMC Technical Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION 3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 3
1.2 TEST STANDARDS 3
1.3 TEST FACILITY 4
2. SYSTEM TEST CONFIGURATION 5
2.1 EUT CONFIGURATION 5
2.2 EUT EXERCISE 5
2.3 GENERAL TEST PROCEDURES 5
2.4 MEASUREMENT UNCERTAINTY 5
2.5 MEASURE RESULTS EXPLANATION EXAMPLE 6
2.6 LIST OF MEASURING EQUIPMENTS USED 7
3. SUMMARY OF TEST RESULTS 8
4. OUTPUT POWER MEASUREMENT 9
4.1 APPLICABLE STANDARD 9
4.2 EUT SETUP 9
4.3 TEST EQUIPMENT LIST AND DETAILS 9
4.4 TEST PROCEDURE 9
4.5 TEST RESULT 10
5. TEST OF PEAK POWER SPECTRAL DENSITY 11
5.1 APPLICABLE STANDARD 11
5.2 EUT SETUP 11
5.3 TEST EQUIPMENT LIST AND DETAILS 11
5.4 TEST PROCEDURE 11
5.5 TEST RESULT 12
6. TEST OF 6DB BANDWIDTH 14
6.1 APPLICABLE STANDARD 14
6.2 EUT SETUP 14
6.3 TEST EQUIPMENT LIST AND DETAILS 14
6.4 TEST PROCEDURE 14
6.5 TEST RESULT 15
7. TEST OF CONDUCTED SPURIOUS EMISSION 17
7.1 APPLICABLE STANDARD 17
7.2 EUT SETUP 17
7.3 TEST EQUIPMENT LIST AND DETAILS 17
8.4 TEST PROCEDURE 17
7.5 TEST RESULT 17
8. TEST OF RADIATED SPURIOUS EMISSION 20
8.1 RADIATED SPURIOUS EMISSION 20
8.1.1 LIMITS 20
8.1.2 EUT SETUP 20
8.1.3 TEST PROCEDURE 21
8.1.4 TEST RESULT 23
9. TEST OF BAND EDGES EMISSION 29
9.1 APPLICABLE STANDARD 29
9.2 EUT SETUP 29
9.3 TEST EQUIPMENT LIST AND DETAILS 29
9.4 TEST PROCEDURE 29
9.5 TEST RESULT 31
10. ANTENNA REQUIREMENT 33
10.1 STANDARD APPLICABLE 33
10.2 ANTENNA CONNECTED CONSTRUCTION 33

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	**Mine Site Technologies Pty Ltd.**
Address of Applicant:	113, Wicks Road, North Ryde, NSW 2113, AUSTRALIA
Manufacturer:	**Mine Site Technologies Pty Ltd.**
Address of Manufacturer:	113, Wicks Road, North Ryde, NSW 2113, AUSTRALIA

General Description of E.U.T

Items	Description
EUT Description:	UT33 Tag
Model No.:	PT33
Frequency Band:	IEEE 802.11b : 2412MHz～2462MHz;
Channel Spacing:	IEEE 802.11b : 5MHz
Number of Channels:	IEEE 802.11b :11 Channels
Type of Modulation:	IEEE 802.11b：CCK
Antenna Type:	Multilayer Chip Antenna
Antenna Gain:	1.5dBi
Power Rating:	DC 3.6V

Remark:* *The test data gathered are from the production sample provided by the manufacturer.*

HONGCAI TESTING

1.2 Test standards

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

KDB558074 D01 V03r03: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247.

RSS-GEN Issue 4: General Requirements for Compliance of Radio Apparatus.

RSS 247 Issue 1: Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel：+86 755 86337020(60Lines) Fax：+86 755 86337028 Web：www.hct-test.com

1.3 Test Facility

All measurement required was performed at laboratory of Shenzhen CTL Testing Technology Co., Ltd. Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

FCC – Registration No.: 970318
Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December, 2013.

IC Registration No.: 9618B
The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the connecting is requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the table, which is 0.8 m above ground plane According to the requirements in ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is a placed on as turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in ANSI C63.10-2013.

2.4 Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Transmitter power conducted	+/- 0.57 dB
Transmitter power Radiated	+/- 2.20 dB
Conducted spurious emission 9KHz-40 GHz	+/- 2.20 dB
Occupied Bandwidth	+/- 0.01 dB
Power Line Conducted Emission	+/- 3.20 dB
Radiated Emission	+/- 4.32 dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

2.5 Measure Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable less and attenuator factor.
Offset= RF cable less+ attenuator factor.

Note: Using a temporary antenna connector for the EUT when the conducted measurements are performed.

Equipment	Manufacturer	Model No.	Frequency range(GHz)	Attenuation values(dBm)
Line	Zhenjiang south electronic	RG316	1-12	0.08
Connector	Zhenjiang south electronic	ESIB7	1-12	0.01







Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

2.6 List of Measuring Equipments Used

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Last Calibration	Due Calibration
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2015-7-25	2016-7-24
2	BCT-EMC002	EMI Test Receiver	R&S	ES PI	100097	2015-11-1	2016-10-31
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2015-7-25	2016-7-24
4	BCT-EMC018	TRILOGBroadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2015-7-25	2016-7-24
5	BCT-EMC021	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2015-11-1	2016-10-31
6	BCT-EMC026	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2015-7-25	2016-7-24
7	BCT-EMC029	6DB Attenuator	FRANKONIA	N/A	1001698	2015-7-25	2016-7-24
8	BCT-EMC032	10dB attenuator	ELECTRO-METRICS	EM-7600	836	2015-7-25	2016-7-24
9	BCT-EMC036	Spectrum Analyzer	R&S	FSP	100397	2015-11-1	2016-10-31
10	BCT-EMC037	Broadband preamplifier	SCH WARZBECK	BBV9718	9718-182	2015-7-25	2016-7-24
11	BCT-EMC039	Horn Antenna	SCHWARZBECK	BBHA 9120D	0437	2015-7-25	2016-7-24
12	BCT-EMC038	Horn Antenna	SCHWARZBECK	BBHA9170	0483	2015-7-25	2016-7-24
13	BCT-EMC050	Pulse power sensor	Anritsu	MA2411B	110553	2015-11-1	2016-10-31
14	BCT-EMC050	Power Meter	Anritsu	ML2487B	100345	2015-11-1	2016-10-31

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

3. SUMMARY OF Test RESULTS

FCC/IC Rules	Description of Test	Result
FCC §15.207 IC RSS-GEN Clause 8.8	AC Power Line Conducted Emission	N/A
FCC §15.247(b) IC RSS-247 Issue1 Clause 5.4 (4)	Output Power Measurement	Pass
FCC §15.247(e) IC RSS-247 Issue1 Clause 5.2 (2)	Power Spectral Density	Pass
FCC §15.247(a) IC RSS-247 Issue1 Clause 5.2 (1) IC RSS-GEN Clause 6.6	6dB Bandwidth 99%Occupied Bandwidth	Pass
FCC §15.247 (d) IC RSS-247 Issue1 Clause 5.5	Conducted Spurious Emission	Pass
FCC §15.205 and §15.209 IC RSS-247 Issue1 Clause 5.5	Radiated Spurious Emission	Pass
FCC§15.247 (d) and §15.205 and §15.209 IC RSS-247 Issue1 Clause 5.5	Unwanted Emissions	Pass
FCC §15.203/15.247(b)/(c) IC RSS-GEN Clause 8.3	Antenna Requirement	Pass

Note:N/A is not Applicable.

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

4. Output Power Measurement

4.1 Applicable standard

Refer to FCC §15.247 (b) and IC RSS-247 Issue1 Clause 5.4 (4).

KDB 558074 v03r03 – Section 9.1.2 PKPM1 Peak Power, Method

KDB 558074 v03r03 – Section 9.2.3.2 Method AVGPM-G

The maximum permissible conducted output power is 1Watt.

4.2 EUT Setup



4.3 Test Equipment List and Details

See section 2.6

4.4 Test Procedure

Method PKPM1 (Peak Power Measurement)

Peak power measurement were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor, The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was than or equal to 50MHz.

HONGCAI TESTING

Method AVGPM-G (Average Power Measurement)

Average power measurement were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor, The pulse meter implemented triggering capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter, The trace was averaged over 100 traces to obtain the final measured average power.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

4.5 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2412	20.65	30	PASS
Middle	2437	19.99	30	PASS
High	2462	19.29	30	PASS

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

5. Test of Peak Power Spectral Density

5.1 Applicable standard

Refer to FCC §15.247 (e) and IC RSS-247 Issue1 Clause 5.2 (2).

KDB 558074v03r03 – Section 10.2 Method PKPSD

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 EUT Setup

Spectrum Analyzer

5.3 Test Equipment List and Details

See section 2.6

5.4 Test Procedure

The transmitter output was connected to the spectrum analyzer and the parameter was set as below:

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ⩾ 3 kHz.
4. Set the VBW ⩾ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

5.5 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	RF Power Level in 3KHz RBW (dBm)	Maximum Limit (dBm)	Pass / Fail
Low	2412	-7.62	8	PASS
Middle	2437	-8.16	8	PASS
High	2462	-7.70	8	PASS

POWER SPECTRAL DENSITY (IEEE 802.11b MODE CH Low)



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

POWER SPECTRAL DENSITY (IEEE 802.11b MODE CH Mid)



POWER SPECTRAL DENSITY (IEEE 802.11b MODE CH High)

HONGCAI TESTING



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

6. Test of 6dB Bandwidth

6.1 Applicable standard

Refer to FCC §15.247 (a) (2) and IC RSS-247 Issue1 Clause 5.2 (1), IC RSS-GEN Clause 6.6

KDB558074 v03r03 – Section 8.2 Option 2

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 EUT Setup

Spectrum Analyzer

6.3 Test Equipment List and Details

See section 2.6

6.4 Test Procedure

The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. The transmitter output was connected to a spectrum analyzer and the parameter was set as below:

1. Set resolution bandwidth (RBW) = 100 kHz.

2. Set the video bandwidth (VBW) ⩾ 3 x RBW.

3. Detector = Peak.

4. Trace mode = max hold.

5. Sweep = auto couple.

6. Allow the trace to stabilize.

7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

6.5 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

IEEE 802.11b mode

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	10.24	500	PASS
Middle	2437	10.32	500	PASS
High	2462	10.24	500	PASS

6dB BANDWIDTH (IEEE 802.11b MODE CH Low)



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

6dB BANDWIDTH (IEEE 802.11b MODE CH Mid)



6dB BANDWIDTH (IEEE 802.11b MODE CH High)

HONGCAI TESTING



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

7. Test of Conducted Spurious Emission

7.1 Applicable standard

Refer to FCC §15.247 (d) and IC RSS-247 Issue1 Clause 5.5.

KDB 558074 v03r03 – Section 11.3

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

7.2 EUT Setup

Spectrum Analyzer

7.3 Test Equipment List and Details

See section 2.6

8.4 Test Procedure

1. Set start frequency to DTS channel edge frequency.

2. Set stop frequency so as to encompass the spectrum to be examined.

3. Set RBW = 100 kHz.

4. Set VBW ≥ 300 kHz.

5. Detector = peak.

6. Trace Mode = max hold.

7. Sweep = auto couple.

8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

7.5 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: TX Mode

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

Test Result: PASS

IEEE 802.11b mode

CH Low



CH Mid



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

CH High



HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

8. Test of Radiated Spurious Emission

8.1 Radiated Spurious Emission

Refer to FCC §15.205 and §15.209, IC RSS-247 Clause 5.5

8.1.1 Limits

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

8.1.2 EUT Setup

For radiated emission below 30MHz



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

For radiated emission from 30MHz to1GHz



For radiated emission from above1GHz



8.1.3 Test Procedure

KDB 558074 v03r03 – Section 12.1, 12.2.7

<u>Quasi-Peak Field Strength Measurements</u>

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Set RBW = 120kHz(for emissions from 30MHz-1GHz)
3. Detector = Quasi-Peak
4. Trace Mode = max hold.
5. Sweep = auto couple.
6. Trace was allowed to stabilize

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Set RBW = 1MHz

3. Set VBW = 3MHz

4. Detector = Peak

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Set RBW = 1MHz

3. Set VBW = 3MHz

4. Detector = power average (RMS)

5. Number of measurement points=1001 (>= 2 x span/RBW)

6. Sweep = auto couple.

7. Trace (RMS) averaging was performed over at least 100 traces

HONGCAI TESTING

NOTE:

1. Configure the EUT according to ANSI C63.10-2013

2. The turntable was rotated by 360 degrees to determine the position of the highest radiation. the EUT of this type was measured in the three orthogonal planes to insure that all possible placements of the EUT were properly measured.

3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.

4. For band edge emission, the antenna tower was scan (from 1 M to 4 M) and then the turn table was rotated (from 0 degree to 360 degrees) to find the maximum reading.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

8.1.4 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: TX Mode

Note:
1. Worst-case radiated emission below 30MHz is IEEE 802.11b TX (CH Low) mode.
2. Worst-case radiated emission below 1GHz is IEEE 802.11b TX (CH High) mode.
3. Worst-case radiated emission above 1GHz is IEEE 802.11b TX (CH Low, Middle, High) mode.

RADIATED EMISSION BELOW 30 MHz

IEEE 802.11b TX (CH Low) operating Mode:

Frequency	Meter Reading	Antenna Factor	Cable Loss	Emission Levels	Limits	Margin	Detector Mode
(MHz)	(dBµV)	(dB/M)	(dB)	(dBµV/M)	(dB µ V/M)	(dB)	PK/QP
5.49	22.76	8.23	1.03	29.96	67	-37.04	QP
18.84	22.47	9.07	1.19	30.35	49.5	-19.15	QP
23.36	23.79	9.25	1.08	31.96	49.5	-17.54	QP
28.33	23.89	8.43	1.66	30.66	49.5	-18.84	QP

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

Spurious Emission Below 1GHz: IEEE 802.11b TX (CH High)

EUT:	UT33 Tag
M/N:	PT33
Operating Condition:	TX Mode
Test Site:	3m CHAMBER
Operator:	Chen
Test Specification:	AC 120V/60Hz
Comment:	Polarization: Horizontal

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength

Start Frequency	Stop Frequency	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1



MEASUREMENT RESULT:

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	25.00	20.8	40.0	15.0	QP	0.0	0.00	HORIZONTAL
288.020000	29.10	15.2	46.0	16.9	QP	0.0	0.00	HORIZONTAL
385.020000	30.80	17.7	46.0	15.2	QP	0.0	0.00	HORIZONTAL
433.520000	27.40	18.8	46.0	18.6	QP	0.0	0.00	HORIZONTAL
482.020000	32.00	20.0	46.0	14.0	QP	0.0	0.00	HORIZONTAL
926.280000	31.50	26.2	46.0	14.5	QP	0.0	0.00	HORIZONTAL

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

Spurious Emission Below 1GHz : IEEE 802.11b TX (CH High)

EUT:	UT33 Tag
M/N:	PT33
Operating Condition:	TX Mode
Test Site:	3m CHAMBER
Operator:	Chen
Test Specification:	AC 120V/60Hz
Comment:	Polarization: Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength

Start Frequency	Stop Frequency	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	JB1



MEASUREMENT RESULT:

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	25.00	20.8	40.0	15.0	QP	0.0	0.00	VERTICAL
72.680000	18.70	8.3	40.0	21.3	QP	0.0	0.00	VERTICAL
103.720000	23.40	12.0	43.5	20.1	QP	0.0	0.00	VERTICAL
288.020000	22.00	15.2	46.0	24.0	QP	0.0	0.00	VERTICAL
538.280000	25.30	20.6	46.0	20.7	QP	0.0	0.00	VERTICAL
891.360000	31.80	25.8	46.0	14.2	QP	0.0	0.00	VERTICAL

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

RADIATED EMISSION ABOVE 1 GHz

IEEE 802.11b TX (CH Low)

Channel Low（2412MHz）								
Maximum Frequency (MHz)	Polarity and Level					Limit (dBμV/m)	Margin (dBμV/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dBμV	Transd	Result dBμV/m			
1380.66	H	1	48.67	-7.97	40.7	74	-33.3	P
			35.91	-7.97	27.94	54	-26.06	A
1380.22	V	1	48.09	-7.97	40.12	74	-33.88	P
			35.52	-7.97	27.55	54	-26.45	A
2412	H	1	105.83	-6.47	99.36	----	----	P
			95.22	-6.47	88.75	----	----	A
2412	V	1	107.82	-6.47	101.35	----	----	P
			97.02	-6.47	90.55	----	----	A
4824	H	1	43.29	0.52	43.81	74	-30.19	P
			32.91	0.52	33.43	54	-20.57	A
4824	V	1	44.11	0.52	44.63	74	-29.37	P
			32.82	0.52	33.34	54	-20.66	A
7236	H	1	43.19	7.41	50.6	74	-23.4	P
			33.28	7.41	40.69	54	-13.31	A
7236	V	1	43.98	7.41	51.39	74	-22.61	P
			33.39	7.41	40.8	54	-13.2	A
11145.34	H	1	----	----	----	----	----	----
			----	----	----	----	----	----
16327.65	----	----	----	----	----	----	----	----
25376.32	----	----	----	----	----	----	----	----

Remark: 1.Transd=Antenna Factor + Cable Loss - Pre-amplifier
Margin = Level-Limit
Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value
2. Data of measurement within this frequency range shown " -" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=3MHz, A(Average): RBW=1MHz, VBW=3MHz.
4. The test limit distance is 3m limit

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel：+86 755 86337020(60Lines) Fax：+86 755 86337028 Web：www.hct-test.com

IEEE 802.11b TX (CH Middle)

Channel Middle（2437MHz）								
Maximum Frequency (MHz)	Polarity and Level					Limit (dBμV/m)	Margin (dBμV/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dBμV	Transd	Result dBμV/m			
1326.33	H	1	48.91	-8.23	40.68	74	-33.32	P
			37.02	-8.23	28.79	54	-25.21	A
1326.22	V	1	49.93	-8.23	41.7	74	-32.3	P
			37.24	-8.23	29.01	54	-24.99	A
2437	H	1	105.90	-6.37	99.53	----	----	P
			96.42	-6.37	90.05	----	----	A
2437	V	1	109.40	-6.37	103.03	----	----	P
			97.93	-6.37	91.56	----	----	A
4874	H	1	45.09	0.75	45.84	74	-28.16	P
			34.4	0.75	35.15	54	-18.85	A
4874	V	1	45.22	0.75	45.97	74	-28.03	P
			34.42	0.75	35.17	54	-18.83	A
7311	H	1	44.29	7.48	51.77	74	-22.23	P
			33.93	7.48	41.41	54	-12.59	A
7311	V	1	44.40	7.48	51.88	74	-22.12	P
			34.31	7.48	41.79	54	-12.21	A
11238.52	H	1	----	----	----	----	----	----
			----	----	----	----	----	----
16327.71	----	----	----	----	----	----	----	----
25376.58	----	----	----	----	----	----	----	----

Remark: 1.Transd=Antenna Factor + Cable Loss - Pre-amplifier
Margin = Level-Limit
Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value
2. Data of measurement within this frequency range shown " -" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=3MHz, A(Average): RBW=1MHz, VBW=3MHz.
4. The test limit distance is 3m limit

HCT HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel：+86 755 86337020(60Lines) Fax：+86 755 86337028 Web：www.hct-test.com

IEEE 802.11b TX (CH High)

Channel High（2462MHz）								
Maximum Frequency (MHz)	Polarity and Level					Limit (dBμV/m)	Margin (dBμV/m)	Mark (P/Q/A)
	Polarity	Height (m)	Reading dBμV	Transd	Result dBμV/m			
1312.66	H	1	49.18	-8.23	40.95	74	-33.05	P
			37.40	-8.23	29.17	54	-24.83	A
1311.67	V	1	49.89	-8.23	41.66	74	-32.34	P
			37.98	-8.23	29.75	54	-24.25	A
2462	H	1	105.09	-6.28	98.81	----	----	P
			95.20	-6.28	88.92	----	----	A
2462	V	1	108.09	-6.28	101.81	----	----	P
			96.13	-6.28	89.85	----	----	A
4924	H	1	44.12	0.97	45.09	74	-28.91	P
			33.93	0.97	34.9	54	-19.1	A
4924	V	1	46.92	0.97	47.89	74	-26.11	P
			35.24	0.97	36.21	54	-17.79	A
7386	H	1	45.13	7.56	52.69	74	-21.31	P
			34.2	7.56	41.76	54	-12.24	A
7386	V	1	43.98	7.56	51.54	74	-22.46	P
			33.93	7.56	41.49	54	-12.51	A
11243.58	H	1	----	----	----	----	----	----
			----	----	----	----	----	----
16327.45	----	----	----	----	----	----	----	----
25376.26	----	----	----	----	----	----	----	----

Remark: 1.Transd=Antenna Factor + Cable Loss - Pre-amplifier
Margin = Level-Limit
Mark: P means Peak Value, Q means Quasi Peak Value, A means Average Value
2. Data of measurement within this frequency range shown " -" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=3MHz, A(Average): RBW=1MHz, VBW=3MHz.
4. The test limit distance is 3m limit

HCT HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel：+86 755 86337020(60Lines) Fax：+86 755 86337028 Web：www.hct-test.com

9. Test of Band Edges Emission

9.1 Applicable standard

Refer to FCC §15.247 (d), IC RSS-247 Issue1 Clause 5.5

KDB558074 v03r03 – Section 11.3

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions that fall in the restricted bands, as defined in Section 15.205, must also comply with the radiated emission limits specified in Section 15.209.

9.2 EUT Setup

Radiated Measurement Setup



Conducted Measurement Setup

Spectrum Analyzer

9.3 Test Equipment List and Details

See section 2.6

9.4 Test Procedure

Conducted Measurement

KDB558074 v03r03 – Section 11.3

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

1.Set the center frequency and span to encompass frequency range to be measured.
2.Set the RBW = 100 kHz.
3.Set the VBW ≥ 3 x RBW.
4.Detector = peak.
5.Sweep time = auto couple.
6.Trace mode = max hold.
7.Allow trace to fully stabilize.
8.Use the peak marker function to determine the maximum amplitude level.

Radiated Measurement

KDB 558074 v03r03 – Section 12.1, 12.2.7

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Set RBW = 1MHz

3. Set VBW = 3MHz

4. Detector = Peak

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. Set RBW = 1MHz

3. Set VBW : Reduce the video bandwidth until no significant variations in the displayed signal are observed in subsequent traces.

4. Detector = power average (RMS)

5. Sweep = auto couple.

6. Trace (RMS) averaging was performed over at least 100 traces

NOTE :

1. Configure the EUT according to ANSI C63.10-2013

2. The turntable was rotated by 360 degrees to determine the position of the highest radiation.

3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.

4. For band edge emission, the antenna tower was scan (from 1 M to 4 M) and then the turn table was rotated (from 0 degree to 360 degrees) to find the maximum reading.

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

9.5 Test Result

Temperature (℃) : 22~23	EUT: UT33 Tag
Humidity (%RH): 50~54	M/N: PT33
Barometric Pressure (mbar): 950~1000	Operation Condition: Tx Mode

PASS

Radiated Test Result
IEEE 802.11b mode

Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
LOW	2390	48.72	74	-25.28	Peak
	2390	36.53	54	-17.47	Average
HIGH	2483.5	47.76	74	-26.24	Peak
	2483.5	36.33	54	-17.67	Average

Note: 1. Emission Level = Emission Read Value + Correction Factor
2. Correction Factor) = Antenna Factor + Cable Loss- amplifier gain
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

HONGCAI TESTING

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

Test of Conducted band edges

CH Low (802.11b MODE)



CH High (802.11b MODE)



Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com

10. ANTENNA REQUIREMENT

10.1 standard Applicable

Section 15.203 & IC RSS-GEN Clause 8.3

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Section 15.247(b)/(c)

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

If the intentional radiator is used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

10.2 Antenna Connected Construction

There are no provisions for connections to an external antenna.
The antenna is designed with permanent attachment and no consideration of replacement.
The antenna used in this product is complied with standard. The maximum Gain of the antenna lower than 6.0dBi and have the definite antenna Specification.

HONGCAI TESTING

…End of Report…

Shenzhen Hongcai Testing Technology Co.,Ltd.
1st—3rd Floor, Building C,Shuanghuan Xin Yi Dai Hi—Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen City, P.R.China 518053
Tel : +86 755 86337020(60Lines) Fax : +86 755 86337028 Web : www.hct-test.com