FCC RADIO TEST REPORT

FCC ID	:	**N7NEM92**
Equipment	:	**Wireless Module**
Brand Name	:	**AirPrime**
Model Name	:	**EM9293**
Applicant	:	**Sierra Wireless, ULC** **13811 Wireless Way, Richmond, BC V6V 3A4 Canada**
Manufacturer	:	**Sierra Wireless, ULC** **13811 Wireless Way, Richmond, BC V6V 3A4 Canada**
Standard	:	**FCC 47 CFR Part 2, 96**

The product was received on Dec. 20, 2022 and testing was performed from Mar. 09, 2023 to Aug. 17, 2023. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**

Summary of Test Result **4**

1 General Description **5**

1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 5
1.4 Applied Standards 6

2 Test Configuration of Equipment Under Test **7**

2.1 Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Support Unit used in test configuration 8
2.4 Frequency List of Low/Middle/High Channels 8

3 Conducted Test Items **9**

3.1 Measuring Instruments 9
3.2 Conducted Output Power 10
3.3 Peak-to-Average Ratio 11
3.4 Occupied Bandwidth 12
3.5 Conducted Band Edge 13
3.6 Conducted Spurious Emission 14
3.7 Frequency Stability 15

4 Radiated Test Items **16**

4.1 Measuring Instruments 16
4.2 Test Setup 16
4.3 Test Result of Radiated Test 17
4.4 Radiated Spurious Emission 18

5 List of Measuring Equipment **19**

6 Measurement Uncertainty **20**

Appendix A. Test Results of Conducted Test

Appendix B. Test Results of Radiated Test

History of this test report

Report No.	Version	Description	Issue Date
FG2D2006L	01	Initial issue of report	Sep. 08, 2023

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
3.3	§96.41	Peak-to-Average Ratio	Pass	-
3.4	§2.1049 §96.41	Occupied Bandwidth	Reporting only	-
3.5	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.6	§2.1051 §96.41	Conducted Spurious Emission	Pass	-
3.7	§2.1055	Frequency Stability for Temperature & Voltage	Pass	-
4.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	9.76 dB under limit at 14429.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Danny Lee

Report Producer: Ming Chen

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs WCDMA/LTE/5G NR, and GNSS.

Remark:

1. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
2. The maximum allowable antenna gain is determined by the manufacturer.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH03-HY
Test Engineer	George Chen and Ivy Yeh
Temperature (℃)	20~24
Relative Humidity (%)	50~58

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY (TAF Code: 3786)
Test Engineer	Jesse Fan, Tim Lee and Wilson Wu
Temperature (℃)	20~25
Relative Humidity (%)	50~60
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786

1.4 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26-2015
- ANSI / TIA-603-E
- FCC 47 CFR Part 2, 96
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in two config (Ant. Horizontal and Ant. Vertical), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report.

Test Items	Band	Bandwidth (MHz)					Modulation					RB #			Test Channel		
		10	15	20	30	40	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	n48	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	n48	v	v	v	v	v	v	v	v	v	v			v		v	
Conducted Band Edge	n48	v	v	v	v	v	v	v	v	v	v	v		v	v	v	v
Peak-to-Average Ratio	n48			v			v	v	v	v	v			v		v	
Conducted Spurious Emission	n48	v	v	v	v	v		v				v			v	v	v
Frequency Stability	n48			v			v							v		v	
Radiated Spurious Emission	n48	Worst Case													v	v	v
Remark	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. For radiated measurement, pre-scanned in two modes, DFT-s OFDM and CP OFDM. The worst cases (DFT-s OFDM) were recorded in this report, and the worst modes of FR1 and LTE for simultaneous transmission were verified and compliant. 5. Test combination are EN-DC 2A_n48A, EN-DC 5A_n48A, EN-DC 13A_n48A and EN-DC 66A_n48A. 6. One representative bandwidth is selected to perform PAR and frequency stability.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Frequency List of Low/Middle/High Channels

5G NR n48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	638000	641666	645332
	Frequency	3570	3624.99	3679.98
30	Channel	637668	641666	645666
	Frequency	3565.02	3624.99	3684.99
20	Channel	637334	641666	646000
	Frequency	3560.01	3624.99	3690
15	Channel	637168	641666	646166
	Frequency	3557.52	3624.99	3692.49
10	Channel	637000	641666	646332
	Frequency	3555	3624.99	3694.98

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power

3.2.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed −13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed −25 dBm/MHz. Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Adjacent Channel Leakage Ratio (ACLR) measurement,

1. The Adjacent Channel Leakage Ratio (ACLR) is the ratio of the average power in the assigned aggregated channel bandwidth to the average power over the equivalent adjacent channel bandwidth.
2. The option ACLR of spectrum analyzer is used and measures the ACLR ratio by setting equivalent channel bandwidth.
3. The measured ACLR ratio shall be at least 30 dB.

3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed −40dBm/MHz.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is −40dBm/MHz.

3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz .

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
   Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Programmable Power Supply	GW Instek	PSS-2005	EL890001	50Hz~60Hz	Sep. 29, 2022	Mar. 09, 2023 ~ Aug. 17, 2023	Sep. 28, 2023	Conducted (TH03-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101049	10Hz~44GHz	Oct. 07, 2022	Mar. 09, 2023 ~ Aug. 17, 2023	Oct. 06, 2023	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃ ~90℃	Sep. 07, 2022	Mar. 09, 2023 ~ Aug. 17, 2023	Sep. 06, 2023	Conducted (TH03-HY)
Base Station (Measure)	Anritsu	MT8821C	6261940327	LTE	Dec. 09, 2022	Mar. 09, 2023 ~ Aug. 17, 2023	Dec. 08, 2023	Conducted (TH03-HY)
Base Station (Measure)	Anritsu	MT8000A	6261849015	FR1	Dec. 09, 2022	Mar. 09, 2023 ~ Aug. 17, 2023	Dec. 08, 2023	Conducted (TH03-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 20, 2022	Mar. 26, 2023~ Jul. 13, 2023	Sep. 19, 2023	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Nov. 10, 2022	Mar. 26, 2023~ Jul. 13, 2023	Nov. 09, 2023	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02114	1GHz~18GHz	Aug. 09, 2022	Mar. 26, 2023~ Jul. 13, 2023	Aug. 08, 2023	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz~18GHz	Jul. 25, 2022	Mar. 26, 2023~ Jul. 13, 2023	Jul. 24, 2023	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00993	18GHz-40GHz	Nov. 24, 2022	Mar. 26, 2023~ Jul. 13, 2023	Nov. 23, 2023	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	00994	18GHz-40GHz	Nov. 04, 2022	Mar. 26, 2023~ Jul. 13, 2023	Nov. 03, 2023	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Oct. 03, 2022	Mar. 26, 2023~ Jul. 13, 2023	Oct. 02, 2023	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	May 24, 2022	Mar. 26, 2023~ Jul. 13, 2023	May 23, 2023	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	May 23, 2023	Mar. 26, 2023~ Jul. 13, 2023	May 22, 2024	Radiation (03CH12-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz-18GHz	Dec. 21, 2022	Mar. 26, 2023~ Jul. 13, 2023	Dec. 20, 2023	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 07, 2022	Mar. 26, 2023~ Jul. 13, 2023	Dec. 06, 2023	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Jan. 10, 2023	Mar. 26, 2023~ Jul. 13, 2023	Jan. 09, 2024	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080-1200-15000-60SS	SN1	1.2GHz High Pass Filter	Mar. 14, 2023	Mar. 26, 2023~ Jul. 13, 2023	Mar. 13, 2024	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN2	3GHz High Pass Filter	Mar. 14, 2023	Mar. 26, 2023~ Jul. 13, 2023	Mar. 13, 2024	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872.5-6750-18000-40ST	SN2	6.75GHz High Pass Filter	Mar. 14, 2023	Mar. 26, 2023~ Jul. 13, 2023	Mar. 13, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 07, 2023	Mar. 26, 2023~ Jul. 13, 2023	Mar. 06, 2024	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 20, 2022	Mar. 26, 2023~ Jul. 13, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Dec. 20, 2022	Mar. 26, 2023~ Jul. 13, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803953/2	30MHz~40GHz	Dec. 20, 2022	Mar. 26, 2023~ Jul. 13, 2023	Dec. 19, 2023	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Mar. 26, 2023~ Jul. 13, 2023	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Mar. 26, 2023~ Jul. 13, 2023	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Mar. 26, 2023~ Jul. 13, 2023	N/A	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	Jan. 11, 2023	Mar. 26, 2023~ Jul. 13, 2023	Jan. 10, 2024	Radiation (03CH12-HY)

6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.31 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.63 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.14 dB

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

NR n48 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	Maximum Output Power (dBm)	Maximum Output Power (W)
10	1	1	PI/2 BPSK	24.34	24.46	24.47	24.56	0.2858
10	1	22		24.40	24.52	24.52		
10	12	6		24.39	24.56	24.51		
10	1	0		23.86	24.00	23.93		
10	1	23		23.80	23.95	23.93		
10	24	0		23.96	24.08	23.96		
10	1	1	QPSK	24.37	24.49	24.45	24.51	0.2825
10	1	22		24.30	24.42	24.42		
10	12	6		24.42	24.51	24.51		
10	1	0		23.32	23.46	23.51		
10	1	23		23.32	23.39	23.43		
10	24	0		23.41	23.52	23.52		
10	1	1	16-QAM	23.39	23.60	23.73	23.73	0.2360
10	1	1	64-QAM	21.90	22.00	22.05		
10	1	1	256-QAM	19.88	19.82	19.74		

NR n48 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	Maximum Output Power (dBm)	Maximum Output Power (W)
15	1	1	PI/2 BPSK	20.73	24.77	24.82	24.86	0.3062
15	1	36		24.69	24.76	20.69		
15	18	9		24.79	24.82	24.86		
15	1	0		20.68	24.31	24.26		
15	1	37		24.18	24.22	20.85		
15	36	0		20.71	24.32	20.78		
15	1	1	QPSK	20.71	24.83	24.76	24.83	0.3041
15	1	36		24.64	24.71	20.72		
15	18	9		24.78	24.78	24.81		
15	1	0		20.71	23.79	23.78		
15	1	37		23.63	23.73	20.72		
15	36	0		20.74	23.79	20.78		
15	1	1	16-QAM	19.82	23.88	23.94	23.94	0.2477
15	1	1	64-QAM	19.71	22.32	22.35		
15	1	1	256-QAM	20.05	20.08	20.12		

NR n48 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	Maximum Output Power (dBm)	Maximum Output Power (W)
20	1	1	PI/2 BPSK	20.54	24.69	24.61	24.70	0.2951
20	1	49		24.62	24.54	20.50		
20	25	12		24.66	24.66	24.70		
20	1	0		20.50	24.11	24.13		
20	1	50		24.09	24.07	20.50		
20	50	0		20.58	24.16	20.65		
20	1	1	QPSK	20.50	24.66	24.59	24.66	0.2924
20	1	49		24.54	24.54	20.50		
20	25	12		24.60	24.66	24.66		
20	1	0		20.48	23.65	23.68		
20	1	50		23.56	23.52	20.51		
20	50	0		20.61	23.69	20.57		
20	1	1	16-QAM	19.72	23.78	23.76	23.78	0.2388
20	1	1	64-QAM	19.54	22.17	22.15		
20	1	1	256-QAM	19.79	19.97	19.88		

NR n48 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	Maximum Output Power (dBm)	Maximum Output Power (W)
30	1	1	PI/2 BPSK	14.38	20.93	14.47	24.90	0.3090
30	1	76		14.19	20.70	14.38		
30	36	18		14.29	24.86	24.90		
30	1	0		14.42	20.93	14.45		
30	1	77		14.19	20.66	14.39		
30	75	0		14.29	20.91	14.45		
30	1	1	QPSK	14.37	20.91	14.44	24.91	0.3097
30	1	76		14.15	20.70	14.40		
30	36	18		14.30	24.88	24.91		
30	1	0		14.41	20.92	14.43		
30	1	77		14.18	20.69	14.37		
30	75	0		14.32	20.85	14.43		
30	1	1	16-QAM	14.05	21.10	13.98	21.10	0.1288
30	1	1	64-QAM	13.88	20.99	14.03		
30	1	1	256-QAM	13.73	20.26	13.76		

NR n48 Maximum Average Power [dBm]								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	Maximum Output Power (dBm)	Maximum Output Power (W)
40	1	1	PI/2 BPSK	14.20	20.72	14.28	24.75	0.2985
40	1	104		14.14	20.65	14.27		
40	50	25		14.23	24.75	14.32		
40	1	0		14.14	20.72	14.31		
40	1	105		14.15	20.58	14.28		
40	100	0		14.16	20.17	14.27		
40	1	1	QPSK	14.17	20.68	14.32	24.72	0.2965
40	1	104		14.11	20.61	14.27		
40	50	25		14.16	24.72	14.26		
40	1	0		14.18	20.68	14.35		
40	1	105		14.14	20.55	14.31		
40	100	0		14.20	20.18	14.31		
40	1	1	16-QAM	13.82	20.90	13.92	20.90	0.1230
40	1	1	64-QAM	13.63	20.69	13.85		
40	1	1	256-QAM	13.43	20.02	13.60		

FR1 n48

Peak-to-Average Ratio

Mode	FR1 n48 / 20MHz / DFT-S OFDM				
Mod.	PI/2 BPSK	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	4.02	4.64	5.54	6.10	PASS
Mode	FR1 n48 / 20MHz / DFT-S OFDM				
Mod.	256QAM				Limit: 13dB
RB Size	Full RB				Result
Middle CH	6.48				PASS

FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



QPSK



16QAM



64QAM



256QAM



26dB Bandwidth

Mode	FR1 n48 : 26dB BW(MHz) / DFT-S OFDM							
BW	10MHz	15MHz	20MHz	30MHz	40MHz	50MHz	60MHz	70MHz
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK
Middle CH	9.87	14.69	19.54	28.65	38.84	-	-	-
BW	80MHz	90MHz	100MHz					
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK					
Middle CH	-	-	-					

Mode	FR1 n48 : 26dB BW(MHz) / CP OFDM							
BW	10MHz		15MHz		20MHz		30MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	9.93	9.77	15.52	15.17	20.06	19.98	29.97	29.67
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	9.63	9.79	15.44	15.44	20.06	19.94	29.61	29.79
BW	40MHz		50MHz		60MHz		70MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	41.00	40.84	-	-	-	-	-	-
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	41.00	40.84	-	-	-	-	-	-
BW	80MHz		90MHz		100MHz			
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM		
Middle CH	-	-	-	-	-	-		
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM		
Middle CH	-	-	-	-	-	-		

FR1 n48 / 10MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 10MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 15MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 15MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 20MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 30MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 30MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 40MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 40MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



Occupied Bandwidth

Mode	FR1 n48 : OB BW(MHz) / DFT-S OFDM							
BW	10MHz	15MHz	20MHz	30MHz	40MHz	50MHz	60MHz	70MHz
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK
Middle CH	8.61	12.99	17.89	26.84	36.04	-	-	-
BW	80MHz	90MHz	100MHz					
Mod.	PI/2 BPSK	PI/2 BPSK	PI/2 BPSK					
Middle CH	-	-	-					

Mode	FR1 n48 : OB BW(MHz) / CP OFDM							
BW	10MHz		15MHz		20MHz		30MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	8.64	8.60	13.66	13.68	18.29	18.26	27.83	27.92
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	8.59	8.59	13.70	13.68	18.28	18.28	27.85	27.85
BW	40MHz		50MHz		60MHz		70MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	38.08	38.03	-	-	-	-	-	-
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM
Middle CH	38.04	38.25	-	-	-	-	-	-
BW	80MHz		90MHz		100MHz			
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM		
Middle CH	-	-	-	-	-	-		
Mod.	64QAM	256QAM	64QAM	256QAM	64QAM	256QAM		
Middle CH	-	-	-	-	-	-		

FR1 n48 / 10MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK

FR1 n48 / 10MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 15MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 15MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 20MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 20MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 30MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 30MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



FR1 n48 / 40MHz / DFT-S OFDM / Middle Channel / Full RB

PI/2 BPSK



FR1 n48 / 40MHz / CP OFDM / Middle Channel / Full RB

QPSK



16QAM



64QAM



256QAM



Unwanted Emission (MASK)

FR1 n48 / 10MHz / DFT-S OFDM / PI/2 BPSK

Lowest Channel

1RB0



1RBmax



Full RB



FR1 n48 / 10MHz / DFT-S OFDM / PI/2 BPSK

Middle Channel

1RB0



1RBmax



Full RB



FR1 n48 / 10MHz / DFT-S OFDM / PI/2 BPSK

Highest Channel

1RB0



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.517 06 GHz	-45.12 dBm	-5.12 dB
3.530 GHz	3.680 GHz	1.000 MHz	3.679 93 GHz	-43.80 dBm	-18.80 dB
3.680 GHz	3.689 GHz	1.000 MHz	3.688 82 GHz	-30.40 dBm	-17.40 dB
3.689 GHz	3.690 GHz	100.000 kHz	3.690 00 GHz	-19.84 dBm	-6.84 dB
3.690 GHz	3.700 GHz	1.000 MHz	3.690 92 GHz	24.63 dBm	-5.37 dB
3.700 GHz	3.701 GHz	100.000 kHz	3.700 04 GHz	-53.70 dBm	-40.70 dB
3.701 GHz	3.710 GHz	1.000 MHz	3.702 31 GHz	-42.74 dBm	-29.74 dB
3.710 GHz	3.720 GHz	1.000 MHz	3.713 38 GHz	-44.19 dBm	-19.19 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.793 48 GHz	-45.40 dBm	-5.40 dB

1RBmax



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.449 63 GHz	-45.12 dBm	-5.12 dB
3.530 GHz	3.680 GHz	1.000 MHz	3.666 14 GHz	-44.58 dBm	-19.58 dB
3.680 GHz	3.689 GHz	1.000 MHz	3.682 71 GHz	-43.32 dBm	-30.32 dB
3.689 GHz	3.690 GHz	100.000 kHz	3.689 34 GHz	-53.76 dBm	-40.76 dB
3.690 GHz	3.700 GHz	1.000 MHz	3.699 08 GHz	24.28 dBm	-5.72 dB
3.700 GHz	3.701 GHz	100.000 kHz	3.700 05 GHz	-20.97 dBm	-7.97 dB
3.701 GHz	3.710 GHz	1.000 MHz	3.701 26 GHz	-28.57 dBm	-15.57 dB
3.710 GHz	3.720 GHz	1.000 MHz	3.711 54 GHz	-43.29 dBm	-18.29 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.776 49 GHz	-45.37 dBm	-5.37 dB

Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.446 63 GHz	-45.21 dBm	-5.21 dB
3.530 GHz	3.680 GHz	1.000 MHz	3.679 03 GHz	-38.20 dBm	-13.20 dB
3.680 GHz	3.689 GHz	1.000 MHz	3.689 00 GHz	-26.44 dBm	-13.44 dB
3.689 GHz	3.690 GHz	100.000 kHz	3.689 97 GHz	-27.60 dBm	-14.60 dB
3.690 GHz	3.700 GHz	1.000 MHz	3.691 77 GHz	16.45 dBm	-13.55 dB
3.700 GHz	3.701 GHz	100.000 kHz	3.700 06 GHz	-25.15 dBm	-12.15 dB
3.701 GHz	3.710 GHz	1.000 MHz	3.701 00 GHz	-27.43 dBm	-14.43 dB
3.710 GHz	3.720 GHz	1.000 MHz	3.710 75 GHz	-39.57 dBm	-14.57 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.724 35 GHz	-43.84 dBm	-3.84 dB

FR1 n48 / 10MHz / DFT-S OFDM / QPSK

Lowest Channel

1RB0



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.528 15 GHz	-45.14 dBm	-5.14 dB
3.530 GHz	3.540 GHz	1.000 MHz	3.539 60 GHz	-43.18 dBm	-18.18 dB
3.540 GHz	3.549 GHz	1.000 MHz	3.548 80 GHz	-31.16 dBm	-18.16 dB
3.549 GHz	3.550 GHz	100.000 kHz	3.550 00 GHz	-20.17 dBm	-7.17 dB
3.550 GHz	3.560 GHz	1.000 MHz	3.550 92 GHz	25.24 dBm	-4.76 dB
3.560 GHz	3.561 GHz	100.000 kHz	3.560 13 GHz	-53.53 dBm	-40.53 dB
3.561 GHz	3.570 GHz	1.000 MHz	3.561 61 GHz	-43.55 dBm	-30.55 dB
3.570 GHz	3.720 GHz	1.000 MHz	3.634 06 GHz	-44.72 dBm	-19.72 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.793 88 GHz	-45.24 dBm	-5.24 dB

1RBmax



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.527 75 GHz	-45.15 dBm	-5.15 dB
3.530 GHz	3.540 GHz	1.000 MHz	3.537 28 GHz	-44.11 dBm	-19.11 dB
3.540 GHz	3.549 GHz	1.000 MHz	3.548 56 GHz	-43.46 dBm	-30.46 dB
3.549 GHz	3.550 GHz	100.000 kHz	3.549 85 GHz	-53.52 dBm	-40.52 dB
3.550 GHz	3.560 GHz	1.000 MHz	3.559 13 GHz	25.27 dBm	-4.73 dB
3.560 GHz	3.561 GHz	100.000 kHz	3.560 01 GHz	-20.40 dBm	-7.40 dB
3.561 GHz	3.570 GHz	1.000 MHz	3.561 25 GHz	-31.78 dBm	-18.78 dB
3.570 GHz	3.720 GHz	1.000 MHz	3.571 57 GHz	-44.48 dBm	-19.48 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.816 65 GHz	-45.14 dBm	-5.14 dB

Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.529 15 GHz	-42.55 dBm	-2.55 dB
3.530 GHz	3.540 GHz	1.000 MHz	3.536 71 GHz	-38.17 dBm	-13.17 dB
3.540 GHz	3.549 GHz	1.000 MHz	3.548 96 GHz	-26.18 dBm	-13.18 dB
3.549 GHz	3.550 GHz	100.000 kHz	3.549 97 GHz	-27.66 dBm	-14.66 dB
3.550 GHz	3.560 GHz	1.000 MHz	3.555 40 GHz	16.11 dBm	-13.89 dB
3.560 GHz	3.561 GHz	100.000 kHz	3.560 04 GHz	-25.42 dBm	-12.42 dB
3.561 GHz	3.570 GHz	1.000 MHz	3.561 16 GHz	-27.27 dBm	-14.27 dB
3.570 GHz	3.720 GHz	1.000 MHz	3.571 57 GHz	-39.84 dBm	-14.84 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.806 76 GHz	-45.35 dBm	-5.35 dB

FR1 n48 / 10MHz / DFT-S OFDM / QPSK

Middle Channel

1RB0



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.484 60 GHz	-45.11 dBm	-5.11 dB
3.530 GHz	3.610 GHz	1.000 MHz	3.609 88 GHz	-44.44 dBm	-19.44 dB
3.610 GHz	3.619 GHz	1.000 MHz	3.618 73 GHz	-29.79 dBm	-16.79 dB
3.619 GHz	3.620 GHz	100.000 kHz	3.619 98 GHz	-21.05 dBm	-8.05 dB
3.620 GHz	3.630 GHz	1.000 MHz	3.620 82 GHz	24.73 dBm	-5.27 dB
3.630 GHz	3.631 GHz	100.000 kHz	3.630 12 GHz	-53.85 dBm	-40.85 dB
3.631 GHz	3.640 GHz	1.000 MHz	3.632 60 GHz	-43.72 dBm	-30.72 dB
3.640 GHz	3.720 GHz	1.000 MHz	3.647 23 GHz	-44.68 dBm	-19.68 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.763 71 GHz	-45.30 dBm	-5.30 dB

1RBmax



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.477 10 GHz	-44.99 dBm	-4.99 dB
3.530 GHz	3.610 GHz	1.000 MHz	3.604 61 GHz	-45.01 dBm	-20.01 dB
3.610 GHz	3.619 GHz	1.000 MHz	3.612 84 GHz	-42.96 dBm	-29.96 dB
3.619 GHz	3.620 GHz	100.000 kHz	3.619 59 GHz	-53.87 dBm	-40.87 dB
3.620 GHz	3.630 GHz	1.000 MHz	3.629 18 GHz	23.57 dBm	-6.43 dB
3.630 GHz	3.631 GHz	100.000 kHz	3.630 00 GHz	-19.84 dBm	-6.84 dB
3.631 GHz	3.640 GHz	1.000 MHz	3.631 31 GHz	-30.91 dBm	-17.91 dB
3.640 GHz	3.720 GHz	1.000 MHz	3.641 80 GHz	-43.99 dBm	-18.99 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.763 01 GHz	-45.27 dBm	-5.27 dB

Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.430 GHz	3.530 GHz	1.000 MHz	3.441 94 GHz	-45.28 dBm	-5.28 dB
3.530 GHz	3.610 GHz	1.000 MHz	3.609 16 GHz	-33.49 dBm	-8.49 dB
3.610 GHz	3.619 GHz	1.000 MHz	3.618 92 GHz	-25.86 dBm	-12.86 dB
3.619 GHz	3.620 GHz	100.000 kHz	3.619 95 GHz	-27.03 dBm	-14.03 dB
3.620 GHz	3.630 GHz	1.000 MHz	3.626 84 GHz	15.56 dBm	-14.44 dB
3.630 GHz	3.631 GHz	100.000 kHz	3.630 00 GHz	-25.23 dBm	-12.23 dB
3.631 GHz	3.640 GHz	1.000 MHz	3.631 09 GHz	-25.93 dBm	-12.93 dB
3.640 GHz	3.720 GHz	1.000 MHz	3.641 08 GHz	-34.46 dBm	-9.46 dB
3.720 GHz	3.820 GHz	1.000 MHz	3.810 96 GHz	-45.35 dBm	-5.35 dB