



广东森领通信科技有限公司

GUANGDONG SLEING COMM-TECH CO., LTD

承认书

SPECIFICATION APPROVAL SHEET

客 户 :

CUSTOMER

客 户 料 号 :

CUS PART NO

版次:

REV

X1

品 名 / 规格 :

1G 刀锋天线

单重:

SPECIFICATION

weight

供 方 料 号 :

SUP PART NO

SLEingA100630201-F07

日 期 :

DATE

2025.05.19

厂 商 核 准 :

SUP APPROVED

核准 APPROVED	结构审核 Structure audit	RF审核 RF CHECKED	品保审核 QA CHECKED	承办 DESIGNED
1 李仕俊	李仕俊	李仕俊	李仕俊	邓付荣

客 户 核 准 :

CUS APPROVED

核准 APPROVED	审核 CHECKED	品保审核 QA CHECKED	承办 DESIGNED

广东森领通信科技有限公司

GUANGDONG SLEING COMM-TECH CO., LTD

广东省东莞市松山湖园区工业东路24号6栋402室

Room 402, Building 6, No. 24, Industrial East Road, Songshan Lake Park,
Dongguan City, Guangdong Province

Tel: +86-076989208968

Fax: +86-0769-89208969

www.sleing.com


正本由承办单位保存

承认书项目表 (Spec Item)

序号(NO.)	项目(Project)	备注(Remark)	页码(Page)
1	承认书封面 (Spec Cover)		1
2	变更记录 (MODIFICATION RECORD SHEET)		2
3	承认书项目表 (Spec Item)		3
4	工程成品图 (Drawing)		4
5	电性测试报告 (Test Reports)		5
6	S参数测试 (S Parameter Test)		6
7	测试设备 (Test Setup)		7
8	方向图(Patten)		8
9	测试效率 (Test Efficiency)		9
10	产品包装规范 (Product packaging specification)		10
11	温度循环报告 (Temperature cycle report)		11-14
12	交变湿热报告 (Alternating humidity and heat report)		15-18
13	盐雾测试报告 (Salt spray test report)		19

Give clear indication of:

1. The contents of the acknowledgement shall be arranged in order according to the items in the check sheet.
2. The number of copies of the acceptance letter shall be printed according to the customer's requirements, and the SGS report shall be stamped with the engineering seal.
3. All materials shall be confirmed by the customer. Any material/process/changes that may affect product quality and environmental quality must be re-sent to the customer for confirmation before import.
4. SGS report is valid for one year.
5. According to the contents attached to the actual acknowledgement, check the check form: "Yes" is provided, "no" is provided according to customer requirements.

1



电性测试报告 Test Reports

Electrical Properties	
Frequency	860~930MHz
Impedance	50 Ohm Nominal
V.S.W.R	≤ 3.0
Return Loss	-6 dB Max
Radiation	Omni-directional
Gain (Peak)	3.0 $\pm$ 1.5dBi
Polarization	Linear, Vertical
Admitted Power	2 W
Connector	RP-SMA
Physical Properties	
Antenna Material	TPEE/PC/PBT
Antenna Color .	White
Cable Type	RG-178
Operating Temp	-40~ +85°C
Storage Temp	-40 ~ +85 °C

S参数测试 S Parameter Test



Agilent E5071C Network Analyzer



RF Antenna(Return Loss)




测试设备 Test Setup




方向图 Pattern

1.3 2D Radiation patterns test results (Passive Antenna)



1.5 3D Radiation patterns test results (Passive Antenna)

3D



测试效率

Test Efficiency

Test Point ID	Freq. (MHz)	Gain (dBi)	Efficiency (%)
1	860.0	3.72	67.1%
2	865.0	3.98	70.0%
3	870.0	3.75	69.1%
4	875.0	3.54	66.1%
5	880.0	3.70	66.8%
6	885.0	3.67	67.4%
7	890.0	3.39	64.0%
8	895.0	3.25	61.2%
9	900.0	3.49	63.0%
10	905.0	3.36	61.3%
11	910.0	3.21	57.1%
12	915.0	3.23	54.8%
13	920.0	2.91	53.7%
14	925.0	2.59	51.6%
15	930.0	2.22	49.2%

实物图片





产品包装规范

Product packaging specification

日期/Date: 2023.02.25

page:

1 of 1

成品名称 Name of finished product	1G刀锋天线	客户 customer			
成品料号 Finished product number	SLEingA100630201-F07	版本 REV.	A/0		
 单PCS天线 (2) 50PCS装一PE袋，PE袋上需标贴产品标签，以标示产品名称、规格、数量、日期并热封处理。  (3) 装箱：每箱装10-20包（共500-1000PCS）  (4) 外箱均需贴产品标签，以标示产品名称、规格、数量、日期。 (5) 每批次产品均需附上“出厂检验报告”。 (6) 储存条件：温度：-5℃-+30℃，湿度：20%-70%，年限一年。					
承办 DESIGNED	胡赵海（Jreey）	审核 CHECKED	胡赵海（Jreey）	核准 APPROVED	朱正锐（Jongrei）