

Date: 2000-02-28

TEST REPORT

Page 1 of 4

No.: HM102184

APPLICANT: (CODE : EWI001)

EWIG INDUSTRIES CO. LTD.
13/F., Houtex Ind'l Bldg.,
16 Hung To Road, Kwun Tong, Kowloon,
HONG KONG.

DATE OF SAMPLES RECEIVED:

2000-02-03

TEST DURATION

2000-02-25

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: Wireless IN/OUT Temperature
Manufacturer: EWIG MFG. CO., LTD
Model Number: 358F11
Brand Name: N/A
Rating: 3Vd.c., 0.005A, 0.015W
Origin: China

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiator.

RESULT/ REMARK:

Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the clause 15.109(a) for the Receiver Section of Federal Communication Rules and Regulation Part 15 and ANSI C63.4-1992 Section 12.1.1.1-2.

TEST EQUIPMENT AUDIT:

Please see Appendix A

Law Man Kit
Testing Engineer

Kitty Choy
Verify by

Patrick Wong
Patrick Wong
for Managing Director

Date: 2000-02-28

TEST REPORT

Page 2 of 4

No.: HM102184

TEST SUMMARY

- (A) Measurement of Radiated EmissionsSatisfactory
- (B) Line Conducted Voltage TestNot applicable

TEST DATA

Please refer to the attached result sheets.

Date: 2000-02-28

TEST REPORT

Page 3 of 4

No.: HM102184

*** RECEIVER SECTION ***

(A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109(a)

TEST CONDITION : Normal

TEST DATE : 2000.02.25

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)		FCC Limit	
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m	
433.6	19.5	H	+	19.5	39.0	89.1	200.0
867.2	<1.0		+	28.5	<29.5	<29.9	200.0
1300.8	<1.0		+	25.8	<26.8	<21.8	500.0
1734.4	<1.0		+	26.2	<27.2	<22.9	500.0
2168.0	<1.0		+	28.0	<29.0	<28.2	500.0
2601.5	<1.0		+	28.5	<29.5	<29.9	500.0
3035.1	<1.0		+	30.6	<31.6	<38.0	500.0
3468.7	<1.0		+	32.0	<33.0	<44.7	500.0
3902.3	<1.0		+	33.2	<34.0	<51.2	500.0
4335.9	<1.0		+	33.3	<34.3	<51.9	500.0

=====SUMMARY=====

All data is within limits

=====

Broad-band Antennas were used and both polarizations of emissions were measured

Polarizations at highest reading indicated as:

H -- Horizontal

V -- Vertical

=====

NOTES FOR THE RADIATION MEASUREMENT

- (1) Test site facility:
Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC Rules.
- (2) Distance between the ET and measuring antenna:
3 meters.
- (3) Measuring instrumentations:
CISPR Quasi-peak type field strength meter (25 MHz - 1000 MHz and 1GHz-18GHz).6dB bandwidth set at 120KHz. Also, peak level of the fundamental emissions was measured in order to determine compliance with the 20dB peak to average limit specified in Section 15.231 of the FCC new Rules.
- (4) Measuring antenna:
Broad band antenna for the frequency range 25-1000 MHz, connected with 10 meters coaxial cable.Horn antenna for the frequency range 1-18 GHz, connected with high frequency coaxial cable.Cable loss of the coaxial cable. Cable included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarizations.
- (5) Frequency range scanned:
The frequency range from 25 MHz to 1000 MHz had been searched. Readings of the highest emissions relating to the limit were reported as above.
- (6) Arrangement of EUT:
During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.
- (7) Measuring Procedure:
In accordance with the relevant clauses of the FCC Rules Part 15 section 15.109(a) and ANSI C63.4:1992 section 12.1.1.1-2.
For superregenerative receivers, an independent signal generator had been used to radiated an unmodulated wave (cw) signal to the receiver at its operating frequency in order to “cohere” or resolve the individual components of the characteristic broadband emission from such a receiver. The level of such signal may need to be adjusted in order to accomplish this.
- (8) Measuring Uncertainty:
The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 300MHz = $\pm 3.7\text{dB}$, 300MHz to 1000MHz = $\pm 3.0\text{dB}/-2.7\text{dB}$.
1GHz to 18GHz = $\pm 3.3\text{dB}/-3.4\text{dB}$.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC’s Equipment Authorization Program. This test itself is not an Approval Test.

*** End of Document ***