

CCT R&D Ltd.

Application
For
Certification

5.8GHz Frequency Hopping Spread Spectrum Cell Dock with Bluetooth

(FCC ID: NC8SD7505)

0609839
KL/ Ann Choy
August 29, 2006

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2741 1693 Website: www.hk.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Security Code Information
<i>EXHIBIT 10:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

CCT R&D Ltd. - MODEL: SD7505

FCC ID: NC8SD7505

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DSS-Part 15 Spread Spectrum Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :
date

Company Name agrees to notify the Commission by:
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [04-05-05 Edition] provision.

Report prepared by:

Lam Chun Cheong, Kenneth
Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone: 852-2173-8474
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 <u>Summary of test results</u>	2
2.0 <u>General Description</u>	4
2.1 Product Description	4
2.2 Related Submittal(s) Grants	5
2.3 Test Methodology	5
2.4 Test Facility	5
3.0 <u>System Test Configuration</u>	7
3.1 Justification	7
3.2 EUT Exercising Software	7
3.3 Support Equipment List and Description	8
3.4 Measurement Uncertainty	9
3.5 Equipment Modification	9
4.0 <u>Measurement Results</u>	11
4.1 Maximum Conducted Output Power at Antenna Terminals	11
4.2 Maximum 20 dB RF Bandwidth	12
4.3 Minimum Number of Hopping Frequencies	13
4.4 Minimum Hopping Channel Carrier Frequency Separation	14
4.5 Average Time of Occupancy	15
4.6 Out of Band Conducted Emissions	16
4.7 Out of Band Radiated Emissions	17
4.8 Transmitter Radiated Emissions in Restricted Bands	18
4.9 Field Strength Calculation	19
4.10 Radiated Emission Configuration Photograph - Cell Dock	20
4.11 Radiated Emission Data - Cell Dock	21
4.12 AC Line Conducted Emission	25
4.13 Line Conducted Configuration Photograph - Cell Dock	26
4.14 Line Conducted Emission Configuration Data	27
4.15 Radiated Emission from Digital Section of Transceiver	28
4.16 Transmitter Duty Cycle Calculation and Measurements	30
5.0 <u>Equipment Photographs</u>	32
6.0 <u>Product Labelling</u>	34
7.0 <u>Technical Specifications</u>	36
8.0 <u>Instruction Manual</u>	38
9.0 <u>Security Code Information</u>	40
10.0 <u>Confidentiality Request</u>	42

INTERTEK TESTING SERVICES

List of attached file

Exhibit type	File Description	filename
Cover Letter	Confidentiality Request	request.pdf
Test Report	Test Report	report.pdf
Test Report	Maximum Output Power Plot	maxop.pdf
Test Report	20 dB Bandwidth Plot	20dB.pdf
Test Report	Minimum Number of Hopping Frequencies	chno.pdf
Test Report	Minimum Hopping Channel Carrier Frequency Separation	fsepa.pdf
Test Report	Average Channel Occupancy Time	avetime.pdf
Test Report	Out Band Antenna Conducted Emission Plot	obantcon.pdf
Test Report	Duty Cycle Calculation and Measurement	dcc.pdf
Test Report	Conducted Emission Test Result	conduct.pdf
Test Setup Photo	Radiated Emission for Cell Dock	config photos.doc
Test Setup Photo	Conducted Emission	config photos.doc
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
RF Exposure Info	RF Safety	RF exposure info.pdf
Operation Description	Technical Description	descri.pdf
Operation Description	Security Code Information	security code information.pdf

EXHIBIT 1
SUMMARY OF TEST RESULTS

INTERTEK TESTING SERVICES

1.0 Summary of Test

CCT R&D Ltd. - MODEL: SD7505

FCC ID: NC8SD7505

TEST	REFERENCE	RESULTS
Max. Output Power	15.247(b)	Pass
Max. 20 dB Bandwidth	15.247(a)(1)	Pass
Min. No. of Hopping Frequencies	15.247(a)(1)	Pass
Min. Hopping Channel Carrier Frequency Separation	15.247(a)(1)	Pass
Average Time of Occupancy	15.247(a)(1)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

EXHIBIT 2
GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

2.0 **General Description**

2.1 Product Description

The SD7505 is a cell dock which is an accessory of a 5.8GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID. It operates at frequency range of 5725.809MHz-5848.889MHz with 139 physical hopping frequencies and 75 logical hopping frequencies. On the other hand, it has another RF module for Bluetooth that operates at frequency range of 2402MHz-2480MHz.

With Bluetooth and 5.8GHz wireless communications enable, the cell dock allows a user uses a cordless handset to dial out or receive cellular phone calls via the cellular network. It has a "Registration" button on the bottom to register itself to a base unit of 5.8GHz cordless phone, and it also has a "Bluetooth" button that manages Bluetooth connections to a Bluetooth-equipped mobile device. Besides, connecting with a Motorola compatible cellular phone, it is a cradle and is used for downloading phonebook data and charging the cellular phone only.

The antennas used in unit is integral, and the test sample is a prototype.

The circuit description and frequency hopping algorithm is saved with filename: descri.pdf. The receiver input bandwidth provided by the manufacturer is 900kHz.

2.2 Related Submittal(s) Grants

This is an application for certification of a DSS - Part 15 Spread Spectrum Transmitter. One transmitter is included in this application. The device is also subject to Part 68 Registration. On the other hand, a 2.4GHz transmitter - Bluetooth, a composite device subject to an additional equipment authorization, has the same as this FCC ID: NC8SD7505, and has been filed at the same time.

Part of a system operates with another device, 5.8GHz FHSS cordless phone, that requires a certification application. The related application has been granted under FCC ID: NC8SD7581.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in 47 CFR Part 2.

2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

EXHIBIT 3
SYSTEM TEST CONFIGURATION

3.0 **System Test Configuration**

3.1 Justification

For emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The cell dock was powered by an AC adaptor.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the cell dock unit attaches to peripherals, they are connected and operational (as typical as possible). The base unit and the handset are remotely located as far from the antenna and the cell dock as possible to ensure full power transmission from the cell dock. Else, the cell dock is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

HARDWARE:

The unit was operated standalone. An AC adaptor (provided with the unit) was used to power the device. Its description is listed below.

- (1) An AC adaptor (120VAC to 9VDC 700mA, Model: DU41090070C)

CABLES:

There are no special cables necessary for compliance of this product.

OTHERS:

- (1) A 5.8GHz FHSS Cordless Phone with Caller ID, Speakerphone, and Digital Answering Machine, Model: SD7581, S/N: 718VGE02B4, FCC ID: NC8SD7581 (Supplied by Client)
- (2) Cellular Phone, Model: Motorola V66 GPRS, CMII ID: 2001CP0157 (Supplied by Client)

INTERTEK TESTING SERVICES

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification


Any modifications installed previous to testing by CCT R&D Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Lam Chun Cheong, Kenneth
Senior Lead Engineer
Intertek Testing Services Hong Kong Ltd.
Agent for CCT R&D Ltd.*



Signature

August 29, 2006 Date

EXHIBIT 4
MEASUREMENT RESULTS

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1) :

- ☐ The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.
- ☒ The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW>20dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyser.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

(Cell Dock) Antenna Gain = 0 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 5725.809	18.77	75.3
Middle Channel: 5787.350	19.98	99.5
High Channel: 5848.889	18.87	77.1

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: ☒ included in OFFSET function
☐ added to SA raw reading

dBm max. output level = 19.98 dBm (30dBm or less)

Please refer to the attached plots for details:

Plot D1A: Low Channel Output Power
Plot D1B: Middle Channel Output Power
Plot D1C: High Channel Output Power

For electronic filing, the above plots are saved with filename: maxop.pdf

For RF Safety, the information is saved with filename: RF exposure info.pdf.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1)(ii):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 20 dB lower than PEAK level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

(Cell Dock)	
Frequency (MHz)	20 dB Bandwidth (kHz)
5848.889	696

Refer to the following plots for 20 dB bandwidth sharp:

Plot D2A: Low Channel 20 dB RF Bandwidth

Plot D2B: Middle Channel 20 dB RF Bandwidth

Plot D2C: High Channel 20 dB RF Bandwidth

Requirement: the maximum 20dB bandwidth is 1MHz

For electronic filing, the above plots are saved with filename: 20dB.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(ii) :

The RF passband of the EUT was divided into 7 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes in each band. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

Cell Dock	
No. of hopping channels	75

Minimum Requirements: at least 75 hopping channels for 5725MHz-5850MHz.

For electronic filing, the above plots are saved with filename: chno.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) :

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[] 25 kHz [x] 20 dB bandwidth of hopping channel: 696kHz

Cell Dock	
Channel Separation	896 kHz

Plot D4: Channel 70 and Channel 71

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: fsepa.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.5 Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)(ii)

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (20 seconds for 902-928 MHz devices, if the 20dB bandwidth is less than 250kHz, 10 seconds for 902-928 MHz if the 20dB bandwidth is or greater than 250kHz, "0.4 seconds x Number of hopping channels employed" seconds for 2400-2483.5 MHz, 30 seconds for 5725-5850 MHz). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Average 0.4 seconds maximum occupancy in 30 seconds for 5725MHz-5850MHz.

Cell Dock (Worst-case: double-slots operation)	
Average Occupancy Time = $1\text{ms} \times 40 \times 2$	80 ms

Refer to attached spectrum analyzer plot D5A & plots D5B-C(single-slot operation).

For electronic filing, the above plots are saved with filename: avetime.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.6 Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot D6A1 - D6A2: Low Channel Emissions
Plot D6B1 - D6B2: Middle Channel Emissions
Plot D6C1 - D6C2: High Channel Emissions
Plot D6D1 - D6D2: Modulation Products Emission*

The plots showed the 2nd harmonic and modulation products at the band edges of 5725MHz and 5850MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

*These 2 plots are shown the worst-case which has been already considered between enable and disable the hopping function of the EUT.

For electronic filing, the above plots are saved with filenames: obantcon.pdf

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.7 Out of Band Radiated Emissions (for emissions in 4.6 above that are less than 20 dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, all emissions more than 20dB below fundamental
- ☐ See attached data sheet

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.8 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.9 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.10 Radiated Emission Configuration Photograph - Cell Dock

Worst Case Radiated Emission
at
22903.237 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505


Date of Test: May 19-July 14, 2006

4.11 Radiated Emission Data - Cell Dock

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 16.9 dB margin compare with the peak limit

TEST PERSONNEL:



Tester Signature

Jess Tang, Lead Engineer
Typed/Printed Name

August 29, 2006
Date

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505
Mode : TX-Channel 1

Date of Test: May 19-July 14, 2006

Table 1, Cell Dock

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	*11451.619	37.8	33	40.8	45.6	33.9	11.7	54.0	-42.3
H	*22903.237	53.8	35	38.3	57.1	33.9	23.2	54.0	-30.8
H	*31523.260	50.6	35	40.4	56.0	33.9	22.1	54.0	-31.9

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 16.9dB margin at 22903.237MHz.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505
Mode : TX-Channel 70

Date of Test: May 19-July 14, 2006

Table 2, Cell Dock

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	*11574.701	38.4	33	40.5	45.9	33.9	12.0	54.0	-42.0

- NOTES:
1. Peak detector is used for the emission measurement.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505
Mode : TX-Channel 139

Date of Test: May 19-July 14, 2006

Table 3, Cell Dock

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
H	*11697.779	38.6	33	40.5	46.1	33.9	12.2	54.0	-41.8

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.12 AC Line Conducted Emission, FCC Rule 15.207:

☐ Not required; battery operation only

☒ Test data attached

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.13 Line Conducted Configuration Photograph - Cell Dock

Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006


4.14 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

TEST PERSONNEL:



Tester Signature

Jess Tang, Lead Engineer
Typed/Printed Name

August 29, 2006
Date

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.15 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref: 15.109

- ☐ Not required - No digital part
- ☒ Test results are attached
- ☐ Included in the separated DOC report.

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505
Mode: Talk

Date of Test: May 19-July 14, 2006

Table 7, Cell Dock

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	34.828	35.6	16	10.0	29.6	40.0	-10.4
V	43.009	35.4	16	10.0	29.4	40.0	-10.6
V	51.200	33.6	16	11.0	28.6	40.0	-11.4
V	59.486	34.2	16	10.0	28.2	40.0	-11.8
H	231.384	25.4	16	18.0	27.4	46.0	-18.6
H	239.429	24.0	16	19.0	27.0	46.0	-19.0
H	247.485	22.8	16	20.0	26.8	46.0	-19.2
H	256.308	21.0	16	21.0	26.0	46.0	-20.0

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.

Test Engineer: Jess Tang

INTERTEK TESTING SERVICES

Company: CCT R&D Ltd.
Model: SD7505

Date of Test: May 19-July 14, 2006

4.16 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Cell Dock:

Duty cycle (DC) = Maximum ON time in 100ms/100ms
= (1ms x 2)/100ms for double-slots operation

Duty cycle correction, dB = $20 \times \log(\text{DC})$
= $20 \times \log(0.02)$
= -33.9 dB

X	See attached spectrum analyzer chart (s) for transmitter timing Base Unit: Plot D7
	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

For electronic filing, the above plots are saved with filenames: dcc.pdf

EXHIBIT 5
EQUIPMENT PHOTOGRAPHS

5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

EXHIBIT 6
PRODUCT LABELLING

6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename:
label.pdf

EXHIBIT 7
TECHNICAL SPECIFICATIONS

7.0 **Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 8
INSTRUCTION MANUAL

8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is on page iii of the Instruction Manual.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 9
SECURITY CODE INFORMATION

9.0 **Security code information**

For electronic filing, a security code information is saved with filename: security code information.pdf

EXHIBIT 10
CONFIDENTIALITY REQUEST

10.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.