



FCC ID: NCI-P650IVF02-0
Report No.: T180801N05-MF

Page: 1 / 8
Rev.: 00

IEEE C95.1
KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

60 Inch TFT-LCD Display

Model: P650IVF02.0

Trade Name: AUO

Issued to

VIA Technologies, Inc.
8F, No.535, Zhongzheng Rd., Xindian Dist, New Taipei City 231,
Taiwan(R.O.C)

Issued By

Compliance Certification Services Inc.
Tainan Laboratory
No.8, Jiucengling, Xinhua Dist., Tainan City 712,
Taiwan (R.O.C.)
TEL: 886-6-580-2201
FAX: 886-6-580-2202
<http://www.ccsrf.com>
E-Mail : service@ccsrf.com
Issued Date: September 25, 2018

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T180801N05-MF

Page: 2 / 8
Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 25, 2018	Initial Issue	ALL	Daphne Liang



Report No.: T180801N05-MF

Page: 3 / 8
Rev.: 00

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. LIMIT	5
3. EUT SPECIFICATION.....	5
4. TEST RESULTS	7
5. MAXIMUM PERMISSIBLE EXPOSURE.....	8



Report No.: T180801N05-MF

Page: 4 / 8
Rev.: 00

1. TEST RESULT CERTIFICATION

We hereby certify that:

The equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirement of the applicable standards. The test record, data evaluation and Equipment under Test (EUT) configurations represented herein are true and accurate accounts of the measurement of the sample's RF characteristics under the conditions specified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
IEEE C95.1 2005 KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted

Approved by:

Jeter Wu
Assistant Manager

Reviewed by:

Eric Huang
Section Manager

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

3. EUT SPECIFICATION

EUT	60 Inch TFT-LCD Display
Model	P650IVF02.0
Trade Name	
Model Discrepancy	N/A
Frequency band (Operating)	☒ 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz ☒ 802.11a, 802.11n HT20 : 5180MHz ~ 5240MHz; 5745 ~ 5825MHz 802.11n HT40 : 5190MHz ~ 5230MHz; 5755 ~ 5795MHz 802.11ac VHT80 : 5210MHz; 5755MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna Specification	Antenna (1TX1RX), 2pcs Manufacturer: WIFI-Link Technologies Inc. Type: PCB Mode: WLDF-5024-07-07 Gain : 5dBi (2.4G) / 7dBi (5G) Antenna Gain 2.4GHz 5.00 dBi (Numeric gain: 3.16) worst Antenna Gain 5GHz 7.00 dBi (Numeric gain: 5.01) worst
Maximum Average output power	IEEE 802.11b Mode : 18.03 dBm (63.533 mW) IEEE 802.11g Mode : 13.00 dBm (19.953 mW) IEEE 802.11n HT20 Mode : 12.39 dBm (17.338 mW) IEEE 802.11n HT40 Mode : 12.15 dBm (16.406 mW) IEEE 802.11a Mode : 13.15 dBm (20.654 mW) IEEE 802.11n HT20 Mode: 13.49 dBm (22.336 mW) IEEE 802.11n HT40 Mode: 12.45 dBm (17.579 mW) IEEE 802.11AC HT80 Mode: 12.02 dBm (15.922 mW)



Report No.: T180801N05-MF

Page: 6 / 8
Rev.: 00

Maximum Tune up Power	IEEE 802.11b Mode :	19.03 dBm	(79.983 mW)
	IEEE 802.11g Mode :	14.00 dBm	(25.119 mW)
	IEEE 802.11n HT20 Mode :	13.39 dBm	(21.827 mW)
	IEEE 802.11n HT40 Mode :	13.15 dBm	(20.654 mW)
	IEEE 802.11a Mode :	14.15 dBm	(26.002 mW)
	IEEE 802.11n HT20 Mode:	14.49 dBm	(28.120 mW)
	IEEE 802.11n HT40 Mode:	13.45 dBm	(22.131 mW)
	IEEE 802.11AC HT80 Mode:	13.02 dBm	(20.045 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A		

Notes: For 2.4GHz and 5GHz could not be use as transmit/receive at the same time.



Report No.: T180801N05-MF

Page: 7 / 8
Rev.: 00

4. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

IEEE 802.11b Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Low	2412	79.983	3.16	20	0.0503	1	Pass

IEEE 802.11g Mode :

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2437	25.119	3.16	20	0.0158	1	Pass

IEEE 802.11n HT 20 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2437	21.827	3.16	20	0.0137	1	Pass

IEEE 802.11n HT 40 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	2437	20.654	3.16	20	0.0130	1	Pass

IEEE 802.11a Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	5785	26.002	5.01	20	0.0259	1	Pass

IEEE 802.11n HT20 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
High	5825	28.120	5.01	20	0.0280	1	Pass

IEEE 802.11n HT40 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
High	5795	22.131	5.01	20	0.0221	1	Pass

IEEE 802.11AC HT80 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Mid	5775	20.045	5.01	20	0.0200	1	Pass