


FCC RF Test Report

APPLICANT : Option nv
EQUIPMENT : GTM671W
BRAND NAME : Option
MODEL NAME : MO6712
FCC ID : NCMOMO6712
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS 8) : 1.12 W
GSM850 (EDGE 8) : 0.36 W
GSM1900 (GPRS 8) : 0.98 W
GSM1900 (EDGE 8) : 0.51 W
WCDMA Band V (RMC 12.2Kbps) : 0.11 W
WCDMA Band II (RMC 12.2Kbps) : 0.26 W
EMISSION DESIGNATOR : GMSK : 248KGXW
8PSK : 244KG7W
QPSK : 4M16F9W

The product was received on Nov. 26, 2010 and completely tested on Apr. 02, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	6
1.4 Testing Site.....	7
1.5 Applied Standards	7
1.6 Ancillary Equipment List.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	10
3 TEST RESULT	11
3.1 Conducted Output Power Measurement.....	11
3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	13
3.3 Occupied Bandwidth Measurement	17
3.4 Band Edge Measurement.....	24
3.5 Conducted Emission Measurement	31
3.6 Field Strength of Spurious Radiation Measurement	47
3.7 Frequency Stability Measurement.....	61
4 LIST OF MEASURING EQUIPMENT	68
5 UNCERTAINTY OF EVALUATION	69
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG0N2627	Rev. 01	Initial issue of report	Apr. 20, 2011



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 29.53 dB at 5636 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

Option nv

Gaston Geenslaan 14, 3001 Leuven, Belgium

1.2 Manufacturer

Option nv

Gaston Geenslaan 14, 3001 Leuven, Belgium

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GTM671W
Brand Name	Option
Model Name	MO6712
FCC ID	NCMOMO6712
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.46 dBm GSM1900 : 29.11 dBm WCDMA Band V : 22.21 dBm WCDMA Band II : 23.40 dBm
Maximum ERP/EIRP	GSM850 (GPRS 8) : 1.12 W (30.51 dBm) GSM850 (EDGE 8) : 0.36 W (25.51 dBm) GSM1900 (GPRS 8) : 0.98 W (29.91 dBm) GSM1900 (EDGE 8) : 0.51 W (27.06 dBm) WCDMA Band V (RMC 12.2Kbps) : 0.11 W (20.26 dBm) WCDMA Band II (RMC 12.2Kbps) : 0.26 W (24.20 dBm)
Antenna Type	Fixed External Antenna
Antenna Peak Gain	824 ~ 849 MHz : 1.0 dBi 1850~1910 MHz : 2.0 dBi
HW Version	3.1
SW Version	1.7.3.0
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM HSUPA : BPSK
Type of Emission	GMSK : 248KGXW 8PSK : 244KG7W QPSK : 4M16F9W
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH05-HY	722060/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5
- ♦ KDB 412172 D01 Determining ERP and ERIP v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (Certification), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS 8 Link ■ EDGE 8 Link	■ GPRS 8 Link ■ EDGE 8 Link
GSM 1900	■ GPRS 8 Link ■ EDGE 8 Link	■ GPRS 8 Link ■ EDGE 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

Note:


1. The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, the co-location test modes are not required.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.72	31.69	31.49	28.90	28.95	28.67
GPRS 8	32.46	32.41	32.23	28.97	29.11	28.94
GPRS 10	31.68	31.69	31.63	28.66	28.82	28.38
GPRS 12	28.79	28.67	28.51	25.33	25.68	25.82
EGPRS 8	27.16	27.09	27.14	26.26	26.24	26.24
EGPRS 10	26.46	26.34	26.36	24.90	25.09	25.04
EGPRS 12	23.36	23.48	23.55	21.63	22.01	22.03

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.21	22.03	21.90	23.40	23.31	22.80
HSDPA Subtest-1	21.52	21.42	21.50	22.88	22.88	22.28
HSDPA Subtest-2	21.59	21.44	21.50	22.79	22.87	22.24
HSDPA Subtest-3	21.59	21.03	21.04	22.46	22.42	21.84
HSDPA Subtest-4	21.64	20.99	21.10	22.44	22.32	21.77
HSUPA Subtest-1	21.04	20.97	21.05	22.17	22.12	22.41
HSUPA Subtest-2	20.02	19.82	19.92	20.97	20.90	20.93
HSUPA Subtest-3	20.48	20.10	20.24	21.56	21.50	21.23
HSUPA Subtest-4	20.43	20.12	20.21	21.19	21.20	20.84
HSUPA Subtest-5	20.95	20.60	21.04	22.16	22.53	21.78

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GPRS 8)	128 (Low)	824.2	32.46	1.76
	189 (Mid)	836.4	32.41	1.74
	251 (High)	848.8	32.23	1.67
GSM850 (EDGE 8)	128 (Low)	824.2	27.16	0.52
	189 (Mid)	836.4	27.09	0.51
	251 (High)	848.8	27.14	0.52
WCDMA Band V (RMC 12.2Kbps)	4132 (Low)	826.4	22.21	0.17
	4182 (Mid)	836.4	22.03	0.16
	4233 (High)	846.6	21.90	0.15

PCS Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM1900 (GPRS 8)	512 (Low)	1850.2	28.97	0.79
	661 (Mid)	1880.0	29.11	0.81
	810 (High)	1909.8	28.94	0.78
GSM1900 (EDGE 8)	512 (Low)	1850.2	26.26	0.42
	661 (Mid)	1880.0	26.24	0.42
	810 (High)	1909.8	26.24	0.42
WCDMA Band II (RMC 12.2Kbps)	9262 (Low)	1852.4	23.40	0.22
	9400 (Mid)	1880.0	23.31	0.21
	9538 (High)	1907.6	22.80	0.19

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

The ERP/EIRP test method follows the KDB 412172 D01, Determining ERP and EIRP v01, and radiated method uses substitution method according to ANSI / TIA / EIA-603-C-2004 and shown in clauses of 3.2.3 to 3.24.

When the EUT power is measured using a direct connection between the transmitter antenna port and the measurement instrumentation via a coaxial cable (conducted test), and the transmit antenna gain is a known quantity, then the ERP/EIRP can be calculated by direct application of equation ($ERP/EIRP = \text{conducted power} + \text{antenna gain} - \text{cable loss}$) and using the relationships defined in equation ($ERP = EIRP - 2.15\text{dB}$).

The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on an non-conductive rotating platform with 0.8 meter height in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RBW= 3MHz,VBW= 3MHz, and peak detector settings.
2. During the measurement, the EUT was enforced in maximum power and linked with a base station. The highest emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by dipole antenna (substitution antenna) at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$.

3.2.4 Test Setup



3.2.5 Test Result of ERP

GSM850 (GPRS 8) Radiated Power ERP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	ERP (dBm)	ERP (W)
824.2	32.46	1.0	0.8	30.51	1.12
836.4	32.41	1.0	0.8	30.46	1.11
848.8	32.23	1.0	0.8	30.28	1.07

* ERP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB) - 2.15

GSM850 (EDGE 8) Radiated Power ERP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	ERP (dBm)	ERP (W)
824.2	27.16	1.0	0.8	25.51	0.36
836.4	27.09	1.0	0.8	25.14	0.33
848.8	27.14	1.0	0.8	25.19	0.33

* ERP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB) - 2.15

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	ERP (dBm)	ERP (W)
826.40	22.21	1.0	0.8	20.26	0.11
836.40	22.03	1.0	0.8	20.08	0.10
846.60	21.90	1.0	0.8	19.95	0.10

* ERP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB) - 2.15

Test Result of EIRP

GSM1900 (GPRS 8) Radiated Power EIRP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	EIRP (dBm)	EIRP (W)
1850.2	28.97	2.0	1.2	29.77	0.95
1880.0	29.11	2.0	1.2	29.91	0.98
1909.8	28.94	2.0	1.2	29.74	0.94

* EIRP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB)

GSM1900 (EDGE 8) Radiated Power EIRP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	EIRP (dBm)	EIRP (W)
1850.2	26.26	2.0	1.2	27.06	0.51
1880.0	26.24	2.0	1.2	27.04	0.51
1909.8	26.24	2.0	1.2	27.04	0.51

* EIRP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB)

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP					
Frequency (MHz)	Max. Conducted Power (dBm)	Antenna gain (dBi)	Cable loss of antenna gain (dB)	EIRP (dBm)	EIRP (W)
1852.40	23.40	2.0	1.2	24.20	0.26
1880.00	23.31	2.0	1.2	24.11	0.26
1907.60	22.80	2.0	1.2	23.60	0.23

* EIRP = Max. Conducted Power (dBm) + Antenna gain (dBi) - Cable loss of antenna gain (dB)

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup




3.3.5 Test Result (Plots) of Occupied Bandwidth

Band :	GSM 850	Power Stage :	High
Test Mode :	GPRS 8 Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 13.JAN.2011 10:07:17

26dB Bandwidth Plot on Channel 189



Date: 13.JAN.2011 10:05:53



Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 189


Date: 13.JAN.2011 12:11:20

26dB Bandwidth Plot on Channel 189


Date: 13.JAN.2011 12:09:57



Band :	GSM 1900	Power Stage :	High
Test Mode :	GPRS 8 Link		

99% Occupied Bandwidth Plot on Channel 661


Date: 13.JAN.2011 11:34:42

26dB Bandwidth Plot on Channel 661


Date: 13.JAN.2011 11:33:18



Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		


99% Occupied Bandwidth Plot on Channel 661

Date: 13.JAN.2011 11:58:18


26dB Bandwidth Plot on Channel 661

Date: 13.JAN.2011 11:56:54

Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 4182



Date: 13.JAN.2011 14:07:28

26dB Bandwidth Plot on Channel 4182



Date: 13.JAN.2011 14:06:05



Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 9400

Date: 13.JAN.2011 13:50:31

26dB Bandwidth Plot on Channel 9400

Date: 13.JAN.2011 13:49:08

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly $BW/100$.


3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Power Stage :	High
Test Mode :	GPRS 8 Link		

Lower Band Edge Plot on Channel 128



Date: 13.JAN.2011 10:09:17


Higher Band Edge Plot on Channel 251




Date: 13.JAN.2011 10:09:46



Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 128


Date: 13.JAN.2011 12:13:21

Higher Band Edge Plot on Channel 251


Date: 13.JAN.2011 12:13:49



Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link		

Lower Band Edge Plot on Channel 512

Date: 13.JAN.2011 11:36:43


Higher Band Edge Plot on Channel 810

Date: 13.JAN.2011 11:37:11




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 512



Date: 13.JAN.2011 12:00:18


Higher Band Edge Plot on Channel 810




Date: 13.JAN.2011 12:00:46



Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 4132


Date: 13.JAN.2011 14:09:31

Higher Band Edge Plot on Channel 4233


Date: 13.JAN.2011 14:09:59



Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 9262

Date: 13.JAN.2011 13:52:34

Higher Band Edge Plot on Channel 9538

Date: 13.JAN.2011 13:53:02

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup




3.5.5 Test Result (Plots) of Conducted Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 13.JAN.2011 10:40:18

Conducted Emission Plot between 1GHz ~ 3GHz


Date: 13.JAN.2011 10:40:38




Conducted Emission Plot between 3GHz ~ 7GHz




Date: 13.JAN.2011 10:40:52

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2011 10:41:06

Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		


Conducted Emission Plot between 30MHz ~ 1GHz


Date: 13.JAN.2011 11:23:48

Conducted Emission Plot between 1GHz ~ 3GHz



Date: 13.JAN.2011 11:24:06

Conducted Emission Plot between 3GHz ~ 7GHz




Date: 13.JAN.2011 11:24:21

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2011 11:24:35

Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 13.JAN.2011 11:45:04

Conducted Emission Plot between 1GHz ~ 3GHz


Date: 13.JAN.2011 11:45:19




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2011 11:45:55


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 13.JAN.2011 11:46:09




Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.JAN.2011 11:46:23




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz


Date: 13.JAN.2011 12:05:04

Conducted Emission Plot between 1GHz ~ 3GHz

Date: 13.JAN.2011 12:05:19

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2011 12:05:37

Conducted Emission Plot between 7GHz ~ 13.6GHz


Date: 13.JAN.2011 12:05:52




Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 13.JAN.2011 12:06:06

Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 13.JAN.2011 14:15:41

Conducted Emission Plot between 1GHz ~ 3GHz


Date: 13.JAN.2011 14:15:59




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2011 14:16:13


Conducted Emission Plot between 7GHz ~ 9GHz




Date: 13.JAN.2011 14:16:27




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz


Date: 13.JAN.2011 14:00:25

Conducted Emission Plot between 1GHz ~ 3GHz

Date: 13.JAN.2011 14:00:39

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 13.JAN.2011 14:01:03

Conducted Emission Plot between 7GHz ~ 13.6GHz


Date: 13.JAN.2011 14:01:17



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 13.JAN.2011 14:01:31

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	21~23°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.32	-13	-39.32	-58.9	-53.51	2.15	5.49	H	Pass
2509	-52.43	-13	-39.43	-62.3	-54.32	2.38	6.41	H	Pass




Band :	GSM850	Temperature :	21~23°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.08	-13	-34.08	-53.14	-48.27	2.15	5.49	V	Pass
2509	-49.56	-13	-36.56	-59.53	-51.45	2.38	6.41	V	Pass
3345	-51.28	-13	-38.28	-62.76	-54.61	2.86	8.34	V	Pass




Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-52.29	-13	-39.29	-58.11	-53.48	2.15	5.49	H	Pass




Band :	GSM850	Temperature :	21~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.54	-13	-34.54	-53.38	-48.73	2.15	5.49	V	Pass




Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5636	-43.35	-13	-30.35	-63.6	-50.27	3.9072	10.83	H	Pass




Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-48.50	-13	-35.50	-61.7	-54.63	2.9292	9.06	V	Pass
5636	-42.53	-13	-29.53	-62.14	-49.45	3.9072	10.83	V	Pass




Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		






Band :	GSM1900	Temperature :	21~23°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-50.58	-13	-37.58	-64.38	-56.71	2.9292	9.06	V	Pass
5636	-44.70	-13	-31.70	-64.02	-51.62	3.9072	10.83	V	Pass




Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line. Spurious emissions within 1000MHz ~ 10th harmonic were not found any signals.		



Site : 03CH05-HY
Condition : FCC PART22H/24E HF_EIRP_101221 HORIZONTAL
Project : FG 0N2627




Band :	WCDMA Band V	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-55.64	-13	-42.64	-61.12	-56.83	2.15	5.49	V	Pass




Band :	WCDMA Band II	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.12	-13	-34.12	-60.46	-53.25	2.9292	9.06	H	Pass



Band :	WCDMA Band II	Temperature :	21~23°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	45~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-43.19	-13	-30.19	-57.19	-49.32	2.9292	9.06	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



**3.7.6 Test Result of Temperature Variation**

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	-13	-0.02	-19	-0.02	
0	-35	-0.04	-37	-0.04	
10	24	0.03	18	0.02	
20	20	0.02	-30	-0.04	
30	-34	-0.04	-40	-0.05	
40	-41	-0.05	21	0.02	
50	19	0.02	38	0.04	



Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	49	0.03	63	0.03	
0	-36	-0.02	46	0.02	
10	-18	-0.01	-29	-0.02	
20	-48	-0.03	13	0.01	
30	-40	-0.02	-51	-0.03	
40	-50	-0.03	-46	-0.02	
50	-46	-0.02	-56	-0.03	



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	-22	-0.03	
0	-24	-0.03	
10	23	0.03	
20	28	0.03	
30	26	0.03	
40	-25	-0.03	
50	-25	-0.03	



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	48	0.03	
0	37	0.02	
10	42	0.02	
20	-33	-0.02	
30	27	0.01	
40	-37	-0.02	
50	-49	-0.03	

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS 8	3.3	-27	-0.03	2.5	PASS
		3.0	-25	-0.03		
		3.6	22	0.03		
	EDGE 8	3.3	-36	-0.04		
		3.0	-42	-0.05		
		3.6	-32	-0.04		
GSM 1900 CH661	GPRS 8	3.3	-31	-0.02		
		3.0	-49	-0.03		
		3.6	-32	-0.02		
	EDGE 8	3.3	-45	-0.02		
		3.0	-29	-0.02		
		3.6	-62	-0.03		
WCDMA Band V CH4182	RMC 12.2Kbps	3.3	-33	-0.04		
		3.0	-28	-0.03		
		3.6	-31	-0.04		
WCDMA Band II CH9400	RMC 12.2Kbps	3.3	-48	-0.03		
		3.0	-49	-0.03		
		3.6	-39	-0.02		

Note: Normal Voltage = 3.3V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Jun. 08, 2009	Jun. 07, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 11, 2010	Jun. 10, 2011	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Jul. 30, 2010	Jul. 29, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101352	9KHz-40GHz	Nov. 03, 2010	Nov. 02, 2011	Radiation (03CH05-HY)
Amplifier	COM-POWER	PA-103	161075	1KHz - 1GHz	Mar. 29, 2011	Mar. 28, 2012	Radiation (03CH05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2725	30MHz ~ 1GHz	Nov. 06, 2010	Nov. 05, 2011	Radiation (03CH05-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH05-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1GHz- 26.5GHz	Apr. 15, 2010	Apr. 14, 2011	Radiation (03CH05-HY)
Turn Table	HD	Deis HD 2000	420/611	0 - 360 degree	N/A	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	MA 240	240/666	1 m - 4 m	N/A	N/A	Radiation (03CH05-HY)
Horn Antenna	ESCO	3117	00066584	1GHz ~ 18GHz	Aug. 05, 2010	Aug. 04, 2011	Radiation (03CH05-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH05-HY)
System Simulator	R&S	CMU200	117591	N/A	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\log(1-\Gamma_1\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP0N2627 as below.