

ENGINEERING STATEMENT

For Type Certification of

MIDLAND USA INC.

Model No: 70-0671B

FCC ID: NCP700671B

I am an Electronics Engineer, a principal in the firm of Hyak Laboratories, Inc., Springfield, Virginia. My education and experience are a matter of record with the Federal Communications Commission.

Hyak Laboratories, Inc. has been authorized by Midland USA Inc. to make type certification measurements on the 70-0671B transceiver. These tests made by me or under my supervision in our Springfield laboratory.

Test data and documentation required by the FCC for Type Certification are included in this report. The data verifies that the above mentioned transceiver meets FCC requirements and Type Certification is requested.

Rowland S. Johnson

Dated: October 28, 1999

A. INTRODUCTION

The following data are submitted in connection with this request for Type Certification of the 70-0671B transceiver in accordance with Part 2, Subpart J of the FCC Rules.

The 70-0671B is a VHF, frequency modulated transceiver intended for 25 kHz land mobile applications in the 36 to 42 MHz band. It operates from a 13.8 vehicle supply. Nominal output power rating is 110 watts.

The transceiver is electrically identical, except for operating range, to the 70-0671C for which Type Certification is pending.

B. RF POWER OUTPUT (Paragraph 2.985(a) of the Rules)

RF power output was measured with a Bird 4421 RF power meter and a Bird 8325 attenuator as a 50 ohm dummy load. Maximum power measured was 110 watts.

C. MODULATION CHARACTERISTICS

Occupied Bandwidth

(Paragraphs 2.989(c), 90.209(b)(4) and 90.210(d) of the Rules)

Figure 1 is a plot of the sideband envelope of the transmitter for 110 watt output taken with an Advantest R3361A spectrum analyzer. Modulation corresponded to conditions of 2.989(c)(1) and consisted of 2500 Hz tone at an input level 16 dB greater than that necessary to produce 50% modulation at 2640 Hz, the frequency of maximum response. Measured modulation under these conditions was 4.0 kHz.

The plot has unmodulated carrier as 0 dBm reference.

The plots are within the limits imposed by Paragraph 90.210(b) for frequency modulation. The horizontal scale (frequency) is 10 kHz per division and the vertical scale (amplitude) is a logarithmic presentation equal to 10 dB per division.

FIGURE 1

OCCUPIED BANDWIDTH

	ATTENUATION IN dB BELOW MEAN OUTPUT POWER Required
On any frequency more than 50% up to and including 100% of the authorized bandwidth, 20 kHz (10-20 kHz)	25
On any frequency more than 100%, up to and including 250% of the authorized bandwidth (20-50 kHz)	35
On any frequency removed from the assigned frequency by more than 250% of the authorized bandwidth (over 50 kHz)	$43+10\text{Log}P = 63$ ($P = 110 \text{ W}$)

OCCUPIED BANDWIDTH
FCC ID: NCP700671B

FIGURE 1

C. MODULATION CHARACTERISTICS (Continued)

The plot is within the limits imposed by Paragraph 90.210(b) for frequency modulation. The horizontal scale (frequency) is 10 kHz per division and the vertical scale (amplitude) is a logarithmic presentation equal to 10 dB per division.

D. SPURIOUS EMISSIONS AT THE ANTENNA TERMINALS
(Paragraph 2.991 of the Rules)

The 70-0671B transmitter was tested for spurious emissions at the antenna terminals while the equipment was modulated with a 2500 Hz signal, 16 dB above minimum input signal for 50% (2.5 kHz deviation) modulation at 2640 Hz, the frequency of highest sensitivity.

Measurements were made with Tektronix 494P spectrum analyzer coupled to the transmitter output terminal through a Bird 8325 power attenuator. A notch filter was used to attenuate the carrier.

During the tests, the transmitter was terminated in the 50 ohm attenuator. Power was monitored on a Bird 43 Thru-Line wattmeter; dc supply was 13.8 volts throughout the tests.

Spurious emissions were measured at 110 watts output throughout the RF spectrum from 12 (lowest frequency generated in the transmitter is 12.8 MHz) to the tenth harmonic of the carrier.

Any emissions that were between the required attenuation and the noise floor of the spectrum analyzer were recorded. Data are shown in Table 1.

E. DESCRIPTION OF RADIATED SPURIOUS MEASUREMENT FACILITIES

A description of the Hyak Laboratories' radiation test facility is a matter of record with the FCC. The facility meets ANSI 63.4-1992 and was accepted for radiation measurements from 25 to 1000 MHz on October 1, 1976 and is currently listed as an accepted site.

TABLE 1

TRANSMITTER CONDUCTED SPURIOUS
39.000, 13.8 Vdc Input, 110 W

<u>Spurious Frequency MHz</u>	<u>dB Below Carrier Reference</u>
78.000	73
117.000	85
156.000	87

195.000	91
234.000	72
273.000	89
312.000	97
351.000	>100
390.000	100

Required: 43+10Log(P) 63

All other emissions from 12 MHz to the tenth harmonic were 20 dB or more below FCC limit.

*Reference data only, more than 20 dB below FCC limit.

NOTE: Carrier notch filter used to increase dynamic range.

F. FIELD STRENGTH MEASUREMENTS OF SPURIOUS RADIATION

Field intensity measurements of radiated spurious emissions from the Midland 70-0671B were made with a Tektronix 494P spectrum analyzer using Singer DM-105A calibrated dipole antennas.

The transmitter and dummy load were located in an open field 3 meters from the test antenna. Supply voltage was a power supply with a terminal voltage under load of 13.8 Vdc.

Output power was 110 watts at 46.000 MHz operating frequency. The transmitter and test antennas were arranged to maximize pickup. Both vertical and horizontal test antennae polarization were employed.

Reference level for the spurious radiation was taken as an ideal dipole excited by 110 watts, the output power of the transmitter according to the following relationship:*

$$E = \frac{(49.2P_t)^{1/2}}{R}$$

where E = electric-field intensity in volts/meter
 P_t = transmitter power in watts
 R = distance in meters
 for this case $E = \frac{(49.2 \times 110.0)^{1/2}}{3} = 24.5 \text{ V/m}$

Since the spectrum analyzer is calibrated in decibels above one milliwatt (dBm), a conversion, for convenience, was made from dBu to dBm.

$$\begin{aligned} 24.5 \text{ volts/meter} &= 24.5 \times 10^6 \text{ uV/m} \\ \text{dBu/m} &= 20 \text{ Log}_{10}(24.5 \times 10^6) \\ &= 148 \text{ dBu/m} \end{aligned}$$

Since 1 uV/m = -107 dBm, the reference becomes

$$148 - 107 = 41 \text{ dBm}$$

*Reference Data for Radio Engineers, Fourth Edition, International Telephone and Telegraph Corp., p. 676.

F. FIELD STRENGTH MEASUREMENTS (Continued)

The transmitter and test antennae were arranged to maximize pickup. Both vertical and horizontal test antenna polarization were employed.

The measurement system was capable of detecting signals 100 dB below the reference level. Measurements were made from the lowest frequency generated within the unit (12 MHz), to 10 times operating frequency. Data after application of antenna factors and line loss corrections are shown in Table 2.

TABLE 2
 TRANSMITTER CABINET RADIATED SPURIOUS

39.000 MHz, 13.8 Vdc, 110 watts

<u>Spurious Frequency MHz</u>	<u>dB Below Carrier Reference¹</u>
78.000	74H
117.000	77H
156.000	71V
195.000	82V
234.000	78H

273.000	75H
312.000	85*
351.000	95*
390.000	98*
Required:	63

¹Worst-case polarization, H-Horizontal, V-Vertical.

* Reference data only, more than 20 dB below FCC limit.

All other spurious from 12 MHz to 390 GHz were 20 dB or more below FCC limit.