

Prüfbericht-Nr.: <i>Test report no.:</i>	CN25RI4K 001	Auftrags-Nr.: <i>Order no.:</i>	48253121	Seite 1 von 48 Page 1 of 48
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2024-09-13	
Auftraggeber: <i>Client:</i>	Edimax Technology Co., Ltd. No.278 , Xinhu 1st Rd., Neihu Dist., Taipei City, Taiwan			
Prüfgegenstand: <i>Test item:</i>	2T2R 802.11be Wi-Fi 7 BE6500 USB Dongle			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	EW-7822UBE			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15E Test report (WiFi 5GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart E Section 15.407			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2024-12-30			
Prüfmuster-Nr.: <i>Test sample no:</i>	A003900059-008 A003900059-006			
Prüfzeitraum: <i>Testing period:</i>	2025-01-13 - 2025-02-26			
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Taipei Testing Site			
Prüflaboratorium: <i>Testing laboratory:</i>	Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
überprüft von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	Ausstellungsdatum: <i>Issue date:</i>			
Stellung / Position:	Stellung / Position:			
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>				
Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>				
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
* Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN25RI4K 001

Seite 2 von 48
Page 2 of 48

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.
Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.
Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.
Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.407(a) & 15.203	Antenna Requirement	Pass
5.1.2	15.407(a)	Maximum Conducted Output Power	Pass
5.1.3	15.407(h)(1)	Transmit Power Control (TPC)	Pass
5.1.4	15.407(a)	26 dB Bandwidth	Pass
5.1.4	2.1049	99% Occupied Bandwidth	Pass
5.1.5	15.407(e)	6 dB Bandwidth (U-NII-3 Band only)	Pass
5.1.6	15.407(g)	Frequency Stability	Pass
5.1.7	15.407(a)	Power Spectral Density	Pass
5.1.8	15.407(b) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.1.9	15.407(h) & KDB 905462 D02	Dynamic Frequency Selection	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS.....	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY.....	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION.....	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS.....	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.4 SUBMITTED DOCUMENTS.....	11
4. TEST SET-UP AND OPERATION MODES	12
4.1 PRINCIPLE OF CONFIGURATION SELECTION	12
4.2 CARRIER FREQUENCY AND CHANNEL	13
4.3 TEST OPERATION AND TEST SOFTWARE.....	14
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	17
4.5 TEST SETUP DIAGRAM	17
4.6 DUTY CYCLE OF TEST SIGNAL	20
5. TEST RESULTS	23
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	23
5.1.1 Antenna Requirement	23
5.1.2 Maximum Conducted Output Power	24
5.1.3 Transmit Power Control (TPC).....	30
5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth.....	31
5.1.5 6 dB Bandwidth (5725-5850MHz).....	32
5.1.6 Frequency Stability Measurement.....	33
5.1.7 Power Spectral Density.....	35
5.1.8 Radiated Spurious Emissions	37
5.1.9 Dynamic Frequency Selection	42
5.2 MAINS EMISSION	47
5.2.1 Mains Conducted Emission.....	47

Prüfbericht - Nr.: **CN25RI4K 001**
Test Report No.

Seite 5 von 48
Page 5 of 48

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 6 von 48
Page 6 of 48

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2025-04-15

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart E Section 15.407
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10:2013
KDB 789033 D02 General UNII Test Procedures New Rules v02r01
KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
KDB 662911 D01 Multiple Transmitter Output v02r01

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a 2T2R 802.11be Wi-Fi 7 BE6500 USB Dongle. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	2T2R 802.11be Wi-Fi 7 BE6500 USB Dongle
Type Identification	EW-7822UBE
FCC ID	NDD9578222405

Technical Specification of EUT

Item	EUT information
Operating Frequency Range	Band 1: 5180 MHz ~ 5250 MHz Band 2: 5250 MHz ~ 5350 MHz Band 3: 5470 MHz ~ 5725 MHz Band 4: 5725 MHz ~ 5850 MHz
Channel Number	<5150 MHz ~ 5350 MHz> 8 for 802.11a/n/ac/ax/be HT20/VHT20/HE20/EHT20 4 for 802.11n/ac/ax/be HT40/VHT40/HE40/EHT40 2 for 802.11ac/ax/be VHT80/HE80/EHT80 1 for 802.11ac/ax/be VHT160/HE160/EHT160 <5470 MHz ~ 5725 MHz> 11 for 802.11a/n/ac/ax/be HT20/VHT20/HE20/EHT20 5 for 802.11n/ac/ax/be HT40/VHT40/HE40/EHT40 2 for 802.11ac/ax/be VHT80/HE80/EHT80 1 for 802.11ac/ax/be VHT160/HE160/EHT160 <5725 MHz ~ 5850 MHz> 5 for 802.11a/n/ac/ax/be HT20/VHT20/HE20/EHT20 2 for 802.11n/ac/ax/be HT40/VHT40/HE40/EHT40 1 for 802.11ac/ax/be VHT80/HE80/EHT80
Data Rate	802.11a: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7 802.11ac: up to MCS9 802.11ax: up to MCS11 802.11be: up to MCS13
Operation Voltage	5 Vdc
Modulation	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) OFDMA (1024QAM, 4096QAM)

Item	EUT information
Maximum Output Power (mW)	5180 ~ 5250 MHz: 44.52 5250 ~ 5320 MHz: 44.06 5500 ~ 5700 MHz: 61.38 5745 ~ 5825 MHz: 59.92
Maximum EIRP (mW)	5250 ~ 5320 MHz: 69.83 5500 ~ 5700 MHz: 137.42
DFS Mode	Slave without radar detection
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Note: There're 2 configurations of the EUT listed as below. Since the only difference is the thermal pad which does not affect the RF characteristics, only the main sample was chosen for the final test.

EUT	Difference
Main sample	EUT with heat sink
2 nd sample	EUT with heat sink and thermal pad

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

802.11a		802.11n HT20 802.11ac VHT20 802.11ax HE20 802.11be EHT20		802.11n HT40 802.11ac VHT40 802.11ax HE40 802.11be EHT40		802.11ac VHT80 802.11ax HE80 802.11be EHT80		802.11ac VHT160 802.11ax HE160 802.11be EHT160	
Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting
36	13.25	36	13.25	38	13.25	42	13.25	50	12.5
40	13.25	40	13.25	46	13.25	58	13.25	114	13
48	13.25	48	13.25	54	13.25	106	14.5		
52	13.25	52	13.25	62	13.25	122	14.5		
60	13.25	60	13.25	102	14.5	155	14.5		
64	13.25	64	13.25	110	14.5				
100	14.5	100	14.5	134	14.5				
116	14.5	116	14.5	151	14.5				
140	14.5	140	14.5	159	14.5				
149	14.5	149	14.5						
157	14.5	157	14.5						
165	14.5	165	14.5						

4.2 Carrier Frequency and Channel

Channel	Frequency (MHz)	802.11a 802.11n HT20 802.11ac VHT20 802.11ax HE20 802.11be EHT20	802.11n HT40 802.11ac VHT40 802.11ax HE40 802.11be EHT40	802.11ac VHT80 802.11ax HE80 802.11be EHT80	802.11ac VHT160 802.11ax HE160 802.11be EHT160
36	5180	V			
38	5190		V		
40	5200	V			
42	5210			V	
44	5220	V			
46	5230		V		
48	5240	V			
50	5250				V
52	5260	V			
54	5270		V		
56	5280	V			
58	5290			V	
60	5300	V			
62	5310		V		
64	5320	V			
100	5500	V			
102	5510		V		
104	5520	V			
106	5530			V	
108	5540	V			
110	5550		V		
112	5560	V			
114	5570				V
116	5580	V			
118	5590		V		
120	5600	V			
122	5610			V	
124	5620	V			
126	5630		V		
128	5640	V			
132	5660	V			
134	5670		V		
136	5680	V			
140	5700	V			
149	5745	V			
151	5755		V		
153	5765	V			
155	5775			V	
157	5785	V			
159	5795		V		
161	5805	V			
165	5825	V			

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	AX Series MP Tool V2.0.44
---------------	---------------------------

The samples were used as follows:

A003900059-008

A003900059-006

Full test was applied on all test modes, but only worst case was shown.

The EUT provides two completed transmitters and receivers.

Modulation Mode	Tx Function
802.11a	2TX
802.11n HT20	2TX
802.11n HT40	2TX
802.11ac VHT20	2TX
802.11ac VHT40	2TX
802.11ac VHT80	2TX
802.11ac VHT160	2TX
802.11ax HE20	2TX
802.11ax HE40	2TX
802.11ax HE80	2TX
802.11ax HE160	2TX
802.11be EHT20	2TX
802.11be EHT40	2TX
802.11be EHT80	2TX
802.11be EHT160	2TX

* The modulation and bandwidth are similar for 802.11n mode HT20/HT40 and 802.11ac mode VHT20/VHT40/VHT80/VHT160 and 802.11ax mode HE20/HE40/HE80/HE160 and 802.11be mode EHT20/EHT40/EHT80/EHT160, therefore, only investigated worse case as representative mode in test report.

** The EUT only supports Full RU, not support Partial RUs.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Z-plane**.
2. "-" means no effect.

Antenna Port Conducted Measurement

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11a	5180-5250	36 to 48	36, 40, 48	6.0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11n HT20 (Power only)	5180-5250	36 to 48	36, 40, 48	MCS0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11n HT40 (Power only)	5180-5250	38 to 46	38, 46	MCS0
-		5250-5320	54 to 62	54, 62	
-		5500-5700	102 to 134	102, 110, 134	
-		5745-5825	151 to 159	151, 159	
-	802.11ac VHT20 (Power only)	5180-5250	36 to 48	36, 40, 48	NSS1 MCS0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11ac VHT40 (Power only)	5180-5250	38 to 46	38, 46	NSS1 MCS0
-		5250-5320	54 to 62	54, 62	
-		5500-5700	102 to 134	102, 110, 134	
-		5745-5825	151 to 159	151, 159	
-	802.11ac VHT80 (Power only)	5180-5250	42	42	NSS1 MCS0
-		5250-5320	58	58	
-		5500-5700	106 to 122	106, 122	
-		5745-5825	155	155	
-	802.11ac VHT160 (Power only)	5180-5320	50	50	NSS1 MCS0
-		5500-5700	114	114	
-	802.11ax HE20 (Power only)	5180-5250	36 to 48	36, 40, 48	NSS1 MCS0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11ax HE40 (Power only)	5180-5250	38 to 46	38, 46	NSS1 MCS0
-		5250-5320	54 to 62	54, 62	
-		5500-5700	102 to 134	102, 110, 134	
-		5745-5825	151 to 159	151, 159	
-	802.11ax HE80 (Power only)	5180-5250	42	42	NSS1 MCS0
-		5250-5320	58	58	
-		5500-5700	106 to 122	106, 122	
-		5745-5825	155	155	
-	802.11ax HE160 (Power only)	5180-5320	50	50	NSS1 MCS0
-		5500-5700	114	114	

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11be EHT20	5180-5250	36 to 48	36, 40, 48	NSS1 MCS0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT40	5180-5250	38 to 46	38, 46	NSS1 MCS0
-		5250-5320	54 to 62	54, 62	
-		5500-5700	102 to 134	102, 110, 134	
-		5745-5825	151 to 159	151, 159	
-	802.11be EHT80	5180-5250	42	42	NSS1 MCS0
-		5250-5320	58	58	
-		5500-5700	106 to 122	106, 122	
-		5745-5825	155	155	
-	802.11be EHT160	5180-5320	50	50	NSS1 MCS0
-		5500-5700	114	114	

Radiated Spurious Emissions (Above 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11a	5180-5250	36 to 48	36, 40, 48	6.0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT20	5180-5250	36 to 48	36, 40, 48	NSS1 MCS0
-		5250-5320	52 to 64	52, 60, 64	
-		5500-5700	100 to 140	100, 116, 140	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT40	5180-5250	38 to 46	38, 46	NSS1 MCS0
-		5250-5320	54 to 62	54, 62	
-		5500-5700	102 to 134	102, 110, 134	
-		5745-5825	151 to 159	151, 159	
-	802.11be EHT80	5180-5250	42	42	NSS1 MCS0
-		5250-5320	58	58	
-		5500-5700	106 to 122	106, 122	
-		5745-5825	155	155	
-	802.11be EHT160	5180-5320	50	50	NSS1 MCS0
-		5500-5700	114	114	

Radiated Spurious Emissions (Below 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
EUT with Notebook	802.11be EHT20	5500-5700	100 to 140	140	NSS1 MCS0
EUT with Cradle	802.11be EHT20	5500-5700	100 to 140	140	NSS1 MCS0

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 17 von 48
Page 17 of 48

Mains Conducted Emission Test

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
EUT with Notebook	802.11be EHT20	5500-5700	100 to 140	140	NSS1 MCS0
EUT with Cradle	802.11be EHT20	5500-5700	100 to 140	140	NSS1 MCS0

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	20.6-22.8 °C	46-48 %	Andy Chen
Radiated Spurious Emissions above 1 GHz	22.6-23.8 °C	53-54 %	Chuan Chu
Radiated Spurious Emissions below 1 GHz	22.6-23.8 °C	53-54 %	Chuan Chu
Mains Conducted Emission	20.9 °C	60 %	Chuan Chu

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


No.	Product	Brand	Model	Description
A	Cradle	Always Tai Lai Co., Ltd.	ATL-1694	--

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
EUT with Notebook								
1	Adapter	Lenovo	ADLX45NCC3A	N/A	NO	NO	180	--
2	Notebook	Lenovo	TP00018A	N/A	-	-	-	--
3	USB Cable	E-books	E-IPD235	N/A	NO	NO	200	--
EUT with Cradle								
1	Adapter	DELL	LA65NM130	N/A	NO	NO	186	Radiated
2	Notebook	DELL	Latitude 7490	887V7Y2	-	-	-	
1	Adapter	Lenovo	TPN-CA16	N/A	NO	NO	180	Mains Conducted
2	Notebook	Lenovo	15s-du0007TX	CND93662VF	-	-	-	

4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>
EUT with Notebook




EUT with Cradle




<Mains Conducted Emission mode>

EUT with Notebook





EUT with Cradle








4.6 Duty Cycle of Test Signal

Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11a	1.376	1.358	98.73	0.06
802.11n HT20	1.900	1.890	99.47	0.02
802.11n HT40	1.236	1.224	99.03	0.04
802.11ac VHT20	1.910	1.895	99.21	0.03
802.11ac VHT40	1.242	1.230	99.03	0.04
802.11ac VHT80	0.878	0.864	98.41	0.07
802.11ac VHT160	0.878	0.864	98.41	0.07
802.11ax HE20	1.183	1.168	98.73	0.06
802.11ax HE40	1.179	1.164	98.73	0.06
802.11ax HE80	0.870	0.856	98.39	0.07
802.11ax HE160	0.478	0.464	97.07	0.13
802.11be EHT20	3.379	3.365	99.57	0.02
802.11be EHT40	1.740	1.724	99.08	0.04
802.11be EHT80	0.878	0.866	98.63	0.06
802.11be EHT160	0.486	0.472	97.04	0.13







5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the antenna information is as listed below. The antenna is with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Antenna	Antenna Gain (dBi)				Antenna Type
	Band 1	Band 2	Band 3	Band 4	
1	1.90	1.90	2.70	3.00	PIFA Antenna
2	2.00	2.00	3.50	3.60	PIFA Antenna
Max. Peak Gain	2.00	2.00	3.50	3.60	-
Power Directional Gain	2.00	2.00	3.50	3.60	-
PSD Directional Gain	4.96	4.96	6.12	6.32	-

Note: PSD Directional Gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$

Refer to EUT photo for details.

5.1.2 Maximum Conducted Output Power

Limit

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125 mW (21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250 mW (24 dBm)
U-NII-2A	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-2C	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-3	---	1 Watt (30 dBm)

Note: B* is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;


Array Gain = 0 dB (i.e., no array gain) for channel widths $\geq$ 40 MHz for any N_{ANT} ;

Array Gain = 5 log(N_{ANT}/N_{SS}) dB or 3 dB, whichever is less for 20 MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = 10 log(N_{ANT}/N_{SS}) dB.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2024/03/12	2025/03/11	2025/1/13	2025/2/5
Power Sensor	Anritsu	MA2411B	1725269	2024/03/12	2025/03/11	2025/1/13	2025/2/5

Test Procedures

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to AVERAGE. Duty factor is not added to measured value.

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 25 von 48
Page 25 of 48

Test Result
<802.11a>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
36	5180	13.26	13.32	16.30	42.66	24.00
40	5200	13.31	13.35	16.34	43.06	24.00
48	5240	13.26	13.34	16.31	42.76	24.00
52	5260	13.25	13.21	16.24	42.08	23.71
60	5300	13.19	13.15	16.18	41.50	23.70
64	5320	13.20	13.18	16.20	41.69	23.69
100	5500	14.63	14.61	17.63	57.95	23.70
116	5580	14.70	14.61	17.67	58.42	23.69
140	5700	14.82	14.73	17.79	60.06	23.68
149	5745	14.67	14.62	17.66	58.28	30.00
157	5785	14.68	14.62	17.66	58.35	30.00
165	5825	14.67	14.63	17.66	58.35	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(18.66) = 23.71 \text{ dBm} < 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(18.62) = 23.70 \text{ dBm} < 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(18.58) = 23.69 \text{ dBm} < 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(18.62) = 23.70 \text{ dBm} < 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(18.58) = 23.69 \text{ dBm} < 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(18.54) = 23.68 \text{ dBm} < 24 \text{ dBm}$.

<802.11n HT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
36	5180	13.14	13.22	16.19	41.60	24.00
40	5200	13.18	13.26	16.23	41.98	24.00
48	5240	13.08	13.21	16.16	41.26	24.00
52	5260	13.12	13.08	16.11	40.84	24.00
60	5300	13.08	13.01	16.06	40.32	24.00
64	5320	13.10	13.03	16.08	40.51	24.00
100	5500	14.62	14.52	17.58	57.29	24.00
116	5580	14.59	14.55	17.58	57.28	24.00
140	5700	14.63	14.55	17.60	57.55	24.00
149	5745	14.54	14.51	17.54	56.69	30.00
157	5785	14.55	14.52	17.55	56.82	30.00
165	5825	14.56	14.52	17.55	56.89	30.00

<802.11n HT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
38	5190	13.07	13.18	16.14	41.07	24.00
46	5230	13.13	13.20	16.18	41.45	24.00
54	5270	13.11	13.03	16.08	40.56	24.00
62	5310	13.09	13.03	16.07	40.46	24.00
102	5510	14.54	14.51	17.54	56.69	24.00
110	5550	14.61	14.57	17.60	57.55	24.00
134	5670	14.63	14.57	17.61	57.68	24.00
151	5755	14.56	14.51	17.55	56.82	30.00
159	5795	14.53	14.51	17.53	56.63	30.00

<802.11ac VHT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
36	5180	13.24	13.29	16.28	42.42	24.00
40	5200	13.27	13.33	16.31	42.76	24.00
48	5240	13.19	13.29	16.25	42.18	24.00
52	5260	13.21	13.20	16.22	41.83	24.00
60	5300	13.17	13.13	16.16	41.31	24.00
64	5320	13.20	13.15	16.19	41.55	24.00
100	5500	14.66	14.54	17.61	57.69	24.00
116	5580	14.64	14.59	17.63	57.88	24.00
140	5700	14.72	14.66	17.70	58.89	24.00
149	5745	14.57	14.54	17.57	57.09	30.00
157	5785	14.59	14.54	17.58	57.22	30.00
165	5825	14.59	14.55	17.58	57.28	30.00

<802.11ac VHT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
38	5190	13.16	13.25	16.22	41.84	24.00
46	5230	13.20	13.25	16.24	42.03	24.00
54	5270	13.15	13.07	16.12	40.93	24.00
62	5310	13.15	13.08	16.13	40.98	24.00
102	5510	14.57	14.52	17.56	56.96	24.00
110	5550	14.65	14.61	17.64	58.08	24.00
134	5670	14.66	14.62	17.65	58.21	24.00
151	5755	14.61	14.53	17.58	57.29	30.00
159	5795	14.56	14.52	17.55	56.89	30.00

<802.11ac VHT80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
42	5210	13.20	13.28	16.25	42.17	24.00
58	5290	13.21	13.15	16.19	41.59	24.00
106	5530	14.54	14.60	17.58	57.28	24.00
122	5610	14.59	14.54	17.58	57.22	24.00
155	5775	14.54	14.59	17.58	57.22	30.00

<802.11ac VHT160>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
50	5250	12.59	12.56	15.59	36.19	24.00
114	5570	13.21	12.92	16.08	40.53	24.00

<802.11ax HE20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
36	5180	13.32	13.36	16.35	43.16	24.00
40	5200	13.34	13.39	16.38	43.40	24.00
48	5240	13.29	13.38	16.35	43.11	24.00
52	5260	13.30	13.28	16.30	42.66	24.00
60	5300	13.24	13.21	16.24	42.03	24.00
64	5320	13.28	13.25	16.28	42.42	24.00
100	5500	14.71	14.62	17.68	58.55	24.00
116	5580	14.71	14.68	17.71	58.96	24.00
140	5700	14.80	14.77	17.80	60.19	24.00
149	5745	14.63	14.60	17.63	57.88	30.00
157	5785	14.66	14.64	17.66	58.35	30.00
165	5825	14.64	14.61	17.64	58.01	30.00

<802.11ax HE40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
38	5190	13.23	13.30	16.28	42.42	24.00
46	5230	13.28	13.31	16.31	42.71	24.00
54	5270	13.24	13.19	16.23	41.93	24.00
62	5310	13.25	13.21	16.24	42.08	24.00
102	5510	14.61	14.55	17.59	57.42	24.00
110	5550	14.71	14.64	17.69	58.69	24.00
134	5670	14.70	14.65	17.69	58.69	24.00
151	5755	14.65	14.58	17.63	57.88	30.00
159	5795	14.61	14.55	17.59	57.42	30.00

<802.11ax HE80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
42	5210	13.27	13.33	16.31	42.76	24.00
58	5290	13.29	13.26	16.29	42.51	24.00
106	5530	14.59	14.63	17.62	57.81	24.00
122	5610	14.64	14.61	17.64	58.01	24.00
155	5775	14.59	14.63	17.62	57.81	30.00

<802.11ax HE160>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
50	5250	12.64	12.62	15.64	36.65	24.00
114	5570	13.27	12.99	16.14	41.14	24.00

<802.11be EHT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
36	5180	13.45	13.48	16.48	44.42	24.00
40	5200	13.46	13.49	16.49	44.52	24.00
48	5240	13.43	13.48	16.47	44.31	24.00
52	5260	13.45	13.41	16.44	44.06	24.00
60	5300	13.35	13.30	16.34	43.01	24.00
64	5320	13.40	13.33	16.38	43.41	24.00
100	5500	14.73	14.67	17.71	59.03	24.00
116	5580	14.84	14.77	17.82	60.47	24.00
140	5700	14.90	14.84	17.88	61.38	24.00
149	5745	14.78	14.71	17.76	59.64	30.00
157	5785	14.80	14.73	17.78	59.92	30.00
165	5825	14.77	14.71	17.75	59.57	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(20.50) = 24.12 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(20.54) = 24.13 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(20.54) = 24.13 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(20.66) = 24.15 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(20.54) = 24.13 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(20.74) = 24.17 \text{ dBm} > 24 \text{ dBm}$.

<802.11be EHT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
38	5190	13.34	13.41	16.39	43.51	24.00
46	5230	13.37	13.43	16.41	43.76	24.00
54	5270	13.39	13.30	16.36	43.21	24.00
62	5310	13.39	13.32	16.37	43.31	24.00
102	5510	14.64	14.57	17.62	57.75	24.00
110	5550	14.75	14.68	17.73	59.23	24.00
134	5670	14.85	14.77	17.82	60.54	24.00
151	5755	14.68	14.61	17.66	58.28	30.00
159	5795	14.63	14.58	17.62	57.75	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(39.88) = 27.01 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(39.88) = 27.01 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(39.96) = 27.02 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(39.96) = 27.02 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(39.72) = 26.99 \text{ dBm} > 24 \text{ dBm}$.

<802.11be EHT80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
42	5210	13.38	13.46	16.43	43.96	24.00
58	5290	13.42	13.35	16.40	43.61	24.00
106	5530	14.68	14.75	17.73	59.23	24.00
122	5610	14.77	14.71	17.75	59.57	24.00
155	5775	14.68	14.75	17.73	59.23	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(80.24) = 30.04 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(80.40) = 30.05 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(80.24) = 30.04 \text{ dBm} > 24 \text{ dBm}$.

<802.11be EHT160>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Chain 0	Chain 1	(dBm)	(mW)	
50	5250	12.70	12.67	15.70	37.11	24.00
114	5570	13.34	13.05	16.21	41.76	24.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(80.88) = 30.08 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(162.08) = 33.10 \text{ dBm} > 24 \text{ dBm}$.

5.1.3 Transmit Power Control (TPC)

U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p of less than 500 mW.

Maximum EIRP of this device is 137.42 mW which is less than 500 mW, therefor, TPC function is not required.

TPC	E.I.R.P	15.407(h)(1)
	> 500mW	The TPC mechanism is required for system with an E.I.R.P. of above 500mW
V	< 500mW	-


Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 31 von 48
 Page 31 of 48

5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2024/02/22	2025/02/21	2025/1/13	2025/2/5

Test Procedure

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- For 99% Bandwidth Measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A


Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 32 von 48
 Page 32 of 48

5.1.5 6 dB Bandwidth (5725-5850MHz)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2024/02/22	2025/02/21	2025/1/13	2025/2/5

Test Procedure

MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Results

Please refer to Appendix A


Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 33 von 48
 Page 33 of 48

5.1.6 Frequency Stability Measurement

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2024/02/22	2025/02/21	2025/1/13	2025/2/5
Thermal Chamber	Giant Force	GHT-150-40-CP-SD	MAA1902-011	2024/04/12	2025/04/11	2025/1/13	2025/2/5

Test Procedure

- To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.
- The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 34 von 48
Page 34 of 48

Test Results

Frequency (MHz)	5180			
Voltage (V)	Measurement Frequency (MHz)			Max. Deviation (ppm)
5.25	5179.98032			3.799
5	5179.97742			4.359
4.75	5179.98234			3.409
Temperature (°C)	Measurement Frequency (MHz)			
	0 Minute	2 Minute	5 Minute	10 Minute
50	5179.96122	5179.96237	5179.96151	5179.96266
40	5179.96006	5179.95977	5179.95977	5179.95919
30	5179.97135	5179.9699	5179.96874	5179.96787
20	5179.97742	5179.96758	5179.96122	5179.95861
10	5179.99016	5179.99682	5180.00087	5180.00405
0	5180.02489	5180.02634	5180.0275	5180.02808
-10	5180.04834	5180.04834	5180.0492	5180.0492
-20	5180.06541	5180.06599	5180.06657	5180.06686
Max. Deviation (ppm)	12.627	12.739	12.851	12.907

5.1.7 Power Spectral Density

Limit

For the 5.15~5.25GHz Bands:

For mobile and portable client devices in the 5.15~5.25GHz band, the Maximum Power spectral density shall not exceed 11dBm/MHz. For an indoor access point operating in the band 5.15~5.25GHz, the maximum power spectral density shall not exceed 17dBm/MHz.

For the 5.25~5.35GHz and 5.47~5.725GHz Bands:


The maximum power spectral density shall not exceed 11dBm/MHz.

For the 5.745~5.85GHz Bands:

The maximum power spectral density shall not exceed 30dBm/500kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101512	2024/02/22	2025/02/21	2025/1/13	2025/2/5

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 36 von 48
Page 36 of 48

Test Procedure

For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-1

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value or/and add 10 log (1/duty cycle).

※For U-NII-3:

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
4. Sweep time = auto, trigger set to "free run".
5. Trace average at least 100 traces in power averaging mode.
6. Record the max value or/and add 10 log (1/duty cycle).

For MIMO mode, calculation method follows FCC KDB 662911 Method 2) a) of power density measurement using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

Test Results

Please refer to Appendix A

5.1.8 Radiated Spurious Emissions

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.407(b).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 39 von 48
Page 39 of 48

Test Instruments

Test Period: 2025-01-26 ~ 2025-02-26

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101509	2024/4/30	2025/4/29
Horn Antenna	ETS-Lindgren	3117	00218930	2024/12/10	2025/12/9
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2024/4/30	2025/4/29
HF-AMP + AC source	EMCI	EMC051845SE	980635	2024/3/28	2025/3/27
HF-AMP + AC source	EMCI	EMC184045SE	980656	2025/1/15	2026/1/14
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
30 MHz ~ 1 GHz					
Receiver	R&S	ESR7	102109	2024/2/22	2025/2/20
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2024/3/21	2025/3/20
LF-AMP	Agilent	8447D	2944A107722	2024/3/21	2025/3/20
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
Below 30 MHz					
Receiver	R&S	ESR7	102109	2024/2/22	2025/2/20
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/12/11	2025/12/10
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN25RI4K 001**
Test Report No.

Seite 41 von 48
Page 41 of 48

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

5.1.9 Dynamic Frequency Selection

Limit

<DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection>

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	


<DFS Response Requirement Values>

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	


Kind of Test Site Shielded room

Test Setup


<Setup for Master with injection at the Master>



<Setup for Client with injection at the Master>



<Setup for Client with injection at the Client>



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Keysight	N9000B	MY62361339	2024/01/25	2025/01/24	2025/1/13	2025/1/14
EXG Vector Signal Generator	Keysight	N5172B	MY61253270	2024/12/24	2025/12/23	2025/1/13	2025/1/14
Frequency Extender	Keysight	N5182BX07	MY61500182	2024/12/24	2025/12/23	2025/1/13	2025/1/14

Requirement

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required


Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

Test Results

<802.11be EHT160>

Non-occupancy period

Channel (MHz)	Limit (minute)	Result
5570	30	Pass




Channel Moving Time

Channel (MHz)	Channel Move Time (s)	Limit (s)	Result
5570	0.688	10	Pass

Channel Closing Transmission Time


Channel (MHz)	Channel Closing Transmission Time (ms)	Limit (ms)	Result
5570	2	60	Pass



Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 46 von 48
 Page 46 of 48

Radar Level



5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted emissions as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101938	2024/10/22	2025/10/21
EMI Test Receiver	R&S	ESCI	101094	2024/11/26	2025/11/25

Prüfbericht - Nr.: CN25RI4K 001
Test Report No.

Seite 48 von 48
Page 48 of 48

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results

Please refer to Appendix B.