



FCC RADIO TEST REPORT

Applicant : Partner Tech Corp.

Address : 10FL, 233-2, Baoqiao Road, Xindian,
New Taipei City, Taiwan

Equipment : Mobile POS Terminal

Model No. : M3a-2, EM-110, EMC-21X0 (X could be 0-9, -, A-Z
or blank)

Trade Name : PARTNER

FCC ID. : NDPM3A-2

I HEREBY CERTIFY THAT :

The sample was received on Jan. 17, 2019 and the testing was carried out on Mar. 08, 2019 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Tested by:

Spree Yeh / Engineer

Laboratory Accreditation:

CerpPASS Technology Corporation Test Laboratory





Contents

1. Summary of Test Procedure and Test Results.....	5
1.1 Applicable Standards	5
2. Test Configuration of Equipment under Test.....	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software	8
2.4 Description of Test System.....	8
2.5 General Information of Test.....	9
2.6 Measurement Uncertainty	9
3. Test Equipment and Ancillaries Used for Tests	10
4. Antenna Requirements	11
4.1 Standard Applicable	11
4.2 Antenna Construction and Directional Gain.....	11
5. Test of AC Power Line Conducted Emission	12
5.1 Test Limit	12
5.2 Test Procedures	12
5.3 Typical Test Setup	13
5.4 Test Result and Data	14
5.5 Test Photographs	16
6. Test of Spurious Emission (Radiated)	17
6.1 Test Limit	17
6.2 Test Procedures	17
6.3 Typical Test Setup	18
6.4 Test Result and Data (9kHz ~ 30MHz).....	19
6.5 Test Result and Data (30MHz ~ 1GHz).....	19
6.6 Test Result and Data (1GHz ~ 25GHz).....	21
6.7 Restricted Bands of Operation	27
6.8 Test Photographs (30MHz ~ 1GHz)	28
6.9 Test Photographs (1GHz ~ 25GHz)	29
7. Test of Spurious Emission (Conducted).....	30
7.1 Test Limit	30
7.2 Test Procedure	30
7.3 Test Setup Layout	30
7.4 Test Result and Data	30
8. On Time, Duty Cycle and Measurement methods	33
8.1 Test Limit	33
8.2 Test Procedure	33
8.3 Test Setup Layout	33
8.4 Test Result and Data	33
9. 6dB Bandwidth Measurement Data	35
9.1 Test Limit	35



9.2	Test Procedures	35
9.3	Test Setup Layout	35
9.4	Test Result and Data	35
10.	Maximum Peak and Average Output Power	37
10.1	Test Limit	37
10.2	Test Procedures	37
10.3	Test Setup Layout	37
10.4	Test Result and Data	37
11.	Power Spectral Density	38
11.1	Test Limit	38
11.2	Test Procedures	38
11.3	Test Setup Layout	38
11.4	Test Result and Data	38



History of this test report

Report No.	Issue Date	Description
TEFQ1901083	Mar. 14, 2019	Original



1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.4:2014

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(2)	. 6dB Bandwidth	PASS
15.247(b)	. Maximum Peak Output Power	PASS
15.247(e)	. Power Spectral Density	PASS

This EUT has been also tested and complied with the requirement of FCC Part 15, Subpart B, recorded in a separate test report (TEFV1901083).



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Frequency Range	BT / BLE: 2400-2483.5MHz 802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5725-5850MHz
Modulation Type	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK 802.11b: CCK, DQPSK, DBPSK 802.11g/n/a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM, FHSS, DTS
Data Rate	BT: GFSK: 1Mbps, $\pi/4$ -DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS7, HT20/40 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	Dipole Antenna
Antenna Gain	2400-2483.5MHz: 6.92dBi 5150-5250MHz: 4.12dBi 5725-5850MHz: 5.55dBi
Adapter	EDAC \ EA1024P1 Input: 100-240Vac, 1A, 50-60Hz Output: 12Vdc, 3A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 Model Difference

M3a-2, EM-110, EMC-21X0 (X could be 0-9, -, A-Z or blank) for marketing purpose.



2.3 Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
*00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	*19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	*39	2480
12	2426	26	2454	--	--
13	2428	27	2456	--	--

Note: Channels remarked * are selected to perform test.



2.4 Test Mode and Test Software

- During testing, the interface cables and equipment positions were varied according to ANSI C63.10.
- The complete test system included Notebook and EUT for RF test.
- An executive program, "qdart: win.4.8_installer_00039.311-11-17_08_03_48" was executed to transmit and receive data via Bluetooth.
- The following test modes were performed for the test:

AC Power Line Conducted Emission	
Test Mode	Operating Description
1	GFSK (1Mbps) , Adapter:EDAC \ EA1024P1
Radiated Spurious Emission (below 1GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) , Adapter:EDAC \ EA1024P1
Radiated Spurious Emission (above 1GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) , Adapter:EDAC \ EA1024P1
Conducted Spurious Emission, 6dB Bandwidth, Maximum Peak Output Power, Power Spectral Density	
Test Mode	Operating Description
1	GFSK (1Mbps) , Adapter:EDAC \ EA1024P1

2.5 Description of Test System

Device	Manufacturer	Model No.	Description
Notebook	DELL	Latitude E5450	Power Cable, Non-shielded, 1.8m
USB cable	N/A	N/A	Shielding, 1.2m



2.6 General Information of Test

Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582	
	FCC	TW1079, TW1061, TW1439
	IC	4934E-1, 4934E-2
	VCCI	T-2205 for Telecommunication test C-4663 for Conducted emission test R-4399, R-4218 for Radiated emission test G-10812, G-10813 for radiated disturbance above 1GHz
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 25,000MHz	
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.	

2.7 Measurement Uncertainty

Measurement Item	Uncertainty
Radiated Spurious Emission(9KHz~30MHz)	$\pm 5.007\text{dB}$
Radiated Spurious Emission(30MHz~1GHz)	$\pm 5.157\text{dB}$
Radiated Spurious Emission(1GHz~18GHz)	$\pm 6.383\text{dB}$
Radiated Spurious Emission(18GHz~40GHz)	$\pm 6.648\text{dB}$
Conducted Spurious Emission	$\pm 1.253\text{dB}$
6dB Bandwidth	$\pm 6.89\%$
Power Spectral Density	$\pm 0.630\text{dB}$
26 dB Occupied Bandwidth	$\pm 6.10\%$
Frequency Stability	$\pm 375\text{KHz}$
Channel Frequencies Separation	$\pm 6.10\%$
20dB Bandwidth	$\pm 6.12\%$
Dwell Time	$\pm 1.34\%$
Peak Output Power(Conducted Power Meter)	$\pm 0.86\text{dB}$
Temperature	$\pm 1.2^{\circ}\text{C}$
Humidity	$\pm 2.7\%$
Channel Move Time	$\pm 4.53\%$
Channel Closing Transmission Time	$\pm 6.61\%$
Threshold	$\pm 0.631\text{dB}$
Non occupancy period	$\pm 1.17\%$



3. Test Equipment and Ancillaries Used for Tests

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Receiver	R&S	ESC13	100821	2018/09/12	2019/09/11
LISN	Schwarzbeck	NSLK 8127	8127-516	2018/09/11	2019/09/10
Pulse Limiter	R&S	ESH3-Z2	101933	2018/09/04	2019/09/03
Bilog Antenna	Schwarzbeck	VULB9168	275	2018/09/17	2019/09/16
Active Loop Antenna	EMCO	6507	40855	2018/05/22	2019/05/21
Horn Antenna	EMCO	3115	31601	2018/09/26	2019/09/25
Horn Antenna	EMCO	3116	31970	2018/03/23	2019/03/22
Preamplifier	EM	EM330	60659	2018/03/20	2019/03/19
Preamplifier	EMC INSTRUMENTS	EMC051845SE	980333	2018/09/18	2019/09/17
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2018/10/31	2019/10/30
MXG MW Analog Signal Generator	KEYSIGHT	N5183A	MY50142931	2018/04/10	2019/04/09
Spectrum Analyzer	R&S	FSP40	100219	2018/07/03	2019/07/02
BLUETOOTH TESTER	R&S	CBT	101133	2018/04/02	2019/04/01
Attenuator	KEYSIGHT	8491B	MY39250705	2018/09/04	2019/09/03
Rotary Attenuator	Agilent	8495B	MY42146680	2018/03/29	2019/03/28
Temp & Humi chamber	T-MACHINE	TMJ-9712	T-12-040111	2018/08/30	2019/08/29
Series Power Meter	Anritsu	ML2495A	1224005	2018/03/23	2019/03/22
Power Sensor	Anritsu	MA2411B	1207295	2018/03/23	2019/03/22
Software	Farad	Ez-EMC	ver.ct3a1	N/A	N/A
Software	AUDIX	E3	V8.2014-8-6	N/A	N/A
Software	Keysight	N7607B Signal Studio	V3.0.0.0	N/A	N/A
Software	Keysight	Inservice MonitorUtility	N/A	N/A	N/A



4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna Gain	6.92 dBi



5. Test of AC Power Line Conducted Emission

5.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.4-2014. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

5.2 Test Procedures


- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.





5.4 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode	: Mode 1	Temperature	: 22 °C
Test date	: Mar. 05, 2019	Humidity	: 52 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.16	9.94	22.00	31.94	55.51	-23.57	Average	P
2	0.16	9.94	41.19	51.13	65.51	-14.38	QP	P
3	0.17	9.94	22.32	32.26	55.11	-22.85	Average	P
4	0.17	9.94	42.05	51.99	65.11	-13.12	QP	P
5	0.18	9.94	17.58	27.52	54.40	-26.88	Average	P
6	0.18	9.94	37.16	47.10	64.40	-17.30	QP	P
7	0.19	9.94	18.58	28.52	53.94	-25.42	Average	P
8	0.19	9.94	37.57	47.51	63.94	-16.43	QP	P
9	0.60	9.96	14.44	24.40	46.00	-21.60	Average	P
10	0.60	9.96	19.25	29.21	56.00	-26.79	QP	P
11	11.76	10.34	14.31	24.65	50.00	-25.35	Average	P
12	11.76	10.34	19.35	29.69	60.00	-30.31	QP	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode	: Mode 1	Temperature	: 22 °C
Test date	: Mar. 05, 2019	Humidity	: 52 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F
1	0.15	9.94	23.83	33.77	55.99	-22.22	Average	P
2	0.15	9.94	43.06	53.00	65.99	-12.99	QP	P
3	0.17	9.94	22.62	32.56	55.13	-22.57	Average	P
4	0.17	9.94	42.35	52.29	65.13	-12.84	QP	P
5	0.19	9.94	18.49	28.43	53.92	-25.49	Average	P
6	0.19	9.94	37.76	47.70	63.92	-16.22	QP	P
7	0.23	9.94	14.68	24.62	52.58	-27.96	Average	P
8	0.23	9.94	33.21	43.15	62.58	-19.43	QP	P
9	0.28	9.94	9.50	19.44	50.83	-31.39	Average	P
10	0.28	9.94	26.63	36.57	60.83	-24.26	QP	P
11	12.69	10.33	12.23	22.56	50.00	-27.44	Average	P
12	12.69	10.33	20.25	30.58	60.00	-29.42	QP	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=(LISN or ISN or Current Probe)Factor + Cable Loss



6. Test of Spurious Emission (Radiated)

6.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3


6.2 Test Procedures

- The EUT was placed on a rotatable table top 0.8 meter above ground.
- The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- The table was rotated 360 degrees to determine the position of the highest radiation.
- The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.




6.3 Typical Test Setup


Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup






6.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

6.5 Test Result and Data (30MHz ~ 1GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	107.60	-13.15	42.94	29.79	43.50	-13.71	Peak	400	0	P
2	175.50	-10.26	39.38	29.12	43.50	-14.38	Peak	400	0	P
3	217.21	-11.53	39.08	27.55	46.00	-18.45	Peak	400	0	P
4	293.84	-8.76	46.12	37.36	46.00	-8.64	Peak	400	0	P
5	482.02	-4.12	38.38	34.26	46.00	-11.74	Peak	400	0	P
6	583.87	-1.88	31.36	29.48	46.00	-16.52	Peak	400	0	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBUV)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	123.12	-11.44	38.01	26.57	43.50	-16.93	Peak	100	0	P
2	176.47	-10.40	39.05	28.65	43.50	-14.85	Peak	100	0	P
3	271.53	-9.38	49.82	40.44	46.00	-5.56	Peak	100	0	P
4	293.84	-8.76	49.43	40.67	46.00	-5.33	Peak	100	0	P
5	392.78	-5.93	40.53	34.60	46.00	-11.40	Peak	100	0	P
6	450.01	-4.74	33.73	28.99	46.00	-17.01	Peak	100	0	P

Note: Level=Reading+Factor


Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.6 Test Result and Data (1GHz ~ 25GHz)

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH00	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-15.68	51.80	36.12	54.00	-17.88	Average	167	301	P
2	2390.00	-15.68	62.90	47.22	74.00	-26.78	Peak	167	301	P
3	4804.00	-8.53	37.80	29.27	54.00	-24.73	Average	100	290	P
4	4804.00	-8.53	47.20	38.67	74.00	-35.33	Peak	100	290	P
5	12010.00	1.77	28.50	30.27	54.00	-23.73	Average	100	106	P
6	12010.00	1.77	41.60	43.37	74.00	-30.63	Peak	100	106	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH00	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-15.68	51.20	35.52	54.00	-18.48	Average	100	283	P
2	2390.00	-15.68	62.60	46.92	74.00	-27.08	Peak	100	283	P
3	4804.00	-8.53	32.82	24.29	54.00	-29.71	Average	100	141	P
4	4804.00	-8.53	44.66	36.13	74.00	-37.87	Peak	100	141	P
5	12010.00	1.77	27.49	29.26	54.00	-24.74	Average	100	319	P
6	12010.00	1.77	42.30	44.07	74.00	-29.93	Peak	100	319	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH19	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-15.68	51.60	35.92	54.00	-18.08	Average	167	283	P
2	2390.00	-15.68	62.80	47.12	74.00	-26.88	Peak	167	283	P
3	2483.50	-15.36	51.46	36.10	54.00	-17.90	Average	167	283	P
4	2483.50	-15.36	63.60	48.24	74.00	-25.76	Peak	167	283	P
5	4880.00	-8.30	35.67	27.37	54.00	-26.63	Average	100	296	P
6	4880.00	-8.30	47.49	39.19	74.00	-34.81	Peak	100	296	P
7	7320.00	-3.83	32.62	28.79	54.00	-25.21	Average	100	142	P
8	7320.00	-3.83	44.73	40.90	74.00	-33.10	Peak	100	142	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH19	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-15.68	51.46	35.78	54.00	-18.22	Average	100	302	P
2	2390.00	-15.68	63.50	47.82	74.00	-26.18	Peak	100	302	P
3	2483.50	-15.36	51.20	35.84	54.00	-18.16	Average	100	302	P
4	2483.50	-15.36	62.70	47.34	74.00	-26.66	Peak	100	302	P
5	4880.00	-8.30	32.59	24.29	54.00	-29.71	Average	100	284	P
6	4880.00	-8.30	44.60	36.30	74.00	-37.70	Peak	100	284	P
7	7320.00	-3.83	31.95	28.12	54.00	-25.88	Average	100	351	P
8	7320.00	-3.83	43.79	39.96	74.00	-34.04	Peak	100	351	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode	: Mode 1, CH39	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-15.36	57.21	41.85	54.00	-12.15	Average	160	300	P
2	2483.50	-15.36	64.30	48.94	74.00	-25.06	Peak	160	300	P
3	4960.00	-8.07	36.69	28.62	54.00	-25.38	Average	100	280	P
4	4960.00	-8.07	46.57	38.50	74.00	-35.50	Peak	100	280	P
5	7440.00	-3.52	32.53	29.01	54.00	-24.99	Average	100	104	P
6	7440.00	-3.52	45.10	41.58	74.00	-32.42	Peak	100	104	P


Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode	: Mode 1, CH39	Temperature	: 23 °C
Test Date	: Feb. 19, 2019	Humidity	: 61 %



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2483.50	-15.36	52.30	36.94	54.00	-17.06	Average	100	299	P
2	2483.50	-15.36	61.50	46.14	74.00	-27.86	Peak	100	299	P
3	4960.00	-8.07	32.69	24.62	54.00	-29.38	Average	100	100	P
4	4960.00	-8.07	44.49	36.42	74.00	-37.58	Peak	100	100	P
5	7440.00	-3.52	33.50	29.98	54.00	-24.02	Average	100	317	P
6	7440.00	-3.52	44.53	41.01	74.00	-32.99	Peak	100	317	P

Note: Level=Reading+Factor

Margin=Level-Limit

Factor=Antenna Factor + cable loss - Amplifier Factor



6.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz



7. Test of Spurious Emission (Conducted)


7.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

7.2 Test Procedure

- The transmitter output was connected to the spectrum analyzer via a low loss cable.
- Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- Peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20dB relative to the maximum measured in-band peak PSD level.
- The band edges was measured and recorded.

7.3 Test Setup Layout



7.4 Test Result and Data







Test Result : PASS

Temperature : 22°C

Test Date : Mar. 05, 2019




Humidity : 52%

Note: Test plots refer to the following pages.

Modulation Type: GFSK
CH00Modulation Type: GFSK
CH19



Modulation Type: GFSK
CH39





8. On Time, Duty Cycle and Measurement methods


8.1 Test Limit

None; for reporting purposes only.

8.2 Test Procedure

KDB 558074 Zero-Span Spectrum Analyzer Method.

8.3 Test Setup Layout



8.4 Test Result and Data

Test Date : Mar. 08, 2019


Temperature : 22°C

Humidity : 58%

Modulation Mode	On Time (ms)	Period Time (ms)	Duty Cycle (%)
GFSK	0.40	0.63	64.33%



Modulation Type: GFSK





9. 6dB Bandwidth Measurement Data


9.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

9.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 1~5% of the emission bandwidth and VBW $\geq 3 \times$ RBW.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.
- The 6dB Bandwidth was measured and recorded.

9.3 Test Setup Layout



9.4 Test Result and Data

Test Date : Mar. 08, 2019
Humidity : 58%


Temperature : 22°C

Modulation Type	Channel	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
GFSK	00	2402	684.00	500
	19	2440	678.00	500
	39	2480	678.00	500




Modulation Type: GFSK


CH00



CH19



CH39





10. Maximum Peak and Average Output Power


10.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

10.2 Test Procedures

The antenna port (RF output) of the EUT was connected to the input (RF input) of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

10.3 Test Setup Layout



10.4 Test Result and Data

Test Date : Mar. 08, 2019 Temperature : 22°C
Humidity : 58%

Modulation Type	Channel	Frequency (MHz)	Power Output (dBm)		Power Output (mW)	
			Peak	Average	Peak	Average
GFSK	0	2402	1.56	1.22	1.432	1.324
	19	2440	2.67	2.4	1.849	1.738
	39	2480	1.71	1.25	1.483	1.334

*Average power is for reference only.



11. Power Spectral Density


11.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

11.2 Test Procedures

- The transmitter output was connected to spectrum analyzer.
- The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=auto couple.
- The power spectral density was measured and recorded.

11.3 Test Setup Layout




11.4 Test Result and Data

Test Date : Mar. 08, 2019 Temperature : 22°C
Humidity : 58%

Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)	Limit
GFSK	00	2402	-13.97	7.08
	19	2440	-12.53	7.08
	39	2480	-13.73	7.08



Modulation Type: GFSK
CH00



CH19



CH39

