

TEST REPORT

Ref. n.	TSupPhotos_FCC187795-0	Issue Date:	23/06/2026	Pages:	8
Test object	Type test according to Standards 47 CFR FCC Part 15 Subpart C §15.249				
Applicant	Datamars SA Via Industria 16 - 6184 Lamone - Switzerland				
Trade mark	Tru-Test™ DATAMARS				
Manufacturer	Datamars SA				
Product	Active ear TAG				
Tested model	EARTAG-1				
FCC Identification number	NDX-EARTAG				
Date of test samples receipt	12/05/2026				
No. of tested samples	1 – Sampled by the Manufacturer				
Test date	From 12/05/2026 to 27/05/2026				
Testing site	PRSLAB S.r.l. Unipersonale - Via Campagna 92 - 22020 Faloppio - Como - Italy				
FCC designation number	IT0012				
Verifications carried out by	Daniele AOSANI Laboratory Engineer				
Approved by	Luana PARISI Reviewer				

The test results reported in this test report shall refer only to the samples tested.

The sample has been provided by the customer and the results apply to the sample as received.

This report may not be partially reproduced, except with the prior written permission of the issuing Laboratory.

PRSLAB refuses any responsibility about information provided by the customer contained in this test report.

TABLE OF CONTENTS

0. RELEASE CONTROL RECORD	2
1. TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT).....	3
1.1 EUT Identification	3
1.2 Radio module technical data	4
2. PHOTOGRAPHIC DOCUMENTATION	5

0. RELEASE CONTROL RECORD

TEST REPORT NUMBER	REASON OF CHANGE	DATE OF ISSUE
TSupPhotos_FCC187795-0	Original release	23/06/2026

This document is valid in last revision that deletes and replaces the previous one

1. TECHNICAL INFORMATION OF EQUIPMENT UNDER TEST (EUT)

1.1 EUT Identification

DESCRIPTION	Active ear TAG
MODEL NAME	EARTAG-1
FCC ID	NDX-EARTAG
NODE ID	14099
PRS LAB INTERNAL REFERENCE	BC 128/2026 8/14
TRADEMARK	
MANUFACTURER	Datamars SA
COUNTRY OF MANUFACTURER	Switzerland
SINGLE UNIT OR SYSTEM	Single
POWER SOURCE	Internal battery model CR2477 manufactured by PANASONIC
POWER SUPPLY NOMINAL VOLTAGE	3Vdc
MAX ABSORBED CURRENT OR MAX POWER	NA
OPERATING TEMPERATURE	-10°C ÷ +55°C
FIRMWARE VERSION (Information provided by Customer)	2.6.8
HARDWARE VERSION (Information provided by Customer)	V1.2 (HW20)
DIMENSIONS	See photographic documentation
EUT STANDING	☐ WALL; ☐ CEILING; ☐ TABLE; ☐ FLOOR; ☐ RACK MOUNTED; ☐ BODY WORN; ☐ HANDELD; ☐ PORTABLE; ☐ MOBILE; ☐ VEHICLE; ☒ LIVESTOCK
HIGHEST INTERNAL FREQUENCY (Information provided by Customer)	☐ <108MHz; ☐ 108MHz<F<500MHz; ☐ 500MHz<F<1GHz; ☒ F>1GHz
ANCILLARY EQUIPMENT	☐ YES; ☒ NO
ENVIROMENT (According to ETSI EN 301 489-1 V2.2.3)	☐ FIXED-USE; ☐ VEHICLE USE; ☒ PORTABLE USE

1.2 Radio module technical data

CHIP MANUFACTURER	 SEMTECH®
MODEL NAME	SX1280
ETS CATEGORY	Short Range Device
TYPE OF RADIO DEVICE	TX only
FREQUENCY BAND	2402 ÷ 2480MHz
NUMBER OF CHANNELS	40
CHANNEL BANDWIDTH	1.2MHz
CHANNEL SPACING	2MHz
TYPE OF MODULATION	GFSK
TRANSFER RATE	2 Mbps
ANTENNA TYPE (Information provided by Customer)	PCB Antenna
ANTENNA GAIN (Information provided by Customer)	0.7dBi

2. PHOTOGRAPHIC DOCUMENTATION

PHOTO N° 1 – EUT IDENTIFICATION





PHOTO N°2 - RADIATED EMISSION TEST SETUP





END OF TEST REPORT