

Straubing, August 28, 2001

TEST - REPORT

No. 51118-10523-2

for

Immobilizer 05 470 20

Inductive Reader

Applicant: Leopold Kostal GmbH & Co. KG

Purpose of testing: To show compliance with
FCC Code of Federal Regulations,
Part 15 Subpart C, Section 15.209

Note:

The test data of this report relate only to the individual item which has been tested.
This report shall not be reproduced except in full extent without the written approval
of the testing laboratory.

Table of Contents

1.	Administrative Data	3
2.	Identification of Test Laboratory	4
3.	Summary of Test Results	5
4.	Operation Mode of EUT	6
5.	Configuration of EUT and Peripheral Devices.....	7
6.	Measuring Methods	8
6.1.	Radiated Emission 30 MHz - 1 GHz (FCC §15.205.a,b, §15.209, §15.231.b / RSS-210 Sections 6.1.1.b, 6.3).....	9
6.2.	Radiated Emission 1 GHz - 10 GHz (FCC §15.205.a,b, §15.209, §15.231.b / RSS-210 Sections 6.1.1.b, 6.3).....	11
7.	Equipment List.....	13
8.	Photographs Taken During Testing.....	15
9.	List of Measurements According To FCC Part 15 Subpart C	18
10.	List of Measurements According To Industry Canada RSS- 210.....	19
11.	Referenced Regulations	20
12.	Test Results.....	21
13.	Charts taken during testing	22

1. Administrative Data

Equipment Under Test (EUT): Immobilizer 05 470 20

Serial number(s): 26

Type of equipment: Inductive Reader

Parts/accessories: ---

FCC-ID: ---

Applicant:
(full address) Leopold Kostal GmbH & Co. KG
Hauert 11
D-44227 Dortmund

Contract identification: ---

Contact person: Roy Haasler

Manufacturer: Leopold Kostal GmbH & Co. KG

Receipt of EUT: July 26, 2001

Date of test: August 2001

Note: ---

Responsible for testing: Johann Roidt

Responsible for test report: Johann Roidt

2. Identification of Test Laboratory

Test Laboratory:
(full address): Senton GmbH EMI/EMC Test Center
Aeussere Fruehlingstrasse 45
D-94315 Straubing
Germany

Contact person: Mr. Johann Roidt
Communication: Telephone (+49) 0 94 21 / 55 22-0
Fax (+49) 0 94 21 / 55 22-99
eMail: Office@senton.de

FCC file number: 31040/SIT 1300F2

Industry Canada file number: IC 3050

3. Summary of Test Results

The tested sample complies with the requirements set forth in the

Code of Regulations Part 15 Subpart C, Section §15.209 (intentional radiators) of the Federal Communication Commission (FCC).



Johann Roidt
Technical Manager

4. Operation Mode of EUT

Reading TAG continuously

5. Configuration of EUT and Peripheral Devices

Configuration of cables of EUT

Not applicable

Configuration of peripheral devices connected to EUT

Not applicable

6. Measuring Methods

6.1. Radiated Emission 30 MHz - 1 GHz (FCC §15.205.a,b, §15.209, §15.231.b / RSS-210 Sections 6.1.1.b, 6.3)

Radiated emissions are measured over the frequency range from 30 MHz to 1 GHz. The bandwidth of the EMI-receiver is set to 120 kHz and the detector-function is set to CISPR quasi-peak.

The test setup is made in accordance with ANSI C63.4-1992.

Measurements are made in both the horizontal and vertical planes of polarization. Preliminary scans are taken in a semi-anechoic room using a spectrum analyzer with the detector function set to peak. Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

All tests are performed at a test-distance of 3 meters.

For final testing an open-area test-site is used. During the tests the EUT is rotated all around and the receiving-antenna is raised and lowered from 1 meter to 4 meters to find the maximum levels of emissions. The cables and equipment is placed and moved within the range of position likely to find their maximum emissions.

See figure 2 for the measurement setup.

Test equipment used (see equipment list for details):

01, 02, 05, 12, 38, 39, 40, 41, 58, 61, 64, 66




Figure 2: Measurement setup for radiated emission test below 1 GHz

- | | |
|---|------------------------------|
| 1 Transmitter (EUT) | 4 Measurement antenna |
| 2 Wooden pedestal (if necessary) | 5 Test receiver |
| 3 Wooden table | 6 Turn table |

6.2. Radiated Emission 1 GHz - 10 GHz (FCC §15.205.a,b, §15.209, §15.231.b / RSS-210 Sections 6.1.1.b, 6.3)

Radiated emissions are measured in the frequency range 1 GHz to 10 GHz. Resolution and video bandwidth of the spectrum analyzer are set to 1 MHz. Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

Additional measurements are performed at critical frequencies with reduced span. EUT is rotated all around and receiving antenna is raised and lowered to find the maximum levels of emission. The cables and equipment are placed and moved within the range of position likely to find their maximum emissions.

All tests are performed in a semi-anechoic chamber with a test-distance of 3 meters.

If possible preamplifiers are used for the whole frequency range. Special care is taken to avoid overload in transmit mode (using appropriate attenuators if necessary).

See figure 3 for the measurement setup.

Test equipment used (see equipment list for details):

02, 13, 14, 16, ,42, 44, 45, 57, 64




Figure 3: Measurement setup for radiated emission test above 1 GHz

- | | |
|---|---------------------------------------|
| 1 Transmitter (EUT) | 3 Measurement antenna |
| 2 Wooden pedestal (if necessary) | 4 Preamplifier (if applicable) |
| | 5 Spectrum analyzer |
| | 6 Turn table |
| | 7 Semi anechoic room |

7. Equipment List

To facilitate reference to test equipment used for related tests, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory.


No.	Type	Model	Serial Number	Manufacturer
01	Spectrum Analyzer	R 3271	05050023	Advantest
02	EMI Test Receiver	ESMI	839379/013 839587/006	Rohde & Schwarz
03	Test Receiver	ESH 3	880112/032	Rohde & Schwarz
04	Test Receiver	ESHS 10	860043/016	Rohde & Schwarz
05	Test Receiver	ESV	881414/009	Rohde & Schwarz
06	Test Receiver	ESVP	881120/024	Rohde & Schwarz
07	Audio Analyzer	UPA	862954	Rohde & Schwarz
08	Power Meter	NRVS	836856/015	Rohde & Schwarz
09	Power Sensor	NRV-Z52	837901/030	Rohde & Schwarz
10	Power Sensor	NRV-Z4	863828/015	Rohde & Schwarz
11	Preamplifier	ESV-Z3	860907/004	Rohde & Schwarz
12	Preamplifier	R14601		Advantest
13	Preamplifier	ACX/080-3030	32640	CTT
14	Preamplifier	ACO/180-3530	32641	CTT
15	Signal Generator	SMS	872166/039	Rohde & Schwarz
16	Signal Generator	HP 8673 D	2930A00966	Hewlett Packard
17	Waveform Generator	HP 33120 A	US34005375	Hewlett Packard
18	Attenuator 20 dB	4776-20	9503	Narda
19	Attenuator 10 dB	4776-10	9412	Narda
20	Pulse Limiter	ESH 3-Z2	1144	Rohde & Schwarz
21	Pulse Limiter	11947 A	3107A00566	Hewlett Packard
22	V-Network	ESH 3-Z5	862770/018	Rohde & Schwarz
23	V-Network	ESH 3-Z5	894785/005	Rohde & Schwarz
24	V-Network	ESH 3-Z5	830952/025	Rohde & Schwarz
25	V-Network	ESH 3-Z6	830722/010	Rohde & Schwarz
26	V-Network	NSLK 8127	8127152	Schwarzbeck
27	V-Network	NNLA 8119	8119148	Schwarzbeck
28	V-Network	SE 01	01	Senton
29	T-Network	ESH 3-Z4	890602/011	Rohde & Schwarz
30	T-Network	ESH 3-Z4	890602/012	Rohde & Schwarz
31	High Impedance Probe	TK 9416	01	Schwarzbeck
32	High Impedance Probe	TK 9416	02	Schwarzbeck
33	Current Probe	ESH 2-Z1	863366/18	Rohde & Schwarz
34	Current Probe	ESV-Z1	862553/3	Rohde & Schwarz

No.	Type	Model	Serial Number	Manufacturer
35	Absorbing Clamp	MDS 21	80911	Lüthi
36	Absorbing Clamp	MDS 21	79690	Lüthi
37	Loop Antenna	HFH2-Z2	882964/1	Rohde & Schwarz
38	Biconical Antenna	HK 116	842204/001	Rohde & Schwarz
39	Biconical Antenna	HK 116	836239/02	Rohde & Schwarz
40	Log. Periodic Antenna	HL 223	841516/023	Rohde & Schwarz
41	Log. Periodic Antenna	HL 223	834408/12	Rohde & Schwarz
42	Horn Antenna	3115	9508-4553	Emco
43	Horn Antenna	3160-03	9112-1003	Emco
44	Horn Antenna	3160-04	9112-1001	Emco
45	Horn Antenna	3160-05	9112-1001	Emco
46	Horn Antenna	3160-06	9112-1001	Emco
47	Horn Antenna	3160-07	9112-1008	Emco
48	Horn Antenna	3160-08	9112-1002	Emco
49	Horn Antenna	3160-09	9403-1025	Emco
50	Digital multimeter	199	463386	Keithley
51	DC Power Supply	NGSM 32/10	203	Rohde & Schwarz
52	DC Power Supply	NGB	2455	Rohde & Schwarz
53	DC Power Supply	NGA	386	Rohde & Schwarz
54	Temperature Test Chamber	HT4010	07065550	Heraeus
55	Cable	RG214	1309	Senton
56	Cable	200CM_001	1357	Rosenberger
57	Cable	150CM_001	1479	Rosenberger
58	Cable Set EG1	RG214	1189 - 1191	Senton
59	Cable Set Cabine 1	RG214		Senton
60	Cable Set Cabine 2	RG214		Senton
61	Cable Set Cabine 3	RG214		Senton
62	Shielded Room	No. 1	1451	Senton
63	Shielded Room	No. 2	1452	Senton
64	Semi-anechoic Chamber	No. 3	1453	Siemens
65	Shielded Room	No. 4	1454	Euroshield
66	Open Area Test Site	EG 1		Senton
67	Test fixture			Senton

8. Photographs Taken During Testing


Photo No. 8.1

Test setup for radiated emission test 9 kHz - 30 MHz



Photos No. 8.2 - 8.3

Test setup for radiated emission final test 30 MHz - 1 GHz



9. List of Measurements According To FCC Part 15 Subpart C

FCC Part 15 Subpart C			
Section(s):	Test	Page(s)	Result
	Transmit mode (TX):		
§15.231.c	Bandwidth of emission		Passed
§15.207	Conducted emission test 450 kHz - 30 MHz		Passed
§15.231.b §15.209 §15.205.a,b	Radiated emission test 9 kHz - 30 MHz	---	Not Applicable (acc. to §15.33)
§15.231.b §15.209 §15.205.a,b	Radiated emission test 30 MHz - 1 GHz		Passed
§15.231.b §15.209 §15.205.a,b	Radiated emission test 1 GHz - 5 GHz		Passed
	Receive mode (RX):		
§15.207	Conducted emission test 450 kHz - 30 MHz		Passed
§15.209	Radiated emission test 9 kHz - 30 MHz	---	Not Applicable (acc. to §15.33)
§15.209	Radiated emission test 30 MHz - 1 GHz		Passed
§15.209	Radiated emission test 1 GHz - 2.5 GHz		Passed

10. List of Measurements According To Industry Canada RSS-210

Industry Canada RSS-210 Issue 2			
Section(s):	Test	Page(s)	Result
	Transmit mode (TX):		
6.1.1.c	Bandwidth		Passed
6.6	Conducted emission test 450 kHz - 30 MHz		Passed
6.1.1.b 6.3	Radiated emission test 9 kHz - 30 MHz	---	Not Applicable (acc. to 6.3.e)
6.1.1.b 6.3	Radiated emission test 30 MHz - 1 GHz		Passed
6.1.1.b 6.3	Radiated emission test 1 GHz - 5 GHz		Passed
	Receive mode (RX):		
7.4	Conducted emission test 450 kHz - 30 MHz		Passed
7.3	Radiated emission test 30 MHz - 1 GHz		Passed
7.3	Radiated emission test 1 GHz - 2.5 GHz		Passed

11. Referenced Regulations

All tests were performed with reference to the following regulations and standards:

☒	FCC Part 15 Subpart A	Code of Regulations Part 15 (Radio Frequency Devices), Subpart A (General) of the Federal Communication Commission (FCC)	October 20, 1997
☒	FCC Part 15 Subpart B	Code of Regulations Part 15 (Radio Frequency Devices), Subpart B (Unintentional Radiators) of the Federal Communication Commission (FCC)	October 20, 1997
☒	FCC Part 15 Subpart C	Code of Regulations Part 15 (Radio Frequency Devices), Subpart C (Intentional Radiators) of the Federal Communication Commission (FCC)	October 20, 1997
☒	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz - 40 GHz	October, 1992
☒	RSS-210	Radio Standards Specification RSS-210 Issue 2 for Low Power Licence-Exempt Radiocommunication Devices of Industry Canada	February 24, 1996

12. Test Results

13. Charts taken during testing

Radiated Emission Test 9 kHz - 30 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Shielded room, cabin no. 3

Tested on:
Test distance 3 metres

Date of test: 08/13/2001
Operator: A. Stübinger


Test performed: automatically
File name:

Mode:
- with key

Final results without key:
0.1247 MHz: 78.6 dB μ V/m
0.3739 MHz: 36.5 dB μ V/m

Detector:
Peak / Final Results: QP

Final results:
Selected by hand



Result:
Limit kept

Project file:
51118-10523

Page 23 of 34 Pages

Radiated Emission Test 9 kHz - 30 MHz according to FCC Part 15 Subpart C

Model: Immobilizer 0547020	Mode: - with key
Serial no.: Sample # 52	Final results without key: 0.1247 MHz: 78.6 dBµV/m 0.3739 MHz: 36.5 dBµV/m
Applicant: Leopold Kostal GmbH & Co KG	
Test site: Shielded room, cabin no. 3	
Tested on: Test distance 3 metres	
Date of test: 08/13/2001	Operator: A. Stübinger
Test performed: automatically	File name:

Detector: Peak / Final Results: QP	Final results: Selected by hand
---------------------------------------	------------------------------------

[illegible]

Result: Limit kept	Project file: 51118-10523	Page 24 of 34 Pages
-----------------------	------------------------------	---------------------

Radiated Emission Test 9 kHz - 30 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Shielded room, cabin no. 3

Tested on:
Test distance 3 metres

Date of test: 08/13/2001 Operator: A. Stübinger


Test performed: automatically File name:

Mode:
- with key

Final results without key:
0.1247 MHz: 80.6 dB μ V/m
0.3739 MHz: 34.5 dB μ V/m

Detector:
Average / Final Results: AV

Final results:
Selected by hand



Result:
Limit kept

Project file:
51118-10523

Page 25 of 34 Pages

Radiated Emission Test 9 kHz - 30 MHz according to FCC Part 15 Subpart C

Model: Immobilizer 0547020	Mode: - with key Final results without key: 0.1247 MHz: 80.6 dBµV/m 0.3739 MHz: 34.5 dBµV/m
Serial no.: Sample # 52	
Applicant: Leopold Kostal GmbH & Co KG	
Test site: Shielded room, cabin no. 3	
Tested on: Test distance 3 metres	
Date of test: Operator: 08/13/2001 A. Stübinger	
Test performed: File name: automatically	

Detector: Average / Final Results: AV	Final results: Selected by hand
--	------------------------------------

[illegible]

Result: Limit kept	Project file: 51118-10523	Page 26 of 34 Pages
-----------------------	------------------------------	---------------------

Radiated Emission Test 30 MHz - 300 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Horizontal Polarization


Date of test: 08/13/2001 Operator: A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges



Result:
Prescan

Project file:
51118-10523

Page 27 of 34 Pages

Radiated Emission Test 30 MHz - 300 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Horizontal Polarization

Date of test: 08/13/2001 Operator: A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges

<i>Frequency MHz</i>	<i>Reading dBμV</i>	<i>Correction factor dB</i>	<i>Value dBμV/m</i>	<i>Limit dBμV/m</i>	<i>Limit exceeded</i>
no results					

Result:
Prescan

Project file:
51118-10523

Page 28 of 34 Pages

Radiated Emission Test 30 MHz - 300 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Vertical Polarization


Date of test: 08/13/2001 Operator: A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges



Result:
Prescan

Project file:
51118-10523

Page 29 of 34 Pages

Radiated Emission Test 30 MHz - 300 MHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Vertical Polarization

Date of test: 08/13/2001 Operator:
A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges

<i>Frequency MHz</i>	<i>Reading dBμV</i>	<i>Correction factor dB</i>	<i>Value dBμV/m</i>	<i>Limit dBμV/m</i>	<i>Limit exceeded</i>
no results					

Result:
Prescan

Project file:
51118-10523

Page 30 of 34 Pages

Radiated Emission Test 295 MHz - 1 GHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Horizontal Polarization


Date of test: 08/13/2001 Operator: A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges



Result:
Prescan

Project file:
51118-10523

Page 31 of 34 Pages

Radiated Emission Test 295 MHz - 1 GHz according to FCC Part 15 Subpart C
--

Model: Immobilizer 0547020	Mode: - key plugged in position 3
Serial no.: Sample # 52	
Applicant: Leopold Kostal GmbH & Co KG	
Test site: Semi anechoic room, cabin no. 3	
Tested on: Test distance 3 meters Horizontal Polarization	
Date of test: 08/13/2001	
Test performed: automatically	File name:

Detector: Peak	List of values: 10 dB Margin 50 Subranges
-------------------	---

<i>Frequency MHz</i>	<i>Reading dBμV</i>	<i>Correction factor dB</i>	<i>Value dBμV/m</i>	<i>Limit dBμV/m</i>	<i>Limit exceeded</i>
863.03	2.0	34.2	36.2	46.0	
886.19	2.6	34.6	37.2	46.0	
926.48	2.4	34.7	37.1	46.0	
939.57	2.2	34.6	36.8	46.0	
952.66	2.4	34.7	37.1	46.0	

Result: Prescan	Project file: 51118-10523	Page 32 of 34 Pages
--------------------	------------------------------	---------------------

Radiated Emission Test 295 MHz - 1 GHz according to FCC Part 15 Subpart C

Model:
Immobilizer 0547020

Serial no.:
Sample # 52

Applicant:
Leopold Kostal GmbH & Co KG

Test site:
Semi anechoic room, cabin no. 3

Tested on:
Test distance 3 meters
Vertical Polarization


Date of test: 08/13/2001 Operator: A. Stübinger

Test performed: automatically File name:

Mode:
- key plugged in position 3

Detector:
Peak

List of values:
10 dB Margin 50 Subranges



Result:
Prescan

Project file:
51118-10523

Page 33 of 34 Pages

Radiated Emission Test 295 MHz - 1 GHz
according to FCC Part 15 Subpart C

Model: Immobilizer 0547020	Mode: - key plugged in position 3
Serial no.: Sample # 52	
Applicant: Leopold Kostal GmbH & Co KG	
Test site: Semi anechoic room, cabin no. 3	
Tested on: Test distance 3 meters Vertical Polarization	
Date of test: 08/13/2001	
Test performed: automatically	File name:

Detector: Peak	List of values: 10 dB Margin 50 Subranges
-------------------	---

[illegible]

Result: Prescan	Project file: 51118-10523	Page 34 of 34 Pages
--------------------	------------------------------	---------------------