

RADIO TEST REPORT

Test Report No. 15376096H-R1

Customer	TOYOTA MOTOR CORPORATION
Description of EUT	Smart LF oscillator
Model Number of EUT	TMLF19D-7
FCC ID	NI4TMLF19D-7
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	August 30, 2024
Remarks	-

Representative test engineerTakumi Nishida
Engineer**Approved by**Shinichi Miyazono
Leader

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 23.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No. 15376096H

This report is a revised version of 15376096H. 15376096H is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15376096H	August 26, 2024	-
1	15376096H-R1	August 30, 2024	Correction of the Worst margin for Electric Field Strength of Spurious Emission in Clause 3.2; From "19.4 dB, 843.987 MHz, Horizontal, QP (Mode 2)" To "14.7 dB, 0.67100 MHz, 0 deg., QP (Mode 5)"
1	15376096H-R1	August 30, 2024	Deletion of the following the sentence from Radiated Emission (Fundamental and Spurious Emission) data (Mode 5); * Since the peak emission result satisfied the average limit, duty factor was omitted.
1	15376096H-R1	August 30, 2024	Notation correction of the Duty Cycle data

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information.....	5
SECTION 2: Equipment Under Test (EUT)	5
SECTION 3: Test specification, procedures & results	6
SECTION 4: Operation of EUT during testing.....	9
SECTION 5: Radiated emission (Fundamental and Spurious Emission).....	12
SECTION 6: -20 dB Bandwidth.....	14
SECTION 7: 99 % emission bandwidth	14
APPENDIX 1: Test data	15
Radiated Emission (Fundamental and Spurious Emission)	15
Duty Cycle	21
-20 dB Bandwidth / 99 % emission bandwidth	22
APPENDIX 2: Test instruments	24
APPENDIX 3: Photographs of test setup.....	25
Radiated Emission	25
Worst Case Position	26

SECTION 1: Customer Information

Company Name	TOYOTA MOTOR CORPORATION
Address	1, Toyota-Cho, Toyota, Aichi, 471-8572, Japan
Telephone Number	+81-50-3166-4371
Contact Person	Arinobu Kimura

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Smart LF oscillator
Model Number	TMLF19D-7
Serial Number	Refer to SECTION 4.2
Condition	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	July 31, 2024
Test Date	August 1 to 9, 2024

2.2 Product Description

General Specification

Rating	DC 12 V
--------	---------

Radio Specification

Equipment Type	Transceiver
Frequency of Operation	134.2 kHz
Type of Modulation	ASK
Antenna type	Outside antenna (*1), Inside antenna (*2), Rear antenna (*3), Immobilizer antenna *1: Maximum number of this antenna is 4. *2: Maximum number of this antenna is 3. *3: Maximum number of this antenna is 2.

Smart LF oscillator (model: TMLF19D-7) consists of the following parts:

- Smart ECU
- Outside Antenna
- Inside Antenna
- Rear Antenna
- Immobilizer Antenna

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.209 Radiated emission limits; general requirements.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 8.8	<FCC> Section 15.207 <ISED> RSS-Gen 8.8	N/A	N/A	*1)
Electric Field Strength of Fundamental Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.5, 6.12	<FCC> Section 15.209 <ISED> RSS-210 8.2 RSS-Gen 8.9	8.9 dB 134.2 kHz, 0 deg. Peak with Duty factor (Mode 1)	Complied	Radiated
Electric Field Strength of Spurious Emission	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> RSS-Gen 6.5, 6.6, 6.13	<FCC> Section 15.209 <ISED> RSS-210 8.3 RSS-Gen 8.9	14.7 dB 0.67100 MHz, 0 deg., QP (Mode 5)	Complied	Radiated
-20 dB Bandwidth	<FCC> ANSI C63.10:2013 6 Standard test methods <ISED> -	<FCC> Reference data <ISED> -	N/A	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

FCC Part 15.31 (e)

The EUT provides stable voltage constantly to the wireless transmitter regardless of input voltage. Instead of a new battery, DC power supply was used for the test. That does not affect the test result, therefore the EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99 % emission bandwidth	RSS-Gen 6.7	-	N/A	-	Radiated

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5

-20 dB Bandwidth and 99% Occupied Bandwidth

Item	Unit	Calculated Uncertainty (+/-)
Bandwidth (OBW)	%	0.96

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing


4.1. Operating Mode(s)

Test mode	Remarks
1) Tx 134.2kHz, Outside Antenna in A circuit	*1)
2) Tx 134.2kHz, Rear Antenna in B circuit	*1)
3) Tx 134.2kHz, Inside Antenna in C circuit	*1)
4) Tx 134.2kHz, Immobilizer Antenna in D circuit *2)	*1)
5) Tx 134.2kHz, Outside Antenna and Rear Antenna (B, C, D, E, F and G)	*1)
*Power of the EUT was set by the software as follows; Software: 19CY_IDT_denpa_v01_200721 Version: 01 (Date: 2020.07.21, Storage location: EUT memory) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product. Justification: The system was configured in typical fashion (as a user would normally use it) for testing.	

*1) Refer to Timing of transmission in "Theory of Operation" for details.

*2) This EUT has two modes which transponder key is attached or not. The worst case was confirmed with and without transponder key attached, as a result, the test without transponder key attached was the worst case. Therefore for Electric Field Strength of Fundamental Emission and Electric Field Strength of Spurious Emission tests, the test without transponder key attached was performed only.

4.2 Configuration and Peripherals



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

*The test was performed with Item B as representative, because it was confirmed that there was no difference among Item B to Item E at the pre-check.

*The test was performed with Item F as representative, because it was confirmed that there was no difference among Item F to Item G at the pre-check.

*The test was performed with Item H as representative, because it was confirmed that there was no difference among Item H to Item J at the pre-check.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	Smart ECU	TMLF19D-7	LF19-152 *1) LF19-155 *2)	-	EUT
B	Outside Antenna	D19B3	TD793	-	EUT
C	Outside Antenna	D19B3	TD794	-	EUT
D	Outside Antenna	D19B3	TD795	-	EUT
E	Outside Antenna	D19B3	TD796	-	EUT
F	Rear Antenna	12TA0	TT207	-	EUT
G	Rear Antenna	12TA0	TT208	-	EUT
H	Inside Antenna	18WA0	334	-	EUT
I	Inside Antenna	18WA0	335	-	EUT
J	Inside Antenna	18WA0	336	-	EUT
K	Immobilizer Antenna	18PA5	TP230	-	EUT
L	Switch Box	-	-	-	-
M	Smart key	19CY	117	-	*3)

*1) Used for Mode 1 to 4

*2) Used for Mode 5

*3) Used for Mode 4 only

List of Cables Used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC Cable	2.4	Unshielded	Unshielded	-
2	Antenna Cable	3.0	Unshielded	Unshielded	-
3	Antenna Cable	3.0	Unshielded	Unshielded	-
4	Antenna Cable	3.0	Unshielded	Unshielded	-
5	Antenna Cable	3.0	Unshielded	Unshielded	-
6	Antenna Cable	3.0	Unshielded	Unshielded	-
7	Antenna Cable	3.0	Unshielded	Unshielded	-
8	Antenna Cable	3.0	Unshielded	Unshielded	-
9	Antenna Cable	3.0	Unshielded	Unshielded	-
10	Antenna Cable	3.0	Unshielded	Unshielded	-
11	Antenna Cable	3.0	Unshielded	Unshielded	-
12	DC & Signal Cable	3.0	Unshielded	Unshielded	-

SECTION 5: Radiated emission (Fundamental and Spurious Emission)

Test Procedure

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[Limit conversion]

The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

[Frequency: From 9 kHz to 30 MHz]

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0 deg., 45 deg., 90 deg., and 135 deg., 180 deg.) and horizontal polarization.

*Refer to Figure 2 about Direction of the Loop Antenna.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

These tests were performed in semi anechoic chamber. Therefore, the measured level of emissions may be higher than if measurements were made without a ground plane. However, test results were confirmed to pass against standard limit.

[Frequency: From 30 MHz to 1 GHz]

The measuring antenna height varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

[Test instruments and test settings]

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz
Antenna Type	Loop	Biconical	Logperiodic

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.


Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz
Instrument used	Test Receiver				
Detector	PK / AV	QP	PK / AV	QP	QP
IF Bandwidth	200 Hz	200 Hz	9 kHz	9 kHz	120 kHz
Test Distance	3 m *1)	3 m *1)	3 m *1)	3 m *2)	3 m

*1) Distance Factor: $40 \times \log (3 \text{ m} / 300 \text{ m}) = -80 \text{ dB}$

*2) Distance Factor: $40 \times \log (3 \text{ m} / 30 \text{ m}) = -40 \text{ dB}$

Figure 1: Test Setup


Below 1 GHz




Test Distance: 3 m

Figure 2: Direction of the Loop Antenna

Side View (Vertical)




Top View (Horizontal)



Antenna was not rotated.

Top View (Vertical)



- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz to 1 GHz
Test data : APPENDIX
Test result : Pass

SECTION 6: -20 dB Bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-20 dB Bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer

Test data : APPENDIX

Test result : Pass

SECTION 7: 99 % emission bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
99 % emission bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer

Peak hold was applied as Worst-case measurement.

Test data : APPENDIX

Test result : Pass

APPENDIX 1: Test data

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.1
Semi Anechoic Chamber	No.1	No.1
Date	August 8, 2024	August 9, 2024
Temperature / Humidity	22 deg. C / 53 % RH	24 deg. C / 55 % RH
Engineer	Takumi Nishida (Below 30 MHz)	Takumi Nishida (Above 30 MHz)
Mode	Mode 1	

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	103.0	19.5	-74.1	32.3	-	16.1	45.0	28.9	Fundamental
0deg	0.26840	PK	45.3	19.6	-64.3	32.3	-	-31.7	39.0	70.7	
0deg	0.40260	PK	54.6	19.7	-64.4	32.3	-	-22.4	35.5	57.9	
0deg	0.53680	QP	25.2	19.7	-24.3	32.3	-	-11.7	33.0	44.7	
0deg	0.67100	QP	43.5	19.7	-24.3	32.3	-	6.6	31.1	24.5	
0deg	0.80520	QP	23.1	19.7	-24.3	32.3	-	-13.8	29.5	43.3	
0deg	0.93940	QP	36.2	19.7	-24.3	32.3	-	-0.7	28.1	28.8	
0deg	1.07360	QP	22.1	19.7	-24.3	32.3	-	-14.8	26.9	41.7	
0deg	1.20780	QP	28.7	19.7	-24.3	32.3	-	-8.2	25.9	34.1	
0deg	1.34200	QP	22.0	19.7	-24.2	32.3	-	-14.8	25.0	39.8	
Hori.	36.132	QP	21.8	16.2	7.4	28.5	-	16.9	40.0	23.1	Floor Noise
Hori.	60.325	QP	23.2	7.7	7.9	28.5	-	10.3	40.0	29.7	
Hori.	174.546	QP	20.6	15.9	9.3	28.1	-	17.7	43.5	25.8	Floor Noise
Hori.	295.954	QP	20.0	13.6	10.5	27.7	-	16.4	46.0	29.6	Floor Noise
Hori.	514.436	QP	20.5	17.8	12.0	29.2	-	21.1	46.0	24.9	Floor Noise
Hori.	843.987	QP	20.1	21.4	14.0	29.0	-	26.5	46.0	19.5	Floor Noise
Vert.	36.132	QP	22.0	16.2	7.4	28.5	-	17.1	40.0	22.9	Floor Noise
Vert.	60.325	QP	25.6	7.7	7.9	28.5	-	12.7	40.0	27.3	
Vert.	174.546	QP	21.2	15.9	9.3	28.1	-	18.3	43.5	25.2	Floor Noise
Vert.	295.954	QP	20.2	13.6	10.5	27.7	-	16.6	46.0	29.4	Floor Noise
Vert.	514.436	QP	20.7	17.8	12.0	29.2	-	21.3	46.0	24.7	Floor Noise
Vert.	843.987	QP	20.0	21.4	14.0	29.0	-	26.4	46.0	19.6	Floor Noise

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	103.0	19.5	-74.1	32.3	0.0	16.1	25.0	8.9	Fundamental
0deg	0.26840	PK	45.3	19.6	-64.3	32.3	0.0	-31.7	19.0	50.7	
0deg	0.40260	PK	54.6	19.7	-64.4	32.3	0.0	-22.4	15.5	37.9	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	103.0	19.5	5.9	32.3	-	96.1	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

If Gain 0.0dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

The test result is rounded off, so some differences might be observed.

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.1
Semi Anechoic Chamber	No.1	August 9, 2024
Date	August 8, 2024	24 deg. C / 55 % RH
Temperature / Humidity	22 deg. C / 53 % RH	Takumi Nishida
Engineer	(Below 30 MHz)	(Above 30 MHz)
Mode	Mode 2	

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.5	19.5	-74.1	32.3	-	15.6	45.0	29.4	Fundamental
0deg	0.26840	PK	40.0	19.6	-64.3	32.3	-	-37.0	39.0	76.0	
0deg	0.40260	PK	53.8	19.7	-64.4	32.3	-	-23.2	35.5	58.7	
0deg	0.53680	QP	44.1	19.7	-24.3	32.3	-	7.2	33.0	25.8	
0deg	0.67100	QP	43.2	19.7	-24.3	32.3	-	6.3	31.1	24.8	
0deg	0.80520	QP	22.5	19.7	-24.3	32.3	-	-14.4	29.5	43.9	
0deg	0.93940	QP	38.5	19.7	-24.3	32.3	-	1.6	28.1	26.5	
0deg	1.07360	QP	22.1	19.7	-24.3	32.3	-	-14.8	26.9	41.7	
0deg	1.20780	QP	33.2	19.7	-24.3	32.3	-	-3.7	25.9	29.6	
0deg	1.34200	QP	22.0	19.7	-24.2	32.3	-	-14.8	25.0	39.8	
Hori.	36.132	QP	22.0	16.2	7.4	28.5	-	17.1	40.0	22.9	Floor Noise
Hori.	60.325	QP	23.3	7.7	7.9	28.5	-	10.4	40.0	29.6	
Hori.	174.546	QP	20.8	15.9	9.3	28.1	-	17.9	43.5	25.6	Floor Noise
Hori.	295.954	QP	20.1	13.6	10.5	27.7	-	16.5	46.0	29.5	Floor Noise
Hori.	514.436	QP	20.6	17.8	12.0	29.2	-	21.2	46.0	24.8	Floor Noise
Hori.	843.987	QP	20.2	21.4	14.0	29.0	-	26.6	46.0	19.4	Floor Noise
Vert.	36.132	QP	22.2	16.2	7.4	28.5	-	17.3	40.0	22.7	Floor Noise
Vert.	60.325	QP	25.4	7.7	7.9	28.5	-	12.5	40.0	27.5	
Vert.	174.546	QP	21.1	15.9	9.3	28.1	-	18.2	43.5	25.3	Floor Noise
Vert.	295.954	QP	20.3	13.6	10.5	27.7	-	16.7	46.0	29.3	Floor Noise
Vert.	514.436	QP	20.8	17.8	12.0	29.2	-	21.4	46.0	24.6	Floor Noise
Vert.	843.987	QP	20.0	21.4	14.0	29.0	-	26.4	46.0	19.6	Floor Noise

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.5	19.5	-74.1	32.3	0.0	15.6	25.0	9.4	Fundamental
0deg	0.26840	PK	40.0	19.6	-64.3	32.3	0.0	-37.0	19.0	56.0	
0deg	0.40260	PK	53.8	19.7	-64.4	32.3	0.0	-23.2	15.5	38.7	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.5	19.5	5.9	32.3	-	95.6	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

If Gain 0.0dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

The test result is rounded off, so some differences might be observed.

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.1
Semi Anechoic Chamber	No.1	August 9, 2024
Date	August 8, 2024	24 deg. C / 55 % RH
Temperature / Humidity	22 deg. C / 53 % RH	Takumi Nishida
Engineer	(Below 30 MHz)	(Above 30 MHz)
Mode	Mode 3	

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.9	19.5	-74.1	32.3	-	16.0	45.0	29.0	Fundamental
0deg	0.26840	PK	39.0	19.6	-64.3	32.3	-	-38.0	39.0	77.0	
0deg	0.40260	PK	58.6	19.7	-64.4	32.3	-	-18.4	35.5	53.9	
0deg	0.53680	QP	35.9	19.7	-24.3	32.3	-	-1.0	33.0	34.0	
0deg	0.67100	QP	49.2	19.7	-24.3	32.3	-	12.3	31.1	18.8	
0deg	0.80520	QP	22.5	19.7	-24.3	32.3	-	-14.4	29.5	43.9	
0deg	0.93940	QP	41.2	19.7	-24.3	32.3	-	4.3	28.1	23.8	
0deg	1.07360	QP	22.1	19.7	-24.3	32.3	-	-14.8	26.9	41.7	
0deg	1.20780	QP	33.4	19.7	-24.3	32.3	-	-3.5	25.9	29.4	
0deg	1.34200	QP	22.0	19.7	-24.2	32.3	-	-14.8	25.0	39.8	
Hori.	36.050	QP	22.1	16.2	7.4	28.5	-	17.2	40.0	22.8	Floor Noise
Hori.	60.093	QP	23.4	7.8	7.8	28.5	-	10.5	40.0	29.5	
Hori.	174.573	QP	20.9	15.9	9.3	28.1	-	18.0	43.5	25.5	Floor Noise
Hori.	295.545	QP	20.2	13.6	10.4	27.7	-	16.5	46.0	29.5	Floor Noise
Hori.	514.682	QP	20.7	17.8	12.0	29.2	-	21.3	46.0	24.7	Floor Noise
Hori.	843.987	QP	20.0	21.4	14.0	29.0	-	26.4	46.0	19.6	Floor Noise
Vert.	36.050	QP	22.2	16.2	7.4	28.5	-	17.3	40.0	22.7	Floor Noise
Vert.	60.093	QP	25.5	7.8	7.8	28.5	-	12.6	40.0	27.4	
Vert.	174.573	QP	21.0	15.9	9.3	28.1	-	18.1	43.5	25.4	Floor Noise
Vert.	295.545	QP	20.4	13.6	10.4	27.7	-	16.7	46.0	29.3	Floor Noise
Vert.	514.682	QP	20.9	17.8	12.0	29.2	-	21.5	46.0	24.5	Floor Noise
Vert.	843.987	QP	20.1	21.4	14.0	29.0	-	26.5	46.0	19.5	Floor Noise

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.9	19.5	-74.1	32.3	0.0	16.0	25.0	9.0	Fundamental
0deg	0.26840	PK	39.0	19.6	-64.3	32.3	0.0	-38.0	19.0	57.0	
0deg	0.40260	PK	58.6	19.7	-64.4	32.3	0.0	-18.4	15.5	33.9	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	102.9	19.5	5.9	32.3	-	96.0	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

If Gain 0.0dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

The test result is rounded off, so some differences might be observed.

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.1
Semi Anechoic Chamber	No.1	August 9, 2024
Date	August 8, 2024	24 deg. C / 55 % RH
Temperature / Humidity	22 deg. C / 53 % RH	Takumi Nishida
Engineer	(Below 30 MHz)	(Above 30 MHz)
Mode	Mode 4	

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	96.4	19.5	-74.1	32.3	-	9.5	45.0	35.5	Fundamental
0deg	0.26840	PK	33.7	19.6	-64.3	32.3	-	-43.3	39.0	82.3	
0deg	0.40260	PK	50.9	19.7	-64.4	32.3	-	-26.1	35.5	61.6	
0deg	0.53680	QP	23.5	19.7	-24.3	32.3	-	-13.4	33.0	46.4	
0deg	0.67100	QP	40.0	19.7	-24.3	32.3	-	3.1	31.1	28.0	
0deg	0.80520	QP	22.9	19.7	-24.3	32.3	-	-14.0	29.5	43.5	
0deg	0.93940	QP	32.8	19.7	-24.3	32.3	-	-4.1	28.1	32.2	
0deg	1.07360	QP	23.0	19.7	-24.3	32.3	-	-13.9	26.9	40.8	
0deg	1.20780	QP	27.5	19.7	-24.3	32.3	-	-9.4	25.9	35.3	
0deg	1.34200	QP	23.1	19.7	-24.2	32.3	-	-13.7	25.0	38.7	
Hori.	33.404	QP	22.1	17.2	7.3	28.5	-	18.1	40.0	21.9	Floor Noise
Hori.	60.011	QP	23.3	7.8	7.8	28.5	-	10.4	40.0	29.6	
Hori.	173.344	QP	20.6	15.9	9.3	28.1	-	17.7	43.5	25.8	Floor Noise
Hori.	297.753	QP	20.3	13.6	10.5	27.7	-	16.7	46.0	29.3	Floor Noise
Hori.	516.434	QP	20.3	17.8	12.0	29.2	-	20.9	46.0	25.1	Floor Noise
Hori.	845.596	QP	20.1	21.4	14.0	29.0	-	26.5	46.0	19.5	Floor Noise
Vert.	33.404	QP	22.3	17.2	7.3	28.5	-	18.3	40.0	21.7	Floor Noise
Vert.	60.011	QP	25.2	7.8	7.8	28.5	-	12.3	40.0	27.7	
Vert.	173.344	QP	21.1	15.9	9.3	28.1	-	18.2	43.5	25.3	Floor Noise
Vert.	297.753	QP	20.2	13.6	10.5	27.7	-	16.6	46.0	29.4	Floor Noise
Vert.	516.434	QP	20.6	17.8	12.0	29.2	-	21.2	46.0	24.8	Floor Noise
Vert.	845.596	QP	20.1	21.4	14.0	29.0	-	26.5	46.0	19.5	Floor Noise

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	96.4	19.5	-74.1	32.3	0.0	9.5	25.0	15.5	Fundamental
0deg	0.26840	PK	33.7	19.6	-64.3	32.3	0.0	-43.3	19.0	62.3	
0deg	0.40260	PK	50.9	19.7	-64.4	32.3	0.0	-26.1	15.5	41.6	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

* Since the peak emission result satisfied the average limit, duty factor was omitted.

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	96.4	19.5	5.9	32.3	-	89.5	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

If Gain 0.0dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

The test result is rounded off, so some differences might be observed.

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.1
Semi Anechoic Chamber	No.1	August 9, 2024
Date	August 8, 2024	24 deg. C / 55 % RH
Temperature / Humidity	22 deg. C / 53 % RH	Takumi Nishida
Engineer	(Below 30 MHz)	(Above 30 MHz)
Mode	Mode 5	

PK or QP

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	109.0	19.5	-74.1	32.3	-	22.1	45.0	22.9	Fundamental
0deg	0.26840	PK	53.5	19.6	-64.3	32.3	-	-23.5	39.0	62.5	
0deg	0.40260	PK	68.9	19.7	-64.4	32.3	-	-8.1	35.5	43.6	
0deg	0.53680	QP	35.9	19.7	-24.3	32.3	-	-1.0	33.0	34.0	
0deg	0.67100	QP	53.3	19.7	-24.3	32.3	-	16.4	31.1	14.7	
0deg	0.80520	QP	25.4	19.7	-24.3	32.3	-	-11.5	29.5	41.0	
0deg	0.93940	QP	47.5	19.7	-24.3	32.3	-	10.6	28.1	17.5	
0deg	1.07360	QP	22.6	19.7	-24.3	32.3	-	-14.3	26.9	41.2	
0deg	1.20780	QP	40.9	19.7	-24.3	32.3	-	4.0	25.9	21.9	
0deg	1.34200	QP	22.1	19.7	-24.2	32.3	-	-14.7	25.0	39.7	
Hori.	36.546	QP	21.5	16.1	7.4	28.5	-	16.5	40.0	23.5	Floor Noise
Hori.	75.924	QP	22.1	6.6	8.1	28.5	-	8.3	40.0	31.7	Floor Noise
Hori.	174.124	QP	20.3	15.9	9.3	28.1	-	17.4	43.5	26.1	Floor Noise
Hori.	295.436	QP	20.0	13.6	10.4	27.7	-	16.3	46.0	29.7	Floor Noise
Hori.	514.323	QP	20.4	17.8	12.0	29.2	-	21.0	46.0	25.0	Floor Noise
Hori.	843.596	QP	20.2	21.4	14.0	29.0	-	26.6	46.0	19.4	Floor Noise
Vert.	36.546	QP	22.0	16.1	7.4	28.5	-	17.0	40.0	23.0	Floor Noise
Vert.	75.924	QP	22.1	6.6	8.1	28.5	-	8.3	40.0	31.7	Floor Noise
Vert.	174.124	QP	21.3	15.9	9.3	28.1	-	18.4	43.5	25.1	Floor Noise
Vert.	295.436	QP	20.2	13.6	10.4	27.7	-	16.5	46.0	29.5	Floor Noise
Vert.	514.323	QP	20.3	17.8	12.0	29.2	-	20.9	46.0	25.1	Floor Noise
Vert.	843.596	QP	20.1	21.4	14.0	29.0	-	26.5	46.0	19.5	Floor Noise

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier)

PK with Duty factor

Ant Deg [deg] or Polarity [Hori/Vert]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	109.0	19.5	-74.1	32.3	-22.2	-0.1	25.0	25.1	Fundamental
0deg	0.26840	PK	53.5	19.6	-64.3	32.3	-22.2	-45.7	19.0	64.7	
0deg	0.40260	PK	68.9	19.7	-64.4	32.3	-22.2	-30.3	15.5	45.8	

Result = Reading + Ant Factor + Loss (Cable + Attenuator + Filter + D.Factor) - Gain(Amplifier) + Duty factor *

Result of the fundamental emission at 3 m without Distance factor

Ant Deg [deg]	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
0deg	0.13420	PK	109.0	19.5	5.9	32.3	-	102.1	-	-	Fundamental

Result = Reading + Ant Factor + Loss (Cable+Attenuator) - Gain(Amplifier)

If Gain 0.0dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.
Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).


The test result is rounded off, so some differences might be observed.

Radiated Spurious Emission
(Plot data, Worst case for Fundamental Emission)

Test place
Semi Anechoic Chamber
Date
Temperature / Humidity
Engineer
Mode

Ise EMC Lab.
No.1
August 8, 2024
22 deg. C / 53 % RH
Takumi Nishida
(Below 30 MHz)
Mode 1

No.1
August 9, 2024
24 deg. C / 55 % RH
Takumi Nishida
(Above 30 MHz)



Duty Cycle


Test place Ise EMC Lab.
Semi Anechoic Chamber No.8
Date August 1, 2024
Temperature / Humidity 22 deg. C / 43 % RH
Engineer Ken Fujita

Mode 5

ON time [ms]	Cycle [ms]	Duty (On time/Cycle)	Duty factor [dB]
7.80	100	0.0780	-22.2

$$\text{Duty} = 20 * \log_{10}(\text{ON time/Cycle})$$

Mode 5




-20 dB Bandwidth / 99 % emission bandwidth

Test place
Semi Anechoic Chamber
Date
Temperature / Humidity
Engineer

Ise EMC Lab.
No.8
August 1, 2024
22 deg. C / 43 % RH
Ken Fujita

Mode	99 % emission bandwidth [kHz]	-20 dB Bandwidth [kHz]
1	12.9627	5.490
2	13.5237	5.559
3	14.4040	5.480
4 with key	13.4545	7.957
4 without key	14.9307	8.182
5	12.6334	6.608


*It was confirmed that there were no differences in the bandwidth due to the input voltage.




-20 dB Bandwidth / 99 % emission bandwidth

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.8
Date	August 1, 2024
Temperature / Humidity	22 deg. C / 43 % RH
Engineer	Ken Fujita


Mode 4 with key



Mode 4 without key



Mode 5



APPENDIX 2: Test instruments

Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141198	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	2513	07/10/2024	12
RE	141213	Attenuator(6dB)	Weinschel Corp	2	BK7971	11/16/2023	12
RE	141215	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W/3D-2W/ RG400u/ RFM-E421(SW)	-/01068 (Switcher)	06/24/2024	12
RE	141350	Coaxial Cable	Suhner/storm/Agilent/TSJ	-	-	03/05/2024	12
RE	141530	Digital Tester	Fluke Corporation	FLUKE 26-3	78030621	02/01/2024	12
RE	141557	DIGITAL HITESTER	HIOKI E.E. CORPORATION	3805	070900530	01/31/2024	12
RE	141568	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	2901	01/10/2024	12
RE	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/17/2024	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/17/2024	12
RE	141904	Spectrum Analyzer	Keysight Technologies Inc	N9030A	US51350215	11/08/2023	12
RE	141950	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	11/20/2023	12
RE	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	05/17/2024	12
RE	141998	AC1_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	12/06/2023	24
RE	142152	Loop Antenna	Rohde & Schwarz	HFH2-Z2	836553/009	10/17/2023	12
RE	142226	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	142314	Attenuator	Pasternack Enterprises	PE7390-6	D/C 1504	06/06/2024	12
RE	142528	Detector	Millitech	DET-15-RPFW0	34	-	-
RE	150449	Digital Storage Oscilloscope	Keysight Technologies Inc	DSOX3102T, N2750A	MY56310068, US53331022	10/17/2023	12
RE	159670	Coaxial Cable	UL Japan	-	-	11/21/2023	12
RE	160924	Logperiodic Antenna	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	225	11/29/2023	12
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	244711	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202105	01/25/2024	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated Emission