

- 1.) The "Hg" must be 10 pt font - minimum.
2.) All text lettering must be a minimum of 1.5mm with the exception of "CAUTION" and "ATTENTION" which must be a minimum of 2.7mm.

CD411LC

CD411LC
(Use 4"
Construction)

LED retrofit luminaire conversion for use only with products described and installed in accordance with the instructions provided for this retrofit kit.

RISK OF ELECTRIC SHOCK - SUITABLE FOR DAMP LOCATIONS. SEE INSTRUCTIONS FOR MIN RECESSED HOUSING COMPARTMENT DIMENSIONS

Suitable For Use with Luminaires with a Minimum of 60° C Supply Conductors.

SEE INSTRUCTIONS FOR MIN RECESSED HOUSING COMPARTMENT DIMENSIONS.

SUITABLE FOR TYPE IC LUMINAIRES
USE ONLY IN OPEN LUMINAIRES

SEE INSTRUCTIONS FOR MIN RECESSED HOUSING COMPARTMENT DIMENSIONS.

Retrofit assembly installation subject to approval



FCC ID: NIRC611LC
IC:9486A-CD611LC

Made in China
(Date Code)



E353692
4VD3



TCP# CD411LC
120V, 11W, 0.105A,
60Hz

Made in China



Location of etch in yellow box