

FCC, PART 15, SUBPART C

CERTIFICATION REPORT

For The Race Management System

Model: **RMS** (Transmitter Unit)

FCC ID: **NKBTX3-9V** (Pending)

PREPARED FOR:

Westhold Corporation

4441 Huggins Street
San Diego, CA 92122

PREPARED ON **DECEMBER 10, 1999**

REPORT NUMBER 99-224

This report has been prepared in accordance with all applicable requirements of ANSI C63.4-1992

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	ii of 18

DOCUMENT HISTORY

REVISION	DATE	COMMENTS
-	12/10/99	Initial Release J. L. Griffin

NOTE: Nemko EESI, Inc. hereby makes the following statements so as to conform to Chapter 10 (Test Reports) Requirements of ANSI C63.4 (1992) "Methods and Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz":

- The unit described in this report was received at Nemko EESI, Inc.'s facilities on November 11, 1999. Testing was performed on the units described in this report November 11, 1999.
- The Test Results reported herein apply only to the Units actually tested, and to substantially identical Units.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

This Report is the property of Nemko EESI, Inc., and shall not be reproduced, except in full, without prior written approval of Nemko EESI, Inc.. However, all ownership rights are hereby returned unconditionally to Westhold Corporation, and approval is hereby granted to Westhold Corporation and its employees and agents to reproduce all or part of this report for any legitimate business purpose without further reference to Nemko EESI, Inc..

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	iii of 18

TABLE OF CONTENTS

DOCUMENT HISTORY.....	ii
CERTIFICATION.....	iv
1. ADMINISTRATIVE DATA AND TEST SUMMARY.....	1
1.1 Administrative Data.....	1
1.2 Tests Performed.....	1
2. SYSTEM DESCRIPTION AND CONFIGURATION.....	2
2.1 System Components and Power Cables	2
2.2 Design Modifications for Compliance	2
3. DESCRIPTION OF TEST SITE AND EQUIPMENT.....	2
3.1 Description of Open Area Test Site	2
3.2 Test Equipment.....	3
4. DESCRIPTION OF TESTING METHODS.....	3
4.1 Introduction	3
4.2 Configuration and Methods of Measurements for Radiated Emissions	5
4.3 Radiated Emission Field Strength.....	8
5. TEST RESULTS	9
 EXHIBITS	
Figure 1. General EUT Test Setup Diagram.....	4
Figure 2. Radiated Emissions Frequency ID Test Setup Diagram.....	6
Figure 3. Radiated Emissions (OATS) Test Setup Diagram.....	7
 APPENDICES	
Conducted & Radiated Emissions Measurement Uncertainties	A-1
Nemko EESI, Inc.'s Test Equipment & Facilities Calibration Program.....	B-1


Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	iv of 18

CERTIFICATION

The Radio Frequency Interference (RFI) testing, data evaluation and this report have been prepared by Nemko EESI, Inc., an independent electromagnetic compatibility consulting and test laboratory.

The testing and data collection were accomplished in accordance with the requirements of the ANSI, C63.4-1992 standard and the applicable sections of FCC, Part 15, Subpart C for intentionally radiating equipment. Refer to the Administrative Summary for a description of the test sample.

I certify the data, data evaluation and equipment configuration herein to be a true and accurate representation of the sample's radio frequency interference emission characteristics, as of the test date(s), and for the design of the test sample utilized to compile this report.


 J. L. Griffin
 Director of Laboratory Operations

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	1 of 18

1. ADMINISTRATIVE DATA AND TEST SUMMARY

1.1 Administrative Data

CLIENT: Westhold Corporation
4441 Huggins Street
San Diego, CA 92122
(858) 558-4512
(858) 558-4706 – fax

CONTACT: Julian Lin

DATE(S) OF TEST: November 11, 1999

TEST SPECIFICATION: FCC, Part 15, Subpart C, for intentional radiators
(for periodic, low-power transmitters)

EQUIPMENT UNDER TEST (EUT): Race Management System
Model Number: RMS (Transmitter Unit)
Serial Number: N/A
FCC ID Number (pending): NKBTX3-9V

EUT transmitter fundamental frequency: 10.24 MHz

1.2 Tests Performed

<i>Specification</i>	<i>Frequency Range</i>	<i>Compliance Status</i>
FCC, CFR 47, §15.209 Radiated Spurious Emissions	10.23 MHz – 1000 MHz	PASS



J. L. Griffin, Nemko EESI, Inc.

Please refer to the Test Results section of this report for further details.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	2 of 18

2. SYSTEM DESCRIPTION AND CONFIGURATION

2.1 System Components and Power Cables

DEVICE	MANUFACTURER MODEL # SERIAL #	POWER CABLE
EUT- Race Management System (Transmitter Unit)	Westhold Corporation RMS N/A	(EUT is battery powered)

2.2 Design Modifications for Compliance

Device: Race Management System

Model: RMS

No design modifications were made to this EUT during testing.

3. DESCRIPTION OF TEST SITE AND EQUIPMENT

3.1 Description of Open Area Test Site

The test site is located at 11696 Sorrento Valley Road, Suite F, San Diego, CA 92121. The site is physically located 18 miles Northwest of downtown San Diego. The general area is a valley 1.5 miles east of the Pacific Ocean. This particular part of the valley tends to minimize ambient levels, i.e. radio and TV broadcast stations and land mobile communications. The ten-meter site is located behind the office/lab building. It conforms to the normalized site attenuation limits and construction specifications as set in the EN 55022 (1987), CISPR 16 and 22 (1985) and ANSI C63.4-1992 documents. The site attenuation characteristics are verified for compliance every year and was last registered with the Federal Communications Commission on October 21, 1996, FCC Document Number 31040/SIT (1300B3). The site is currently registered through December 30, 1999.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	3 of 18

3.2 Test Equipment

The following test equipment was used to collect data for this report. All devices used were of current calibration and of the type required in the applicable documents section of this report.

DEVICE	MANUFACTURER	MODEL	ASSET #	CAL. DATE	CAL. DUE
Quasi-Peak Adapter	Hewlett Packard	85650A	533	4/16/99	10/16/99
Spectrum Analyzer Display	Hewlett Packard	85662A	404	4/16/99	10/16/99
Spectrum Analyzer	Hewlett Packard	8568B	104	4/16/99	10/16/99
RF Preselector	Hewlett Packard	85685A	403	11/02/99	11/02/00
Antenna, Log Periodic	EMCO	3146	111	8/30/99	8/30/00
Antenna, Biconical	EMCO	3104	115	5/17/99	5/17/00
Antenna, Loop	Electrometrics	ALR-25M	134	3/18/99	3/18/00
Open Area Test Site	Nemko EESI, Inc.	North	9998	8/14/99	8/14/00

4. DESCRIPTION OF TESTING METHODS


4.1 Introduction

As required in 47 CFR, Parts 2 and 15, the methods employed to test the radiated and conducted emissions (as applicable) of the EUT are those contained within the American National Standards Institute (ANSI) document C63.4-1992, titled "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz." All applicable FCC Rule Sections that provide further guidance for performance of such testing are also observed.

For General Test Configuration please refer to Figure 1 on the following page.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	4 of 18

Figure 1. General EUT Test Setup Diagram



NOT TO SCALE

CONFIGURATION LEGEND

1. Test Laboratory
2. Non-Conducting tables 80 cm above ground plane
3. EUT: Race Management System (Transmit Unit)

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	5 of 18

4.2 Configuration and Methods of Measurements for Radiated Emissions


Section 8 of ANSI C63.4 determines the general configuration and procedures for measuring the radiated emissions of equipment under test. Initially, the primary emission frequencies are identified inside the test lab by positioning a broadband receive antenna one meter from the EUT to locate frequencies of significant radiation. Normally this is done inside a shielded chamber to eliminate ambients. Next, the EUT is placed on a turntable on a 3 meter open area test site (registered with the FCC in accord with its Rules and ANSI C63.4) and the receive antenna is located at a distance of three meters from the EUT.

The EUT is configured to operate with a series of periodic transmissions, representing a “normally operating” mode. To ensure that the maximum emission at each discrete frequency of interest is observed, the receive antenna is varied in height from one to four meters and rotated to produce horizontal and vertical polarities, and the turntable is also rotated to determine the worst emitting configuration.

For Frequency ID and Radiated Emissions test configurations please refer to Figures 3 and 4 on the following pages.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	6 of 18

Figure 2. Radiated Emissions Frequency ID Test Setup Diagram




NOT TO SCALE

CONFIGURATION LEGEND

1. Test Laboratory
2. Spectrum Analyzer with Quasi-Peak Adapter
3. Coax interconnect from Antenna to Spectrum Analyzer
4. Receive Antenna (basic relative position)
5. Non-Conducting table 80 cm above ground plane
6. EUT: Race Management System

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	7 of 18

Figure 3. Radiated Emissions (OATS) Test Setup Diagram



NOT TO SCALE

CONFIGURATION LEGEND

1. Ground plane (11 X 17 meters)
2. Spectrum Analyzer with Quasi-Peak Adapter
3. Coax interconnect from Receive Antenna to Spectrum Analyzer
4. Antenna Mast with motorized mounting assembly
5. Receive Antenna (basic relative position)
6. Non-Conducting table 80 cm above ground plane
7. EUT: Race Management System

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	8 of 18

4.3 Radiated Emission Field Strength

47 CFR sections §15.201, §15.203, §15.205 and §15.209 specify the general emission specification limits and several specific parameter measures for low power periodic transmitters operating in the frequency ranges 40.66-40.70 MHz, and above 70 MHz. Compliance to the specific sections are listed below.

§15.203: The device under test has an external antenna. The user has no practical means to attach an additional external antenna or attach a different external antenna to the transmitter. This complies with the requirements of this section.

§15.205 and §15.209: These sections specify the radiated emissions limits and restricted bands of operation. Please refer to the data sheets attached to this report for a tabulated list of the emission frequencies and their compliance status.

In order to obtain the true field strength reading, the spectrum analyzer reading is corrected for amplifier gain, antenna factor and cable loss. The Corrected Analyzer Reading is then given by the following formula:

$$\text{Corrected Analyzer Reading} = (\text{Spectrum Analyzer Reading}) - \text{AG} + \text{AF} + \text{CL}$$

where AG = Amplifier Gain
 AF = Antenna Factor
 CL = Cable Loss

The corrected analyzer reading is then compared with the above determined emission specification limits.

The following is a sample calculation using this procedure:

Data Sheet:	page 9
Frequency:	10.230 MHz
Spectrum Analyzer Reading (at 3 m):	7.100 dBμV
Combined Amp. Gain, Cable & Antenna Factor:	+38.900 dB/m
Corrected Analyzer Reading (at 3 m):	46.000 dBμV/m
Corrected Analyzer Reading (at 3 m):	46.0 dBμV/m
Emission Spec. Limit (at 3 m):	49.5 dBμV/m
Difference Margin (dB):	-3.5 dB (PASS)

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	9 of 18

5. TEST RESULTS

Electromagnetic Engineering Services, Incorporated
FCC, Part 15C, 15.209 Radiated Emissions Data Sheet
(3m Open Area Test Site)

Client: Westhold Corp.

EUT: Race Management System Transmitter

Model #: 9Volt Version

Conducted by: 

Date of Test: 11-11-99

Test Distance, Amp. gain: 3 m, 0 dB

Frequency (MHz)	Spectrum Analyzer Reading at 3m (dBμV)	Antenna Polarization (vertical or horizontal)	f_0	Amp. Gain & Cable Loss, Distance & Antenna Factor Correction for 3 m (dBuV/m)	Total Interference Level at 3 m (dBμV/m)	Emission Spec. Limit at 3 m (dBμV/m)	Difference Margin (dB)
10.230	7.1	v	f_0	38.9	46.0	49.5	-3.5
30.740	12.7	v	f_3	14.9	27.6	40.0	-12.4
40.960	15.7	v	f_4	13.4	29.1	40.0	-10.9
61.440	15.3	v	f_6	12.5	27.8	40.0	-12.2
317.460	8.5	v	-	21.1	29.6	46.0	-16.4
337.930	5.4	v	-	20.6	26.0	46.0	-20.0
389.140	5.5	v	-	21.9	27.4	46.0	-18.6
522.270	5.5	v	-	25.8	31.3	46.0	-14.7
716.000	6.1	h	-	30.0	36.1	46.0	-9.9
737.300	5.4	h	-	30.1	35.5	46.0	-10.5
788.500	5.6	h	-	31.2	36.8	46.0	-9.3
809.000	6.1	h	-	31.6	37.7	46.0	-8.3
880.690	5.6	h	-	32.8	38.4	46.0	-7.6
901.160	5.9	h	-	33.0	38.9	46.0	-7.1

Test Conditions: Standard radiated emissions test set up on FCC registered open field site. The highest emissions for all antenna heights, polarities, and table orientations are the only emissions recorded.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	A-1 of 18

APPENDIX A

Conducted & Radiated Emissions Measurement Uncertainties

1. Introduction

ISO Guide 25(1990) and ANSI/NCSL Z540-1(1994) require that all measurements contained in a test report be "traceable". "Traceability" is defined in the *International Vocabulary of Basic and General Terms in Metrology* (ISO: 1993) as: "the property of the result of a measurement... whereby it can be related to stated references, usually national or international standards, through an unbroken chain of comparisons, *all having stated uncertainties*".

The purposes of this Appendix are to "state the *Measurement Uncertainties*" of the conducted emissions and radiated emissions measurements contained in Section 5 of this Test Report, and to provide a practical explanation of the meaning of these measurement uncertainties.

2. Statement Of The Worst-Case Measurement Uncertainties For The Conducted And Radiated Emissions Measurements Contained In This Test Report

Table 1: Worst-Case Expanded Uncertainty "U" of Measurement for a k=2 Coverage Factor

Conducted Emissions Measurement Detection Systems	Applicable Frequency Range	"U" for a k=2 Coverage Factor	Applicable (If checked)
HP8568B Spectrum Analyzer with QPA and HP8447F Preamplifier	150 kHz - 30 MHz	+/- 3.0 dB	
HP8566B Spectrum Analyzer with QPA and Preselector	9 kHz - 30 MHz	+/- 2.9 dB	
Radiated Emissions Measurement Detection Systems	Applicable Frequency Range	"U" for a k=2 Coverage Factor	Applicable (If checked)
HP8568B Spectrum Analyzer with QPA & HP8447F Preamplifier	30 MHz - 200 MHz	+4.0 dB, -4.1 dB	✓
HP8568B Spectrum Analyzer with QPA & HP8447F Preamplifier	200 MHz-1000 MHz	+/- 3.5 dB	✓
HP8566B Spectrum Analyzer with QPA & Preselector	30 MHz - 200 MHz	+3.9 dB, -4.0 dB	
HP8566B Spectrum Analyzer with QPA & Preselector	200 MHz-1000 MHz	+/- 3.4 dB	
HP8566B Spectrum Analyzer with QPA & HP 8449A Preamplifier	1 GHz - 18 GHz	+2.5 dB, -2.6 dB	
HP8566B Spectrum Analyzer with QPA & HP8449A	18 GHz - 40 GHz	+/- 3.4 dB	

<i>Nemko EESI, Inc.</i>		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	A-2 of 18

Preamplifier			
--------------	--	--	--

NOTES:

1. Applies to 3 and 10 meter measurement distances
2. Applies to all valid combinations of Transducers (i.e. LISNs, Line Voltage Probes, and Antennas, as appropriate)
3. Excludes the Repeatability of the EUT

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	A-3 of 18

3. Practical Explanation Of The Meaning Of The Conducted And Radiated Emissions Measurement Uncertainties

In general, a “Statement of Measurement Uncertainty” means that with a certain (specified) confidence level, the “true” value of a measurand will be between a (stated) upper bound and a (stated) lower bound.

In the specific case of EMC Measurements in this test report, the measurement uncertainties of the conducted emissions measurements and the radiated emissions measurements have been calculated in accordance with the method detailed in the following documents:

- *ISO Guide to the Expression of Uncertainty in Measurement* (ISO, 1993)
- NIS 81:1994, *The Treatment of Uncertainty in EMC Measurements* (NAMAS, 1994)
- NIST Technical Note 1297(1994), *Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results* (NIST, 1994)

The calculation method used in these documents requires that the stated uncertainty of the measurements be expressed as an “*expanded uncertainty*”, *U*, with a *k=2 coverage factor*. The practical interpretation of this method of expressing measurement uncertainty is shown in the following example:

EXAMPLE:

Assume that at 39.51 MHz, the (measured) radiated emissions level was equal to +26.5 dBμV/m, and that the +/- 2σ (i.e. 95% confidence level) measurement uncertainty was +/- 3.4 dB.

In the example above, the phrase “*k = 2 Coverage Factor*” simply means that the measurement uncertainty is stated to cover +/-2 standard deviations (i.e. a 95% confidence interval) about the measurand. The measurand is the radiated emissions measurement of +26.5 dBμV/m at 39.51 MHz, and the 95% bounds for the uncertainty are –3.4 dB to + 3.4 dB. One can thus be 95% confident that the “true” value of the radiated emissions measurement is between +23.1 dBμV/m and +29.5 dBμV/m. *In effect, this means that in the above example there is only a 2.5% chance that the “true” radiated emissions value exceeds +29.5 dBmV/m.*

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	B-1 of 18

APPENDIX B

Nemko EESI, Inc.'s Test Equipment & Facilities Calibration Program

Nemko EESI, Inc. operates a comprehensive Periodic Calibration Program in order to ensure the validity of all test data. Nemko EESI's Periodic Calibration Program is fully compliant to the requirements of NVLAP Policy Guide PG-1-1988, ANSI/NCSL Z540-1 (1994), ISO 10012-1 (1993-05-01), ISO Guide 25 (1990), ISO-9000 and EN 45001. Nemko EESI, Inc.'s calibration program therefore meets or exceed the US national commercial and military requirements [N.B. ANSI/NCSL Z540-1 (1994) replaces MIL-STD-45662A].

Specifically, all of Nemko EESI's *primary reference standard devices* (e.g. vector voltmeters, multimeters, attenuators and terminations, RF power meters and their detector heads, oscilloscope mainframes and plug-ins, spectrum analyzers, RF preselectors, quasi-peak adapters, interference analyzers, impulse generators, signal generators and pulse/function generators, field-strength meters and their detector heads, etc.) and certain *secondary standard devices* (e.g. RF Preamplifiers used in CISPR 11/22 and FCC Part 15/18 tests) are periodically recalibrated by:

- A Nemko EESI-approved independent (third party) metrology laboratory that uses NIST-traceable standards and that is ISO Guide 25-accredited as a calibration laboratories by NIST; or,
- A Nemko EESI-approved independent (third party) metrology laboratory that uses NIST-traceable standards and that is ISO Guide 25-accredited as a calibration laboratory by another accreditation body (such as A2LA) that is mutually recognized by NIST; or,
- A manufacturer of Measurement and Test Equipment (M&TE), if the manufacturer uses NIST-traceable standards and is ISO Guide 25-accredited as calibration laboratory either by NIST or by another accreditation body (such as A2LA) that is mutually recognized by NIST; or
- A manufacturer of M&TE (or by a Nemko EESI-approved independent third party metrology laboratory) that is not ISO Guide 25-accredited. (In these cases, Nemko EESI conducts an annual audit of the manufacturer or metrology laboratory for the purposes of proving traceability to NIST, ensuring that adequate and repeatable calibration procedures are being applied, and verifying conformity with the other requirements of ISO Guide 25).

In all cases, the entity performing the Calibration is required to furnish Nemko EESI with a calibration test report and/or certificate of calibration, and a "calibration sticker" on each item of M&TE that is successfully calibrated.

Nemko EESI, Inc.		11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 Phone (858) 793-9911 Fax (858) 259-7170		
DATE	DOCUMENT NAME	SUBMITTAL #	FCC ID	PAGE
12/10/99	Westhold Corporation RMS FCC 'C' Certification Report	99-224	NKBTX3-9V	B-2 of 18

Calibration intervals are normally one year, except when the manufacture advises a shorter interval (e.g. the HP 8568B Spectrum Analyzer is recalibrated every six months) or if US Government directives or client requirements demand a shorter interval. Items of instrumentation/related equipment which fail during routine use, or which suffer visible mechanical damage (during use or while in transit), are sidelined pending repair and recalibration. (Repairs are carried out either in-house [if minor] or by a Nemko EESI-approved independent [third party] metrology laboratory, or by the manufacturer of the item of M&TE).

Each antenna used for CISPR 11 and CISPR 22 and FCC Part 15 and Part 18 radiated emissions testing (and for testing to the equivalent European Norms) is calibrated annually by either a NIST (or A2LA) ISO Guide 25-Accredited third-party Antenna Calibration Laboratory or by the antenna's OEM if the OEM is NIST or A2LA ISO Guide 25-accredited as an antenna calibration laboratory. The antenna calibrations are performed using the methods specified in Annex G.5 of CISPR 16-1(1993) or ANSI C63.5-1991, including the "Three-Antenna Method". Certain other kinds of antennas (e.g. magnetic-shielded loop antennas) are calibrated annually by either a NIST (or A2LA) ISO Guide 25-accredited third-party antenna calibration laboratory, or by the antenna's OEM if the OEM is NIST or A2LA ISO Guide 25-accredited as an antenna calibration laboratory using the procedures specified in the latest version of SAE ARP-958.

In accordance with FCC and other regulations, Nemko EESI recalibrates its suite of antennas used for radiated emissions tests on an annual basis. These calibrations are performed as a precursor to the FCC-required annual revalidation of the Normalized Site Attenuation properties of Nemko EESI's Open Area Test Site. Nemko EESI, Inc. uses the procedures given in both Subclause 16.6 and Annex G.2 of CISPR 16-1 (1993), and, ANSI C63.4-1992 when performing the normalized site attenuation measurements.