



Product Service

Choose certainty.
Add value.

March 28, 2014

Page 1 of 72

Prüfbericht / Test Report

Nr. / No. 69558-18208-1 (Edition 3)

Applicant: ELDAT GmbH
Type of equipment: Handheld Remote Control Transmitter
Type designation: M3-2314 anciently HS37x28 (315 MHz)
Order No.: 4500039287
Test standards: FCC Code of Federal Regulations,
CFR 47, Part 15,
Sections 15.205, 15.207, 15.215 and 15.231

Industry Canada Radio Standards Specifications
RSS-GEN Issue 3, Sections 7.2.2 and 7.2.4 and
RSS-210 Issue 8, Section A1.1 (Category I Equipment)

Note:

The test data of this report is related only to the individual item which has been tested. This report shall not be reproduced except in full extent without the written approval of the testing laboratory.

Table of Contents

1	Description of the Equipment Under Test (EUT)	3
2	Administrative Data	4
3	Identification of the Test Laboratory	5
4	Summary	6
5	Operation Mode and Configuration of EUT	7
6	Measurement Procedures	8
6.1	Bandwidth Measurements.....	8
6.2	Pulse Train Measurement.....	9
6.3	Radiated Emission Measurement 9 kHz to 30 MHz.....	10
6.4	Radiated Emission in Fully or Semi Anechoic Room	12
6.5	Radiated Emission at Alternative Test Site	14
7	Photographs Taken During Testing.....	16
8	Test Results	23
8.1	Occupied Bandwidth	25
8.2	Bandwidth of the Emission.....	29
8.3	Bandwidth of Momentary Signals.....	31
8.4	Designation of Emissions.....	32
8.5	Pulse Train Measurement.....	33
8.6	Restricted Bands of Operation	36
8.7	Periodic Operation Requirements	38
8.8	Radiated Emission Measurement 9 kHz to 30 MHz.....	40
8.9	Radiated Emission Measurement 30 MHz to 3.2 GHz	41
8.10	Exposure of Humans to RF Fields	43
9	Referenced Regulations	45
10	Test Equipment List with Calibration Data.....	47
11	Revision History	48
Annex A	Charts taken during testing.....	49

1 Description of the Equipment Under Test (EUT)

General data of EUT

Type designation ¹ :	M3-2314 anciently HS37x28 (315 MHz)
Parts ² :	
Serial number(s):	28677846
Manufacturer:	ELDAT GmbH
Type of equipment:	Handheld Remote Control Transmitter
Version:	As received
FCC ID:	NKPD304315SI
Industry Canada ID:	3126A-M32312SI
Additional parts/accessories:	

Technical data of EUT

Application frequency range:	315 MHz
Frequency range:	315 MHz
Operating frequency:	315 MHz
Type of modulation:	ASK
Pulse train:	
Pulse width:	
Number of RF-channels:	1
Channel spacing:	---
Designation of emissions:	
Type of antenna:	Integrated on printed board
Size/length of antenna:	12 cm
Connection of antenna:	☐ detachable ☒ not detachable
Type of power supply:	Battery supply
Specifications for power supply:	nominal voltage: 3.0 V

¹ Type designation of the system if EUT consists of more than one part.

² Type designations of the parts of the system, if applicable.

2 Administrative Data

Application details

Applicant (full address):	ELDAT GmbH Im Gewerbepark 14 D-15711 Königs Wusterhausen
Contact person:	Ms. Marlies Hofmann
Order number:	4500039287
Receipt of EUT:	2013-01-16 and 2013-03-01
Date(s) of test:	2013-01-22 (Duty-Cycle test with first test sample, only) and 2013-04-29 to 2013-05-02
Note(s):	

Report details

Report number:	69558-18208-1
Edition:	3
Issue date:	2014-03-28

3 Identification of the Test Laboratory

Details of the Test Laboratory

Company name:	TÜV SÜD Product Service GmbH
Address:	Aeussere Fruehlingstrasse 45 D-94315 Straubing Germany
FCC test site registration number	90926
Industry Canada test site registration:	3050A-2
Contact person:	Mr. Johann Roidt
	Phone: +49 9421 5522-0 Fax: +49 9421 5522-99

4 Summary

Summary of test results

The tested sample complies with the requirements set forth in the

Code of Federal Regulations CFR 47, Part 15, Sections 15.205, 15.215 and 15.231(a)-(d)

of the Federal Communication Commission (FCC) and the

Radio Standards Specifications

RSS-Gen Issue 3, Sections 7.2.2 and

RSS-210 Issue 8, Sections A1.1.1 to A1.1.4 (Category I Equipment)

of Industry Canada (IC).

Personnel involved in this report

Laboratory Manager:



Mr. Johann Roidt

Responsible for testing:



Mr. Martin Steindl

Responsible for test report:

Mr. Martin Steindl

5 Operation Mode and Configuration of EUT

Operation Mode(s)

Transmitting continuously with modulation

Configuration(s) of EUT

The EUT was configured as stand alone device. Full tests were performed in three orthogonal directions.

List of ports and cables

Port	Description	Classification ³	Cable type	Cable length

List of devices connected to EUT

Item	Description	Type Designation	Serial no. or ID	Manufacturer

List of support devices

Item	Description	Type Designation	Serial no. or ID	Manufacturer

³ Ports shall be classified as ac power, dc power or signal/control port

6 Measurement Procedures

6.1 Bandwidth Measurements

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 2, section 2.202(a) CFR 47 Part 15, section 15.215(c) IC RSS-Gen Issue 3, sections 4.6.1 and 4.6.2 IC RSS-210 Issue 8, section A1.1.3 ANSI C63.4, annex H.6
Guide:	ANSI C63.4 / IC RSS-Gen Issue 3, sections 4.6.1 and 4.6.2
Measurement setup:	☐ Conducted: See below ☒ Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.4)
If antenna is detachable bandwidth measurements shall be performed at the antenna connector (conducted measurement) when the transmitter is adjusted in accordance with the tune-up procedure, if applicable. The RF output terminals are connected to a spectrum analyzer. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable. If radiated measurements are performed the same test setups and instruments are used as with radiated emission measurements for the appropriate frequency range. The analyzer settings are specified by the test description of the appropriate test record(s).	

6.2 Pulse Train Measurement

Measurement Procedure:	
Rules and specifications:	CFR 47 Part 15, section 15.35(c) IC RSS-Gen Issue 3, section 4.5
Guide:	ANSI C63.4
Measurement setup:	☐ Conducted: See below (direct connection or via test fixture) ☒ Radiated: Radiated Emission in Fully or Semi Anechoic Room (6.4)
If antenna is detachable pulse train measurements shall be performed at the antenna connector (conducted measurement). The RF output terminals are connected to a spectrum analyzer or to a diode detector in combination with an oscilloscope. If required, a resistive matching network equal to the impedance specified or employed for the antenna is used as well as dc block and appropriate attenuators (50 Ohms). The electrical characteristics of the radio frequency load attached to the output terminals shall be stated, if applicable. If antenna is not detachable a test fixture may be used instead of direct connection to RF output terminals. If radiated measurements are performed similar test setups and instruments are used as with radiated emission measurements for the appropriate frequency range. However, the spectrum analyzer may be replaced by a diode detector connected to an oscilloscope.	

6.3 Radiated Emission Measurement 9 kHz to 30 MHz

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.231(b)(3)
 IC RSS-210 Issue 8, section A1.1.2(b)

Guide: ANSI C63.4

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.


Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.



Test instruments used:

Type	Designation	Inv.-no.	Serial No. or ID	Manufacturer
☒ Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
☐ EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
☐ Test receiver	ESHS 10	1028	860043/016	Rohde & Schwarz
☐ Preamplifier	Cabin no. 2 CPA9231A	1716	3557	Schaffner
☒ Loop antenna	HFH2-Z2	1016	882964/1	Rohde & Schwarz
☒ Fully anechoic room	No. 2	1452	---	Albatross
☐ Semi anechoic room	No. 3	1453	---	Siemens
☐ Semi anechoic room	No. 8	2057	---	Albatross

6.4 Radiated Emission in Fully or Semi Anechoic Room

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.231
 IC RSS-210 Issue 8, section A1.1.2

Guide: ANSI C63.4

Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.


All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz a semi anechoic room complying with the NSA requirements of ANSI C63.4 for alternative test sites is used (see 6.5). If prescans are recorded in fully anechoic room they are indicated appropriately.



Test instruments used:

Type		Designation	Inv.-no.	Serial No. or ID	Manufacturer
☒	Spectrum analyzer	FSP30	1666	100036	Rohde & Schwarz
☐	EMI test receiver	Cabin no. 3 ESPI7	2010	101018	Rohde & Schwarz
☐	EMI test receiver	ESU8	2044	100232	Rohde & Schwarz
☐	EMI test receiver	ESMI	1569	839379/013 839587/006	Rohde & Schwarz
☒	Preamplifier	Cabin no. 2 CPA9231A	1716	3557	Schaffner
☐	Preamplifier	R14601	1142	13120026	Advantest
☒	Preamplifier (1 - 8 GHz)	AFS3-00100800-32-LN	1684	847743	Miteq
☐	Preamplifier (0.5 - 8 GHz)	AMF-4D-005080-25-13P	1685	860149	Miteq
☐	Preamplifier (8 - 18 GHz)	ACO/180-3530	1484	32641	CTT
☐	External Mixer	WM782A	1576	845881/005	Tektronix
☐	Harmonic Mixer Accessories	FS-Z30	1577	624413/003	Rohde & Schwarz
☒	Trilog antenna	Cabin no. 2 VULB 9163	1802	9163-214	Schwarzbeck
☐	Trilog antenna	Cabin no. 3 VULB 9163	1722	9163-188	Schwarzbeck
☐	Trilog antenna	Cabin no. 8 VULB 9163	2058	9163-408	Schwarzbeck
☒	Horn antenna	3115	1516	9508-4553	EMCO
☐	Horn antenna	3160-03	1010	9112-1003	EMCO
☐	Horn antenna	3160-04	1011	9112-1001	EMCO
☐	Horn antenna	3160-05	1012	9112-1001	EMCO
☐	Horn antenna	3160-06	1013	9112-1001	EMCO
☐	Horn antenna	3160-07	1014	9112-1008	EMCO
☐	Horn antenna	3160-08	1015	9112-1002	EMCO
☐	Horn antenna	3160-09	1265	9403-1025	EMCO
☐	Horn antenna	3160-10	1575	399185	EMCO
☒	Fully anechoic room	No. 2	1452	---	Albatross
☐	Semi anechoic room	No. 3	1453	---	Siemens
☐	Semi anechoic room	No. 8	2057	---	Albatross

6.5 Radiated Emission at Alternative Test Site

Measurement Procedure:

Rules and specifications: CFR 47 Part 15, sections 15.215(b) and 15.231
IC RSS-210 Issue 8, section A1.1.2

Guide: ANSI C63.4

Radiated emission in the frequency range 30 MHz to 1 GHz is measured within a semi-anechoic room with groundplane complying with the NSA requirements of ANSI C63.4 for alternative test sites. A linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna") is used. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in fully anechoic room.

If no prescan in a fully anechoic room is used first a peak scan is performed in four positions to get the whole spectrum of emission caused by EUT with the measuring antenna raised and lowered from 1 to 4 m to find table position, antenna height and antenna polarization for the maximum emission levels.

Data reduction is applied to these results to select those levels having less margin than 10 dB to or exceeding the limit using subranges and limited number of maximums. Further maximization is following.

With detector of the test receiver set to quasi-peak final measurements are performed immediately after frequency zoom (for drifting disturbances) and maximum adjustment.


Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

In cases where prescans in a fully anechoic room are taken (e. g. if EUT is operating for a short time only or battery is discharged quickly) final measurements with quasi-peak detector are performed manually at frequencies indicated by prescan with EUT rotating all around and receiving antenna raising and lowering within 1 meter to 4 meters to find the maximum levels of emission.

Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected.

Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.





Test instruments used:


Type		Designation	Inv.-no.	Serial No. or ID	Manufacturer
☒	EMI test receiver	ESU8	2044	100232	Rohde & Schwarz
☒	Trilog antenna	Cabin no. 8 VULB 9163	2058	9163-408	Schwarzbeck
☒	Semi anechoic room	No. 8	2057	---	Albatross

7 Photographs Taken During Testing

Test setup for radiated emission measurement 9 kHz – 30 MHz



Test setup for radiated emission measurement 9 kHz – 30 MHz - continued -



Test setup for radiated emission measurement (fully anechoic room)




Test setup for radiated emission measurement (fully anechoic room) - continued -



Test setup for radiated emission measurement (alternate test site)



Test setup for radiated emission measurement (alternate test site) - continued -



8 Test Results

FCC CFR 47 Parts 2 and 15			
Section(s)	Test	Page	Result
2.1046(a)	Conducted output power	---	Not applicable
2.202(a)	Occupied bandwidth	25	Recorded
15.215(c) 15.231(c)	Bandwidth of the emission	29	Test passed
2.201, 2.202	Class of emission	32	Calculated
15.35(c)	Pulse train measurement for pulsed operation	33	Recorded
15.205(a)	Restricted bands of operation	36	Test passed
15.207	Conducted AC powerline emission 150 kHz to 30 MHz	---	Not applicable
15.231(a)	Periodic operation requirements	38	Test passed
15.205(b) 15.231(b)	Radiated emission 9 kHz to 30 MHz	40	Test passed
15.205(b) 15.215(b) 15.231(b)	Radiated emission 30 MHz to 3.2 GHz	41	Test passed
15.231(d)	Carrier frequency stability	---	Not applicable

IC RSS-Gen Issue 3

Section(s)	Test	Page	Result
4.8	Transmitter output power (conducted)	---	Not applicable
4.6.1	Occupied Bandwidth	25	Recorded
8	Designation of emissions	32	Calculated
4.5	Pulsed operation	33	Recorded
7.2.4	Conducted AC powerline emission 150 kHz to 30 MHz	---	Not applicable
7.2.2(a)	Restricted bands and unwanted emission frequencies	36	Test passed
7.2.2(b)(c), 7.2.5	Unwanted emissions 9 kHz to 30 MHz	40	Test passed
7.2.2(b)(c), 7.2.6	Unwanted emissions 30 MHz to 3.2 GHz	41	Test passed
5.5	Exposure of Humans to RF Fields	43	Exempted from SAR and RF evaluation

IC RSS-210 Issue 8


Section(s)	Test	Page	Result
A1.1.1	Requirements for momentarily operated devices	38	Test passed
A1.1.2	Unwanted emissions 9 kHz to 30 MHz	40	Test passed
A1.1.2	Unwanted emissions 30 MHz to 3.2 GHz	41	Test passed
A1.1.3	Bandwidth of momentary signals	31	Test passed
A1.1.4	Carrier frequency stability	---	Not applicable

8.1 Occupied Bandwidth

Rules and specifications:	CFR 47 Part 2, section 2.202(a) ANSI C63.4, annex H.6	
Guide:	ANSI C63.4	
Description:	The occupied bandwidth according to CFR 47 Part 2, section 2.202(a), is measured as the 99% emission bandwidth, i.e. below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission. The occupied bandwidth according to ANSI C63.4, annex H.6; is measured as the frequency range defined by the points that are 26 dB down relative to the maximum level of the modulated carrier. The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
	The video bandwidth shall be at least three times greater than the resolution bandwidth.	
Measurement procedure:	Bandwidth Measurements (6.1)	

Comment:	
Date of test:	May 2, 2013
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Date: 2.MAY.2013 16:03:58


Occupied Bandwidth (99 %): **88 kHz**

Occupied Bandwidth (continued)

Rules and specifications:	IC RSS-Gen Issue 3, section 4.6.1
Guide:	IC RSS-Gen Issue 3, section 4.6.1
Description:	If not specified in the applicable RSS the occupied bandwidth is measured as the 99% emission bandwidth. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is also recorded. The span between the two recorded frequencies is the occupied bandwidth.
Measurement procedure:	Bandwidth Measurements (6.1)

Comment:	
Date of test:	May 2, 2013
Test site:	Fully anechoic room, cabin no. 2

Occupied Bandwidth (99 %):



Date: 2.MAY.2013 16:03:58

Occupied Bandwidth (99 %): **88 kHz**

8.2 Bandwidth of the Emission

Rules and specifications:	CFR 47 Part 15, section 15.215(c)	
Guide:	ANSI C63.4	
Description:	The 20 dB bandwidth of the emission is measured as the frequency range defined by the points that are 20 dB down relative to the maximum level of the modulated carrier. For intentional radiators operating under the alternative provisions to the general emission limits the requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation. The resolution bandwidth of the spectrum analyzer shall be set to a value greater than 5.0% of the allowed bandwidth. If no bandwidth specifications are given, the following guidelines are used:	
	Fundamental frequency	Minimum resolution bandwidth
	9 kHz to 30 MHz	1 kHz
	30 MHz to 1000 MHz	10 kHz
	1000 MHz to 40 GHz	100 kHz
	The video bandwidth shall be at least three times greater than the resolution bandwidth.	
Measurement procedure:	Bandwidth Measurements (6.1)	
Comment:		
Date of test:	May 2, 2013	
Test site:	Fully anechoic room, cabin no. 2	



DISPLAY LINE 1

59.19 dBµV

Ref 102.3 dBµV

* Att 0 dB

* RBW 10 kHz

VBW 30 kHz


SWT 20 ms

Marker 1 [T1]

79.19 dBµV

315.004000000 MHz

1 PK
VIEW



Center 315 MHz

200 kHz/

Span 2 MHz

Date: 2.MAY.2013 16:05:33

Permitted frequency band:	315 MHz	
20 dB bandwidth:	56 kHz	
Carrier frequency stability:	☐ specified	☒ not specified
Maximum frequency tolerances:	---	
Bandwidth of the emission:	56 kHz	within permitted frequency band ⁴ : ☒ yes ☐ no

Test Result:	Test passed
--------------	-------------

⁴ If a frequency stability is not specified, it is recommended that the fundamental emission is kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.3 Bandwidth of Momentary Signals

Rules and specifications:	IC RSS-210 Issue 8, section A1.1.3
Guide:	IC RSS-Gen Issue 3, section 4.6.1
Limit:	For the purpose of Section A1.1, the 99% bandwidth shall be no wider than 0.25% of the centre frequency for devices operating between 70 and 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the centre frequency.

Operating frequency:	315 MHz
Bandwidth limit:	787.5 kHz
Occupied bandwidth:	88 kHz
Emission bandwidth within bandwidth limit:	☒ yes ☐ no

Test Result:	Test passed
--------------	-------------

8.4 Designation of Emissions

Rules and specifications:	CFR 47 Part 2, sections 2.201 and 2.202 IC RSS-Gen Issue 3, sections 8
Guide:	ANSI C63.4 / TRC-43

Type of modulation:	Amplitude Modulation
---------------------	----------------------

B_n = Necessary Bandwidth	$B_n = 2BK$
B = Modulation rate	$B = 28 \text{ kHz}$
K = Overall numerical factor	$K = 1$
Calculation:	$B_n = 2 \cdot (28 \text{ kHz}) \cdot 1 = 56 \text{ kHz}$


Designation of Emissions:	56K0A1D
---------------------------	----------------

8.5 Pulse Train Measurement

Rules and specifications:	CFR 47 Part 15, section 15.35(c) IC RSS-Gen Issue 3, section 4.5
Guide:	ANSI C63.4
Measurement procedure:	Pulse Train Measurement (6.2)

Comment:	
Date of test:	2013-01-22
Test site:	Fully anechoic room, cabin no. 2

Total Pulse Train:



Date: 22. JAN. 2013 13:28:27



DELTA MARKER 1

1.54 ms

Ref 90 dBµV

*Att 20 dB

RBW 100 kHz

VBW 300 kHz


SWT 10 ms

Delta 1 [T1]

0.77 dB

1.540000 ms

1 AP
CLRWR



A

SGL

TRG

Center 315.01 MHz

1 ms/

Date: 22.JAN.2013 13:29:15



DELTA MARKER 1

800 μ s

Ref 90 dB μ V

* Att 20 dB

RBW 100 kHz

VBW 300 kHz


SWT 10 ms

Delta 1 [T1]

-0.24 dB

800.000000 μ s

1 AP
CLRWR



Date: 22.JAN.2013 13:29:34


Calculation of pulse train correction:

TX-On-Time (worst case):	T_{on}	=	28.08 ms
Pulse Train Time:	T_{pt}	=	110 ms
Period Time:	T_{period}	=	100 ms
Pulse Train Correction:	C_{pt}	=	$20 \cdot \log(T_{on} / T_{period})$ dB
		=	-11.03 dB

8.6 Restricted Bands of Operation

Rules and specifications:	CFR 47 Part 15, section 15.205(a) IC RSS-210 Issue 8, section 7.2.2(a)
Guide:	ANSI C63.4
Limit:	Only spurious emissions are permitted in any of the frequency bands listed in CFR 47 Part 15, section 15.205(a) or IC RSS-210 Issue 7, section 2.2(a).
Measurement procedure:	Radiated Emission in Fully or Semi Anechoic Room (6.4)

Comment:	
Date of test:	2013-05-02
Test site:	Fully anechoic room, cabin no. 2
Test distance:	3 meters



Date: 2.MAY.2013 16:13:28



Test Result:


Test passed

8.7 Periodic Operation Requirements

Rules and specifications:	CFR 47 Part 15, section 15.231(a) IC RSS-210 Issue 8, section A1.1.1
Guide:	---

Periodic operation requirements	Applicable	Declared by applicant	Test performed	Passed
The transmitter is used for				
☐ security or safety applications ☒ other applications		☒		
The transmitter is operated				
☒ manually ☐ automatically		☒		
Periodic operation according to				
☒ CFR 47 Part 15, section 15.231(a) / IC RSS-210 Issue 7, section A1.1.1				
Only control signals are sent and there is no continuous transmission	☒	☒	☐	☒
A manually operated transmitter employs a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released	☒	☐	☒	☒
A transmitter activated automatically ceases transmission within 5 seconds after activation	☐	☐	☐	☐
Periodic transmissions at regular predetermined intervals are ☐ not performed ☐ performed with total transmission time of two seconds per hour or less (for polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications)	☐	☐	☐	☐
☐ CFR 47 Part 15, section 15.231(e) / IC RSS-210 Issue 7, section A1.1.5				
The device is provided with a means for automatically limiting operation so that the duration of each transmission is not greater than one second and the silent period between transmissions is at least 30 times the duration of the transmission but in no case less than 10 seconds.	☐	☐	☐	☐

Note: Result may be based on the appropriate declaration of the applicant (i.e. no test is performed). However, in this case there is no verification by the test laboratory.



Date: 11.APR.2014 14:32:30

Transmitter deactivates 132.5 ms after releasing the button.

8.8 Radiated Emission Measurement 9 kHz to 30 MHz

Rules and specifications:	CFR 47 Part 15, sections 15.215(b) and 15.231(b)(3) IC RSS-210 Issue 8, section A1.1.2(b)			
Guide:	ANSI C63.4			
Limit:	Frequency of Emission (MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance d (meters)
	0.009 - 0.490	$2400/F(\text{kHz})$	$67.6 - 20 \cdot \log(F(\text{kHz}))$	300
	0.490 - 1.705	$24000/F(\text{kHz})$	$87.6 - 20 \cdot \log(F(\text{kHz}))$	30
	1.705 - 30.000	30	29.5	30
Additionally, the level of any unwanted emissions shall not exceed the level of the fundamental emission.				
Measurement procedure:	Radiated Emission Measurement 9 kHz to 30 MHz (6.3)			

Comment:	
Date of test:	2013-05-02
Test site:	Fully anechoic room, cabin no. 2

Test Result:	Test passed
--------------	-------------

Extrapolation factor: -40 dB/decade										
Frequency (MHz)	Detector	Distance		Reading Value (dBµV)	Correction Factor (dB/m)	Extrapolation Factor (dB)	Pulse Train Correction (dB)	Final Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
		d1 (m)	d (m)							
0,47820	Peak	3	300	39,2	20,0	-80,0		-20,8	14,0	34,8
0,52770	Peak	3	30	34,6	20,0	-40,0		14,6	33,2	18,6

Sample calculation of final values:

$$\text{Extrapolation Factor (dB)} = (\log(d) - \log(d_1)) \cdot \text{Extrapolation Factor (dB/decade)}$$

$$\text{Final Value (dB}\mu\text{V/m)} = \text{Reading Value } d_1 \text{ (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} + \text{Extrapolation Factor (dB)} + \text{Pulse Train Correction (dB)}$$

Note: Extrapolation factor (dB) and final value ($\text{dB}\mu\text{V/m}$) are relating to distance d.

8.9 Radiated Emission Measurement 30 MHz to 3.2 GHz

Rules and specifications:	CFR 47 Part 15, sections 15.205, 15.215(b) and 15.231(b) IC RSS-210 Issue 8, section A1.1.2																																						
Guide:	ANSI C63.4																																						
Limit:	In addition to the provisions of section 15.205, the field strength shall not exceed the levels as listed in the table below or the general limits shown in section 15.209, whichever limit permits a higher field strength. In no case shall the level of the unwanted emissions exceed the field strength of the fundamental emission. <table> <tr> <th>Frequency of Emission (MHz)</th><th>Field Strength of Fundamental (µV/m)</th><th>Field Strength of Fundamental (dBµV/m)</th><th>Field Strength of Spurious Emissions (µV/m)</th><th>Field Strength of Spurious Emissions (dBµV/m)</th></tr> <tr> <td>40.66 - 40.70</td><td>2,250</td><td>67.0</td><td>225 **</td><td>47.0</td></tr> <tr> <td>70 - 130</td><td>1,250</td><td>61.9</td><td>125</td><td>41.9</td></tr> <tr> <td>130 - 174</td><td>1,250 to 3,750 *</td><td>61.9 to 71.5</td><td>125 to 375 *</td><td>41.9 to 51.5</td></tr> <tr> <td>174 - 260</td><td>3,750</td><td>71.5</td><td>375</td><td>51.5</td></tr> <tr> <td>260 - 470</td><td>3,750 to 12,500 *</td><td>71.5 to 81.9</td><td>375 to 1,250 *</td><td>51.5 to 61.9</td></tr> <tr> <td>Above 470</td><td>12,500</td><td>81.9</td><td>1,250</td><td>61.9</td></tr> </table> * linear interpolations ** for harmonics only				Frequency of Emission (MHz)	Field Strength of Fundamental (µV/m)	Field Strength of Fundamental (dBµV/m)	Field Strength of Spurious Emissions (µV/m)	Field Strength of Spurious Emissions (dBµV/m)	40.66 - 40.70	2,250	67.0	225 **	47.0	70 - 130	1,250	61.9	125	41.9	130 - 174	1,250 to 3,750 *	61.9 to 71.5	125 to 375 *	41.9 to 51.5	174 - 260	3,750	71.5	375	51.5	260 - 470	3,750 to 12,500 *	71.5 to 81.9	375 to 1,250 *	51.5 to 61.9	Above 470	12,500	81.9	1,250	61.9
Frequency of Emission (MHz)	Field Strength of Fundamental (µV/m)	Field Strength of Fundamental (dBµV/m)	Field Strength of Spurious Emissions (µV/m)	Field Strength of Spurious Emissions (dBµV/m)																																			
40.66 - 40.70	2,250	67.0	225 **	47.0																																			
70 - 130	1,250	61.9	125	41.9																																			
130 - 174	1,250 to 3,750 *	61.9 to 71.5	125 to 375 *	41.9 to 51.5																																			
174 - 260	3,750	71.5	375	51.5																																			
260 - 470	3,750 to 12,500 *	71.5 to 81.9	375 to 1,250 *	51.5 to 61.9																																			
Above 470	12,500	81.9	1,250	61.9																																			
Measurement procedures:	Radiated Emission in Fully or Semi Anechoic Room (6.4) Radiated Emission at Alternative Test Site (6.5)																																						

Comment:	
Date of test:	2013-04-29 and 2013-05-02
Test site:	Frequencies ≤ 1 GHz: Semi-anechoic room, cabin no. 8 Frequencies > 1 GHz: Fully anechoic room, cabin no. 2
Test distance:	3 meters

Test Result:	Test passed
--------------	-------------

Frequency (MHz)	Antenna Polarization	Detector	Receiver Reading (dBµV)	Correction Factor (dB/m)	Pulse Train Correction (dB)	Final Value (dBµV/m)	Limit (dBµV/m)	Margin (dB)
315,000	horizontal	Peak	68,8	15,2	-11,0	73,0	75,6	2,6
630,000	horizontal	Quasi-Peak	7,6	21,4		29,0	55,6	26,6
945,000	horizontal	Quasi-Peak	6,5	25,1		31,6	55,6	24,0
1575,000	vertical	Peak	9,6	30,4	-11,0	28,6	54,0	25,4
1890,000	vertical	Peak	9,8	31,7	-11,0	30,6	55,6	25,1

Sample calculation of final values:

$$\text{Final Value (dB}\mu\text{V/m)} = \text{Reading Value (dB}\mu\text{V)} + \text{Correction Factor (dB/m)} \\ + \text{Pulse Train Correction (dB)}$$

8.10 Exposure of Humans to RF Fields

Rules and specifications:	IC RSS-Gen Issue 3, section 5.6
Guide:	IC RSS-102 Issue 4, section 2.5

Exposure of Humans to RF Fields	Applicable	Declared by applicant	Measured	Exemption
The antenna is				
☐ detachable				
The conducted output power (CP in watts) is measured at the antenna connector: $CP = \dots\dots\dots \text{W}$ The effective isotropic radiated power (EIRP in watts) is calculated using ☐ the numerical antenna gain: $G = \dots\dots\dots$ $EIRP = G \cdot CP \Rightarrow EIRP = \dots\dots\dots \text{W}$ ☐ the field strength⁵ in V/m: $FS = \dots\dots\dots \text{V/m}$ $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = \dots\dots\dots \text{W}$ with: Distance between the antennas in m: $D = \dots\dots\dots \text{m}$			☐	
☒ not detachable				
A field strength measurement is used to determine the effective isotropic radiated power (EIRP in watts) given by⁵: $EIRP = \frac{(FS \cdot D)^2}{30} \Rightarrow EIRP = 75.4 \mu\text{W}$ with: Field strength in V/m: $FS = 15.85 \text{ mV/m}$ Distance between the two antennas in m: $D = 3 \text{ m}$			☒	☒
Selection of output power				
The output power TP is the higher of the conducted or effective isotropic radiated power (e.i.r.p.): $TP = 75.4 \mu\text{W}$				

⁵ The conversion formula is valid only for properly matched antennas. In other cases the transmitter output power may have to be measured by a terminated measurement when applying the exemption clauses. If an open area test site is used for field strength measurement, the effect due to the metal ground reflecting plane should be subtracted from the maximum field strength value in order to reference it to free space, before calculating TP.

9 Referenced Regulations

All tests were performed with reference to the following regulations and standards:

☒	CFR 47 Part 2	Code of Federal Regulations Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)	October 1, 2012
☒	CFR 47 Part 15	Code of Federal Regulations Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)	October 1, 2012
☒	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	December 11, 2003 (published on January 30, 2004)
☐	ANSI C63.4	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	June 7, 2009 (published on September 15, 2009)
☒	RSS-Gen	Radio Standards Specification RSS-Gen Issue 3 containing General Requirements and Information for the Certification of Radiocommunication Equipment, published by Industry Canada	December 2010
☒	RSS-210	Radio Standards Specification RSS-210 Issue 8 for Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, published by Industry Canada	December 2010
☐	RSS-310	Radio Standards Specification RSS-310 Issue 3 for Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category II Equipment, published by Industry Canada	December 2010
☒	RSS-102	Radio Standards Specification RSS-102 Issue 4: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), published by Industry Canada	March 2010, footnote 13 updated December 2010
☐	ICES-003	Interference-Causing Equipment Standard ICES-003 Issue 4 for Digital Apparatus, published by Industry Canada	February 7, 2004
☒	CISPR 22	Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, "Information Technology Equipment – Radio Disturbance Characteristics – Limits and Methods of Measurement"	1997

☐	CAN/CSA- CEI/IEC CISPR 22	Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment	2002
		CAN/CSA CISPR 22-10 Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement (Adopted IEC CISPR 22:2008, sixth edition, 2008-09)	
☐	CAN/CSA CISPR 22-10	Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement (Adopted IEC CISPR 22:2008, sixth edition, 2008-09)	2010
☒	TRC-43	Notes Regarding Designation of Emissions (Including Necessary Bandwidth and Classification), Class of Station and Nature of Service, published by Industry Canada	October, 2008

10 Test Equipment List with Calibration Data

Type	Inv.-No.	Type Designation	Serial Number	Manufacturer	Calibration Organization	Last Calibration	Next Calibration
EMI test receiver	2044	ESU8	100232	Rohde & Schwarz	Rohde & Schwarz	07/2012	01/2014
Spectrum analyser	1666	FSP30	100063	Rohde & Schwarz	Rohde & Schwarz	11/2012	05/2014
Preamplifier	1684	AFS3-00100800-32-LN	847743	MITEQ	TÜV SÜD PS-EMC-STR	11/2011	05/2013
Preamplifier	1716	CPA9231A	3557	Schaffner EMC Systems	TÜV SÜD PS-EMC-STR	07/2012	01/2014
Double ridged waveguide horn antenna	1516	3115	9508-4553	EMCO Elektronik	Seibersdorf Laboratories	11/2012	11/2014
Loop antenna	1016	HFH2-Z2	882964/0001	Rohde & Schwarz	Rohde & Schwarz	11/2012	05/2014
TRILOG Broadband Antenna	2058	VULB 9163	9163-408	Schwarzbeck	Rohde & Schwarz	11/2012	05/2014

Note 1: No calibration required.

Note 2: Not calibrated separately but with the whole test system when recording calibration data.

Note 3: No calibration required. Devices are checked before use.

Note 4: No calibration required. Devices are checked by calibrated equipment during test.


11 Revision History

Revision History			
<i>Edition</i>	<i>Date</i>	<i>Issued by</i>	<i>Modifications</i>
1	2013-05-08	Martin Steindl (gz)	First Edition
2	2014-03-28	J. Roidt (aw)	Change in type designation; FCC ID and IC no. added (page 3)
3	2014-04-14	M. Steindl	Plot for deactivation of transmitter added

Annex A Charts taken during testing


Radiated Emission Test 9 kHz - 30 MHz acc. to FCC Part 15 Subpart C (FAR)

Model: HS37x28 315 MHz Serial no.: --- Applicant: ELDAT GmbH Test site: Fully anechoic room, cabin no. 2 Tested on: Test distance 3 metres Date of test: 05/02/2013 Operator: M. Steindl Test performed: by hand File name: default.emi	Comment: - Transmitting continuously - EUT flat on table
Detector: Peak	List of values: 10 dB Margin 50 Subranges




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Model: HS37x28 315 MHz</td> </tr> <tr> <td colspan="2">Serial no.: ---</td> </tr> <tr> <td colspan="2">Applicant: ELDAT GmbH</td> </tr> <tr> <td colspan="2">Test site: Fully anechoic room, cabin no. 2</td> </tr> <tr> <td colspan="2">Tested on: Test distance 3 metres Horizontal Polarization</td> </tr> <tr> <td>Date of test: 05/02/2013</td> <td>Operator: M. Steindl</td> </tr> <tr> <td>Test performed: automatically</td> <td>File name: default.emi</td> </tr> </table>	Model: HS37x28 315 MHz		Serial no.: ---		Applicant: ELDAT GmbH		Test site: Fully anechoic room, cabin no. 2		Tested on: Test distance 3 metres Horizontal Polarization		Date of test: 05/02/2013	Operator: M. Steindl	Test performed: automatically	File name: default.emi	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Comment: - Transmitting continuously - EUT flat on table</td> </tr> </table>	Comment: - Transmitting continuously - EUT flat on table
Model: HS37x28 315 MHz																
Serial no.: ---																
Applicant: ELDAT GmbH																
Test site: Fully anechoic room, cabin no. 2																
Tested on: Test distance 3 metres Horizontal Polarization																
Date of test: 05/02/2013	Operator: M. Steindl															
Test performed: automatically	File name: default.emi															
Comment: - Transmitting continuously - EUT flat on table																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Detector: Peak</td> </tr> </table>	Detector: Peak	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>List of values: 10 dB Margin 50 Subranges</td> </tr> </table>	List of values: 10 dB Margin 50 Subranges													
Detector: Peak																
List of values: 10 dB Margin 50 Subranges																




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Model: HS37x28 315 MHz</td> </tr> <tr> <td colspan="2">Serial no.: ---</td> </tr> <tr> <td colspan="2">Applicant: ELDAT GmbH</td> </tr> <tr> <td colspan="2">Test site: Fully anechoic room, cabin no. 2</td> </tr> <tr> <td colspan="2">Tested on: Test distance 3 metres Vertical Polarization</td> </tr> <tr> <td>Date of test: 05/02/2013</td> <td>Operator: M. Steindl</td> </tr> <tr> <td>Test performed: automatically</td> <td>File name: default.emi</td> </tr> </table>	Model: HS37x28 315 MHz		Serial no.: ---		Applicant: ELDAT GmbH		Test site: Fully anechoic room, cabin no. 2		Tested on: Test distance 3 metres Vertical Polarization		Date of test: 05/02/2013	Operator: M. Steindl	Test performed: automatically	File name: default.emi	Comment: - Transmitting continuously - EUT flat on table
Model: HS37x28 315 MHz															
Serial no.: ---															
Applicant: ELDAT GmbH															
Test site: Fully anechoic room, cabin no. 2															
Tested on: Test distance 3 metres Vertical Polarization															
Date of test: 05/02/2013	Operator: M. Steindl														
Test performed: automatically	File name: default.emi														
Detector: Peak	List of values: 10 dB Margin 50 Subranges														




Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)


<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT flat on table
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		



Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT flat on table
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Vertical Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		






— FCC 15.109 Class B * Final Result 1-QPK

EUT flat on table, Peak value noted


Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Model: HS37x28 315 MHz</td> </tr> <tr> <td colspan="2">Serial no.: ---</td> </tr> <tr> <td colspan="2">Applicant: ELDAT GmbH</td> </tr> <tr> <td colspan="2">Test site: Fully anechoic room, cabin no. 2</td> </tr> <tr> <td colspan="2">Tested on: Test distance 3 metres Horizontal Polarization</td> </tr> <tr> <td>Date of test: 05/02/2013</td> <td>Operator: M. Steindl</td> </tr> <tr> <td>Test performed: automatically</td> <td>File name: default.emi</td> </tr> </table>	Model: HS37x28 315 MHz		Serial no.: ---		Applicant: ELDAT GmbH		Test site: Fully anechoic room, cabin no. 2		Tested on: Test distance 3 metres Horizontal Polarization		Date of test: 05/02/2013	Operator: M. Steindl	Test performed: automatically	File name: default.emi	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td> Comment: - Transmitting continuously - EUT flat on table </td> </tr> </table>	Comment: - Transmitting continuously - EUT flat on table
Model: HS37x28 315 MHz																
Serial no.: ---																
Applicant: ELDAT GmbH																
Test site: Fully anechoic room, cabin no. 2																
Tested on: Test distance 3 metres Horizontal Polarization																
Date of test: 05/02/2013	Operator: M. Steindl															
Test performed: automatically	File name: default.emi															
Comment: - Transmitting continuously - EUT flat on table																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Detector: Peak</td> </tr> </table>	Detector: Peak	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td> List of values: Selected by hand </td> </tr> </table>	List of values: Selected by hand													
Detector: Peak																
List of values: Selected by hand																




Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">Model: HS37x28 315 MHz</td> </tr> <tr> <td colspan="2">Serial no.: ---</td> </tr> <tr> <td colspan="2">Applicant: ELDAT GmbH</td> </tr> <tr> <td colspan="2">Test site: Fully anechoic room, cabin no. 2</td> </tr> <tr> <td colspan="2">Tested on: Test distance 3 metres Vertical Polarization</td> </tr> <tr> <td>Date of test: 05/02/2013</td> <td>Operator: M. Steindl</td> </tr> <tr> <td>Test performed: automatically</td> <td>File name: default.emi</td> </tr> </table>	Model: HS37x28 315 MHz		Serial no.: ---		Applicant: ELDAT GmbH		Test site: Fully anechoic room, cabin no. 2		Tested on: Test distance 3 metres Vertical Polarization		Date of test: 05/02/2013	Operator: M. Steindl	Test performed: automatically	File name: default.emi	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Comment: - Transmitting continuously - EUT flat on table</td> </tr> </table>	Comment: - Transmitting continuously - EUT flat on table
Model: HS37x28 315 MHz																
Serial no.: ---																
Applicant: ELDAT GmbH																
Test site: Fully anechoic room, cabin no. 2																
Tested on: Test distance 3 metres Vertical Polarization																
Date of test: 05/02/2013	Operator: M. Steindl															
Test performed: automatically	File name: default.emi															
Comment: - Transmitting continuously - EUT flat on table																
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Detector: Peak</td> </tr> </table>	Detector: Peak	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>List of values: Selected by hand</td> </tr> </table>	List of values: Selected by hand													
Detector: Peak																
List of values: Selected by hand																




Radiated Emission Test 9 kHz - 30 MHz acc. to FCC Part 15 Subpart C (FAR)

Model: HS37x28 315 MHz	Comment: - Transmitting continuously - EUT on long side
Serial no.: ---	
Applicant: ELDAT GmbH	
Test site: Fully anechoic room, cabin no. 2	
Tested on: Test distance 3 metres	
Date of test: 05/02/2013	Operator: M. Steindl
Test performed: by hand	File name: default.emi
Detector: Peak	List of values: Selected by hand




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT on long side
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT on long side
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Vertical Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		




Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)

Model: HS37x28 315 MHz Serial no.: --- Applicant: ELDAT GmbH Test site: Fully anechoic room, cabin no. 2 Tested on: Test distance 3 metres Horizontal Polarization Date of test: 05/02/2013 Operator: M. Steindl Test performed: automatically File name: default.emi	Comment: - Transmitting continuously - EUT on long side
Detector: Peak	List of values: Selected by hand




Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)


<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT on long side
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Vertical Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		



Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT on long side
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: Selected by hand																		






— FCC 15.109 Class B * Final Result 1-QPK

EUT on long side, Peak value noted


Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Comment:</td></tr> <tr><td style="padding: 2px;">- Transmitting continuously</td></tr> <tr><td style="padding: 2px;">- EUT on long side</td></tr> </table>	Comment:	- Transmitting continuously	- EUT on long side
Model:	HS37x28 315 MHz																					
Serial no.:	---																					
Applicant:	ELDAT GmbH																					
Test site:	Fully anechoic room, cabin no. 2																					
Tested on:	Test distance 3 metres Vertical Polarization																					
Date of test:	Operator:																					
05/02/2013	M. Steindl																					
Test performed:	File name:																					
automatically	default.emi																					
Comment:																						
- Transmitting continuously																						
- EUT on long side																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Detector:</td></tr> <tr><td style="padding: 2px;">Peak</td></tr> </table>	Detector:	Peak	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">List of values:</td></tr> <tr><td style="padding: 2px;">Selected by hand</td></tr> </table>	List of values:	Selected by hand																	
Detector:																						
Peak																						
List of values:																						
Selected by hand																						




Radiated Emission Test 9 kHz - 30 MHz acc. to FCC Part 15 Subpart C (FAR)

Model: HS37x28 315 MHz Serial no.: --- Applicant: ELDAT GmbH Test site: Fully anechoic room, cabin no. 2 Tested on: Test distance 3 metres Date of test: 05/02/2013 Operator: M. Steindl Test performed: by hand File name: default.emi	Comment: - Transmitting continuously - EUT in upright position
Detector: Peak	List of values: Selected by hand




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT in upright position
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		




Radiated Emission Test 30 MHz - 500 MHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT in upright position
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Vertical Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: 10 dB Margin 50 Subranges																		




Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT in upright position
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: Selected by hand																		




Radiated Emission Test 500 MHz - 1 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Comment:</td></tr> <tr><td style="padding: 2px;">- Transmitting continuously</td></tr> <tr><td style="padding: 2px;">- EUT in upright position</td></tr> </table>	Comment:	- Transmitting continuously	- EUT in upright position
Model:	HS37x28 315 MHz																					
Serial no.:	---																					
Applicant:	ELDAT GmbH																					
Test site:	Fully anechoic room, cabin no. 2																					
Tested on:	Test distance 3 metres Vertical Polarization																					
Date of test:	Operator:																					
05/02/2013	M. Steindl																					
Test performed:	File name:																					
automatically	default.emi																					
Comment:																						
- Transmitting continuously																						
- EUT in upright position																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Detector:</td></tr> <tr><td style="padding: 2px;">Peak</td></tr> </table>	Detector:	Peak	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">List of values:</td></tr> <tr> <td style="padding: 2px;">10 dB Margin</td><td style="padding: 2px;">50 Subranges</td></tr> </table>	List of values:	10 dB Margin	50 Subranges																
Detector:																						
Peak																						
List of values:																						
10 dB Margin	50 Subranges																					



Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Horizontal Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Horizontal Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT in upright position
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Horizontal Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: Selected by hand																		



Radiated Emission Test 1 GHz - 3.5 GHz acc. to FCC Part 15 Subpart C (FAR)

<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="padding: 2px;">Model:</td><td style="padding: 2px;">HS37x28 315 MHz</td></tr> <tr><td style="padding: 2px;">Serial no.:</td><td style="padding: 2px;">---</td></tr> <tr><td style="padding: 2px;">Applicant:</td><td style="padding: 2px;">ELDAT GmbH</td></tr> <tr><td style="padding: 2px;">Test site:</td><td style="padding: 2px;">Fully anechoic room, cabin no. 2</td></tr> <tr><td style="padding: 2px;">Tested on:</td><td style="padding: 2px;">Test distance 3 metres Vertical Polarization</td></tr> <tr> <td style="padding: 2px;">Date of test:</td><td style="padding: 2px;">Operator:</td></tr> <tr> <td style="padding: 2px;">05/02/2013</td><td style="padding: 2px;">M. Steindl</td></tr> <tr> <td style="padding: 2px;">Test performed:</td><td style="padding: 2px;">File name:</td></tr> <tr> <td style="padding: 2px;">automatically</td><td style="padding: 2px;">default.emi</td></tr> </table>	Model:	HS37x28 315 MHz	Serial no.:	---	Applicant:	ELDAT GmbH	Test site:	Fully anechoic room, cabin no. 2	Tested on:	Test distance 3 metres Vertical Polarization	Date of test:	Operator:	05/02/2013	M. Steindl	Test performed:	File name:	automatically	default.emi	Comment: - Transmitting continuously - EUT in upright position
Model:	HS37x28 315 MHz																		
Serial no.:	---																		
Applicant:	ELDAT GmbH																		
Test site:	Fully anechoic room, cabin no. 2																		
Tested on:	Test distance 3 metres Vertical Polarization																		
Date of test:	Operator:																		
05/02/2013	M. Steindl																		
Test performed:	File name:																		
automatically	default.emi																		
Detector: Peak	List of values: Selected by hand																		

