


FCC Test Report

FCC ID : NKR-DHUB81
Equipment : 11abgn WLAN/Bluetooth Combo adapter
Model No. : DHUB-81, 700-0022-001
Brand Name : WNC
Applicant : Wistron Neweb Corporation
Address : 20 Park Avenue II, Hsinchu Science Park,
Hsinchu 308,Taiwan,R.O.C.
Standard : 47 CFR FCC Part 15.247
Received Date : Feb. 18, 2014
Tested Date : Feb. 20 ~ Feb. 28, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS.....	11
3.1	Conducted Emissions.....	11
3.2	6dB and Occupied Bandwidth.....	14
3.3	RF Output Power	17
3.4	Power Spectral Density	19
3.5	Unwanted Emissions into Restricted Frequency Bands	21
3.6	Unwanted Emissions into Non-Restricted Frequency Bands	41
4	TEST LABORATORY INFORMATION	50

Release Record

Report No.	Version	Description	Issued Date
FR421807AI	Rev. 01	Initial issue	Apr. 21, 2014

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.166MHz 47.58 (Margin -7.58dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]:11490.00MHz 52.59 (Margin -1.41dB) - AV	Pass
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 11a: 24.62 HT20: 24.59 HT40: 24.50	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description
WNC	DHUB-81	11abgn WLAN/Bluetooth Combo adapter	marketing purpose
	700-0022-001		
✦ All models are electrically identical, different model names are for marketing purpose. ✦ The above models, model DHUB-81 was selected as a representative one for the final test and only its data was recorded in this report.			

1.1.2 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS
5725-5850	a	5745-5825	149-165 [5]	2	6-54 Mbps
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	MCS 0-15
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	MCS 0-15
Note 1: RF output power specifies that Maximum Conducted Output Power. Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.					

1.1.3 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)			
				5150~5250	5250~5350	5470~5725	5725~5850
1	Left (ANT1)	Printed	NA	-2.93	-2.65	-2.71	-3.84
2	Right (ANT0)	Printed	NA	-3.14	-2.83	-2.73	-3.12

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from host
-------------------	----------------

1.1.5 Accessories

N/A

1.1.6 Channel List

Frequency band (MHz)	5725~5850
802.11 a / HT20	802.11n HT40

Channel	Frequency(MHz)	Channel	Frequency(MHz)
149	5745	151	5755
153	5765	159	5795
157	5785	---	---
161	5805	---	---
165	5825	---	---

1.1.7 Test Tool and Duty Cycle

Test Tool	Mtool, V2.0.0.9		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11a	99.31%	0.03
	HT20	99.25%	0.03
	HT40	98.19%	0.08


1.1.8 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11a	5745	76
11a	5785	76
11a	5825	76
HT20	5745	76
HT20	5785	76
HT20	5825	76
HT40	5755	68
HT40	5795	76

1.2 Local Support Equipment List

Support Equipment List						
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	E6430	---	DoC	USB 0.5m non-shielded cable with 1 core.

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Preamplifier	Burgeon	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014
Preamplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014
Preamplifier	EM	EM18G40G	060572	Jun. 20, 2013	Jun. 19, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission above 1GHz				
Test Site	966 chamber 2 / (03CH02-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Note: Calibration Interval of instruments listed above is two year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Spectrum Analyzer	Agilent	N9010A	MY53400091	Oct. 07, 2013	Oct. 06, 2014
Power Sensor	Anritsu	MA2411B	1207366	Oct. 24, 2013	Oct. 23, 2014
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r01

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 35.286 Hz
Conducted power	± 0.536 dB
Frequency error	± 35.286 Hz
Temperature	± 0.3 °C
Conducted emission	± 2.946 dB
AC conducted emission	± 2.43 dB
Radiated emission	± 2.49 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	19°C / 65%	Skys Huang
Radiated Emissions	03CH02-WS	17-18°C / 63-65%	Anderson Hong
RF Conducted	TH01-WS	22°C / 62%	Felix Sung

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	11a	5745	MCS 0	---
Radiated Emissions ≤1GHz	11a	5745	MCS 0	---
RF Output Power	11a	5745 / 5785 / 5825	6 Mbps	---
6dB bandwidth	HT20	5745 / 5785 / 5825	MCS 0	
Power spectral density	HT40	5755 / 5795	MCS 0	
NOTE:				
1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.				

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Modulation Mode	11a	Test Freq. (MHz)	5745
Power Phase	Line		

Level (dBuV)

Date: 2014-03-03




	Freq	Level	Limit	Over	Read	LISN	cable	
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark
			dBuV	dB	dBuV	dB	dB	
1	0.169	42.42	55.03	-12.61	41.91	0.40	0.11	Average
2*	0.169	54.96	65.03	-10.07	54.45	0.40	0.11	QP
3	0.221	38.76	52.79	-14.03	38.21	0.39	0.16	Average
4	0.221	46.18	62.79	-16.61	45.63	0.39	0.16	QP
5	1.289	17.36	46.00	-28.64	16.86	0.42	0.08	Average
6	1.289	25.14	56.00	-30.86	24.64	0.42	0.08	QP
7	3.547	28.71	46.00	-17.29	28.03	0.45	0.23	Average
8	3.547	37.89	56.00	-18.11	37.21	0.45	0.23	QP
9	8.776	21.03	50.00	-28.97	20.37	0.53	0.13	Average
10	8.776	26.02	60.00	-33.98	25.36	0.53	0.13	QP
11	21.486	18.74	50.00	-31.26	17.90	0.55	0.29	Average
12	21.486	29.77	60.00	-30.23	28.93	0.55	0.29	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	11a	Test Freq. (MHz)	5745
Power Phase	Neutral		

Level (dBuV)



Date: 2014-03-03

Frequency (MHz)

	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1*	0.166	47.58	55.16	-7.58	47.00	0.48	0.10	Average
2	0.166	54.18	65.16	-10.98	53.60	0.48	0.10	QP
3	0.211	34.67	53.18	-18.51	34.02	0.48	0.17	Average
4	0.211	41.35	63.18	-21.83	40.70	0.48	0.17	QP
5	0.255	36.54	51.60	-15.06	35.93	0.48	0.13	Average
6	0.255	39.65	61.60	-21.95	39.04	0.48	0.13	QP
7	3.123	24.14	46.00	-21.86	23.42	0.51	0.21	Average
8	3.123	35.13	56.00	-20.87	34.41	0.51	0.21	QP
9	3.820	34.56	46.00	-11.44	33.81	0.52	0.23	Average
10	3.820	38.88	56.00	-17.12	38.13	0.52	0.23	QP
11	22.180	23.91	50.00	-26.09	23.03	0.55	0.33	Average
12	22.180	29.01	60.00	-30.99	28.13	0.55	0.33	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).

Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 6dB and Occupied Bandwidth


3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup




3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N _{TX}	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11a	2	5745	15.88	14.38	---	---	500
11a	2	5785	15.07	15.07	---	---	500
11a	2	5825	16.29	15.13	---	---	500
HT20	2	5745	15.94	15.13	---	---	500
HT20	2	5785	16.93	15.13	---	---	500
HT20	2	5825	15.13	15.71	---	---	500
HT40	2	5755	36.29	36.29	---	---	500
HT40	2	5795	36.29	36.41	---	---	500



Modulation Mode	N _{TX}	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11a	2	5745	21.24	20.30	---	---
11a	2	5785	21.13	19.07	---	---
11a	2	5825	20.30	19.83	---	---
HT20	2	5745	21.45	19.39	---	---
HT20	2	5785	20.30	20.30	---	---
HT20	2	5825	21.42	18.99	---	---
HT40	2	5755	37.25	37.25	---	---
HT40	2	5795	38.23	37.58	---	---



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- ☒ Antenna gain $\leq 6\text{dBi}$, no any corresponding reduction is in output power limit.
- ☐ Antenna gain $> 6\text{dBi}$
 - ☐ Non Fixed, point to point operations.
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
 - ☐ Fixed, point to point operations
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

- ☒ Maximum Peak Conducted Output Power
 - ☐ **Spectrum analyzer**
 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
 - ☒ **Power meter**
 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- ☒ Maximum Conducted Output Power (For reference only)
 - ☒ **Power meter**
 1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup



3.3.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Peak conducted output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11a	2	5745	21.43	21.78	---	---	289.656	24.62	30.00
11a	2	5785	21.37	21.57	---	---	280.637	24.48	30.00
11a	2	5825	21.29	21.52	---	---	276.492	24.42	30.00
HT20	2	5745	21.55	21.59	---	---	287.101	24.58	30.00
HT20	2	5785	21.41	21.75	---	---	287.980	24.59	30.00
HT20	2	5825	21.34	21.73	---	---	285.081	24.55	30.00
HT40	2	5755	21.22	21.51	---	---	274.014	24.38	30.00
HT40	2	5795	21.37	21.60	---	---	281.632	24.50	30.00

Modulation Mode	N _{TX}	Freq. (MHz)	Conducted (average) output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11a	2	5745	19.71	19.24	---	---	177.487	22.49	30.00
11a	2	5785	19.74	19.48	---	---	182.905	22.62	30.00
11a	2	5825	19.51	19.22	---	---	172.891	22.38	30.00
HT20	2	5745	19.55	18.93	---	---	168.320	22.26	30.00
HT20	2	5785	19.93	19.53	---	---	188.144	22.74	30.00
HT20	2	5825	19.45	19.07	---	---	168.828	22.27	30.00
HT40	2	5755	17.91	17.71	---	---	120.822	20.82	30.00
HT40	2	5795	19.41	19.38	---	---	173.993	22.41	30.00

Note: Conducted average output power is for reference only.

3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- ☒ Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 3kHz, VBW = 10kHz.
 2. Detector = Peak, Sweep time = auto couple.
 3. Trace mode = max hold, allow trace to fully stabilize.
 4. Use the peak marker function to determine the maximum amplitude level.
- ☐ Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 1. Set the RBW = 100kHz, VBW = 300 kHz.
 2. Detector = RMS, Sweep time = auto couple.
 3. Set the sweep time to: $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$.
 4. Perform the measurement over a single sweep.
 5. Use the peak marker function to determine the maximum amplitude level.\


3.4.3 Test Setup



3.4.4 Test Result of Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11a	2	5745	-1.79	8
11a	2	5785	-2.10	8
11a	2	5825	-2.01	8
HT20	2	5745	-2.27	8
HT20	2	5785	-2.47	8
HT20	2	5825	-1.04	8
HT40	2	5755	-8.27	8
HT40	2	5795	-5.96	8

Note: Test result is bin-by-bin summing measured value of each TX port.



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.5.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	11a	Test Freq. (MHz)	5745
Polarization	Horizontal		
Level (dBuV/m) </			

Modulation	11a	Test Freq. (MHz)	5745
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	72.68	24.84	40.00	-15.16	44.82	-19.98	Peak	---	---
2	156.10	31.84	43.50	-11.66	48.93	-17.09	Peak	---	---
3	231.76	27.93	46.00	-18.07	46.68	-18.75	Peak	---	---
4	527.61	31.28	46.00	-14.72	42.53	-11.25	Peak	---	---
5	697.36	30.60	46.00	-15.40	39.05	-8.45	Peak	---	---
6	840.92	36.31	46.00	-9.69	42.60	-6.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a

Modulation	11a	Test Freq. (MHz)	5745
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.54	54.00	-16.46	44.21	-6.67	Average	---	---
2	1500.00	51.43	74.00	-22.57	58.10	-6.67	Peak	---	---
3	7660.00	41.38	54.00	-12.62	29.40	11.98	Average	---	---
4	7660.00	54.18	74.00	-19.82	42.20	11.98	Peak	---	---
5	11490.00	51.63	54.00	-2.37	37.94	13.69	Average	---	---
6	11490.00	61.68	74.00	-12.32	47.99	13.69	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5745																																																																						
Polarization	Vertical																																																																								
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 FCC CLASS-B FCC CLASS-B (AVG) Frequency (MHz) 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 2 4 3 6 5 <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1500.00</td><td>35.69</td><td>54.00</td><td>-18.31</td><td>42.36</td><td>-6.67</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1500.00</td><td>48.82</td><td>74.00</td><td>-25.18</td><td>55.49</td><td>-6.67</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>7660.00</td><td>40.74</td><td>54.00</td><td>-13.26</td><td>28.76</td><td>11.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>7660.00</td><td>54.58</td><td>74.00</td><td>-19.42</td><td>42.60</td><td>11.98</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11490.00</td><td>52.59</td><td>54.00</td><td>-1.41</td><td>38.90</td><td>13.69</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11490.00</td><td>63.90</td><td>74.00</td><td>-10.10</td><td>50.21</td><td>13.69</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1500.00	35.69	54.00	-18.31	42.36	-6.67	Average	---	---	2	1500.00	48.82	74.00	-25.18	55.49	-6.67	Peak	---	---	3	7660.00	40.74	54.00	-13.26	28.76	11.98	Average	---	---	4	7660.00	54.58	74.00	-19.42	42.60	11.98	Peak	---	---	5	11490.00	52.59	54.00	-1.41	38.90	13.69	Average	---	---	6	11490.00	63.90	74.00	-10.10	50.21	13.69	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1500.00	35.69	54.00	-18.31	42.36	-6.67	Average	---	---																																																																
2	1500.00	48.82	74.00	-25.18	55.49	-6.67	Peak	---	---																																																																
3	7660.00	40.74	54.00	-13.26	28.76	11.98	Average	---	---																																																																
4	7660.00	54.58	74.00	-19.42	42.60	11.98	Peak	---	---																																																																
5	11490.00	52.59	54.00	-1.41	38.90	13.69	Average	---	---																																																																
6	11490.00	63.90	74.00	-10.10	50.21	13.69	Peak	---	---																																																																
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																									

Modulation	11a	Test Freq. (MHz)	5785
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.89	54.00	-16.11	44.56	-6.67	Average	---	---
2	1500.00	51.88	74.00	-22.12	58.55	-6.67	Peak	---	---
3	7713.30	41.05	54.00	-12.95	29.18	11.87	Average	---	---
4	7713.30	53.72	74.00	-20.28	41.85	11.87	Peak	---	---
5	11570.00	51.27	54.00	-2.73	37.50	13.77	Average	---	---
6	11570.00	61.28	74.00	-12.72	47.51	13.77	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5785
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.18	54.00	-18.82	41.85	-6.67	Average	---	---
2	1500.00	48.57	74.00	-25.43	55.24	-6.67	Peak	---	---
3	7713.30	40.53	54.00	-13.47	28.66	11.87	Average	---	---
4	7713.30	54.23	74.00	-19.77	42.36	11.87	Peak	---	---
5	11570.00	52.32	54.00	-1.68	38.55	13.77	Average	---	---
6	11570.00	63.70	74.00	-10.30	49.93	13.77	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5825
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.42	54.00	-16.58	44.09	-6.67	Average	---	---
2	1500.00	51.26	74.00	-22.74	57.93	-6.67	Peak	---	---
3	3883.30	42.93	54.00	-11.07	39.06	3.87	Average	---	---
4	3883.30	55.87	74.00	-18.13	52.00	3.87	Peak	---	---
5	11650.00	51.28	54.00	-2.72	37.40	13.88	Average	---	---
6	11650.00	61.33	74.00	-12.67	47.45	13.88	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	11a	Test Freq. (MHz)	5825
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.24	54.00	-18.76	41.91	-6.67	Average	---	---
2	1500.00	48.46	74.00	-25.54	55.13	-6.67	Peak	---	---
3	3883.30	42.64	54.00	-11.36	38.77	3.87	Average	---	---
4	3883.30	56.03	74.00	-17.97	52.16	3.87	Peak	---	---
5	11650.00	52.28	54.00	-1.72	38.40	13.88	Average	---	---
6	11650.00	63.42	74.00	-10.58	49.54	13.88	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	5745																																																																																										
Polarization	Horizontal																																																																																												
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 FCC CLASS-B FCC CLASS-B (AVG) Frequency (MHz) 2 4 6 3 5 1500 7660 11490 <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1500.00</td><td>37.86</td><td>54.00</td><td>-16.14</td><td>44.53</td><td>-6.67</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1500.00</td><td>51.63</td><td>74.00</td><td>-22.37</td><td>58.30</td><td>-6.67</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>7660.00</td><td>41.72</td><td>54.00</td><td>-12.28</td><td>29.74</td><td>11.98</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>7660.00</td><td>54.52</td><td>74.00</td><td>-19.48</td><td>42.54</td><td>11.98</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11490.00</td><td>51.13</td><td>54.00</td><td>-2.87</td><td>37.44</td><td>13.69</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11490.00</td><td>61.27</td><td>74.00</td><td>-12.73</td><td>47.58</td><td>13.69</td><td>Peak</td><td>---</td><td>---</td></tr></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1500.00	37.86	54.00	-16.14	44.53	-6.67	Average	---	---	2	1500.00	51.63	74.00	-22.37	58.30	-6.67	Peak	---	---	3	7660.00	41.72	54.00	-12.28	29.74	11.98	Average	---	---	4	7660.00	54.52	74.00	-19.48	42.54	11.98	Peak	---	---	5	11490.00	51.13	54.00	-2.87	37.44	13.69	Average	---	---	6	11490.00	61.27	74.00	-12.73	47.58	13.69	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																				
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																				
		dBuV/m			dBuV			cm	deg																																																																																				
1	1500.00	37.86	54.00	-16.14	44.53	-6.67	Average	---	---																																																																																				
2	1500.00	51.63	74.00	-22.37	58.30	-6.67	Peak	---	---																																																																																				
3	7660.00	41.72	54.00	-12.28	29.74	11.98	Average	---	---																																																																																				
4	7660.00	54.52	74.00	-19.48	42.54	11.98	Peak	---	---																																																																																				
5	11490.00	51.13	54.00	-2.87	37.44	13.69	Average	---	---																																																																																				
6	11490.00	61.27	74.00	-12.73	47.58	13.69	Peak	---	---																																																																																				

Modulation	HT20	Test Freq. (MHz)	5745
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.94	54.00	-18.06	42.61	-6.67	Average	---	---
2	1500.00	49.17	74.00	-24.83	55.84	-6.67	Peak	---	---
3	7660.00	40.93	54.00	-13.07	28.95	11.98	Average	---	---
4	7660.00	55.00	74.00	-19.00	43.02	11.98	Peak	---	---
5	11490.00	52.17	54.00	-1.83	38.48	13.69	Average	---	---
6	11490.00	63.45	74.00	-10.55	49.76	13.69	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	5785
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.64	54.00	-16.36	44.31	-6.67	Average	---	---
2	1500.00	51.25	74.00	-22.75	57.92	-6.67	Peak	---	---
3	7713.30	41.42	54.00	-12.58	29.55	11.87	Average	---	---
4	7713.30	54.29	74.00	-19.71	42.42	11.87	Peak	---	---
5	11570.00	50.72	54.00	-3.28	36.95	13.77	Average	---	---
6	11570.00	60.74	74.00	-13.26	46.97	13.77	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	5785
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.49	54.00	-18.51	42.16	-6.67	Average	---	---
2	1500.00	48.87	74.00	-25.13	55.54	-6.67	Peak	---	---
3	7713.30	40.58	54.00	-13.42	28.71	11.87	Average	---	---
4	7713.30	54.78	74.00	-19.22	42.91	11.87	Peak	---	---
5	11570.00	51.80	54.00	-2.20	38.03	13.77	Average	---	---
6	11570.00	62.79	74.00	-11.21	49.02	13.77	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT20	Test Freq. (MHz)	5825																																																																																										
Polarization	Horizontal																																																																																												
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 Frequency (MHz) 2 4 6 3 5 FCC CLASS-B FCC CLASS-B (AVG) <table><tr><th></th><th>Freq.</th><th>Emission</th><th>Limit</th><th>Margin</th><th>SA</th><th>Factor</th><th>Remark</th><th>ANT</th><th>Turn</th></tr><tr><th></th><th>MHz</th><th>level</th><th>dBuV/m</th><th>dB</th><th>reading</th><th>dB</th><th></th><th>High</th><th>Table</th></tr><tr><th></th><th></th><th>dBuV/m</th><th></th><th></th><th>dBuV</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1500.00</td><td>37.78</td><td>54.00</td><td>-16.22</td><td>44.45</td><td>-6.67</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1500.00</td><td>51.58</td><td>74.00</td><td>-22.42</td><td>58.25</td><td>-6.67</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>3883.30</td><td>43.29</td><td>54.00</td><td>-10.71</td><td>39.42</td><td>3.87</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>3883.30</td><td>56.20</td><td>74.00</td><td>-17.80</td><td>52.33</td><td>3.87</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11650.00</td><td>50.89</td><td>54.00</td><td>-3.11</td><td>37.01</td><td>13.88</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11650.00</td><td>60.93</td><td>74.00</td><td>-13.07</td><td>47.05</td><td>13.88</td><td>Peak</td><td>---</td><td>---</td></tr></table>					Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn		MHz	level	dBuV/m	dB	reading	dB		High	Table			dBuV/m			dBuV			cm	deg	1	1500.00	37.78	54.00	-16.22	44.45	-6.67	Average	---	---	2	1500.00	51.58	74.00	-22.42	58.25	-6.67	Peak	---	---	3	3883.30	43.29	54.00	-10.71	39.42	3.87	Average	---	---	4	3883.30	56.20	74.00	-17.80	52.33	3.87	Peak	---	---	5	11650.00	50.89	54.00	-3.11	37.01	13.88	Average	---	---	6	11650.00	60.93	74.00	-13.07	47.05	13.88	Peak	---	---
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn																																																																																				
	MHz	level	dBuV/m	dB	reading	dB		High	Table																																																																																				
		dBuV/m			dBuV			cm	deg																																																																																				
1	1500.00	37.78	54.00	-16.22	44.45	-6.67	Average	---	---																																																																																				
2	1500.00	51.58	74.00	-22.42	58.25	-6.67	Peak	---	---																																																																																				
3	3883.30	43.29	54.00	-10.71	39.42	3.87	Average	---	---																																																																																				
4	3883.30	56.20	74.00	-17.80	52.33	3.87	Peak	---	---																																																																																				
5	11650.00	50.89	54.00	-3.11	37.01	13.88	Average	---	---																																																																																				
6	11650.00	60.93	74.00	-13.07	47.05	13.88	Peak	---	---																																																																																				
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																																																													

Modulation	HT20	Test Freq. (MHz)	5825
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.69	54.00	-18.31	42.36	-6.67	Average	---	---
2	1500.00	48.72	74.00	-25.28	55.39	-6.67	Peak	---	---
3	3883.30	42.93	54.00	-11.07	39.06	3.87	Average	---	---
4	3883.30	56.55	74.00	-17.45	52.68	3.87	Peak	---	---
5	11650.00	52.12	54.00	-1.88	38.24	13.88	Average	---	---
6	11650.00	63.29	74.00	-10.71	49.41	13.88	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Modulation	HT40	Test Freq. (MHz)	5755																																																																						
Polarization	Horizontal																																																																								
Level (dBuV/m) 117 110 90 70 50 30 10 0 1000 6000 10000 14000 18000 22000 26000 30000 34000 40000 2 4 6 1 3 5 FCC CLASS-B FCC CLASS-B (AVG) Frequency (MHz) <table><tr><th></th><th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr><tr><td>1</td><td>1500.00</td><td>37.38</td><td>54.00</td><td>-16.62</td><td>44.05</td><td>-6.67</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>2</td><td>1500.00</td><td>51.47</td><td>74.00</td><td>-22.53</td><td>58.14</td><td>-6.67</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>3</td><td>7673.30</td><td>41.42</td><td>54.00</td><td>-12.58</td><td>29.46</td><td>11.96</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>4</td><td>7673.30</td><td>54.37</td><td>74.00</td><td>-19.63</td><td>42.41</td><td>11.96</td><td>Peak</td><td>---</td><td>---</td></tr><tr><td>5</td><td>11510.00</td><td>48.52</td><td>54.00</td><td>-5.48</td><td>34.82</td><td>13.70</td><td>Average</td><td>---</td><td>---</td></tr><tr><td>6</td><td>11510.00</td><td>58.38</td><td>74.00</td><td>-15.62</td><td>44.68</td><td>13.70</td><td>Peak</td><td>---</td><td>---</td></tr></table> Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).					Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1500.00	37.38	54.00	-16.62	44.05	-6.67	Average	---	---	2	1500.00	51.47	74.00	-22.53	58.14	-6.67	Peak	---	---	3	7673.30	41.42	54.00	-12.58	29.46	11.96	Average	---	---	4	7673.30	54.37	74.00	-19.63	42.41	11.96	Peak	---	---	5	11510.00	48.52	54.00	-5.48	34.82	13.70	Average	---	---	6	11510.00	58.38	74.00	-15.62	44.68	13.70	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	1500.00	37.38	54.00	-16.62	44.05	-6.67	Average	---	---																																																																
2	1500.00	51.47	74.00	-22.53	58.14	-6.67	Peak	---	---																																																																
3	7673.30	41.42	54.00	-12.58	29.46	11.96	Average	---	---																																																																
4	7673.30	54.37	74.00	-19.63	42.41	11.96	Peak	---	---																																																																
5	11510.00	48.52	54.00	-5.48	34.82	13.70	Average	---	---																																																																
6	11510.00	58.38	74.00	-15.62	44.68	13.70	Peak	---	---																																																																

Modulation	HT40	Test Freq. (MHz)	5755
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.43	54.00	-18.57	42.10	-6.67	Average	---	---
2	1500.00	48.82	74.00	-25.18	55.49	-6.67	Peak	---	---
3	7673.30	40.28	54.00	-13.72	28.32	11.96	Average	---	---
4	7673.30	54.39	74.00	-19.61	42.43	11.96	Peak	---	---
5	11510.00	49.42	54.00	-4.58	35.72	13.70	Average	---	---
6	11510.00	60.57	74.00	-13.43	46.87	13.70	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	5795
Polarization	Horizontal		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.55	54.00	-16.45	44.22	-6.67	Average	---	---
2	1500.00	51.68	74.00	-22.32	58.35	-6.67	Peak	---	---
3	7726.70	41.68	54.00	-12.32	29.84	11.84	Average	---	---
4	7726.70	54.67	74.00	-19.33	42.83	11.84	Peak	---	---
5	11590.00	48.87	54.00	-5.13	35.07	13.80	Average	---	---
6	11590.00	58.66	74.00	-15.34	44.86	13.80	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	HT40	Test Freq. (MHz)	5795
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	35.71	54.00	-18.29	42.38	-6.67	Average	---	---
2	1500.00	49.18	74.00	-24.82	55.85	-6.67	Peak	---	---
3	7726.70	40.58	54.00	-13.42	28.74	11.84	Average	---	---
4	7726.70	54.73	74.00	-19.27	42.89	11.84	Peak	---	---
5	11590.00	49.83	54.00	-4.17	36.03	13.80	Average	---	---
6	11590.00	60.93	74.00	-13.07	47.13	13.80	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.6 Unwanted Emissions into Non-Restricted Frequency Bands

3.6.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.6.3 Test Setup





3.6.4 Test Result of Emissions in non-restricted frequency bands

This test item is performed on each TX output individually without summing or adding $10 \log(N_{\text{ANT}})$ since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.


3.6.5 Unwanted Emissions into Non-Restricted Frequency Bands

802.11a






Reference Level




Date: 27.FEB.2014 21:08:58


Tx 5825MHz / 30MHz~40GHz (down 20dBc)



Date: 27.FEB.2014 21:10:44




Date: 27.FEB.2014 21:10:06




Date: 27.FEB.2014 21:10:23


802.11n HT20





Reference Level




Tx 5785MHz / 30MHz~40GHz (down 20dBc)












802.11n HT40





Reference Level



Tx 5795MHz / 30MHz~40GHz (down 20dBc)







4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==