



REVISIONS

REV	DESCRIPTION	DATE	APPROVE
A	NEW RELEASE	03/27/20	SAM SUN



NOTES:

- MATERIAL: PET, $t=0.075$
ADHESIVE: 網紋背膠
FINISH: 上霧PET, $T=0.025$
- COLOR: LV11 PRIMARY GARY,PMS COOL GREY 5C
- 捲狀出貨，不加虛刀
- 離型紙左右間距各 3 ± 0.5 MM,上下間距各 3.0 ± 0.3 MM
- 被貼物材質:ABS
- 印刷公差:尺寸30mm以下為 ±0.3 mm,120~315mm為 ±0.5 mm,315以上 ±0.8 mm
- TEST REQUIREMENT

- DIE LINE (DO NOT PRINT)
- PMS COOL GREY 5C
- LV11 PRIMARY GARY(參照限度樣本)

	TEST ITEM	TEST SPEC	TEST CONDITION	CRITERIA
1	附著力測試	ISO Class.: 1 ASTM Class.: 4 B	ASTM D3359-02/ ISO 2409:2007	Detachment of small flakes of the coating at the intersections of the cuts. A cross-cut area not significantly greater than 5 % is affected.

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN mm AND TOLERANCES ARE: INTEGRAL DIMENSIONS ± 0.2 1 PLACE DECIMAL ± 0.2 ANGULAR DIMENSIONS $\pm 2^\circ$ HOLES UNDER $\varnothing 5.00$ ± 0.2		THIRD ANGLE PROJECTION 		WNC 啟碁科技股份有限公司 Wistron NeWeb Corp. 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan, R.O.C. Tel: 886-3-6667799 Fax: 886-3-5788726	
DRAWN		AMANDA LAI	03/27/20	DWG TITLE LABEL, FCC WARNING, UPDATED, TR1	
ENGR		AMANDA LAI	03/27/20	SIZE A4	
APVD		SAM SUN	03/27/20	DWG NO. 4L.TR100.00401	
SCALE		1/1	SHEET		1 OF 1
				REV	A