

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Report No.: RFBCKS-WTW-P25110456-3

FCC ID: NKR-VMC-QSA525M

Product: 2G/3G/4G/5G module

Brand: WNC

Model No.: VMC-QSA525M

Received Date: 2025/10/29

Test Date: 2025/11/6 ~ 2026/3/13

Issued Date: 2026/5/21

Applicant: WNC Corporation

Address: 20 Park Ave. II, Hsinchu Science Park, Hsinchu 308, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration /
Designation Number: 788550 / TW0003

Approved by: Jeremy Lin , **Date:** 2026/5/21
Jeremy Lin / Project Engineer

This test report consists of 73 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Pettie Chen / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Antenna Description of EUT	9
3.3 Test Mode Applicability and Tested Channel Detail.....	10
3.3.1 LTE Band 48	10
3.4 Test Program Used and Operation Descriptions	12
3.5 Connection Diagram of EUT and Peripheral Devices	12
3.6 Configuration of Peripheral Devices and Cable Connections	12
4 Test Instruments	13
4.1 Maximum EIRP	13
4.2 Modulation Characteristics	13
4.3 Peak to Average Ratio	13
4.4 Bandwidth.....	13
4.5 Conducted Spurious Emissions	14
4.6 Radiated Spurious Emissions below 1GHz.....	14
4.7 Radiated Spurious Emissions above 1GHz	15
4.8 Frequency Stability	16
5 Limits of Test Items.....	17
5.1 Maximum EIRP	17
5.2 Modulation Characteristics	17
5.3 Peak to Average Ratio	17
5.4 Bandwidth.....	17
5.5 Conducted Spurious Emissions	17
5.6 Radiated Spurious Emissions below 1GHz.....	17
5.7 Radiated Spurious Emissions above 1GHz	17
5.8 Frequency Stability	17
6 Test Arrangements.....	18
6.1 Maximum EIRP	18
6.1.1 Test Setup	18
6.1.2 Test Procedure	18
6.2 Modulation Characteristics	19
6.2.1 Test Setup	19
6.2.2 Test Procedure	19
6.3 Peak to Average Ratio	19
6.3.1 Test Setup	19
6.3.2 Test Procedure	19
6.4 Bandwidth.....	20
6.4.1 Test Setup	20
6.4.2 Test Procedure	20
6.5 Conducted Spurious Emissions	21
6.5.1 Test Setup	21
6.5.2 Test Procedure	21
6.6 Radiated Spurious Emissions below 1GHz.....	22
6.6.1 Test Setup	22
6.6.2 Test Procedure	23
6.7 Radiated Spurious Emissions above 1GHz	24
6.7.1 Test Setup	24
6.7.2 Test Procedure	24
6.8 Frequency Stability	25

6.8.1	Test Setup	25
6.8.2	Test Procedure	25
7	Test Results of Test Item	26
7.1	Maximum EIRP	26
7.1.1	LTE Band 48	26
7.2	Modulation Characteristics	38
7.2.1	LTE Band 48	38
7.3	Peak to Average Ratio	39
7.3.1	LTE Band 48	39
7.4	Bandwidth	40
7.4.1	LTE Band 48	40
7.5	Conducted Spurious Emissions	44
7.5.1	LTE Band 48	44
7.6	Radiated Spurious Emissions below 1GHz	63
7.6.1	LTE Band 48	63
7.7	Radiated Spurious Emissions above 1GHz	65
7.7.1	LTE Band 48	65
7.8	Frequency Stability	71
7.8.1	LTE Band 48	71
8	Pictures of Test Arrangements	72
9	Information of the Testing Laboratories	73

Release Control Record

Issue No.	Description	Date Issued
RFBCKS-WTW-P25110456-3	Original release.	2026/5/21

1 Certificate

Product: 2G/3G/4G/5G module

Brand: WNC

Test Model: VMC-QSA525M

Sample Status: Engineering sample

Applicant: WNC Corporation

Test Date: 2025/11/6 ~ 2026/3/13

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Measurement procedure: ANSI/TIA/EIA-603-E 2016
ANSI C63.26-2015
KDB 971168 D01 Power Meas License Digital Systems v03r01
KDB 940660 D01 Part 96 CBRS Eqpt v03

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

Standard / Clause	Test Item	Result	Remark
Part 2.1046 Part 96.41(b)	Maximum EIRP	Pass	Meet the requirement of limit.
Part 2.1047	Modulation Characteristics	Pass	Meet the requirement of limit.
Part 2.1046 Part 96.41(b)	Maximum Power Spectral Density	N/A	This device is End User Device.
Part 96.41(g)	Peak to Average Ratio	Pass	Meet the requirement of limit.
Part 2.1049	Bandwidth	Pass	Meet the requirement of limit.
Part 2.1051 Part 96.41(e)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions below 1GHz	Pass	Minimum passing margin is -4.58 dB at 81.41 MHz
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions above 1GHz	Pass	Minimum passing margin is -3.15 dB at 7250.00 MHz
Part 2.1055	Frequency Stability	Pass	Meet the requirement of limit.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
Effective Radiated Power and Equivalent Isotropically Radiated Power	-	1.371 dB
Peak to Average Ratio	-	0.920 dB
Bandwidth	-	960 Hz
Conducted Spurious Emissions	-	2.12 dB
Radiated Spurious Emissions below 1GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Radiated Spurious Emissions above 1GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB
Frequency Stability	-	0.176 ppm

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	2G/3G/4G/5G module
Brand	WNC
Test Model	VMC-QSA525M
Status of EUT	Engineering sample
Power Supply Rating	3.8Vdc
EUT Category	End User Device
Modulation Type	QPSK, 16QAM, 64QAM, 256QAM
LTE support SISO bands	B48
LTE support MIMO bands	-
PC3 for Power Class	B48
PC2 for Power Class	-
PC1.5 for Power Class	-

Note:

1. EUT Overview

LTE Band 48

Output Power: Full Power

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)	Emission Designator
5 MHz	3552.5 ~ 3697.5	QPSK	0.124	20.93	4M50G7D
		16QAM	0.102	20.08	4M50D7W
		64QAM	0.086	19.36	4M50D7W
		256QAM	0.063	18	4M49D7W
10 MHz	3555 ~ 3695	QPSK	0.127	21.03	8M98G7D
		16QAM	0.105	20.2	8M97D7W
		64QAM	0.087	19.41	8M97D7W
		256QAM	0.065	18.14	8M98D7W
15 MHz	3557.5 ~ 3692.5	QPSK	0.129	21.09	13M5G7D
		16QAM	0.107	20.31	13M5D7W
		64QAM	0.09	19.54	13M5D7W
		256QAM	0.067	18.27	13M5D7W
20 MHz	3560 ~ 3690	QPSK	0.132	21.22	18M0G7D
		16QAM	0.11	20.42	18M0D7W
		64QAM	0.093	19.68	18M0D7W
		256QAM	0.068	18.35	18M0D7W

Output Power: dBm/10 MHz

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)	Emission Designator
15 MHz	3557.5 ~ 3692.5	QPSK	0.128	21.07	13M5G7D
		16QAM	0.107	20.29	13M5D7W
		64QAM	0.089	19.47	13M5D7W
		256QAM	0.067	18.24	13M5D7W
20 MHz	3560 ~ 3690	QPSK	0.132	21.21	18M0G7D
		16QAM	0.110	20.41	18M0D7W
		64QAM	0.091	19.6	18M0D7W
		256QAM	0.068	18.34	18M0D7W

- The MIMO mode is completely uncorrelated, so the directional gain is selected the maximum gain among all antennas.
- For detailed information about each WWAN bands frequency range, bandwidth mode of the product, please refer to section 3.3 of the report.
- The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

Type	Dipole	
Connector	SMA	
Band	Freq. Range (MHz)	Gain (dBi)
LTE B48	3550 ~ 3700	2.7

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. X-axis/ Y-axis/ Z-axis Worst Condition: Z-Axis

Following channel(s) was (were) selected for the final test as listed below:

3.3.1 LTE Band 48


Test Item	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum EIRP	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
	55290(3555.00 MHz) 55990(3625.00 MHz) 56690(3695.00 MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
	55315(3557.50 MHz) 55990(3625.00 MHz) 56665(3692.50 MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
	55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
Modulation Characteristics	55990(3625.00 MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	Full RB
Peak to Average Ratio	55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB
Bandwidth	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	Full RB
	55290(3555.00 MHz) 55990(3625.00 MHz) 56690(3695.00 MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	Full RB
	55315(3557.50 MHz) 55990(3625.00 MHz) 56665(3692.50 MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	Full RB
	55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	Full RB
Conducted Spurious Emissions	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK	1 RB Full RB
	55290(3555.00 MHz) 55990(3625.00 MHz) 56690(3695.00 MHz)	10 MHz	QPSK	1 RB Full RB
	55315(3557.50 MHz) 55990(3625.00 MHz) 56665(3692.50 MHz)	15 MHz	QPSK	1 RB Full RB
	55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK	1 RB Full RB

Test Item	Tested Channel	Channel Bandwidth	Modulation	Mode
Radiated Spurious Emissions below 1GHz	55990(3625.00 MHz)	20 MHz	QPSK	1 RB
Radiated Spurious Emissions above 1GHz	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK	1 RB
	55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK	1 RB
	55340(3560.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK	Full RB

3.4 Test Program Used and Operation Descriptions

There is no need to controlling software during the test, and the EUT can be paired with the Radio Communication Analyzer to test the connection when it is powered on.

3.5 Connection Diagram of EUT and Peripheral Devices



3.6 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	DC Power Supply	OWON	ODP3122	ODP31222137036	NA	Provided by Lab
B	Radio Communication Analyzer	Anritsu	MT8821C	6201462755	NA	Provided by Lab
C	WWAN Antenna	NA	NA	NA	NA	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1	No	0	Supplied by applicant
2	DC Cable	1	2.4	No	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Maximum EIRP

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030B	MY57140938	2025/3/24	2026/3/23
Radio Communication Analyzer Anritsu	MT8821C	6201462755	2025/4/8	2026/4/7
Power Divider MVE	MVE8546	20161123085	2025/1/6	2026/1/5
			2026/1/5	2027/1/4
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in HY - Oven room (Hwaya).
2. Tested Date: 2025/11/6 ~ 2026/1/5

4.2 Modulation Characteristics

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030B	MY57140938	2025/3/24	2026/3/23
Radio Communication Analyzer Anritsu	MT8821C	6201462755	2025/4/8	2026/4/7
Power Divider MVE	MVE8546	20161123085	2026/1/5	2027/1/4
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in HY - Oven room (Hwaya).
2. Tested Date: 2026/1/6 ~ 2026/1/25

4.3 Peak to Average Ratio

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 Conducted Spurious Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030B	MY57140938	2025/3/24	2026/3/23
Radio Communication Analyzer Anritsu	MT8821C	6201462755	2025/4/8	2026/4/7
Power Divider MVE	MVE8546	20161123085	2025/1/6	2026/1/5
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in HY - Oven room(Hwaya).
2. Tested Date: 2025/12/5

4.6 Radiated Spurious Emissions below 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-160	2025/9/16	2026/9/15
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier Agilent	8447D	2944A10638	2025/4/27	2026/4/26
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-CH9-01	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSW43	101582	2025/4/15	2026/4/14
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4(Hwaya).
2. Tested Date: 2025/11/26

4.7 Radiated Spurious Emissions above 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1169	2025/11/9	2026/11/8
	BBHA 9170	9170-480	2025/11/9	2026/11/8
		BBHA9170243	2025/11/9	2026/11/8
MXE EMI Receiver Agilent	N9038A	MY51210203	2025/8/27	2026/8/26
Preamplifier Agilent	8449B	3008A02367	2025/1/5	2026/1/4
Preamplifier EMCI	EMC 184045	980116	2025/9/21	2026/9/20
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2025/6/30	2026/6/29
	EMC102-KM-KM-3000	150929	2025/6/30	2026/6/29
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	2025/1/5	2026/1/4
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2025/1/5	2026/1/4
Signal & Spectrum Analyzer R&S	FSW43	101582	2025/4/15	2026/4/14
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4(Hwaya).
2. Tested Date: 2025/11/19

4.8 Frequency Stability

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
3-channel DC power supply OWON	ODP3033	ODP30332128138	N/A	N/A
Digital Multimeter Fluke	8050A	4660081	2025/6/6	2026/6/5
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
Signal & Spectrum Analyzer R&S	FSV3044	101504	2025/6/18	2026/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A
Temperature & Humidity Chamber Terchy	MHU-225AU	920842	2025/6/25	2026/6/24
Power Divider MVE	MVE8546	20161123085	2026/1/5	2027/1/4

Notes:

1. The test was performed in HY - Oven room (Hwaya).
2. Tested Date: 2026/3/13

5 Limits of Test Items

5.1 Maximum EIRP

For LTE Band 48:

Device Category	Maximum EIRP (dBm/10 MHz)
End User Device	23
Category A CBSD	30
Category B CBSD	47

5.2 Modulation Characteristics

Systems operating in the Citizens Broadband Radio Service must use digital modulation techniques.

A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

5.3 Peak to Average Ratio

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.4 Bandwidth

According to FCC 47 CFR part 2.1049, the occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5% of the total mean power radiated by a given emission.

5.5 Conducted Spurious Emissions

For LTE Band 48:

The conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B MHz (where B is the bandwidth in MHz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B MHz below the lower CBSD-assigned channel edge. At all frequencies greater than B MHz above the upper CBSD assigned channel edge and less than B MHz below the lower CBSD-assigned channel edge, the conducted power of any end user device emission shall not exceed -25 dBm/MHz.

Additional protection levels: The conducted power of emissions below 3540 MHz or above 3710 MHz shall not exceed -25 dBm/MHz, and the conducted power of emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz.

5.6 Radiated Spurious Emissions below 1GHz

For LTE Band 48:

The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz.

5.7 Radiated Spurious Emissions above 1GHz

For LTE Band 48:

The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz.

5.8 Frequency Stability

For LTE Band 48:

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation (authorized frequency block).


6 Test Arrangements

6.1 Maximum EIRP


6.1.1 Test Setup

Conducted Power Measurement:

For full power measurement:



For per 10 MHz power measurement:



6.1.2 Test Procedure

Conducted Power Measurement:

For full power measurement:

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology. The average (rms) power measurement was performed on emulator and power value was measured from power function on emulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

For per 10 MHz power measurement:

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology and link to spectrum analyzer measurements. Set the EUT to transmit under low, middle and high channel and record the power level shown on spectrum analyzer. Power measurements use detector average (rms).

Measurement method refers to ANSI C63.26 section 5.2.4.4.

- Set span to $2 \times$ to $3 \times$ the OBW.
- Set RBW = 1% to 5% of the OBW.
- Set VBW $\geq 3 \times$ RBW.
- Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
- Set Sweep time = auto-couple.
- Detector = power averaging (rms).
- Set sweep trigger to "free run."
- Trace average at least 100 traces in power averaging (rms) mode.
- Use the Band/Channel Power function to determine the integrated power per 10 MHz bandwidth, according to the 47 CFR FCC Part 96 standard.
- If Duty cycle < 98%, Add $10 \log (1/\text{duty cycle})$ to the measured power level to compute the average power during continuous transmission.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively


(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

6.2 Modulation Characteristics

6.2.1 Test Setup




6.2.2 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector, the frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

6.3 Peak to Average Ratio

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Record the maximum PAPR level associated with a probability of 0.1%.

6.4 Bandwidth

6.4.1 Test Setup



6.4.2 Test Procedure

For the 26 dBc bandwidth measurement method, please refer to section 5.4.3 of ANSI C63.26.


- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times$ RBW.
- Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- Set spectrum analyzer detection mode to peak, and the trace mode to max hold.
- Determine the following reference values: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- Determine the “-X dB amplitude” as equal to (Reference Value - X). Alternatively, this calculation can be performed on the spectrum analyzer using the delta-marker measurement function.
- Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB amplitude” determined in step f). If a marker is below this “-X dB amplitude” value it should be as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- The OBW shall be reported by providing plot(s) of the measuring instrument display, to include markers depicting the relevant frequency and amplitude information (e.g., marker table). The frequency and amplitude axis and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

For the occupied bandwidth measurement method, please refer to section 5.4.4 of ANSI C63.26.

- a. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- b. The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times$ RBW.
- c. Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- d. Set spectrum analyzer detection mode to peak, and the trace mode to max hold.
- e. If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f. The OBW shall be reported by providing plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

6.5 Conducted Spurious Emissions

6.5.1 Test Setup




6.5.2 Test Procedure

- a. Measurement refer to ANSI C63.26 section 5.7.
- b. All measurements were done at 3 channels: low, middle and high operational frequency range.
- c. Measuring frequency range is from 9 kHz up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. 10 dB attenuation pad is connected with spectrum.
- d. The fundamental frequency above 1 GHz, the spectrum set RBW = 1 MHz, VBW = 3 MHz, Detector = Average.
- e. The fundamental frequency below 1 GHz, the spectrum set RBW ≥ 100 kHz, VBW $\geq 3 \times$ RBW, Detector = Average.
- f. Measuring frequency band edge, narrow RBW (no less than 1% of the OBW) is used for conducted emission measurement.
- g. For the emissions measurement method, certain channel BW modes demonstrate compliance by integrating with the smaller RBW allowed by the rule.
For example: Where Reference RBW = 1 MHz and a smaller RBW = 100 kHz is used, worst-case integrated BW power = [Max Measured Value (dBm) with RBW = 100 kHz] + $10 \times \log(1000/100)$. To compensate for this integration before comparison to the value, the adjusted reference level offset was increase by 10 dB accordingly.
- h. Record the maximum power value test plot.


6.6 Radiated Spurious Emissions below 1GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

The EUT is configured to set data modulation and maximum power using WWAN technology.

- a. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following ANSI C63.26 section 5.5 and 5.2.7
- e. $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- f. $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.
2. The amplitude of spurious emissions in the range 9 kHz to 30 MHz which are attenuated more than 20 dB below the permissible value need not be reported.

6.7 Radiated Spurious Emissions above 1GHz

6.7.1 Test Setup

For radiated emission above 1 GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure


The EUT is configured to set data modulation and maximum power using WWAN technology.

- In the semi-anechoic chamber, EUT placed on the 1.5 m height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- Following ANSI C63.26 section 5.5 and 5.2.7
- $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.

6.8 Frequency Stability

6.8.1 Test Setup



6.8.2 Test Procedure

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology.

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

7 Test Results of Test Item

7.1 Maximum EIRP

Environmental Conditions:	23°C, 62% RH	Tested By:	Willy Cheng
---------------------------	--------------	------------	-------------

7.1.1 LTE Band 48

LTE Band 48, Channel Bandwidth: 5 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55265	CH 55990	CH 56715
			3552.5 MHz	3625 MHz	3697.5 MHz
QPSK	1	0	18.10	18.23	17.97
	1	12	17.51	17.68	17.42
	1	24	17.86	17.99	17.67
	12	0	17.56	17.67	17.37
	12	6	17.64	17.74	17.42
	12	13	17.59	17.69	17.36
	25	0	17.53	17.71	17.43
16QAM	1	0	17.23	17.38	17.11
	1	12	16.69	16.86	16.59
	1	24	17.10	17.25	16.96
	12	0	16.70	16.88	16.58
	12	6	16.74	16.91	16.66
	12	13	16.74	16.86	16.55
	25	0	16.75	16.94	16.60
64QAM	1	0	16.54	16.66	16.39
	1	12	15.98	16.11	15.81
	1	24	16.38	16.52	16.27
	12	0	15.95	16.12	15.87
	12	6	16.02	16.20	15.87
	12	13	16.07	16.16	15.83
	25	0	15.99	16.15	15.90
256QAM	1	0	15.10	15.30	15.05
	1	12	14.76	14.85	14.60
	1	24	15.08	15.26	15.00
	12	0	14.74	14.83	14.56
	12	6	14.76	14.86	14.57
	12	13	14.75	14.90	14.59
	25	0	14.70	14.88	14.55

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	17.36	18.23	20.06	20.93	23
16QAM	16.55	17.38	19.25	20.08	23
64QAM	15.81	16.66	18.51	19.36	23
256QAM	14.55	15.3	17.25	18	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48, Channel Bandwidth: 10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55290	CH 55990	CH 56690
			3555 MHz	3625 MHz	3695 MHz
QPSK	1	0	18.23	18.33	18.05
	1	24	17.59	17.73	17.38
	1	49	18.03	18.15	17.82
	25	0	17.66	17.80	17.51
	25	12	17.77	17.88	17.58
	25	25	17.74	17.84	17.52
	50	0	17.63	17.74	17.45
16QAM	1	0	17.32	17.50	17.26
	1	24	16.81	16.95	16.65
	1	49	17.19	17.32	17.07
	25	0	16.85	17.03	16.75
	25	12	16.89	17.07	16.80
	25	25	16.88	17.00	16.68
	50	0	16.97	17.07	16.80
64QAM	1	0	16.55	16.71	16.40
	1	24	16.03	16.15	15.85
	1	49	16.55	16.67	16.38
	25	0	16.05	16.21	15.93
	25	12	16.11	16.24	15.93
	25	25	16.03	16.19	15.84
	50	0	16.12	16.30	16.01
256QAM	1	0	15.33	15.44	15.12
	1	24	14.81	14.92	14.58
	1	49	15.19	15.36	15.08
	25	0	14.81	14.91	14.56
	25	12	14.78	14.97	14.64
	25	25	14.76	14.92	14.66
	50	0	14.87	14.98	14.71

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	17.38	18.33	20.08	21.03	23
16QAM	16.65	17.5	19.35	20.2	23
64QAM	15.84	16.71	18.54	19.41	23
256QAM	14.56	15.44	17.26	18.14	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48, Channel Bandwidth: 15 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55315	CH 55990	CH 56665
			3557.5 MHz	3625 MHz	3692.5 MHz
QPSK	1	0	18.25	18.39	18.13
	1	37	17.69	17.87	17.59
	1	74	18.16	18.26	17.94
	36	0	17.75	17.89	17.59
	36	19	17.81	17.94	17.61
	36	39	17.78	17.92	17.61
	75	0	17.77	17.92	17.66
16QAM	1	0	17.43	17.61	17.30
	1	37	16.88	17.06	16.79
	1	74	17.24	17.42	17.15
	36	0	16.96	17.11	16.83
	36	19	17.05	17.17	16.91
	36	39	16.89	17.09	16.82
	75	0	17.05	17.15	16.83
64QAM	1	0	16.72	16.84	16.54
	1	37	16.09	16.27	15.95
	1	74	16.61	16.74	16.41
	36	0	16.25	16.38	16.13
	36	19	16.20	16.39	16.13
	36	39	16.23	16.34	16.03
	75	0	16.32	16.44	16.09
256QAM	1	0	15.44	15.57	15.32
	1	37	14.91	15.06	14.78
	1	74	15.33	15.42	15.14
	36	0	14.82	15.01	14.67
	36	19	14.94	15.14	14.87
	36	39	14.86	15.02	14.71
	75	0	14.88	15.02	14.76

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	17.59	18.39	20.29	21.09	23
16QAM	16.79	17.61	19.49	20.31	23
64QAM	15.95	16.84	18.65	19.54	23
256QAM	14.67	15.57	17.37	18.27	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48, Channel Bandwidth: 20 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55340	CH 55990	CH 56640
			3560 MHz	3625 MHz	3690 MHz
QPSK	1	0	18.36	18.52	18.26
	1	50	17.75	17.96	17.61
	1	99	18.13	18.33	17.98
	50	0	17.81	18.01	17.67
	50	25	17.89	18.09	17.74
	50	50	17.84	18.02	17.75
	100	0	17.86	18.00	17.73
16QAM	1	0	17.55	17.72	17.41
	1	50	16.97	17.17	16.82
	1	99	17.37	17.57	17.20
	50	0	16.99	17.23	16.86
	50	25	17.10	17.26	16.91
	50	50	17.00	17.20	16.86
	100	0	17.04	17.25	16.96
64QAM	1	0	16.81	16.98	16.65
	1	50	16.22	16.40	16.07
	1	99	16.63	16.85	16.57
	50	0	16.28	16.46	16.12
	50	25	16.34	16.49	16.14
	50	50	16.27	16.45	16.09
	100	0	16.31	16.51	16.19
256QAM	1	0	15.48	15.65	15.29
	1	50	14.98	15.14	14.82
	1	99	15.40	15.54	15.17
	50	0	14.94	15.18	14.89
	50	25	15.01	15.20	14.93
	50	50	14.96	15.19	14.86
	100	0	15.01	15.16	14.88

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	17.61	18.52	20.31	21.22	23
16QAM	16.82	17.72	19.52	20.42	23
64QAM	16.07	16.98	18.77	19.68	23
256QAM	14.82	15.65	17.52	18.35	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48, Channel Bandwidth: 15 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55315	CH 55990	CH 56665
			3557.5 MHz	3625 MHz	3692.5 MHz
QPSK	1	0	18.16	18.37	18.07
	1	37	17.60	17.84	17.51
	1	74	18.10	18.24	17.93
	36	0	17.71	17.86	17.57
	36	19	17.78	17.85	17.55
	36	39	17.75	17.91	17.56
	75	0	16.18	16.39	16.11
16QAM	1	0	17.38	17.59	17.26
	1	37	16.84	16.98	16.74
	1	74	17.23	17.38	17.11
	36	0	16.92	17.09	16.82
	36	19	16.96	17.13	16.81
	36	39	16.82	17.00	16.76
	75	0	15.46	15.57	15.29
64QAM	1	0	16.66	16.77	16.51
	1	37	16.04	16.21	15.87
	1	74	16.59	16.66	16.34
	36	0	16.16	16.36	16.04
	36	19	16.18	16.35	16.10
	36	39	16.13	16.30	16.00
	75	0	14.81	14.93	14.56
256QAM	1	0	15.34	15.54	15.30
	1	37	14.87	15.00	14.73
	1	74	15.25	15.33	15.11
	36	0	14.81	14.98	14.62
	36	19	14.93	15.13	14.80
	36	39	14.77	14.97	14.63
	75	0	13.33	13.43	13.17

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	16.11	18.37	18.81	21.07	23.00
16QAM	15.29	17.59	17.99	20.29	23.00
64QAM	14.56	16.77	17.26	19.47	23.00
256QAM	13.17	15.54	15.87	18.24	23.00

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48, Channel Bandwidth: 20 MHz, Output Power: dBm/10 MHz


Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55340	CH 55990	CH 56640
			3560 MHz	3625 MHz	3690 MHz
QPSK	1	0	18.28	18.51	18.24
	1	50	17.65	17.94	17.54
	1	99	18.07	18.23	17.88
	50	0	17.74	17.97	17.57
	50	25	17.87	18.06	17.65
	50	50	17.74	17.99	17.69
	100	0	15.27	15.46	15.18
16QAM	1	0	17.47	17.71	17.34
	1	50	16.95	17.12	16.77
	1	99	17.35	17.50	17.10
	50	0	16.89	17.13	16.78
	50	25	17.04	17.19	16.82
	50	50	16.98	17.18	16.83
	100	0	14.48	14.73	14.40
64QAM	1	0	16.78	16.90	16.64
	1	50	16.12	16.35	16.00
	1	99	16.58	16.76	16.54
	50	0	16.20	16.42	16.10
	50	25	16.29	16.40	16.13
	50	50	16.26	16.43	16.04
	100	0	13.73	13.92	13.69
256QAM	1	0	15.38	15.64	15.20
	1	50	14.91	15.13	14.81
	1	99	15.33	15.48	15.10
	50	0	14.87	15.09	14.86
	50	25	14.96	15.17	14.89
	50	50	14.93	15.09	14.85
	100	0	12.50	12.59	12.33

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	15.18	18.51	17.88	21.21	23.00
16QAM	14.4	17.71	17.1	20.41	23.00
64QAM	13.69	16.9	16.39	19.6	23.00
256QAM	12.33	15.64	15.03	18.34	23.00

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

Spectrum Plot of Worst Value







Note: For the channel bandwidth is less than or equal to 10 MHz, the full power test data please refer to the power per 10 MHz corresponding to the channel bandwidth.

7.2 Modulation Characteristics

Environmental Conditions:	25°C, 68% RH	Tested By:	Noah Chang
---------------------------	--------------	------------	------------

7.2.1 LTE Band 48

LTE Band 48, Channel Bandwidth: 20 MHz

FundamentalConstellation 0 Symbol I 0.7138 Q 0.6998 Meas. Count : 1/ 1  Q I <table><tr><td>EVM</td><td>Avg. 2.50</td><td>Max. 2.50</td><td>Min. 2.50 %(rms)</td><td>Limit ≤ 17.5 %(rms)</td></tr><tr><td>Peak Vector Error</td><td>30.69</td><td>30.69</td><td>30.69 %</td><td></td></tr><tr><td>Carrier Leakage</td><td>-62.27</td><td>-62.27</td><td>-62.27 dBc</td><td></td></tr><tr><td>IQ Imbalance</td><td>100.64</td><td>100.64</td><td>100.64 %(I/Q)</td><td></td></tr></table>	EVM	Avg. 2.50	Max. 2.50	Min. 2.50 %(rms)	Limit ≤ 17.5 %(rms)	Peak Vector Error	30.69	30.69	30.69 %		Carrier Leakage	-62.27	-62.27	-62.27 dBc		IQ Imbalance	100.64	100.64	100.64 %(I/Q)		FundamentalConstellation 0 Symbol I -0.3142 Q -0.9486 Meas. Count : 1/ 1  Q I <table><tr><td>EVM</td><td>Avg. 1.90</td><td>Max. 1.90</td><td>Min. 1.90 %(rms)</td><td>Limit ≤ 12.5 %(rms)</td></tr><tr><td>Peak Vector Error</td><td>25.66</td><td>25.66</td><td>25.66 %</td><td></td></tr><tr><td>Carrier Leakage</td><td>-59.05</td><td>-59.05</td><td>-59.05 dBc</td><td></td></tr><tr><td>IQ Imbalance</td><td>100.65</td><td>100.65</td><td>100.65 %(I/Q)</td><td></td></tr></table>	EVM	Avg. 1.90	Max. 1.90	Min. 1.90 %(rms)	Limit ≤ 12.5 %(rms)	Peak Vector Error	25.66	25.66	25.66 %		Carrier Leakage	-59.05	-59.05	-59.05 dBc		IQ Imbalance	100.65	100.65	100.65 %(I/Q)	
EVM	Avg. 2.50	Max. 2.50	Min. 2.50 %(rms)	Limit ≤ 17.5 %(rms)																																					
Peak Vector Error	30.69	30.69	30.69 %																																						
Carrier Leakage	-62.27	-62.27	-62.27 dBc																																						
IQ Imbalance	100.64	100.64	100.64 %(I/Q)																																						
EVM	Avg. 1.90	Max. 1.90	Min. 1.90 %(rms)	Limit ≤ 12.5 %(rms)																																					
Peak Vector Error	25.66	25.66	25.66 %																																						
Carrier Leakage	-59.05	-59.05	-59.05 dBc																																						
IQ Imbalance	100.65	100.65	100.65 %(I/Q)																																						
QPSK CH 55990 (3625 MHz)	16QAM CH 55990 (3625 MHz)																																								
FundamentalConstellation 0 Symbol I -0.4515 Q 0.4629 Meas. Count : 1/ 1  Q I <table><tr><td>EVM</td><td>Avg. 1.13</td><td>Max. 1.13</td><td>Min. 1.13 %(rms)</td><td>Limit ≤ 8.0 %(rms)</td></tr><tr><td>Peak Vector Error</td><td>17.14</td><td>17.14</td><td>17.14 %</td><td></td></tr><tr><td>Carrier Leakage</td><td>-58.97</td><td>-58.97</td><td>-58.97 dBc</td><td></td></tr><tr><td>IQ Imbalance</td><td>100.59</td><td>100.59</td><td>100.59 %(I/Q)</td><td></td></tr></table>	EVM	Avg. 1.13	Max. 1.13	Min. 1.13 %(rms)	Limit ≤ 8.0 %(rms)	Peak Vector Error	17.14	17.14	17.14 %		Carrier Leakage	-58.97	-58.97	-58.97 dBc		IQ Imbalance	100.59	100.59	100.59 %(I/Q)		FundamentalConstellation 0 Symbol I 0.2318 Q -0.5244 Meas. Count : 1/ 1  Q I <table><tr><td>EVM</td><td>Avg. 0.96</td><td>Max. 0.96</td><td>Min. 0.96 %(rms)</td><td>Limit</td></tr><tr><td>Peak Vector Error</td><td>8.78</td><td>8.78</td><td>8.78 %</td><td></td></tr><tr><td>Carrier Leakage</td><td>-57.04</td><td>-57.04</td><td>-57.04 dBc</td><td></td></tr><tr><td>IQ Imbalance</td><td>100.63</td><td>100.63</td><td>100.63 %(I/Q)</td><td></td></tr></table>	EVM	Avg. 0.96	Max. 0.96	Min. 0.96 %(rms)	Limit	Peak Vector Error	8.78	8.78	8.78 %		Carrier Leakage	-57.04	-57.04	-57.04 dBc		IQ Imbalance	100.63	100.63	100.63 %(I/Q)	
EVM	Avg. 1.13	Max. 1.13	Min. 1.13 %(rms)	Limit ≤ 8.0 %(rms)																																					
Peak Vector Error	17.14	17.14	17.14 %																																						
Carrier Leakage	-58.97	-58.97	-58.97 dBc																																						
IQ Imbalance	100.59	100.59	100.59 %(I/Q)																																						
EVM	Avg. 0.96	Max. 0.96	Min. 0.96 %(rms)	Limit																																					
Peak Vector Error	8.78	8.78	8.78 %																																						
Carrier Leakage	-57.04	-57.04	-57.04 dBc																																						
IQ Imbalance	100.63	100.63	100.63 %(I/Q)																																						
64QAM CH 55990 (3625 MHz)	256QAM CH 55990 (3625 MHz)																																								


7.3 Peak to Average Ratio

Environmental Conditions:	25°C, 68% RH	Tested By:	Noah Chang
---------------------------	--------------	------------	------------

7.3.1 LTE Band 48

LTE Band 48, Channel Bandwidth: 20 MHz

Modulation	Channel	Frequency (MHz)	Measurement Value(dB)	Limit (dB)	Result
QPSK	55340	3560	8.04	13	PASS
QPSK	55990	3625	6.44	13	PASS
QPSK	56640	3690	6.60	13	PASS
16QAM	55340	3560	7.64	13	PASS
16QAM	55990	3625	7.75	13	PASS
16QAM	56640	3690	9.15	13	PASS
64QAM	55340	3560	9.77	13	PASS
64QAM	55990	3625	8.64	13	PASS
64QAM	56640	3690	9.91	13	PASS
256QAM	55340	3560	10.25	13	PASS
256QAM	55990	3625	10.47	13	PASS
256QAM	56640	3690	10.33	13	PASS




7.4 Bandwidth

Environmental Conditions:	25°C, 68% RH	Tested By:	Noah Chang
---------------------------	--------------	------------	------------

7.4.1 LTE Band 48

LTE Band 48, Channel Bandwidth: 5 MHz


Modulation	Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	55265	3552.5	4.4987	4.880
QPSK	55990	3625	4.4936	4.914
QPSK	56715	3697.5	4.4942	4.862
16QAM	55265	3552.5	4.4971	4.934
16QAM	55990	3625	4.4872	4.825
16QAM	56715	3697.5	4.4925	4.840
64QAM	55265	3552.5	4.4998	4.897
64QAM	55990	3625	4.4933	4.870
64QAM	56715	3697.5	4.4932	4.872
256QAM	55265	3552.5	4.4929	4.886
256QAM	55990	3625	4.4894	4.801
256QAM	56715	3697.5	4.4896	4.820



LTE Band 48, Channel Bandwidth: 10 MHz


Modulation	Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	55290	3555	8.9758	9.566
QPSK	55990	3625	8.9679	9.548
QPSK	56690	3695	8.9748	9.540
16QAM	55290	3555	8.9744	9.538
16QAM	55990	3625	8.9637	9.545
16QAM	56690	3695	8.9732	9.575
64QAM	55290	3555	8.9702	9.543
64QAM	55990	3625	8.9637	9.513
64QAM	56690	3695	8.9705	9.520
256QAM	55290	3555	8.9793	9.548
256QAM	55990	3625	8.9790	9.492
256QAM	56690	3695	8.9831	9.567

Spectrum Plot of Worst Value



LTE Band 48, Channel Bandwidth: 15 MHz


Modulation	Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	55315	3557.5	13.4635	14.286
QPSK	55990	3625	13.4780	14.304
QPSK	56665	3692.5	13.4600	14.292
16QAM	55315	3557.5	13.4778	14.268
16QAM	55990	3625	13.4605	14.253
16QAM	56665	3692.5	13.4677	14.278
64QAM	55315	3557.5	13.4638	14.254
64QAM	55990	3625	13.4575	14.269
64QAM	56665	3692.5	13.4597	14.257
256QAM	55315	3557.5	13.4656	14.233
256QAM	55990	3625	13.4522	14.218
256QAM	56665	3692.5	13.4475	14.270



LTE Band 48, Channel Bandwidth: 20 MHz

Modulation	Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	55340	3560	17.9630	19.053
QPSK	55990	3625	17.9586	19.038
QPSK	56640	3690	17.9605	19.073
16QAM	55340	3560	17.9722	19.082
16QAM	55990	3625	17.9604	19.062
16QAM	56640	3690	17.9643	19.070
64QAM	55340	3560	17.9692	19.042
64QAM	55990	3625	17.9481	19.056
64QAM	56640	3690	17.9571	19.048
256QAM	55340	3560	17.9673	19.040
256QAM	55990	3625	17.9385	19.026
256QAM	56640	3690	17.9526	19.025

Spectrum Plot of Worst Value





7.5 Conducted Spurious Emissions

Environmental Conditions:	25°C, 68% RH	Tested By:	Noah Chang
---------------------------	--------------	------------	------------


7.5.1 LTE Band 48

LTE Band 48, Channel Bandwidth: 5 MHz





[RBW = 510 kHz / Reference RBW = 1 MHz]
Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=510kHz] + 10log(1000/510)
To compensate for this integration before comparison to the limit, 2.92 dB was added to Ref Lvl Offset.
i.e. 15.00 dB CF + 2.92 dB integration compensation factor = 17.92 dB Ref Lvl Offset




1RB#MAX CH 56715 (3697.5 MHz)

[RBW = 510 kHz / Reference RBW = 1 MHz]

Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=510kHz] + 10log(1000/510)

To compensate for this integration before comparison to the limit, 2.92 dB was added to Ref Lvl Offset.


i.e. 15.00 dB CF + 2.92 dB integration compensation factor = 17.92 dB Ref Lvl Offset



[RBW = 510 kHz / Reference RBW = 1 MHz]

Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=510kHz] + 10log(1000/510)
To compensate for this integration before comparison to the limit, 2.92 dB was added to Ref Lvl Offset.

i.e. 15.00 dB CF + 2.92 dB integration compensation factor = 17.92 dB Ref Lvl Offset




[RBW = 510 kHz / Reference RBW = 1 MHz]


Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=510kHz] + 10log(1000/510)

To compensate for this integration before comparison to the limit, 2.92 dB was added to Ref Lvl Offset.


i.e. 15.00 dB CF + 2.92 dB integration compensation factor = 17.92 dB Ref Lvl Offset

LTE Band 48, Channel Bandwidth: 10 MHz





1RB#MAX CH 55290 (3555 MHz)




1RB#MAX CH 55990 (3625 MHz)

[RBW = 910 kHz / Reference RBW = 1 MHz]

Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=910kHz] + 10log(1000/910)

To compensate for this integration before comparison to the limit, 0.41 dB was added to Ref Lvl Offset.

i.e. 15.00 dB CF + 0.41 dB integration compensation factor = 15.41 dB Ref Lvl Offset




1RB#MAX CH 56690 (3695 MHz)

[RBW = 910 kHz / Reference RBW = 1 MHz]


Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=910kHz] + 10log(1000/910)

To compensate for this integration before comparison to the limit, 0.41 dB was added to Ref Lvl Offset.

i.e. 15.00 dB CF + 0.41 dB integration compensation factor = 15.41 dB Ref Lvl Offset



[RBW = 910 kHz / Reference RBW = 1 MHz]
Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=910kHz] + 10log(1000/910)
To compensate for this integration before comparison to the limit, 0.41 dB was added to Ref Lvl Offset.
i.e. 15.00 dB CF + 0.41 dB integration compensation factor = 15.41 dB Ref Lvl Offset



1RB#0 CH 56690 (3695 MHz)


[RBW = 910 kHz / Reference RBW = 1 MHz]

Worst-case integrated BW power = [Max Measured Value (dBm) with RBW=910kHz] + 10log(1000/910)

To compensate for this integration before comparison to the limit, 0.41 dB was added to Ref Lvl Offset.


i.e. 15.00 dB CF + 0.41 dB integration compensation factor = 15.41 dB Ref Lvl Offset

LTE Band 48, Channel Bandwidth: 15 MHz







1RB#MAX CH 55315 (3557.5 MHz)




1RB#MAX CH 55990 (3625 MHz)




1RB#MAX CH 56665 (3692.5 MHz)



1RB#0 CH 55315 (3557.5 MHz)





1RB#0 CH 55990 (3625 MHz)




1RB#0 CH 56665 (3692.5 MHz)

LTE Band 48, Channel Bandwidth: 20 MHz







Note: The signal at 9 kHz is IF signal from spectrum analyzer.