

DATE: 07 September 2003

I.T.L. (PRODUCT TESTING) LTD.

EMC Test

for

Nexus Data (1993) Ltd.

Equipment under test:

Water Meter Transmitter

WMIN01

Approved by: _____

I. Raz, EMC Laboratory Manager

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.

Radiated Emission

E.U.T Description Water Meter Transmitter
 Type WMIN01
 Serial Number: Not designated

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal Frequency range: 300 MHz to 1 GHz
 Test Distance: 3 meters Detector: Peak, Quasi-peak
 Operating Frequency: 904.6 MHz

Frequency (MHz)	Peak Amp (dBμV/m)	QP Amp (dBμV/m)	Correction (dB)	Specification (dBμV/m)	Margin (dB μV/m)
329.99	30.5	27.6	15.9	46.0	-18.4
409.02	26.8	19.6	18.6	46.0	-28.4
612.72	32.3	24.2	22.5	46.0	-21.8
964.54	39.5	32.0	28.3	54.0	-22.0

**Figure 1. Radiated Emission. Antenna Polarization: HORIZONTAL.
 Detector: Peak, Quasi-peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.