

# **TIMCO**ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)



## Test Report

Product Name: RC TOY TRANSMITTER

FCC ID: NLB27007TX

Applicant:

**DICKIE-SPIELZEUG GmbH & CO KG  
WERKSTRASSE 1  
D-90765 FUERTH D-90765  
GERMANY**

**Date Receipt: JUNE 23, 2003**

**Date Tested: JUNE 27, 2003**

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG  
FCC ID: NLB27007TX  
REPORT #: D\DICKIE\872GT3\872GT3TestReport.doc

COVER SHEET

# **TIMCO**ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

## **TABLE OF CONTENTS LIST**

**APPLICANT:** DICKIE-SPIELZEUG GmbH & CO KG

**FCC ID:** NLB27007TX

### **TEST REPORT CONTAINING:**

PAGE 1-4.....TEST EQUIPMENT LIST  
PAGE 5.....TEST PROCEDURE  
PAGE 6.....RADIATION INTERFERENCE TEST DATA  
PAGE 7.....OCCUPIED BANDWIDTH  
PAGE 8.....OCCUPIED BANDWIDTH PLOT

### **EXHIBITS CONTAINING:**

EXHIBIT 1.....BLOCK DIAGRAM  
EXHIBIT 2.....SCHEMATIC  
EXHIBIT 3.....INSTRUCTION MANUAL  
EXHIBIT 4.....SAMPLE OF FCC ID LABEL  
EXHIBIT 5.....LOCATION OF FCC ID LABEL  
EXHIBIT 6.....EXTERNAL PHOTOGRAPHS  
EXHIBIT 7.....INTERNAL PHOTOGRAPHS  
EXHIBIT 8.....CIRCUIT DESCRIPTION  
EXHIBIT 9.....TEST SET UP PHOTOGRAPH

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG  
FCC ID: NLB27007TX  
REPORT #: D\DICKIE\872GT3\872GT3TestReport.doc

TABLE OF CONTENTS

# TIMCO ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

## EMC Equipment List

Last Update: 6/27/03

|   | DEVICE                                           | MFGR            | MODEL         | SERNO                    | CAL/CHAR<br>DATE  | DUE DATE<br>or STATUS |
|---|--------------------------------------------------|-----------------|---------------|--------------------------|-------------------|-----------------------|
| X | 3-Meter<br>OATS                                  | TEI             | N/A           | N/A                      | Listed<br>1/13/03 | 1/13/06               |
|   | 3/10-Meter<br>OATS                               | TEI             | N/A           | N/A                      | Listed<br>3/26/01 | 3/26/04               |
|   | Receiver, Beige Tower<br>Spectrum Analyzer       | HP              | 8566B Opt 462 | 3138A07786<br>3144A20661 | CAL<br>8/31/01    | 8/31/03               |
|   | RF Preselector                                   | HP              | 85685A        | 3221A01400               | CAL<br>8/31/01    | 8/31/03               |
|   | Quasi-Peak Adapter                               | HP              | 85650A        | 3303A01690               | CAL<br>8/31/01    | 8/31/03               |
|   | Preamplifier                                     | HP              | 8449B-H02     | 3008A00372               | CHAR<br>3/4/01    | 3/4/03                |
|   | Receiver, Blue Tower<br>Spectrum Analyzer        | HP              | 8568B         | 2928A04729<br>2848A18049 | CAL<br>4/15/03    | 4/15/05               |
|   | RF Preselector                                   | HP              | 85685A        | 2926A00983               | CAL<br>4/15/03    | 4/15/05               |
|   | Quasi-Peak Adapter                               | HP              | 85650A        | 2811A01279               | CAL<br>4/15/03    | 4/15/05               |
| X | Receiver, Silver/Grey Tower<br>Spectrum Analyzer | HP              | 8566B Opt 462 | 3552A22064<br>3638A08608 | CAL<br>10/14/02   | 10/14/04              |
|   | RF Preselector                                   | HP              | 85685A        | 2620A00294               | CAL<br>10/14/02   | 10/14/04              |
|   | Quasi-Peak Adapter                               | HP              | 85650A        | 3303A01844               | CAL<br>10/14/02   | 10/14/04              |
|   | Preamplifier                                     | HP              | 8449B         | 3008A01075               | CHAR<br>1/28/02   | 1/28/04               |
|   | Biconnical Antenna                               | Electro-Metrics | BIA-25        | 1171                     | CAL<br>4/26/01    | 4/26/03               |
| X | Biconnical Antenna                               | Eaton           | 94455-1       | 1096                     | CAL<br>10/1/01    | 10/1/03               |
|   | Biconnical Antenna                               | Eaton           | 94455-1       | 1057                     | CAL<br>3/18/03    | 3/18/05               |
|   | BiconiLog Antenna                                | EMCO            | 3143          | 9409-1043                |                   |                       |
|   | Log-Periodic<br>Antenna                          | Electro-Metrics | LPA-25        | 1122                     | CAL<br>10/2/01    | 10/2/03               |

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG

FCC ID: NLB27007TX

REPORT #: D:\DICKIE\872GT3\872GT3TestReport.doc

# TIMCO ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

|   | DEVICE                                | MFGR                           | MODEL      | SERNO      | CAL/CHAR<br>DATE   | DUE DATE<br>or STATUS |
|---|---------------------------------------|--------------------------------|------------|------------|--------------------|-----------------------|
|   | Log-Periodic<br>Antenna               | Electro-Metrics                | EM-6950    | 632        | CHAR<br>10/15/01   | 10/15/03              |
| X | Log-Periodic<br>Antenna               | Electro-Metrics                | LPA-30     | 409        | CAL<br>3/4/03      | 3/4/05                |
|   | Log-Periodic<br>Antenna               | Eaton                          | 96005      | 1243       | CAL<br>5/8/03      | 5/8/05                |
|   | Dipole Antenna<br>Kit                 | Electro-Metrics                | TDA-30/1-4 | 152        | CAL<br>3/21/01     | 3/21/04               |
|   | Dipole Antenna<br>Kit                 | Electro-Metrics                | TDA-30/1-4 | 153        | CAL<br>9/26/02     | 9/26/05               |
|   | Double-Ridged Horn<br>Antenna         | Electro-Metrics                | RGA -180   | 2319       | CAL<br>2/17/03     | 2/17/05               |
|   | Horn Antenna<br>*(at 3 meters)        | Electro-Metrics                | EM-6961    | 6246       | CAL<br>3/31/03     | 3/31/05               |
|   | Horn Antenna<br>*(at 10 meters)       | Electro-Metrics                | EM-6961    | 6246       | CAL<br>6/4/03      | 6/4/05                |
|   | Horn Antenna                          | ATM                            | 19-443-6R  | None       | No Cal<br>Required |                       |
|   | Passive Loop Antenna                  | EMC Test Systems               | EMCO 6512  | 9706-1211  | CHAR<br>7/10/01    | 7/10/03               |
|   | Harmonic Mixer<br>with Horn Antenna   | Oleson Microwave<br>Labs       | M08HW/A    | F30425-1   | CHAR<br>4/25/03    | 4/25/05               |
|   | Harmonic Mixer<br>with Horn Antenna   | Oleson Microwave<br>Labs       | M12HW/A    | E30425-1   | CHAR<br>4/25/03    | 4/25/05               |
|   | Line Impedance<br>Stabilization . . . | Electro-Metrics                | ANS-25/2   | 2604       | CAL<br>10/9/01     | 10/9/03               |
|   | Line Impedance Stabilization<br>. . . | Electro-Metrics                | EM-7820    | 2682       | CAL<br>3/12/03     | 3/12/05               |
|   | Termaline Wattmeter                   | Bird Electronic<br>Corporation | 611        | 16405      | CAL<br>5/25/99     | 5/25/01               |
|   | Termaline Wattmeter                   | Bird Electronic<br>Corporation | 6104       | 1926       | CHAR<br>12/12/01   | 12/12/03              |
|   | Oscilloscope                          | Tektronix                      | 2230       | 300572     | CHAR<br>2/1/01     | 2/1/03                |
|   | System One                            | Audio Precision                | System One | SYS1-45868 | CHAR<br>4/25/02    | 4/25/04               |
|   | Temperature Chamber                   | Tenney<br>Engineering          | TTRC       | 11717-7    | CHAR<br>1/22/02    | 1/22/04               |
|   | AC Voltmeter                          | HP                             | 400FL      | 2213A14499 | CAL<br>10/9/01     | 10/9/03               |
|   | AC Voltmeter                          | HP                             | 400FL      | 2213A14261 | CHAR<br>10/15/01   | 10/15/03              |
|   | AC Voltmeter                          | HP                             | 400FL      | 2213A14728 | CHAR<br>10/15/01   | 10/15/03              |

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG  
FCC ID: NLB27007TX  
REPORT #: D\ \DICKIE\872GT3\872GT3TestReport.doc

# TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

|  | DEVICE                    | MFGR                    | MODEL            | SERNO        | CAL/CHAR<br>DATE | DUE DATE<br>or STATUS |
|--|---------------------------|-------------------------|------------------|--------------|------------------|-----------------------|
|  | Digital Multimeter        | Fluke                   | 77               | 35053830     | CHAR<br>1/8/02   | 1/8/04                |
|  | Digital Multimeter        | Fluke                   | 77               | 43850817     | CHAR<br>1/8/02   | 1/8/04                |
|  | Digital Multimeter        | HP                      | E2377A           | 2927J05849   | CHAR<br>1/8/02   | 1/8/04                |
|  | Multimeter                | Fluke                   | FLUKE-77-3       | 79510405     | CHAR<br>9/26/01  | 9/26/03               |
|  | Peak Power Meter          | HP                      | 8900C            | 2131A00545   | CHAR<br>1/26/01  | 1/26/03               |
|  | Power Meter               | HP                      | 432A             | 1141A07655   | CAL<br>4/15/03   | 4/15/05               |
|  | Power Meter<br>And Sensor | Bird                    | 4421-107<br>4022 | 0166<br>0218 | CAL<br>4/16/03   | 4/16/05               |
|  | Power Sensor              | HP                      | 478A             | 72129        | CAL<br>4/15/03   | 4/15/05               |
|  | Digital Thermometer       | Fluke                   | 2166A            | 42032        | CAL<br>1/16/02   | 1/16/04               |
|  | Thermometer               | Traulsen                | SK-128           |              | CHAR<br>1/22/02  | 1/22/04               |
|  | Thermometer               | Extech                  | 4028             | 14871-2      | CAL<br>3/7/03    | 3/7/05                |
|  | Hygro-Thermometer         | Extech                  | 445703           | 0602         | CAL<br>10/4/02   | 10/4/04               |
|  | Frequency Counter         | HP                      | 5352B            | 2632A00165   | CAL<br>11/28/01  | 11/28/03              |
|  | Frequency Counter         | HP                      | 5385A            | 2730A03025   | CAL<br>3/7/03    | 3/7/05                |
|  | Power Sensor              | Agilent<br>Technologies | 84811A           | 2551A02705   | CHAR<br>1/26/01  | 1/26/03               |
|  | Service Monitor           | IFR                     | FM/AM 500A       | 5182         | CAL<br>11/22/00  | 11/22/02              |
|  | Comm. Serv. Monitor       | IFR                     | FM/AM 1200S      | 6593         | CAL<br>5/12/02   | 5/12/04               |
|  | Signal Generator          | HP                      | 8640B            | 2308A21464   | CAL<br>2/15/02   | 2/15/04               |
|  | Sweep Generator           | Wiltron                 | 6648             | 101009       | CAL<br>4/15/03   | 4/15/05               |
|  | Sweep Generator           | Wiltron                 | 6669M            | 007005       | CAL<br>3/3/03    | 3/3/05                |
|  | Modulation Analyzer       | HP                      | 8901A            | 3435A06868   | CAL<br>9/5/01    | 9/5/03                |
|  | Modulation Meter          | Boonton                 | 8220             | 10901AB      | CAL<br>4/15/03   | 4/15/05               |

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG

FCC ID: NLB27007TX

REPORT #: D\Dickie\872GT3\872GT3TestReport.doc

# TIMCO ENGINEERING INC.

849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

|  | DEVICE               | MFGR                | MODEL                | SERNO      | CAL/CHAR<br>DATE | DUE DATE<br>or STATUS |
|--|----------------------|---------------------|----------------------|------------|------------------|-----------------------|
|  | Near Field Probe     | HP                  | HP11940A             | 2650A02748 | CHAR<br>2/1/01   | 2/1/03                |
|  | BandReject Filter    | Lorch Microwave     | 5BR4-2400/<br>60-N   | Z1         | CHAR<br>3/2/01   | 3/2/03                |
|  | BandReject Filter    | Lorch<br>Microwave  | 6BR6-2442/<br>300-N  | Z1         | CHAR<br>3/2/01   | 3/2/03                |
|  | BandReject Filter    | Lorch<br>Microwave  | 5BR4-10525/<br>900-S | Z1         | CHAR<br>3/2/01   | 3/2/03                |
|  | Notch Filter         | Lorch<br>Microwave  | 5BRX-850/<br>X100-N  | AD-1       | CHAR<br>4/17/03  | 4/17/05               |
|  |                      |                     |                      |            |                  |                       |
|  | High Pass Filter     | Microlab            | HA-10N               |            | CHAR<br>10/4/01  | 10/4/03               |
|  | High Pass Filter     | Microlab            | HA-20N               |            | CHAR<br>2/7/03   | 2/7/05                |
|  | Audio Oscillator     | HP                  | 653A                 | 832-00260  | CHAR<br>3/1/01   | 3/1/03                |
|  | Frequency Counter    | HP                  | 5382A                | 1620A03535 | CHAR<br>3/2/01   | 3/2/03                |
|  | Frequency Counter    | HP                  | 5385A                | 3242A07460 | CAL<br>3/7/03    | 3/7/05                |
|  | Amplifier            | HP                  | 11975A               | 2738A01969 | CHAR<br>3/1/01   | 3/1/03                |
|  | Egg Timer            | Unk                 |                      |            | CHAR<br>8/31/01  | 8/31/03               |
|  | Measuring Tape, 20M  | Kraftixx            | 0631-20              |            | CHAR<br>2/1/02   | 2/1/04                |
|  | Measuring Tape, 7.5M | Kraftixx            | 7.5M PROFI           |            | 2/1/02           | 2/1/04                |
|  | Coaxial Cable #51    | Insulated Wire Inc. | NPS 2251-2880        | Timco #51  | CHAR<br>1/23/02  | 1/23/04               |
|  | Coaxial Cable #64    | Semflex Inc.        | 60637                | Timco #64  | CHAR<br>1/24/02  | 1/24/04               |
|  | Coaxial Cable #65    | General Cable Co.   | E9917 RG233/U        | Timco #65  | CHAR<br>1/23/02  | 1/23/04               |
|  | Coaxial Cable #106   | Unknown             | Unknown              | Timco #106 | CHAR<br>1/23/02  | 1/23/04               |

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG

FCC ID: NLB27007TX

REPORT #: D:\DICKIE\872GT3\872GT3TestReport.doc

# TIMCO ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

## TEST PROCEDURE

**GENERAL:** This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

**RADIATION INTERFERENCE:** The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 80°C with a humidity of 76%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

**Example:**

Freq (MHz) METER READING + ACF = FS  
33            20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

**ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES:** The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

# TIMCO ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

**APPLICANT:** DICKIE-SPIELZEUG GmbH & CO KG

**FCC ID:** NLB27007TX

**NAME OF TEST:** RADIATION INTERFERENCE

**RULES PART NO.:** 15.227

**REQUIREMENTS:** CARRIER FREQUENCY WILL NOT EXCEEDS 80 dBuV/m AT 3M.  
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

|               |                                  |
|---------------|----------------------------------|
| 30 - 88 MHz   | 40.0 dBuV/M MEASURED AT 3 METERS |
| 88 - 216 MHz  | 43.5 dBuV/M                      |
| 216 - 960 MHz | 46.0 dBuV/m                      |
| ABOVE 960 MHz | 54.0 dBuV/m                      |

## TEST DATA:

| Emission<br>Frequency<br>MHz | Meter<br>Reading<br>dBuV | ANT.<br>POLARITY | Coax<br>Loss<br>dB | Correction<br>Factor<br>dB | Field<br>Strength<br>dBuV/m | Margin<br>dB |
|------------------------------|--------------------------|------------------|--------------------|----------------------------|-----------------------------|--------------|
| 27.10                        | 52.9                     | H                | 0.31               | 13.13                      | 66.34                       | 13.67        |
| 27.10                        | 65.4                     | V                | 0.31               | 13.13                      | 78.84                       | 1.16         |
| 54.22                        | 15.6                     | H                | 0.84               | 10.38                      | 26.82                       | 13.18        |
| 54.22                        | 19.6                     | V                | 0.84               | 10.38                      | 30.82                       | 9.18         |
| 81.35                        | 16.6                     | V                | 1.06               | 9.10                       | 26.76                       | 13.24        |
| 81.35                        | 19.7                     | H                | 1.06               | 9.10                       | 29.86                       | 10.14        |
| 108.58                       | 11.2                     | H                | 1.23               | 11.06                      | 23.49                       | 20.01        |
| 108.58                       | 12.4                     | V                | 1.23               | 11.06                      | 24.69                       | 18.81        |
| 135.62                       | 11.3                     | H                | 1.34               | 14.42                      | 27.06                       | 16.44        |
| 135.62                       | 24.7                     | V                | 1.34               | 14.42                      | 40.46                       | 3.04         |
| 162.74                       | 3.7                      | H                | 1.50               | 16.73                      | 21.93                       | 21.57        |
| 162.74                       | 11.1                     | V                | 1.50               | 16.73                      | 29.33                       | 14.17        |
| 189.89                       | 6.3                      | V                | 1.72               | 14.19                      | 22.21                       | 21.29        |
| 189.89                       | 6.9                      | H                | 1.72               | 14.19                      | 22.81                       | 20.69        |
| 217.00                       | 4.1                      | H                | 1.87               | 12.19                      | 18.16                       | 27.84        |
| 217.00                       | 7.3                      | V                | 1.87               | 12.19                      | 21.36                       | 24.64        |
| 244.10                       | 5.7                      | H                | 1.98               | 12.51                      | 20.19                       | 25.81        |
| 244.10                       | 5.9                      | V                | 1.98               | 12.51                      | 20.39                       | 25.61        |
| 271.24                       | 3.7                      | H                | 2.08               | 13.70                      | 19.48                       | 26.52        |
| 271.24                       | 4.3                      | V                | 2.08               | 13.70                      | 20.08                       | 25.92        |

SAMPLE CALCULATION: FSdBuV/m = MR (dBuV) + ACFdB.

**TEST PROCEDURE:** The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

**TEST RESULTS:** THE UNIT DOES MEET THE FCC REQUIREMENTS.

**PERFORMED BY:** NAM NGUYEN

**DATE:** JUNE 27, 2003

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG

FCC ID: NLB27007TX

REPORT #: D:\DICKIE\872GT3\872GT3TestReport.doc



# **TIMCO**ENGINEERING INC.

849 NW State Road 45  
Newberry, Florida 32669  
<http://www.timcoengr.com>  
888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

**APPLICANT:** DICKIE-SPIELZEUG GmbH & CO KG

**FCC ID:** NLB27007TX

**NAME OF TEST:** Occupied Bandwidth

**RULES PART NO.:** 15.227

**REQUIREMENTS:** The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated to the general limits of 15.209.

**THE GRAPH ON THE NEXT PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.**

**METHOD OF MEASUREMENT:** A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to 10 dB per division. The horizontal scale is set to 10 kHz per division.

**TEST RESULTS:** The unit DOES meet the FCC requirements.

**PERFORMED BY:** NAM NGUYEN

**DATE:** JUNE 27, 2003

APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG  
FCC ID: NLB27007TX  
REPORT #: D\Dickie\872GT3\872GT3TestReport.doc

# TIMCO ENGINEERING INC.


849 NW State Road 45

Newberry, Florida 32669

<http://www.timcoengr.com>

888.472.2424 F 352.472.2030 email: [sid@timcoengr.com](mailto:sid@timcoengr.com)

## OCCUPIED BANDWIDTH PLOT



APPLICANT: DICKIE-SPIELZEUG GmbH & CO KG

FCC ID: NLB27007TX

REPORT #: D\Dickie\872GT3\872GT3TestReport.doc