

RF exposure

According to FCC part 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Average time
(A) Limits for Occupational / Control Exposures				
300 – 1 500	--	--	f/300	6
1 500 - 100000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300 – 1 500	--	--	f/1500	6
1 500 – 100 000	--	--	1	30

f= frequency in MHz

Friis transmission formula: $P_d = (P_{out} \times G) / (4 \times \pi \times R^2)$

Where,

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Results - Worst case

- 2.4G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm²)	Limit (mW/cm²)
802.11b	SISO	16.00	2.92	0.02313	1
802.11g	SISO	15.00	2.92	0.01837	1
802.11n(HT20)	SISO	14.00	2.92	0.01459	1
802.11n(HT40)	SISO	14.00	2.92	0.01459	1

- 5.2G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm ²)	Limit (mW/cm ²)
802.11a	SISO	13.00	5.08	0.02017	1
802.11an(HT20)	SISO	10.00	5.08	0.01011	1
802.11an(HT40)	SISO	10.00	5.08	0.01011	1
802.11ac(VHT20)	SISO	10.00	5.08	0.01011	1
802.11ac(VHT40)	SISO	10.00	5.08	0.01011	1
802.11ac(VHT80)	SISO	9.00	5.08	0.00803	1

- 5.3G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm ²)	Limit (mW/cm ²)
802.11a	SISO	13.00	4.85	0.01925	1
802.11an(HT20)	SISO	10.00	4.85	0.00965	1
802.11an(HT40)	SISO	10.00	4.85	0.00965	1
802.11ac(VHT20)	SISO	10.00	4.85	0.00965	1
802.11ac(VHT40)	SISO	10.00	4.85	0.00965	1
802.11ac(VHT80)	SISO	9.00	4.85	0.00766	1

- 5.5G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm ²)	Limit (mW/cm ²)
802.11a	SISO	12.00	6.89	0.02172	1
802.11an(HT20)	SISO	9.00	6.89	0.01089	1
802.11an(HT40)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT20)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT40)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT80)	SISO	9.00	6.89	0.01089	1

- 5.8G

Operation mode		Max tune-up Average power (dBm)	Antenna gain (dBi)	Power density at 20 cm(mW/cm ²)	Limit (mW/cm ²)
802.11a	SISO	12.00	6.89	0.02172	1
802.11an(HT20)	SISO	9.00	6.89	0.01089	1
802.11an(HT40)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT20)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT40)	SISO	9.00	6.89	0.01089	1
802.11ac(VHT80)	SISO	9.00	6.89	0.01089	1