

FCC Test Report

(PART 27)

Report No.: RF150729C02-2

FCC ID: NM82PQ9120

Test Model: 2PQ9120

Received Date: Jul. 29, 2015

Test Date: Aug. 01, 2015 ~ Sep. 02, 2015

Issued Date: Sep. 16, 2015

Applicant: HTC Corporation

Address: 1F, 6-3 Baoqiang Road, Xindian City, Taipei County 231, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency.



A Q T

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	6
2.2 Test Site And Instruments	7
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System Under Test	9
3.2.1 Description of Support Units	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	14
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Output Power Measurement	15
4.1.1 Limits of Output Power Measurement	15
4.1.2 Test Procedures	15
4.1.3 Test Setup	16
4.1.4 Test Results	17
4.2 Frequency Stability Measurement	28
4.2.1 Limits of Frequency Stability Measurement	28
4.2.2 Test Procedure	28
4.2.3 Test Setup	28
4.2.4 Test Results	29
4.3 Occupied Bandwidth Measurement	31
4.3.1 Limits Of Occupied Bandwidth Measurement	31
4.3.2 Test Procedure	31
4.3.3 Test Setup	31
4.3.4 Test Result	31
4.4 Band Edge Measurement	37
4.4.1 Limits of Band Edge Measurement	37
4.4.2 Test Setup	37
4.4.3 Test Procedures	37
4.4.4 Test Results	38
4.5 Peak To Average Ratio	48
4.5.1 Limits of Peak To Average Ratio Measurement	48
4.5.2 Test Setup	48
4.5.3 Test Procedures	48
4.5.4 Test Results	48
4.6 Conducted Spurious Emissions	54
4.6.1 Limits of Conducted Spurious Emissions Measurement	54
4.6.2 Test Setup	54
4.6.3 Test Procedure	54
4.6.4 Test Results	55
4.7 Radiated Emission Measurement	57
4.7.1 Limits of Radiated Emission Measurement	57
4.7.2 Test Procedure	57
4.7.3 Deviation from Test Standard	57
4.7.4 Test Setup	57
4.7.5 Test Results	58
5 Pictures of Test Arrangements	64
Appendix – Information on the Testing Laboratories	65



A O T

Release Control Record

Issue No.	Description	Date Issued
RF150729C02-2	Original Release	Sep. 16, 2015

1 Certificate of Conformity

Product: Smartphone

Brand: HTC

Test Model: 2PQ9120

Sample Status: Identical Prototype

Applicant: HTC Corporation

Test Date: Aug. 01, 2015 ~ Sep. 02, 2015

Standards: FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Sep. 16, 2015

Ivonne Wu / Supervisor

Approved by :



Date:

Sep. 16, 2015

Kay Wu / Supervisor

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (WCDMA)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -33.05dB at 48.63MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -30.39dB at 32.43MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 12)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	PASS	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -37.02dB at 194.16MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.0153 dB
	200MHz ~1000MHz	2.0224 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.0121 dB
	18GHz ~ 40GHz	1.1508 dB

2.2 Test Site And Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Spectrum Analyzer Agilent Technologies	N9038A	MY52260177	May 19, 2015	May 18, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna ETS-Lindgren	3117	00143293	Jan. 05, 2015	Jan. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 29, 2015	Jun. 28, 2016
Preamplifier Agilent	83017A	MY39501357	Jun. 29, 2015	Jun. 28, 2016
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 27, 2015	Jun. 26, 2016
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 27, 2015	Jun. 26, 2016
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 149147.
5. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	Smartphone	
Brand	HTC	
Test Model	2PQ9120	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion battery)	
Modulation Type	WCDMA	QPSK, BPSK
	LTE	QPSK, 16QAM
Frequency Range	WCDMA	1712.4 ~1752.6MHz
	LTE Band 4 (Channel Bandwidth: 1.4MHz)	1710.7 ~1754.3MHz
	LTE Band 4 (Channel Bandwidth: 3MHz)	1711.5 ~1753.5MHz
	LTE Band 4 (Channel Bandwidth: 5MHz)	1712.5 ~1752.5MHz
	LTE Band 4 (Channel Bandwidth: 10MHz)	1715.0 ~1750.0MHz
	LTE Band 4 (Channel Bandwidth: 15MHz)	1717.5 ~1747.5MHz
	LTE Band 4 (Channel Bandwidth: 20MHz)	1720.0 ~1745.0MHz
	LTE Band 12 (Channel Bandwidth: 1.4MHz)	699.7 ~ 715.3MHz
	LTE Band 12 (Channel Bandwidth: 3MHz)	700.5 ~ 714.5MHz
	LTE Band 12 (Channel Bandwidth: 5MHz)	701.5 ~ 713.5MHz
	LTE Band 12 (Channel Bandwidth: 10MHz)	704.0 ~ 711.0MHz
Emission Designator	WCDMA	4M13F9W
	LTE Band 4 (Channel Bandwidth: 1.4MHz)	1M09G7D
	LTE Band 4 (Channel Bandwidth: 3MHz)	2M69W7D
	LTE Band 4 (Channel Bandwidth: 5MHz)	4M49G7D
	LTE Band 4 (Channel Bandwidth: 10MHz)	8M96G7D
	LTE Band 4 (Channel Bandwidth: 15MHz)	13M4W7D
	LTE Band 4 (Channel Bandwidth: 20MHz)	17M9W7D
	LTE Band 12 (Channel Bandwidth: 1.4MHz)	1M09G7D
	LTE Band 12 (Channel Bandwidth: 3MHz)	2M70G7D
	LTE Band 12 (Channel Bandwidth: 5MHz)	4M49G7D
	LTE Band 12 (Channel Bandwidth: 10MHz)	8M99W7D
Max. ERP Power	LTE Band 12 (Channel Bandwidth: 1.4MHz)	49.79mW
	LTE Band 12 (Channel Bandwidth: 3MHz)	47.65mW
	LTE Band 12 (Channel Bandwidth: 5MHz)	47.87mW
	LTE Band 12 (Channel Bandwidth: 10MHz)	48.07mW
Max. EIRP Power	WCDMA	231.47mW
	LTE Band 4 (Channel Bandwidth: 1.4MHz)	205.59mW
	LTE Band 4 (Channel Bandwidth: 3MHz)	209.89mW
	LTE Band 4 (Channel Bandwidth: 5MHz)	186.85mW
	LTE Band 4 (Channel Bandwidth: 10MHz)	184.29mW
	LTE Band 4 (Channel Bandwidth: 15MHz)	173.58mW
	LTE Band 4 (Channel Bandwidth: 20MHz)	190.41mW


Antenna Type	Fixed Internal Antenna
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:


1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System Under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP / EIRP	Radiated Emission
WCDMA	X-plane	Y-axis
LTE Band 4	Y-plane	Y-axis
LTE Band 12	X-plane	X-axis

WCDMA MODE

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
-	Frequency Stability	1312 to 1513	1413	WCDMA
-	Occupied Bandwidth	1312 to 1513	1312, 1413, 1513	WCDMA
-	Band Edge	1312 to 1513	1312, 1513	WCDMA
-	Peak to Average Ratio	1312 to 1513	1312, 1413, 1513	WCDMA
-	Conducuted Emission	1312 to 1513	1413	WCDMA
-	Radiated Emission	1312 to 1513	1413	WCDMA

LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	19957 to 20393	19957	1.4MHz	QPSK	1 RB / 0 RB Offset
			20393	1.4MHz	QPSK	6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK	1 RB / 5 RB Offset
			20385	3MHz	QPSK	6 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK	1 RB / 0 RB Offset
			20375	5MHz	QPSK	15 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK	1 RB / 14 RB Offset
			20350	10MHz	QPSK	15 RB / 0 RB Offset
		20025 to 20325	20025	15MHz	QPSK	1 RB / 0 RB Offset
			20325	15MHz	QPSK	25 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK	1 RB / 24 RB Offset
			20300	20MHz	QPSK	25 RB / 0 RB Offset
	Conducted Emission	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 12

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23017 to 23173	23017, 23095, 23173	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		23025 to 23165	23025, 23095, 23165	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		23035 to 23155	23035, 23095, 23155	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		23060 to 23130	23060, 23095, 23130	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Frequency Stability	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 2 RB Offset
		23025 to 23165	23095	3MHz	QPSK	1 RB / 7 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 12 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 24 RB Offset
-	Occupied Bandwidth	23017 to 23173	23017, 23095, 23173	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		23025 to 23165	23025, 23095, 23165	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		23035 to 23155	23035, 23095, 23155	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23060 to 23130	23060, 23095, 23130	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23017 to 23173	23017, 23095, 23173	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		23025 to 23165	23025, 23095, 23165	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		23035 to 23155	23035, 23095, 23155	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		23060 to 23130	23060, 23095, 23130	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Band Edge	23017 to 23173	23017	1.4MHz	QPSK	1 RB / 0 RB Offset
			23173	1.4MHz	QPSK	6 RB / 0 RB Offset
		23025 to 23165	23025	3MHz	QPSK	1 RB / 5 RB Offset
			23165	3MHz	QPSK	15 RB / 0 RB Offset
		23035 to 23155	23035	5MHz	QPSK	1 RB / 14 RB Offset
			23155	5MHz	QPSK	15 RB / 0 RB Offset
		23060 to 23130	23035	5MHz	QPSK	1 RB / 0 RB Offset
			23155	5MHz	QPSK	25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK	1 RB / 24 RB Offset
			23130	10MHz	QPSK	25 RB / 0 RB Offset
		23060 to 23130	23060	10MHz	QPSK	1 RB / 0 RB Offset
			23130	10MHz	QPSK	50 RB / 0 RB Offset
-	Conducted Emission	23017 to 23173	23095	1.4MHz	QPSK	1 RB / 49 RB Offset
		23025 to 23165	23095	3MHz	QPSK	50 RB / 0 RB Offset
		23035 to 23155	23095	5MHz	QPSK	1 RB / 2 RB Offset
		23060 to 23130	23095	10MHz	QPSK	1 RB / 7 RB Offset
-	Radiated Emission	23060 to 23130	23095	10MHz	QPSK	1 RB / 12 RB Offset
-						1 RB / 24 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25deg. C, 65%RH	3.85Vdc	Charles Hsiao
Frequency Stability	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Occupied Bandwidth	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Band Edge	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Peak to Average Ratio	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Conducuted Emission	25deg. C, 65%RH	3.85Vdc	Wayne Lin
Radiated Emission	25deg. C, 65%RH	120Vac, 60Hz	Charles Hsiao

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 699-716 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures

EIRP / ERP Measurement:

- All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5MHz for WCDMA and 10MHz for LTE mode.
- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}$.

Conducted Power Measurement:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.4 Test Results

CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	23.06	23.24	23.20
HSDPA Subtest-1	22.09	22.27	22.23
HSDPA Subtest-2	22.06	22.24	22.20
HSDPA Subtest-3	21.56	21.74	21.70
HSDPA Subtest-4	21.50	21.68	21.64
HSUPA Subtest-1	22.19	22.37	22.33
HSUPA Subtest-2	20.15	20.33	20.29
HSUPA Subtest-3	21.20	21.38	21.34
HSUPA Subtest-4	20.21	20.39	20.35
HSUPA Subtest-5	22.13	22.31	22.27

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19957	Mid Ch 20175	High Ch 20393		Low Ch 19957	Mid Ch 20175	High Ch 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	22.30	22.53	22.49	0	21.21	21.44	21.40	1
	1	2	22.22	22.45	22.41	0	21.13	21.36	21.32	1
	1	5	22.21	22.44	22.40	0	21.12	21.35	21.31	1
	3	0	21.38	21.61	21.57	0	20.29	20.52	20.48	1
	3	1	21.31	21.54	21.50	0	20.22	20.45	20.41	1
	3	3	21.19	21.42	21.38	0	20.10	20.33	20.29	1
	6	0	21.21	21.44	21.40	1	20.12	20.35	20.31	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19965	Mid Ch 20175	High Ch 20385		Low Ch 19965	Mid Ch 20175	High Ch 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	22.41	22.64	22.60	0	21.32	21.55	21.51	1
	1	7	22.33	22.56	22.52	0	21.24	21.47	21.43	1
	1	14	22.32	22.55	22.51	0	21.23	21.46	21.42	1
	8	0	21.49	21.72	21.68	1	20.40	20.63	20.59	2
	8	3	21.42	21.65	21.61	1	20.33	20.56	20.52	2
	8	7	21.30	21.53	21.49	1	20.21	20.44	20.40	2
	15	0	21.32	21.55	21.51	1	20.23	20.46	20.42	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19975	Mid Ch 20175	High Ch 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	22.45	22.68	22.64	0	21.36	21.59	21.55	1
	1	12	22.37	22.60	22.56	0	21.28	21.51	21.47	1
	1	24	22.36	22.59	22.55	0	21.27	21.50	21.46	1
	12	0	21.53	21.76	21.72	1	20.44	20.67	20.63	2
	12	6	21.46	21.69	21.65	1	20.37	20.60	20.56	2
	12	13	21.34	21.57	21.53	1	20.25	20.48	20.44	2
	25	0	21.36	21.59	21.55	1	20.27	20.50	20.46	2



Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20000	Mid Ch 20175	High Ch 20350		Low Ch 20000	Mid Ch 20175	High Ch 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	22.56	22.79	22.75	0	21.47	21.70	21.66	1
	1	24	22.48	22.71	22.67	0	21.39	21.62	21.58	1
	1	49	22.47	22.70	22.66	0	21.38	21.61	21.57	1
	25	0	21.64	21.87	21.83	1	20.55	20.78	20.74	2
	25	12	21.57	21.80	21.76	1	20.48	20.71	20.67	2
	25	25	21.45	21.68	21.64	1	20.36	20.59	20.55	2
	50	0	21.47	21.70	21.66	1	20.38	20.61	20.57	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20025	Mid Ch 20175	High Ch 20325		Low Ch 20025	Mid Ch 20175	High Ch 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	22.64	22.87	22.83	0	21.55	21.78	21.74	1
	1	37	22.56	22.79	22.75	0	21.47	21.70	21.66	1
	1	74	22.55	22.78	22.74	0	21.46	21.69	21.65	1
	36	0	21.72	21.95	21.91	1	20.63	20.86	20.82	2
	36	19	21.65	21.88	21.84	1	20.56	20.79	20.75	2
	36	39	21.53	21.76	21.72	1	20.44	20.67	20.63	2
	75	0	21.55	21.78	21.74	1	20.46	20.69	20.65	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20050	Mid Ch 20175	High Ch 20300		Low Ch 20050	Mid Ch 20175	High Ch 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	22.78	23.01	22.97	0	21.69	21.92	21.88	1
	1	50	22.70	22.93	22.89	0	21.61	21.84	21.80	1
	1	99	22.69	22.92	22.88	0	21.60	21.83	21.79	1
	50	0	21.86	22.09	22.05	1	20.77	21.00	20.96	2
	50	25	21.79	22.02	21.98	1	20.70	20.93	20.89	2
	50	50	21.67	21.90	21.86	1	20.58	20.81	20.77	2
	100	0	21.69	21.92	21.88	1	20.60	20.83	20.79	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23017	Mid Ch 23095	High Ch 23173		Low Ch 23017	Mid Ch 23095	High Ch 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	21.95	22.07	21.93	0	20.93	21.05	20.91	1
	1	2	22.18	22.30	22.16	0	21.16	21.28	21.14	1
	1	5	21.93	22.05	21.91	0	20.91	21.03	20.89	1
	3	0	20.96	21.08	20.94	0	19.94	20.06	19.92	1
	3	1	21.15	21.27	21.13	0	20.13	20.25	20.11	1
	3	3	21.10	21.22	21.08	0	20.08	20.20	20.06	1
	6	0	21.09	21.21	21.07	1	20.07	20.19	20.05	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23025	Mid Ch 23095	High Ch 23165		Low Ch 23025	Mid Ch 23095	High Ch 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	22.01	22.13	21.99	0	20.99	21.11	20.97	1
	1	7	22.24	22.36	22.22	0	21.22	21.34	21.20	1
	1	14	21.99	22.11	21.97	0	20.97	21.09	20.95	1
	8	0	21.02	21.14	21.00	1	20.00	20.12	19.98	2
	8	3	21.21	21.33	21.19	1	20.19	20.31	20.17	2
	8	7	21.16	21.28	21.14	1	20.14	20.26	20.12	2
	15	0	21.15	21.27	21.13	1	20.13	20.25	20.11	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23035	Mid Ch 23095	High Ch 23155		Low Ch 23035	Mid Ch 23095	High Ch 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	22.09	22.21	22.07	0	21.07	21.19	21.05	1
	1	12	22.32	22.44	22.30	0	21.30	21.42	21.28	1
	1	24	22.07	22.19	22.05	0	21.05	21.17	21.03	1
	12	0	21.10	21.22	21.08	1	20.08	20.20	20.06	2
	12	6	21.29	21.41	21.27	1	20.27	20.39	20.25	2
	12	13	21.24	21.36	21.22	1	20.22	20.34	20.20	2
	25	0	21.23	21.35	21.21	1	20.21	20.33	20.19	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23060	Mid Ch 23095	High Ch 23130		Low Ch 23060	Mid Ch 23095	High Ch 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	22.20	22.32	22.18	0	21.18	21.30	21.16	1
	1	24	22.43	22.55	22.41	0	21.41	21.53	21.39	1
	1	49	22.18	22.30	22.16	0	21.16	21.28	21.14	1
	25	0	21.21	21.33	21.19	1	20.19	20.31	20.17	2
	25	12	21.40	21.52	21.38	1	20.38	20.50	20.36	2
	25	25	21.35	21.47	21.33	1	20.33	20.45	20.31	2
	50	0	21.34	21.46	21.32	1	20.32	20.44	20.30	2

ERP Power (dBm)

LTE Band 12							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23017	699.7	-14.33	32.719	16.24	42.06	H
	23095	707.5	-14.04	32.736	16.55	45.14	
	23173	715.3	-13.47	32.591	16.97	49.79	
	23017	699.7	-23.23	32.69	7.31	5.38	V
	23095	707.5	-22.78	32.81	7.88	6.14	
	23173	715.3	-22.31	32.74	8.28	6.73	

LTE Band 12							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23017	699.7	-14.10	32.719	16.47	44.35	H
	23095	707.5	-14.88	32.736	15.71	37.20	
	23173	715.3	-13.48	32.591	16.96	49.67	
	23017	699.7	-23.10	32.69	7.44	5.55	V
	23095	707.5	-23.57	32.81	7.09	5.12	
	23173	715.3	-22.37	32.74	8.22	6.64	

LTE Band 12							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23025	700.5	-14.20	32.719	16.37	43.34	H
	23095	707.5	-14.18	32.736	16.41	43.71	
	23165	714.5	-13.66	32.591	16.78	47.65	
	23025	700.5	-23.09	32.69	7.45	5.56	V
	23095	707.5	-22.97	32.81	7.69	5.87	
	23165	714.5	-22.45	32.74	8.14	6.52	

LTE Band 12							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23025	700.5	-14.60	32.719	15.97	39.53	H
	23095	707.5	-15.01	32.736	15.58	36.11	
	23165	714.5	-13.67	32.591	16.77	47.54	
	23025	700.5	-23.50	32.69	7.04	5.06	V
	23095	707.5	-23.64	32.81	7.02	5.04	
	23165	714.5	-22.41	32.74	8.18	6.58	

LTE Band 12							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23035	701.5	-14.28	32.719	16.29	42.55	H
	23095	707.5	-14.34	32.736	16.25	42.13	
	23155	713.5	-13.64	32.591	16.80	47.87	
	23035	701.5	-23.13	32.69	7.41	5.51	V
	23095	707.5	-23.36	32.81	7.30	5.37	
	23155	713.5	-22.48	32.74	8.11	6.47	

LTE Band 12							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23035	701.5	-14.64	32.719	15.93	39.17	H
	23095	707.5	-14.84	32.736	15.75	37.55	
	23155	713.5	-14.09	32.591	16.35	43.16	
	23035	701.5	-23.63	32.69	6.91	4.91	V
	23095	707.5	-23.73	32.81	6.93	4.93	
	23155	713.5	-22.95	32.74	7.64	5.81	

LTE Band 12							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23060	704.0	-14.53	32.727	16.05	40.24	H
	23095	707.5	-13.77	32.739	16.82	48.07	
	23130	711.0	-14.17	32.728	16.41	43.73	
	23060	704.0	-23.38	32.75	7.22	5.27	V
	23095	707.5	-22.71	32.81	7.95	6.24	
	23130	711.0	-22.73	32.84	7.96	6.25	

LTE Band 12							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23060	704.0	-15.27	32.73	15.31	33.96	H
	23095	707.5	-14.21	32.74	16.38	43.45	
	23130	711.0	-14.27	32.73	16.31	42.76	
	23060	704.0	-24.02	32.75	6.58	4.55	V
	23095	707.5	-23.17	32.81	7.49	5.61	
	23130	711.0	-23.00	32.74	7.59	5.74	

EIRP Power (dBm)

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
X	1312	1712.4	-18.84	42.49	23.65	231.47	H
	1413	1732.6	-18.78	42.33	23.55	226.31	
	1513	1752.6	-18.97	42.10	23.13	205.59	
	1312	1712.4	-24.03	42.99	18.96	78.70	V
	1413	1732.6	-24.62	42.74	18.12	64.86	
	1513	1752.6	-23.73	42.21	18.48	70.47	

LTE Band 4							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19957	1710.7	-20.13	42.49	22.36	171.99	H
	20175	1732.5	-19.40	42.33	22.93	196.20	
	20393	1754.3	-18.97	42.10	23.13	205.59	
	19957	1710.7	-23.55	42.99	19.44	87.90	V
	20175	1732.5	-23.08	42.74	19.66	92.47	
	20393	1754.3	-22.88	42.21	19.33	85.70	

LTE Band 4							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19957	1710.7	-19.75	42.49	22.74	187.72	H
	20175	1732.5	-19.91	42.33	22.42	174.46	
	20393	1754.3	-19.95	42.10	22.15	164.06	
	19957	1710.7	-24.02	42.99	18.97	78.89	V
	20175	1732.5	-23.52	42.74	19.22	83.56	
	20393	1754.3	-23.49	42.21	18.72	74.47	

LTE Band 4							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19965	1711.5	-19.86	42.49	22.63	183.02	H
	20175	1732.5	-19.91	42.33	22.42	174.46	
	20385	1753.5	-19.38	42.10	22.72	187.07	
	19965	1711.5	-24.07	42.99	18.92	77.98	V
	20175	1732.5	-23.34	42.74	19.40	87.10	
	20385	1753.5	-22.99	42.21	19.22	83.56	

LTE Band 4							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19965	1711.5	-19.97	42.49	22.52	178.44	H
	20175	1732.5	-19.65	42.33	22.68	185.23	
	20385	1753.5	-18.88	42.10	23.22	209.89	
	19965	1711.5	-24.14	42.99	18.85	76.74	V
	20175	1732.5	-23.52	42.74	19.22	83.56	
	20385	1753.5	-22.83	42.21	19.38	86.70	

LTE Band 4							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19975	1712.5	-19.77	42.49	22.72	186.85	H
	20175	1732.5	-19.87	42.33	22.46	176.08	
	20375	1752.5	-19.44	42.10	22.66	184.50	
	19975	1712.5	-24.08	42.99	18.91	77.80	V
	20175	1732.5	-23.66	42.74	19.08	80.91	
	20375	1752.5	-22.97	42.21	19.24	83.95	

LTE Band 4							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19975	1712.5	-20.32	42.49	22.17	164.63	H
	20175	1732.5	-20.65	42.33	21.68	147.13	
	20375	1752.5	-19.79	42.10	22.31	170.22	
	19975	1712.5	-24.47	42.99	18.52	71.12	V
	20175	1732.5	-24.05	42.74	18.69	73.96	
	20375	1752.5	-23.39	42.21	18.82	76.21	

LTE Band 4							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20000	1715.0	-19.92	42.49	22.57	180.51	H
	20175	1732.5	-19.78	42.33	22.55	179.76	
	20350	1750.0	-19.61	42.10	22.49	177.42	
	20000	1715.0	-23.52	42.99	19.47	88.51	V
	20175	1732.5	-23.66	42.74	19.08	80.91	
	20350	1750.0	-22.86	42.21	19.35	86.10	

LTE Band 4							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20000	1715.0	-19.83	42.49	22.66	184.29	H
	20175	1732.5	-20.59	42.33	21.74	149.18	
	20350	1750.0	-19.45	42.10	22.65	184.08	
	20000	1715.0	-24.13	42.99	18.86	76.91	V
	20175	1732.5	-24.05	42.74	18.69	73.96	
	20350	1750.0	-23.28	42.21	18.93	78.16	

LTE Band 4							
Channel Bandwidth: 15MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20025	1717.5	-20.09	42.49	22.40	173.58	H
	20175	1732.5	-19.98	42.33	22.35	171.67	
	20325	1747.5	-19.72	42.10	22.38	172.98	
	20025	1717.5	-23.51	42.99	19.48	88.72	V
	20175	1732.5	-23.09	42.74	19.65	92.26	
	20325	1747.5	-22.44	42.21	19.77	94.84	

LTE Band 4							
Channel Bandwidth: 15MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20025	1717.5	-20.52	42.49	21.97	157.22	H
	20175	1732.5	-20.75	42.33	21.58	143.78	
	20325	1747.5	-20.34	42.10	21.76	149.97	
	20025	1717.5	-24.39	42.99	18.60	72.44	V
	20175	1732.5	-23.72	42.74	19.02	79.80	
	20325	1747.5	-23.12	42.21	19.09	81.10	

LTE Band 4							
Channel Bandwidth: 20MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20050	1720.0	-20.00	42.49	22.49	177.21	H
	20175	1732.5	-19.97	42.33	22.36	172.07	
	20300	1745.0	-19.53	42.10	22.57	180.72	
	20050	1720.0	-23.65	42.99	19.34	85.90	V
	20175	1732.5	-22.96	42.74	19.78	95.06	
	20300	1745.0	-22.13	42.21	20.08	101.86	

LTE Band 4							
Channel Bandwidth: 20MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20050	1720.0	-20.04	42.49	22.45	175.59	H
	20175	1732.5	-19.53	42.33	22.80	190.41	
	20300	1745.0	-20.28	42.10	21.82	152.05	
	20050	1720.0	-23.80	42.99	19.19	82.99	V
	20175	1732.5	-22.86	42.74	19.88	97.27	
	20300	1745.0	-22.93	42.21	19.28	84.72	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)							Limit (ppm)
	WCDMA	LTE Band 4						
		1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
3.85	0.0007	0.00113	0.00024	0.00111	0.00067	0.00141	0.00044	2.5
3.6	0.0022	0.00139	0.00047	0.00161	0.00125	0.00094	0.00178	2.5
4.40	0.0021	0.00016	0.00051	0.00123	0.00017	0.00043	0.00061	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.40Vdc.

Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)							Limit (ppm)
	WCDMA	LTE Band 4						
		1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	
-30	0.0003	0.00044	0.00213	0.00126	0.00186	0.00220	0.00004	2.5
-20	0.0001	0.00071	0.00193	0.00009	0.00183	0.00116	0.00195	2.5
-10	0.0008	0.00196	0.00088	0.00099	0.00179	0.00208	0.00186	2.5
0	0.0009	0.00009	0.00206	0.00065	0.00142	0.00053	0.00055	2.5
10	0.0013	0.00152	0.00141	0.00175	0.00072	0.00229	0.00152	2.5
20	-0.0006	-0.00173	-0.00059	-0.00227	-0.00112	-0.00018	-0.00149	2.5
30	-0.0014	-0.00225	-0.00109	-0.00020	-0.00129	-0.00006	-0.00231	2.5
40	-0.0021	-0.00203	-0.00184	-0.00008	-0.00137	-0.00192	-0.00062	2.5
50	-0.0013	-0.00211	-0.00094	-0.00081	-0.00016	-0.00012	-0.00114	2.5
60	0.0007	-0.00020	0.00186	0.00122	0.00122	0.00184	0.00123	2.5

Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)				Limit (ppm)
	LTE Band 12				
	1.4MHz	3MHz	5MHz	10MHz	
3.85	0.0034	0.0039	0.0038	0.0013	2.5
3.6	0.0021	0.0055	0.0047	0.0044	2.5
4.40	0.0014	0.0010	0.0054	0.0019	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.40Vdc.

Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)				Limit (ppm)
	LTE Band 12				
	1.4MHz	3MHz	5MHz	10MHz	
-30	0.0016	0.0028	0.0039	0.0001	2.5
-20	0.0021	0.0001	0.0044	0.0020	2.5
-10	0.0032	0.0014	0.0005	0.0041	2.5
0	0.0055	0.0056	0.0029	0.0022	2.5
10	0.0019	0.0045	0.0039	0.0028	2.5
20	-0.0051	-0.0006	-0.0038	-0.0008	2.5
30	-0.0033	-0.0002	-0.0035	-0.0051	2.5
40	-0.0019	-0.0028	-0.0007	-0.0028	2.5
50	-0.0015	-0.0043	-0.0010	-0.0054	2.5
60	0.0033	-0.0008	0.0023	0.0021	2.5

4.3 Occupied Bandwidth Measurement


4.3.1 Limits Of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result

WCDMA		
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
1312	1712.4	4.1270
1413	1732.6	4.1279
1513	1752.6	4.1338



LTE Band 4

Channel Bandwidth: 1.4MHz



Channel Bandwidth: 3MHz

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.0929	1.0908	19965	1711.5	2.6911	2.6921
20175	1732.5	1.0909	1.0889	20175	1732.5	2.6935	2.6944
20393	1754.3	1.0894	1.0885	20385	1753.5	2.6938	2.6943

Spectrum Plot of Worst Value



1.4MHz / QPSK

1.4MHz / 16QAM



3MHz / QPSK

3MHz / 16QAM



LTE Band 4


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.4827	4.4818	20000	1715.0	8.9491	8.9443
20175	1732.5	4.4869	4.4878	20175	1732.5	8.9567	8.9504
20375	1752.5	4.4881	4.4862	20350	1750.0	8.9556	8.9489

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM





A O T

LTE BAND 4

Channel Bandwidth: 15MHz



Channel Bandwidth: 20MHz

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.410	13.382	20050	1720.0	17.878	17.891
20175	1732.5	13.409	13.413	20175	1732.5	17.888	17.894
20325	1747.5	13.402	13.400	20300	1745.0	17.845	17.848

Spectrum Plot of Worst Value



15MHz / QPSK

15MHz / 16QAM



20MHz / QPSK

20MHz / 16QAM



LTE Band 12

Channel Bandwidth: 1.4MHz



Channel Bandwidth: 3MHz

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.0898	1.0891	23025	700.5	2.6935	2.6946
23095	707.5	1.0909	1.0901	23095	707.5	2.6916	2.6945
23173	715.3	1.0909	1.0904	23165	714.5	2.6995	2.6977

Spectrum Plot of Worst Value



1.4MHz / QPSK

1.4MHz / 16QAM



3MHz / QPSK

3MHz / 16QAM



LTE Band 12


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.4881	4.4882	23060	704.0	8.9898	8.9947
23095	707.5	4.4765	4.4743	23095	707.5	8.9201	8.9259
23155	713.5	4.4886	4.4853	23130	711.0	8.9114	8.9119

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



4.4 Band Edge Measurement


4.4.1 Limits of Band Edge Measurement

For operations in the 699-716 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.


4.4.2 Test Setup



4.4.3 Test Procedures

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 13kHz and VB of the spectrum is 51kHz (LTE Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Bandwidth 3MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Bandwidth 5MHz/10MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 150kHz and VB of the spectrum is 470kHz (LTE Bandwidth 15MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 180kHz and VB of the spectrum is 560kHz (LTE Bandwidth 20MHz).
- Record the max trace plot into the test report.

4.4.4 Test Results






A O T


LTE Band 4

Channel Bandwidth: 3MHz

Channel	19965	1 RB	Channel	20385	1 RB
---------	-------	------	---------	-------	------



Channel	19965	15 RB	Channel	20385	15 RB
---------	-------	-------	---------	-------	-------






A O T


LTE Band 4

Channel Bandwidth: 5MHz

Channel	19975	1 RB	Channel	20375	1 RB
---------	-------	------	---------	-------	------



Channel	19975	25 RB	Channel	20375	25 RB
---------	-------	-------	---------	-------	-------






A O T


LTE Band 4

Channel Bandwidth: 10MHz





A O T





A O T

LTE Band 4

Channel Bandwidth: 20MHz

Channel

20050

1 RB

Channel

20300

1 RB



Channel



20050

100 RB

Channel

20300

100 RB






A O T

LTE Band 12

CHANNEL BANDWIDTH: 1.4MHz

Channel	23017	1 RB	Channel	23173	1 RB
---------	-------	------	---------	-------	------



Channel	23017	6 RB	Channel	23173	6 RB
---------	-------	------	---------	-------	------





A O T

LTE Band 12

Channel Bandwidth: 3MHz

Channel

23025

1 RB

Channel

23165

1 RB



Channel

23025

15 RB

Channel

23165

15 RB





A O T

LTE Band 12

Channel Bandwidth: 5MHz

Channel

23035

1 RB

Channel

23155

1 RB



Channel

23035

25 RB

Channel

23155

25 RB






A O T


LTE Band 12

Channel Bandwidth: 10MHz

Channel	23060	1 RB	Channel	23130	1 RB
---------	-------	------	---------	-------	------



Channel	23060	50 RB	Channel	23130	50 RB
---------	-------	-------	---------	-------	-------




4.5 Peak To Average Ratio

4.5.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.5.4 Test Results

WCDMA		
Channel	Frequency (MHz)	Peak to Average Ratio (dB)
1312	1712.4	2.99
1413	1732.6	3.18
1513	1752.6	2.87





A O T

LTE Band 4

Channel Bandwidth: 1.4MHz



Channel Bandwidth: 3MHz

Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.93	6.17	19965	1711.5	4.65	6.45
20175	1732.5	5.39	6.88	20175	1732.5	5.19	7.00
20393	1754.3	4.51	5.70	20385	1753.5	3.86	6.16

Spectrum Plot of Worst Value



1.4MHz / QPSK

1.4MHz / 16QAM



3MHz / QPSK

3MHz / 16QAM



LTE Band 4


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	5.57	6.29	20000	1715.0	5.59	6.40
20175	1732.5	5.86	6.57	20175	1732.5	5.73	6.78
20375	1752.5	5.20	6.40	20350	1750.0	5.24	6.23

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM





A O T

LTE BAND 4

Channel Bandwidth: 5MHz



Channel Bandwidth: 10MHz

Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	5.50	6.53	20050	1720.0	5.73	6.69
20175	1732.5	6.02	6.79	20175	1732.5	5.97	7.17
20325	1747.5	5.63	6.75	20300	1745.0	6.03	7.20

Spectrum Plot of Worst Value



15MHz / QPSK

15MHz / 16QAM



20MHz / QPSK

20MHz / 16QAM



LTE Band 12

Channel Bandwidth: 1.4MHz



Channel Bandwidth: 3MHz

Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	4.31	6.30	23025	700.5	4.73	5.87
23095	707.5	5.18	6.85	23095	707.5	5.20	6.76
23173	715.3	4.21	6.46	23165	714.5	4.37	5.37

Spectrum Plot of Worst Value



1.4MHz / QPSK

1.4MHz / 16QAM



3MHz / QPSK

3MHz / 16QAM






A O T

LTE Band 12


Channel Bandwidth: 5MHz				Channel Bandwidth: 10MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.92	5.82	23060	704.0	4.23	6.96
23095	707.5	5.05	6.67	23095	707.5	4.39	7.05
23155	713.5	3.97	6.34	23130	711.0	5.43	6.51

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13dBm.

4.6.2 Test Setup




4.6.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 8GHz for LTE Band 12, and from 30MHz to 18GHz for WCDMA Band 4 and LTE Band 4. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.4 Test Results

Frequency Range: 30MHz~8GHz




Frequency Range: 30MHz~18GHz




LTE Band 4
Channel 10175


1.4MHz / QPSK




3MHz / QPSK




5MHz / QPSK




10MHz / QPSK



15MHz / QPSK



20MHz / QPSK



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm.

4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}.$

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results


WCDMA:



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
Condition: PART 27(B4/B17) 3m Horizontal
Remark : Band IV_Link_CH1413
Tested by: Charles Hsiao
Plane : Y

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	98.04	-57.65	-47.42	-13.00	-44.65	-10.23	Peak
2	pp 190.38	-49.68	-43.95	-13.00	-36.68	-5.73	Peak
3	218.19	-58.52	-52.58	-13.00	-45.52	-5.94	Peak
4	370.70	-74.11	-69.82	-13.00	-61.11	-4.29	Peak
5	566.70	-71.44	-70.46	-13.00	-58.44	-0.98	Peak
6	855.80	-68.43	-70.04	-13.00	-55.43	1.61	Peak
7	3465.20	-51.23	-65.57	-13.00	-38.23	14.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2015-09-02



Site : 966 chamber 1
 Condition: PART 27(B4/B17) 3m Vertical
 Remark : Band IV_Link_CH1413
 Tested by: Charles Hsiao
 Plane : Y

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	48.63	-46.05	-32.62	-13.00	-33.05	-13.43	Peak
2	153.66	-58.53	-50.67	-13.00	-45.53	-7.86	Peak
3	193.35	-56.60	-50.73	-13.00	-43.60	-5.87	Peak
4	400.80	-71.75	-68.99	-13.00	-58.75	-2.76	Peak
5	589.80	-68.41	-68.40	-13.00	-55.41	-0.01	Peak
6	888.70	-66.49	-69.04	-13.00	-53.49	2.55	Peak
7	3465.20	-49.23	-63.57	-13.00	-36.23	14.34	Peak

LTE Band 4

Channel Bandwidth: 20MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2015-09-02



Site : 966 chamber 1

Condition: PART 27(B4/B17) 3m Horizontal

Remark : LTE_Band 4_QPSK(1,0)_20M_CH20175

Tested by: Charles Hsiao

Plane : Y

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	68.07	-64.38	-51.42	-13.00	-51.38	-12.96	Peak
2	100.20	-57.11	-46.99	-13.00	-44.11	-10.12	Peak
3	193.35	-50.21	-44.34	-13.00	-37.21	-5.87	Peak
4	423.20	-70.99	-67.74	-13.00	-57.99	-3.25	Peak
5	633.20	-67.88	-67.93	-13.00	-54.88	0.05	Peak
6	825.70	-66.46	-68.18	-13.00	-53.46	1.72	Peak
7 pp	3465.00	-49.88	-64.22	-13.00	-36.88	14.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2015-09-02



Site : 966 chamber 1
 Condition: PART 27(B4/B17) 3m Vertical
 Remark : LTE_Band 4_QPSK(1,0)_20M_CH20175
 Tested by: Charles Hsiao
 Plane : Y

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	32.43	-43.39	-32.52	-13.00	-30.39	-10.87	Peak
2	152.31	-58.32	-50.43	-13.00	-45.32	-7.89	Peak
3	193.35	-56.88	-51.01	-13.00	-43.88	-5.87	Peak
4	424.60	-70.84	-67.55	-13.00	-57.84	-3.29	Peak
5	588.40	-68.30	-68.25	-13.00	-55.30	-0.05	Peak
6	921.60	-65.57	-69.41	-13.00	-52.57	3.84	Peak
7	3465.00	-49.63	-63.97	-13.00	-36.63	14.34	Peak

LTE Band 12

Channel Bandwidth: 10MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2015-09-02



Site : 966 chamber 1

Condition: PART 22/24/27 3m Horizontal

Remark : LTE_Band 12_QPSK(1,24)_10M_CH23095

Tested by: Charles Hsiao

Plane : X

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	68.34	-64.76	-51.94	-13.00	-51.76	-12.82	Peak
2	96.96	-57.71	-47.42	-13.00	-44.71	-10.29	Peak
3 pp	194.16	-50.02	-44.11	-13.00	-37.02	-5.91	Peak
4	435.80	-71.64	-68.11	-13.00	-58.64	-3.53	Peak
5	605.20	-67.36	-67.73	-13.00	-54.36	0.37	Peak
6	844.60	-65.91	-67.41	-13.00	-52.91	1.50	Peak
7	1415.00	-56.80	-63.16	-13.00	-43.80	6.36	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2015-09-02



Site : 966 chamber 1
 Condition: PART 22/24/27 3m Vertical
 Remark : LTE_Band 12_QPSK(1,24)_10M_CH23095
 Tested by: Charles Hsiao
 Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	pp	48.36	-56.41	-42.98	-13.00	-43.41	-13.43 Peak
2		150.96	-59.86	-51.94	-13.00	-46.86	-7.92 Peak
3		194.70	-56.91	-50.95	-13.00	-43.91	-5.96 Peak
4		395.90	-70.67	-67.72	-13.00	-57.67	-2.95 Peak
5		659.10	-68.14	-67.96	-13.00	-55.14	-0.18 Peak
6		806.80	-67.00	-68.93	-13.00	-54.00	1.93 Peak
7		1415.00	-56.77	-63.13	-13.00	-43.77	6.36 Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---