



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Smartphone
MODEL NAME : 2Q5V200
FCC ID : NM82Q5V200
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 02, 2018 and testing was completed on Feb. 08, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI/TIA-603-E and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Laboratory SPORTON INTERNATIONAL INC.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

**No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	12
3 CONDUCTED TEST RESULT	13
3.1 Measuring Instruments.....	13
3.2 Test Setup	13
3.3 Test Result of Conducted Test.....	13
3.4 Conducted Output Power and ERP/EIRP	14
3.5 Peak-to-Average Ratio	15
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	16
3.7 Conducted Band Edge	17
3.8 Conducted Spurious Emission	18
3.9 Frequency Stability	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments.....	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test.....	20
4.4 Field Strength of Spurious Radiation Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG810208A	Rev. 01	Initial issue of report	Mar. 15, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 19.89 dB at 2544.000 MHz



1 General Description

1.1 Applicant

HTC Corporation

No. 88, Sec. 3, Zhongxing Rd. Xindian Dist., New Taipei City, Taiwan

1.2 Manufacturer

Shanghai Longcheer Technology Co., Ltd

Building 1, No.401, Caobao Rd., Xuhui Dist, Shanghai, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Model Name	2Q5V200
FCC ID	NM82Q5V200
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth v3.0 + EDR / Bluetooth v4.0 LE
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power	GSM/GPRS/EDGE: 850: 32.52 dBm 1900: 29.53 dBm WCDMA: Band V: 23.10 dBm Band II: 22.75 dBm Band IV: 22.95 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: -1 dBi PCS Band: 0 dBi AWS Band: 0 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GPRS class 8	GMSK	0.8650	0.0407 ppm	245KGXW
Part 22H	GSM850 EDGE class 8	8PSK	0.2799	0.0335 ppm	256KG7W
Part 22H	WCDMA Band V RMC 12.2Kbps	BPSK	0.0989	0.0514 ppm	4M20F9W
Part 24E	GSM1900 GPRS class 8	GMSK	0.9441	0.0176 ppm	243KGXW
Part 24E	GSM1900 EDGE class 8	8PSK	0.4102	0.0176 ppm	246KG7W
Part 24E	WCDMA Band II RMC 12.2Kbps	BPSK	0.1884	0.0112 ppm	4M17F9W
Part 27L	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1972	0.0144 ppm	4M18F9W

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.	
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	TH01-KS	630927

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	03CH11-HY	214511

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. Note: Test data subcontracted: radiated spurious emissions only in section 4.4 of this report



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI/TIA-603-E
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.
3. 30 MHz to 10th harmonic for WCDMA Band IV.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.4 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.4 + 10 = 14.4 \text{ (dB)}\end{aligned}$$

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.8 and ANSI/TIA-603-E Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Jan. 31, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Radio communication analyzer	Anritsu	MT8820C	6201300652	2G/3G/LTE_ full band	Aug. 08, 2017	Jan. 31, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 12, 2017	Jan. 31, 2018	Oct. 11, 2018	Conducted (TH01-KS)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VS WR : 2.5:1 max	Jul. 18, 2017	Feb.06,2018 ~ Feb.08,2018	Jul. 17, 2018	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 10, 2016	Feb.06,2018 ~ Feb.08,2018	Nov. 09, 2018	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-	35414&AT-N0 602	30MHz~1GHz	Oct. 14, 2017	Feb.06,2018 ~ Feb.08,2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 16, 2017	Feb.06,2018 ~ Feb.08,2018	Oct. 15, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1GHz ~ 18GHz	Mar. 17, 2017	Feb.06,2018 ~ Feb.08,2018	Mar. 16, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Feb.06,2018 ~ Feb.08,2018	Nov. 22, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 10, 2016	Feb.06,2018 ~ Feb.08,2018	Nov. 09, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2017	Feb.06,2018 ~ Feb.08,2018	Oct. 18, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-10 80-1200-15	SN2	1.2G High Pass	Sep. 18, 2017	Feb.06,2018 ~ Feb.08,2018	Sep. 17, 2018	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-27 00-3000-18 000-60SS	SN3	2.7G High Pass	Sep. 18, 2017	Feb.06,2018 ~ Feb.08,2018	Sep. 17, 2018	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Feb.06,2018 ~ Feb.08,2018	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1~4m	N/A	Feb.06,2018 ~ Feb.08,2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Feb.06,2018 ~ Feb.08,2018	N/A	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Nov. 02, 2017	Feb.06,2018 ~ Feb.08,2018	Nov. 01, 2018	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917057 6	18GHz- 40GHz	Apr. 27, 2017	Feb.06,2018 ~ Feb.08,2018	Apr. 26, 2018	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Nov. 27, 2017	Feb.06,2018 ~ Feb.08,2018	Nov. 26, 2018	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-00 101800-30-	1590074	1GHz~18GHz	May 22, 2017	Feb.06,2018 ~ Feb.08,2018	May 21, 2018	Radiation (03CH11-HY)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.4dB
--	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.7dB
--	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.0dB
--	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.52	32.44	32.34	29.52	29.53	29.75
GPRS class 8	32.51	32.43	32.32	29.52	29.52	29.72
GPRS class 10	30.73	30.71	30.60	27.69	27.71	27.88
GPRS class 11	28.75	28.73	28.63	25.71	25.75	25.98
GPRS class 12	27.53	27.72	27.61	24.67	24.75	24.97
EGPRS class 8	27.53	27.45	27.62	25.84	25.88	26.13
EGPRS class 10	25.13	25.19	25.22	23.56	23.61	23.97
EGPRS class 11	23.45	23.57	23.49	22.39	22.49	22.72
EGPRS class 12	22.60	22.68	22.60	21.18	21.27	21.58



Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2Kbps	23.06	23.07	23.06	22.72	22.74	22.66	22.93	22.92	22.91
RMC 12.2K	23.10	23.09	23.08	22.73	22.75	22.67	22.95	22.94	22.93
HSDPA Subtest-1	21.99	22.00	22.00	21.74	21.78	21.70	22.05	22.10	22.13
HSDPA Subtest-2	21.96	21.96	21.88	21.26	21.26	21.20	22.00	21.99	22.06
HSDPA Subtest-3	21.48	21.47	21.40	21.24	21.23	21.24	21.40	21.49	21.55
HSDPA Subtest-4	21.47	21.45	21.36	21.23	21.21	21.20	21.43	21.48	21.55
DC-HSDPA Subtest-1	21.98	21.99	21.96	21.73	21.72	21.69	22.03	22.09	22.12
DC-HSDPA Subtest-2	21.93	21.93	21.82	21.21	21.20	21.23	21.98	21.96	22.03
DC-HSDPA Subtest-3	21.43	21.35	21.42	21.19	21.21	21.21	21.35	21.35	21.45
DC-HSDPA Subtest-4	21.42	21.37	21.32	21.20	21.23	21.16	21.36	21.45	21.39
HSUPA Subtest-1	19.98	20.05	20.00	19.88	19.86	19.79	20.07	20.08	20.15
HSUPA Subtest-2	19.97	20.07	20.00	20.81	20.90	20.82	19.97	20.08	20.18
HSUPA Subtest-3	20.96	21.09	20.94	19.33	19.48	19.39	20.94	21.01	21.12
HSUPA Subtest-4	19.54	19.56	19.57	20.85	20.78	20.72	19.53	19.55	19.65
HSUPA Subtest-5	20.90	20.90	20.90	19.78	19.77	19.79	20.90	21.00	21.00
HSPA+ (16QAM) Subtest-1	19.52	19.54	19.56	19.32	19.45	19.36	19.53	19.51	19.62

**ERP/EIRP**

GSM850 ($G_T - L_C = -1.0\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	32.52	32.44	32.34
Conducted Power (Watts)	1.7865	1.7539	1.7140
ERP(dBm)	29.37	29.29	29.19
ERP(Watts)	0.8650	0.8492	0.8299

EDGE850 ($G_T - L_C = -1.0\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	27.53	27.45	27.62
Conducted Power (Watts)	0.5662	0.5559	0.5781
ERP(dBm)	24.38	24.30	24.47
ERP(Watts)	0.2742	0.2692	0.2799



GSM1900 ($G_T - L_C = 0\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	29.52	29.53	29.75
Conducted Power (Watts)	0.8954	0.8974	0.9441
EIRP(dBm)	29.52	29.53	29.75
EIRP(Watts)	0.8954	0.8974	0.9441

EDGE1900 ($G_T - L_C = 0\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	25.84	25.88	26.13
Conducted Power (Watts)	0.3837	0.3873	0.4102
EIRP(dBm)	25.84	25.88	26.13
EIRP(Watts)	0.3837	0.3873	0.4102



WCDMA Band V ($G_T - L_C = -1.0\text{dB}$)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency	826.4	836.4	846.6
(MHz)			
Conducted Power (dBm)	23.10	23.09	23.08
Conducted Power (Watts)	0.2042	0.2037	0.2032
ERP(dBm)	19.95	19.94	19.93
ERP(Watts)	0.0989	0.0986	0.0984

WCDMA Band II ($G_T - L_C = 0\text{dB}$)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	22.73	22.75	22.67
Conducted Power (Watts)	0.1875	0.1884	0.1849
EIRP(dBm)	22.73	22.75	22.67
EIRP(Watts)	0.1875	0.1884	0.1849

WCDMA Band IV ($G_T - L_C = 0\text{dB}$)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency	1712.4	1732.6	1752.6
(MHz)			
Conducted Power (dBm)	22.95	22.94	22.93
Conducted Power (Watts)	0.1972	0.1968	0.1963
EIRP(dBm)	22.95	22.94	22.93
EIRP(Watts)	0.1972	0.1968	0.1963

Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	2.84	PASS
Middle CH	0.12	3.10	
Highest CH	0.12	2.87	


Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.2	3.39	PASS
Middle CH	0.17	3.22	
Highest CH	0.17	3.48	

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.87	2.87	2.81	PASS
Middle CH	2.72	3.01	2.29	
Highest CH	2.87	2.72	2.64	



GSM850 (GSM)


Lowest Channel



Date: 31 JAN 2018 02:54:31


GSM850 (EDGE class 8)

Lowest Channel




Date: 31 JAN 2018 03:23:48

Middle Channel




Date: 31 JAN 2018 02:55:43

Middle Channel




Date: 31 JAN 2018 03:24:03

Highest Channel



Date: 31 JAN 2018 02:56:00

Highest Channel




Date: 31 JAN 2018 03:24:12



GSM1900 (GSM)


Lowest Channel



Date: 31 JAN 2018 03:43:03


GSM1900 (EDGE class 8)

Lowest Channel




Date: 31 JAN 2018 04:00:58

Middle Channel



Date: 31 JAN 2018 03:43:16

Middle Channel




Date: 31 JAN 2018 04:01:06

Highest Channel



Date: 31 JAN 2018 03:43:27

Highest Channel




Date: 31 JAN 2018 04:01:13




WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel




Highest Channel




Highest Channel



WCDMA Band IV (RMC 12.2Kbps)
Lowest Channel


Date: 31 JAN 2018 05:48:26

Middle Channel


Date: 31 JAN 2018 05:48:40

Highest Channel


Date: 31 JAN 2018 05:48:47

**26dB Bandwidth**

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.316	0.316
Middle CH	0.316	0.318
Highest CH	0.317	0.326


Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.318	0.314
Middle CH	0.318	0.312
Highest CH	0.316	0.314

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.72	4.73	4.72
Middle CH	4.72	4.71	4.75
Highest CH	4.72	4.72	4.72



GSM850 (GSM)


Lowest Channel



Date: 31 JAN 2018 02:58:33


GSM850 (EDGE class 8)

Lowest Channel




Date: 31 JAN 2018 03:10:10

Middle Channel



Date: 31 JAN 2018 02:48:07

Middle Channel




Date: 31 JAN 2018 03:10:43

Highest Channel



Date: 31 JAN 2018 02:40:41

Highest Channel




Date: 31 JAN 2018 03:11:16



GSM1900 (GSM)

Lowest Channel



Date: 31 JAN 2018 03:28:15

GSM1900 (EDGE class 8)

Lowest Channel




Date: 31 JAN 2018 03:45:58

Middle Channel



Date: 31 JAN 2018 03:28:54

Middle Channel



Date: 31 JAN 2018 03:46:38

Highest Channel



Date: 31 JAN 2018 03:29:31

Highest Channel




Date: 31 JAN 2018 03:47:10



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 31 JAN 2018 05:06:32


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 31 JAN 2018 04:53:43

Middle Channel




Date: 31 JAN 2018 05:07:07

Middle Channel




Date: 31 JAN 2018 04:54:21

Highest Channel



Date: 31 JAN 2018 05:07:47

Highest Channel




Date: 31 JAN 2018 04:54:56




WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel



**Occupied Bandwidth**

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.245	0.256
Middle CH	0.243	0.250
Highest CH	0.242	0.251

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.243	0.243
Middle CH	0.243	0.246
Highest CH	0.243	0.246

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.17	4.17	4.16
Middle CH	4.20	4.17	4.18
Highest CH	4.16	4.17	4.16




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel





GSM1900 (GSM)


Lowest Channel



Date: 31 JAN 2018 03:33:12

GSM1900 (EDGE class 8)

Lowest Channel



Date: 31 JAN 2018 03:49:42

Middle Channel



Date: 31 JAN 2018 03:33:47

Middle Channel



Date: 31 JAN 2018 03:52:16

Highest Channel



Date: 31 JAN 2018 03:34:20

Highest Channel




Date: 31 JAN 2018 03:50:47



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 31 JAN 2018 05:17:56


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 31 JAN 2018 04:55:55

Middle Channel




Date: 31 JAN 2018 05:18:28

Middle Channel




Date: 31 JAN 2018 04:56:37

Highest Channel



Date: 31 JAN 2018 05:19:00

Highest Channel




Date: 31 JAN 2018 04:57:08




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 31 JAN 2018 05:38:03

Middle Channel







Date: 31 JAN 2018 05:38:37

Highest Channel




Date: 31 JAN 2018 05:38:09

**Conducted Band Edge****GSM850 (GSM)****Lowest Band Edge****Highest Band Edge****GSM850 (EDGE class 8)****Lowest Band Edge****Highest Band Edge**



GSM1900 (GSM)

Lowest Band Edge



Date: 31 JAN 2018 03:35:53


Highest Band Edge



Date: 31 JAN 2018 03:37:28


GSM1900 (EDGE class 8)

Lowest Band Edge



Date: 31 JAN 2018 03:52:18

Highest Band Edge




Date: 31 JAN 2018 03:53:48



WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge




Highest Band Edge






WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge






Conducted Spurious Emission

GSM850 (GSM)


Lowest Channel



Date: 31 JAN 2018 02:48:35


GSM850 (EDGE class 8)

Lowest Channel




Date: 31 JAN 2018 03:19:50

Middle Channel




Date: 31 JAN 2018 02:58:54

Middle Channel




Date: 31 JAN 2018 03:21:08

Highest Channel



Date: 31 JAN 2018 02:52:14

Highest Channel




Date: 31 JAN 2018 03:22:29




GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 31 JAN 2018 05:46:02

Middle Channel



Date: 31 JAN 2018 05:47:22

Highest Channel



Date: 31 JAN 2018 05:48:41

**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0036	0.0155	PASS
40	Normal Voltage	0.0407	0.0072	
30	Normal Voltage	0.0012	0.0299	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0371	0.0096	
0	Normal Voltage	0.0227	0.0335	
-10	Normal Voltage	0.0215	0.0227	
-20	Normal Voltage	0.0012	0.0072	
-30	Normal Voltage	0.0024	0.0239	
20	Maximum Voltage	0.0036	0.0143	
20	Normal Voltage	0.0036	0.0108	
20	Battery End Point	0.0191	0.0120	

Note: Normal Voltage = 4.0V. ; Battery End Point (BEP) =3.8V. ; Maximum Voltage =4.5 V



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0160	0.0064	PASS
40	Normal Voltage	0.0011	0.0176	
30	Normal Voltage	0.0048	0.0122	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0176	0.0144	
0	Normal Voltage	0.0138	0.0154	
-10	Normal Voltage	0.0011	0.0165	
-20	Normal Voltage	0.0133	0.0101	
-30	Normal Voltage	0.0016	0.0186	
20	Maximum Voltage	0.0160	0.0106	
20	Normal Voltage	0.0005	0.0027	
20	Battery End Point	0.0037	0.0016	

Note:

1. Normal Voltage = 4.0V. ; Battery End Point (BEP) =3.8V. ; Maximum Voltage =4.5 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0155	PASS
40	Normal Voltage	0.0418	
30	Normal Voltage	0.0395	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0179	
0	Normal Voltage	0.0359	
-10	Normal Voltage	0.0012	
-20	Normal Voltage	0.0203	
-30	Normal Voltage	0.0311	
20	Maximum Voltage	0.0514	
20	Normal Voltage	0.0191	
20	Battery End Point	0.0048	

Note: Normal Voltage = 4.0V. ; Battery End Point (BEP) =3.8V. ; Maximum Voltage =4.5 V



Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0112	PASS
40	Normal Voltage	0.0101	
30	Normal Voltage	0.0021	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0005	
0	Normal Voltage	0.0016	
-10	Normal Voltage	0.0080	
-20	Normal Voltage	0.0032	
-30	Normal Voltage	0.0000	
20	Maximum Voltage	0.0021	
20	Normal Voltage	0.0080	
20	Battery End Point	0.0096	

Note:

1. Normal Voltage = 4.0V. ; Battery End Point (BEP) =3.8V. ; Maximum Voltage =4.5V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0144	PASS
40	Normal Voltage	0.0133	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0110	
0	Normal Voltage	0.0075	
-10	Normal Voltage	0.0040	
-20	Normal Voltage	0.0006	
-30	Normal Voltage	0.0069	
20	Maximum Voltage	0.0069	
20	Normal Voltage	0.0098	
20	Battery End Point	0.0023	

Note:

1. Normal Voltage = 4.0V. ; Battery End Point (BEP) =3.8V. ; Maximum Voltage =4.5V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

GSM850 (GPRS class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-37.85	-13	-24.85	-47.78	-44.8	0.53	9.63	H
	2472	-35.42	-13	-22.42	-48.68	-43.4	0.65	10.78	H
	3296	-38.92	-13	-25.92	-54.85	-48	0.76	11.99	H
	4120	-45.26	-13	-32.26	-62.63	-54.6	0.86	12.35	H
	4944	-49.31	-13	-36.31	-69.35	-58.7	0.66	12.20	H
	5768	-53.41	-13	-40.41	-74.57	-63.3	1.00	13.04	H
	6592	-55.77	-13	-42.77	-78.61	-64.9	0.92	12.20	H
	7416	-51.58	-13	-38.58	-75.99	-58.8	1.18	10.55	H
	1648	-45.85	-13	-32.85	-55.09	-52.8	0.53	9.63	V
	2472	-43.42	-13	-30.42	-57.24	-51.4	0.65	10.78	V
	3296	-43.12	-13	-30.12	-59.06	-52.2	0.76	11.99	V
	4120	-51.16	-13	-38.16	-69.44	-60.5	0.86	12.35	V
	4944	-49.41	-13	-36.41	-69.66	-58.8	0.66	12.20	V
	5768	-49.91	-13	-36.91	-71.43	-59.8	1.00	13.04	V
	6592	-51.97	-13	-38.97	-75.64	-61.1	0.92	12.20	V
	7416	-49.48	-13	-36.48	-73.83	-56.7	1.18	10.55	V
Middle	1672	-43.80	-13	-30.80	-53.88	-50.8	0.53	9.68	H
	2512	-35.70	-13	-22.70	-48.45	-43.7	0.66	10.81	H
	3344	-40.98	-13	-27.98	-56.63	-50.2	0.76	12.13	H
	4184	-47.06	-13	-34.06	-64.35	-56.4	0.84	12.33	H
	5016	-51.86	-13	-38.86	-71.46	-61	0.94	12.23	H
	5856	-53.54	-13	-40.54	-75.23	-63.3	1.08	12.99	H
	6696	-55.70	-13	-42.70	-78.52	-64.7	0.82	11.97	H
	7528	-53.05	-13	-40.05	-76.86	-60.2	1.18	10.48	H
	1672	-47.10	-13	-34.10	-57.24	-54.1	0.53	9.68	V
	2512	-45.50	-13	-32.50	-58.25	-53.5	0.66	10.81	V



	3344	-48.68	-13	-35.68	-64.37	-57.9	0.76	12.13	V
	4184	-51.46	-13	-38.46	-68.79	-60.8	0.84	12.33	V
	5016	-48.16	-13	-35.16	-67.84	-57.3	0.94	12.23	V
	5856	-53.94	-13	-40.94	-75.68	-63.7	1.08	12.99	V
	6696	-53.00	-13	-40.00	-75.89	-62	0.82	11.97	V
	7528	-51.55	-13	-38.55	-75.39	-58.7	1.18	10.48	V
Highest	1696	-51.85	-13	-38.85	-62.24	-58.9	0.53	9.73	H
	2544	-32.89	-13	-19.89	-46.3	-40.9	0.67	10.83	H
	3400	-44.92	-13	-31.92	-61.12	-54.3	0.77	12.30	H
	4248	-49.79	-13	-36.79	-66.92	-59.1	0.84	12.30	H
	5096	-51.82	-13	-38.82	-71.69	-61.1	0.96	12.39	H
	5944	-57.02	-13	-44.02	-78.29	-66.6	1.20	12.93	H
	6792	-55.92	-13	-42.92	-78.78	-64.8	0.72	11.76	H
	1696	-51.35	-13	-38.35	-61.1	-58.4	0.53	9.73	V
	2544	-42.79	-13	-29.79	-55.93	-50.8	0.67	10.83	V
	3400	-47.12	-13	-34.12	-62.84	-56.5	0.77	12.30	V
	4248	-51.59	-13	-38.59	-70.13	-60.9	0.84	12.30	V
	5096	-52.32	-13	-39.32	-72.75	-61.6	0.96	12.39	V
	5944	-56.32	-13	-43.32	-77.77	-65.9	1.20	12.93	V
	6792	-52.72	-13	-39.72	-76.41	-61.6	0.72	11.76	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-43.55	-13	-30.55	-53.34	-50.5	0.53	9.63	H
	2472	-45.32	-13	-32.32	-58.75	-53.3	0.65	10.78	H
	3296	-57.12	-13	-44.12	-72.54	-66.2	0.76	11.99	H
	1648	-50.25	-13	-37.25	-59.74	-57.2	0.53	9.63	V
	2472	-46.92	-13	-33.92	-60.89	-54.9	0.65	10.78	V
	3296	-59.62	-13	-46.62	-75.12	-68.7	0.76	11.99	V
Middle	1672	-40.40	-13	-27.40	-50.46	-47.4	0.53	9.68	H
	2512	-46.10	-13	-33.10	-59.2	-54.1	0.66	10.81	H
	3344	-48.88	-13	-35.88	-74.93	-58.1	0.76	12.13	H
	1672	-48.60	-13	-35.60	-58.14	-55.6	0.53	9.68	V
	2512	-54.50	-13	-41.50	-67.89	-62.5	0.66	10.81	V
	3344	-59.38	-13	-46.38	-75.29	-68.6	0.76	12.13	V
Highest	1696	-42.65	-13	-29.65	-52.68	-49.7	0.53	9.73	H
	2544	-48.89	-13	-35.89	-61.93	-56.9	0.67	10.83	H
	3400	-59.32	-13	-46.32	-74.96	-68.7	0.77	12.30	H
	1696	-49.55	-13	-36.55	-59.29	-56.6	0.53	9.73	V
	2544	-50.49	-13	-37.49	-64.07	-58.5	0.67	10.83	V
	3400	-59.22	-13	-46.22	-75.02	-68.6	0.77	12.30	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-46.69	-13	-33.69	-63.68	-58.48	0.72	12.52	H
	5550	-46.62	-13	-33.62	-68.48	-58.79	1.00	13.17	H
	7404	-45.31	-13	-32.31	-70.42	-54.7	1.18	10.57	H
	9252	-46.79	-13	-33.79	-76.31	-57.3	1.39	11.89	H
	12948	-42.42	-13	-29.42	-76.76	-54.97	1.45	13.99	H
	3702	-51.54	-13	-38.54	-69.7	-63.33	0.72	12.52	V
	5550	-47.95	-13	-34.95	-69.9	-60.12	1.00	13.17	V
	7404	-45.43	-13	-32.43	-70.33	-54.82	1.18	10.57	V
	9252	-43.87	-13	-30.87	-73.15	-54.38	1.39	11.89	V
	12948	-42.06	-13	-29.06	-74.2	-54.61	1.45	13.99	V
Middle	3762	-51.74	-13	-38.74	-68.89	-63.55	0.69	12.50	H
	5640	-45.51	-13	-32.51	-67.23	-57.64	0.98	13.12	H
	7518	-47.78	-13	-34.78	-72.69	-57.05	1.18	10.45	H
	9399	-46.40	-13	-33.40	-75.87	-56.43	1.45	11.48	H
	3762	-52.95	-13	-39.95	-71.31	-64.76	0.69	12.50	V
	5640	-45.62	-13	-32.62	-67.51	-57.75	0.98	13.12	V
	7518	-48.36	-13	-35.36	-73.32	-57.63	1.18	10.45	V
	9399	-42.35	-13	-29.35	-71.61	-52.38	1.45	11.48	V
Highest	3822	-47.89	-13	-34.89	-65.16	-59.67	0.69	12.47	H
	5730	-48.17	-13	-35.17	-69.91	-60.24	0.99	13.06	H
	7638	-50.10	-13	-37.10	-75.28	-59.7	1.18	10.79	H
	9546	-45.86	-13	-32.86	-75.54	-55.48	1.67	11.28	H
	11457	-43.47	-13	-30.47	-74.89	-53.71	1.51	11.75	H
	3822	-49.71	-13	-36.71	-68.2	-61.49	0.69	12.47	V
	5730	-43.69	-13	-30.69	-65.64	-55.76	0.99	13.06	V
	7638	-49.18	-13	-36.18	-74.11	-58.78	1.18	10.79	V
	9546	-41.99	-13	-28.99	-70.98	-51.61	1.67	11.28	V
	11457	-44.65	-13	-31.65	-76.49	-54.89	1.51	11.75	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-53.46	-13	-40.46	-70.45	-65.25	0.72	12.52	H
	5550	-55.61	-13	-42.61	-77.47	-67.78	1.00	13.17	H
	7404	-53.75	-13	-40.75	-78.86	-63.14	1.18	10.57	H
	3702	-55.03	-13	-42.03	-73.19	-66.82	0.72	12.52	V
	5550	-51.55	-13	-38.55	-73.5	-63.72	1.00	13.17	V
	7404	-53.72	-13	-40.72	-78.62	-63.11	1.18	10.57	V
Middle	3762	-55.31	-13	-42.31	-72.46	-67.12	0.69	12.50	H
	5643	-55.06	-13	-42.06	-76.78	-67.19	0.98	13.11	H
	7524	-53.28	-13	-40.28	-78.2	-62.57	1.18	10.47	H
	3762	-54.34	-13	-41.34	-72.7	-66.15	0.69	12.50	V
	5643	-55.56	-13	-42.56	-77.45	-67.69	0.98	13.11	V
	7524	-53.25	-13	-40.25	-78.22	-62.54	1.18	10.47	V
Highest	3822	-53.52	-13	-40.52	-70.79	-65.3	0.69	12.47	H
	5730	-53.68	-13	-40.68	-75.42	-65.75	0.99	13.06	H
	7644	-52.53	-13	-39.53	-77.74	-62.15	1.18	10.80	H
	3822	-55.72	-13	-42.72	-74.21	-67.5	0.69	12.47	V
	5730	-53.19	-13	-40.19	-75.14	-65.26	0.99	13.06	V
	7644	-52.91	-13	-39.91	-77.9	-62.53	1.18	10.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V (RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1656	-58.53	-13	-45.53	-68.15	-65.5	0.53	9.64	H
	2480	-59.12	-13	-46.12	-72.42	-67.1	0.65	10.78	H
	3312	-58.27	-13	-45.27	-73.83	-67.4	0.76	12.04	H
	1656	-58.73	-13	-45.73	-68.34	-65.7	0.53	9.64	V
	2480	-59.62	-13	-46.62	-73.46	-67.6	0.65	10.78	V
	3312	-53.67	-13	-40.67	-69.67	-62.8	0.76	12.04	V
Middle	1672	-59.80	-13	-46.80	-69.44	-66.8	0.53	9.68	H
	2512	-60.50	-13	-47.50	-73.86	-68.5	0.66	10.81	H
	3344	-58.58	-13	-45.58	-74.45	-67.8	0.76	12.13	H
	1672	-59.40	-13	-46.40	-68.97	-66.4	0.53	9.68	V
	2512	-58.60	-13	-45.60	-72.14	-66.6	0.66	10.81	V
	3344	-56.68	-13	-43.68	-72.68	-65.9	0.76	12.13	V
Highest	1688	-55.77	-13	-42.77	-65.54	-62.8	0.53	9.71	H
	2540	-60.89	-13	-47.89	-74.08	-68.9	0.67	10.82	H
	3392	-58.44	-13	-45.44	-74.38	-67.8	0.77	12.28	H
	1688	-59.27	-13	-46.27	-68.29	-66.3	0.53	9.71	V
	2540	-60.09	-13	-47.09	-73.79	-68.1	0.67	10.82	V
	3392	-53.34	-13	-40.34	-69.12	-62.7	0.77	12.28	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II (RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3702	-43.91	-13	-30.91	-60.82	-55.7	0.72	12.52	H
	5556	-54.63	-13	-41.63	-75.89	-66.8	1.00	13.17	H
	7410	-54.22	-13	-41.22	-78.93	-63.6	1.18	10.56	H
	3702	-49.41	-13	-36.41	-67.16	-61.2	0.72	12.52	V
	5556	-54.43	-13	-41.43	-76.15	-66.6	1.00	13.17	V
	7410	-54.62	-13	-41.62	-78.93	-64	1.18	10.56	V
Middle	3762	-43.09	-13	-30.09	-59.94	-54.9	0.69	12.50	H
	5642	-55.07	-13	-42.07	-76.59	-67.2	0.98	13.11	H
	7520	-53.92	-13	-40.92	-78.28	-63.2	1.18	10.46	H
	3762	-47.79	-13	-34.79	-65.64	-59.6	0.69	12.50	V
	5642	-54.17	-13	-41.17	-75.72	-66.3	0.98	13.11	V
	7520	-53.72	-13	-40.72	-78.37	-63	1.18	10.46	V
Highest	3816	-44.31	-13	-31.31	-61.31	-56.1	0.69	12.47	H
	5723	-56.43	-13	-43.43	-77.59	-68.5	0.99	13.07	H
	7630	-52.92	-13	-39.92	-78.07	-62.5	1.18	10.76	H
	3816	-48.31	-13	-35.31	-66.59	-60.1	0.69	12.47	V
	5723	-55.53	-13	-42.53	-77.25	-67.6	0.99	13.07	V
	7630	-53.62	-13	-40.62	-78.29	-63.2	1.18	10.76	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3426	-45.20	-13	-32.20	-62.04	-56.8	0.77	12.38	H
	5142	-55.19	-13	-42.19	-75.6	-66.7	0.97	12.48	H
	6850	-55.10	-13	-42.10	-78.6	-65.9	0.83	11.63	H
	3426	-45.50	-13	-32.50	-61.89	-57.1	0.77	12.38	V
	5142	-56.69	-13	-43.69	-77.07	-68.2	0.97	12.48	V
	6850	-54.80	-13	-41.80	-78.56	-65.6	0.83	11.63	V
Middle	3468	-46.47	-13	-33.47	-63.71	-58.2	0.78	12.50	H
	5196	-55.60	-13	-42.60	-76.38	-67.2	0.99	12.59	H
	6930	-54.85	-13	-41.85	-77.82	-65.3	1.01	11.45	H
	3468	-44.17	-13	-31.17	-61.76	-55.9	0.78	12.50	V
	5196	-56.80	-13	-43.80	-77.7	-68.4	0.99	12.59	V
	6930	-54.15	-13	-41.15	-78.1	-64.6	1.01	11.45	V
Highest	3510	-49.68	-13	-36.68	-66.45	-61.5	0.78	12.60	H
	5256	-51.00	-13	-38.00	-71.95	-62.7	1.01	12.71	H
	7010	-53.38	-13	-40.38	-77.14	-63.5	1.17	11.28	H
	3510	-48.48	-13	-35.48	-66.26	-60.3	0.78	12.60	V
	5256	-54.90	-13	-41.90	-75.57	-66.6	1.01	12.71	V
	7010	-53.58	-13	-40.58	-77.43	-63.7	1.17	11.28	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.