


RF Exposure Evaluation Report

FCC ID : NM82QCD100
Equipment : Dongle
Brand Name : VIVE
Model Name : 2QCD100
Applicant : HTC Corporation
No. 88, Section 3, Zhongxing Road, Xindian
District, New Taipei City 231, Taiwan
Manufacturer : HTC Corporation
No.88, Section 3, Zhongxing Rd., Xindian Dist,
New Taipei City 231 Taiwan
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Mar. 16, 2023, and testing was started from Apr. 06, 2023 and completed on Apr. 19, 2023. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB 447498 D04 Interim General RF Exposure Guidance v01 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

History of This Test Report.....	3
1. General Description.....	4
1.1. EUT General Information	4
1.2. Testing Location Information	4
2. RF Exposure Evaluation	5
2.1. Applicable Standard	5
2.2. SAR evaluation	5
Photographs of EUT V01	

1. General Description

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Proprietary	2400-2483.5	2402-2480	GFSK

1.2. Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory			
☒ Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)		
	TEL: 886-3-327-3456		FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.			
☐ Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)		
	TEL: 886-3-318-0787		FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.			

2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01,
Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)
2.4G;D1D	2.60	3.21	5.81	0.00	2.32	0.50	B	2.788

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01 exclusion thresholds is $2.32 < 2.788$, RF exposure evaluation is not required.

————THE END————