


FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Tablet
MODEL NAME : PG41200
FCC ID : NM8PG41200
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Transmission System (DTS)

The product was received on Jan. 28, 2011 and completely tested on Mar. 03, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Testing Site	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 RF Power	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 RF Utility	9
3 TEST RESULT	10
3.1 6dB Bandwidth Measurement	10
3.2 Output Power Measurement	17
3.3 Band Edges Measurement	19
3.4 Spurious Emission Measurement	27
3.5 Power Spectral Density Measurement	37
3.6 AC Conducted Emission Measurement	44
3.7 Radiated Emission Measurement	48
3.8 Antenna Requirements	69
4 LIST OF MEASURING EQUIPMENT	70
5 UNCERTAINTY OF EVALUATION	71
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR112806B	Rev. 01	Initial issue of report	Apr. 12, 2011

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	A8.4	Power Output	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.4	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.5	15.247(e)	A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.6	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 19.0 dB at 0.31 MHz
3.7	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.91 dB at 4824 MHz
3.8	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

HTC Corporation

1F., No. 6-3, Baoqiang Rd., Xindian City, Taipei, Taiwan

1.2 Manufacturer

HTC Corporation

1F., No. 6-3, Baoqiang Rd., Xindian City, Taipei, Taiwan

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Tablet
Model Name	PG41200
FCC ID	NM8PG41200
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	11
Carrier Frequency of Each Channel	$2412+(n-1)*5$ MHz; $n=1\sim11$
Channel Spacing	5 MHz
Maximum Output Power to Antenna	802.11b : 20.14 dBm (0.10 W) 802.11g : 22.66 dBm (0.19 W) 802.11n (BW 20MHz) : 22.16 dBm (0.16 W)
Antenna Type	PIFA Antenna with gain 0 dBi
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Transmission System (DTS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	722060/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 (Measurement Guidelines of DTS)
- ANSI C63.4-2003
- IC RSS-210 Issue 8

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Power

Preliminary tests were performed in different data rate and recorded the RF power output in the following table:

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 06	2437 MHz	20.14	20.11	20.12	20.13

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 06	2437 MHz	22.66	22.65	22.2	22.24	21.85	21.82	22.16	22.24

Channel	Frequency	2.4GHz 802.11n (BW 20MHz) RF Power (dBm)							
		OFDM Data Rate							
		MCS=0	MCS=1	MCS=2	MCS=3	MCS=4	MCS=5	MCS=6	MCS=7
CH 06	2437 MHz	22.16	21.46	21.67	21.57	21.37	21.29	21.17	20.97

Remark:

1. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports.
2. The data rates of WLAN 802.11b/g/n were set in 1Mbps for 802.11b, 6Mbps for 802.11g, and MCS=0 for 802.11n (BW 20MHz), for all the test cases due to the highest RF output power.
3. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30 MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases		
Test Item	802.11b (Modulation : DSSS)	802.11g/n (Modulation : OFDM)
Conducted TCs	Mode 1 : 802.11b CH01_2412 MHz Mode 2 : 802.11b CH06_2437 MHz Mode 3 : 802.11b CH11_2462 MHz	Mode 4: 802.11g_CH01_2412 MHz Mode 5: 802.11g_CH06_2437 MHz Mode 6: 802.11g_CH11_2462 MHz Mode 7: 802.11n (BW 20M)_CH01_2412 MHz Mode 8: 802.11n (BW 20M)_CH06_2437 MHz Mode 9: 802.11n (BW 20M)_CH11_2462 MHz
Radiated TCs	Mode 1 : 802.11b CH01_2412 MHz + TC Mode 2 : 802.11b CH06_2437 MHz + TC Mode 3 : 802.11b CH11_2462 MHz + TC	Mode 4: 802.11g_CH01_2412 MHz + TC Mode 5: 802.11g_CH06_2437 MHz + TC Mode 6: 802.11g_CH11_2462 MHz + TC Mode 7: 802.11n (BW 20M)_CH01_2412 MHz + TC Mode 8: 802.11n (BW 20M)_CH06_2437 MHz + TC Mode 9: 802.11n (BW 20M)_CH11_2462 MHz + TC
AC Conducted Emission	Mode 1 : CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + GPS Rx + Battery 1 + Earphone + Adapter Mode 2 : CDMA200 BC1 Idle + Bluetooth Link + WLAN Link + GPSR Rx + Battery 2 + Earphone + Adapter	
Remark:		
1. TC stands for Test Configuration, and consists of earphone and Adapter.		
2. The worst case of conducted emission is mode 1; only the test data of it was reported.		

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

The programmed RF utility "shortcut to WifiTool.exe" is installed in EUT to provide channel selection, power level, data rate and the application type. RF Utility can send transmitting signal for all testing. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz.
In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth


Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11b 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	7.04	0.5	Pass
06	2437	7.52	0.5	Pass
11	2462	7.00	0.5	Pass


Mode 1 : 6 dB Bandwidth Plot on 802.11b Channel 01



Date: 4.FEB.2011 14:26:22

Mode 2 : 6 dB Bandwidth Plot on 802.11b Channel 06


Date: 4.FEB.2011 14:39:58

Mode 3 : 6 dB Bandwidth Plot on 802.11b Channel 11



Date: 4.FEB.2011 14:58:35



Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11g 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	15.44	0.5	Pass
06	2437	15.32	0.5	Pass
11	2462	15.08	0.5	Pass

Mode 4 : 6 dB Bandwidth Plot on 802.11g Channel 01



Date: 4.FEB.2011 15:35:18



Ref 20 dBm Att 20 dB RBW 100 kHz Delta 1 [T1] VBW 300 kHz 1.12 dB 15.32000000 MHz

Marker 1 [T1] -1.96 dBm 2.429240000 GHz

Offset 20 dB

Center 2.437 GHz 2 MHz/ Span 20 MHz

Date: 4.FEB.2011 15:22:56

1.99
p1

p2

Ref 20 dBm Att 20 dB RBW 100 kHz VBW 300 kHz SWT 20 ms Delta 1 [T1] 0.01 dB 15.080000000 MHz

20 Offset 20.4 dB

Marker 1 [T1] -3.50 dBm 2.454520000 GHz

Center 2.462 GHz Span 20 MHz


Date: 4.FEB.2011 15:10:45



Test Mode :	Mode 7, 8, 9	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11n (BW 20MHz) 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	15.42	0.5	Pass
06	2437	15.44	0.5	Pass
11	2462	15.08	0.5	Pass


Mode 7 : 6 dB Bandwidth Plot on 802.11n(BW 20MHz) Channel 01



Date: 4.FEB.2011 15:48:12




Mode 8 : 6 dB Bandwidth Plot on 802.11n(BW 20MHz) Channel 06



Date: 4.FEB.2011 16:00:32

Mode 9 : 6 dB Bandwidth Plot on 802.11n(BW 20MHz) Channel 11



Date: 4.FEB.2011 16:12:40

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the power meter by a low loss cable.
3. Measure the power by power meter.

3.2.4 Test Setup



3.2.5 Test Result of Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11b Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	17.92	30	Pass
06	2437	20.14	30	Pass
11	2462	17.32	30	Pass

Test Mode :	Mode 4, 5, 6	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11g Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	21.23	30	Pass
06	2437	22.66	30	Pass
11	2462	21.17	30	Pass

Test Mode :	Mode 7, 8, 9	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11n (BW 20MHz) Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	20.55	30	Pass
06	2437	22.16	30	Pass
11	2462	20.67	30	Pass

3.3 Band Edges Measurement

3.3.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Conducted emission test: Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Apply to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep=Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation as in FCC Section 15.35(b) and (c).

3.3.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.3.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~24℃
Test Band :	802.11b	Relative Humidity :	47~49%
Test Channel :	01	Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.42	53.34	-20.66	74	48.98	32.18	6.03	33.85	113	359	Peak
2389.42	41.18	-12.82	54	36.82	32.18	6.03	33.85	113	359	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.61	52.02	-21.98	74	47.66	32.18	6.03	33.85	100	189	Peak
2389.61	40.13	-13.87	54	35.77	32.18	6.03	33.85	100	189	Average

Test Mode :	Mode 3	Temperature :	23~24℃
Test Band :	802.11b	Relative Humidity :	47~49%
Test Channel :	11	Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.85	54.08	-19.92	74	49.52	32.28	6.18	33.9	113	356	Peak
2483.85	42.23	-11.77	54	37.67	32.28	6.18	33.9	113	356	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	53.34	-20.66	74	48.78	32.28	6.18	33.9	100	180	Peak
2483.5	41.39	-12.61	54	36.83	32.28	6.18	33.9	100	180	Average



Test Mode :	Mode 4	Temperature :	23~24℃
Test Band :	802.11g	Relative Humidity :	47~49%
Test Channel :	01	Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	65.34	-8.66	74	60.98	32.18	6.03	33.85	114	358	Peak
2389.99	45.4	-8.6	54	41.04	32.18	6.03	33.85	114	358	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	61.94	-12.06	74	57.58	32.18	6.03	33.85	100	190	Peak
2389.99	44.16	-9.84	54	39.8	32.18	6.03	33.85	100	190	Average

Test Mode :	Mode 6	Temperature :	23~24℃
Test Band :	802.11g	Relative Humidity :	47~49%
Test Channel :	11	Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.66	61.51	-12.49	74	56.95	32.28	6.18	33.9	113	25	Peak
2483.66	42.13	-11.87	54	37.57	32.28	6.18	33.9	113	25	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	61.97	-12.03	74	57.41	32.28	6.18	33.9	100	180	Peak
2483.5	41.04	-12.96	54	36.48	32.28	6.18	33.9	100	180	Average



Test Mode :	Mode 7	Temperature :	23~24℃
Test Band :	802.11n (BW 20MHz)	Relative Humidity :	47~49%
Test Channel :	01	Test Engineer :	David Yang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.61	65.8	-8.2	74	61.44	32.18	6.03	33.85	113	0	Peak
2389.61	44.58	-9.42	54	40.22	32.18	6.03	33.85	113	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.42	61.72	-12.28	74	57.36	32.18	6.03	33.85	100	192	Peak
2389.42	42.31	-11.69	54	37.95	32.18	6.03	33.85	100	192	Average

Test Mode :	Mode 9	Temperature :	23~24℃
Test Band :	802.11n (BW 20MHz)	Relative Humidity :	47~49%
Test Channel :	11	Test Engineer :	David Yang


ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	59.88	-14.12	74	55.32	32.28	6.18	33.9	112	26	Peak
2483.5	41.64	-12.36	54	37.08	32.28	6.18	33.9	112	26	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	55.23	-18.77	74	50.67	32.28	6.18	33.9	115	3	Peak
2483.5	37.76	-16.24	54	33.2	32.28	6.18	33.9	115	3	Average

3.3.6 Test Plots of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	50~53%
Test Channel :	01 and 11	Test Engineer :	Phoenix Chen

Low Band Edge Plot on 802.11b Channel 01



Date: 4.FEB.2011 14:27:33

High Band Edge Plot on 802.11b Channel 11




Date: 4.FEB.2011 14:59:23




Test Mode :	Mode 4 and 6	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	50~53%
Test Channel :	01 and 11	Test Engineer :	Phoenix Chen

Low Band Edge Plot on 802.11g Channel 01



Date: 4.FEB.2011 15:36:29

High Band Edge Plot on 802.11g Channel 11



Date: 4.FEB.2011 15:11:33



Low Band Edge Plot on 802.11n (BW 20MHz) Channel 01



High Band Edge Plot on 802.11n (BW 20MHz) Channel 11



3.4 Spurious Emission Measurement

3.4.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.4.4 Test Setup



3.4.5 Test Plots of Spurious Emission


Test Mode :	Mode 1	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 14:37:29

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 14:37:46




Test Mode :	Mode 2	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 14:56:50

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 14:57:07




Test Mode :	Mode 3	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 15:08:47

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 15:09:04




Test Mode :	Mode 4	Temperature :	24~26℃
Test Band :	802.11g	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 15:45:58


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 15:46:16



Test Mode :	Mode 5	Temperature :	24~26
Test Band :	802.11g	Relative Humidity :	50~53
Test Channel :	06	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz


Date: 4.FEB.2011 15:32:58

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz


Date: 4.FEB.2011 15:33:16



Test Mode :	Mode 6	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz

Date: 4.FEB.2011 15:21:01


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz

Date: 4.FEB.2011 15:21:19




Test Mode :	Mode 7	Temperature :	24~26℃
Test Band :	802.11n (BW 20MHz)	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 15:58:56

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 15:59:14




Test Mode :	Mode 8	Temperature :	24~26℃
Test Band :	802.11n (BW 20MHz)	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 4.FEB.2011 16:10:10


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 4.FEB.2011 16:10:28



Test Mode :	Mode 9	Temperature :	24~26°C
Test Band :	802.11n (BW 20MHz)	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz

Date: 4.FEB.2011 16:23:10

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz

Date: 4.FEB.2011 16:23:27

3.5 Power Spectral Density Measurement

3.5.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The test follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Take the measured data from spectrum analyzer.

3.5.4 Test Setup




3.5.5 Test Result of Power Spectral Density

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11b Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-5.94	8	Pass
06	2437	-3.50	8	Pass
11	2462	-6.32	8	Pass


Mode 1 : PSD Plot on 802.11b Channel 01



Date: 4.FEB.2011 14:37:06




Mode 2 : PSD Plot on 802.11b Channel 06



Date: 4.FEB.2011 14:56:27

Mode 3 : PSD Plot on 802.11b Channel 11




Date: 4.FEB.2011 15:08:24



Test Mode :	Mode 4, 5, 6	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	802.11g Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-12.77	8	Pass
06	2437	-11.27	8	Pass
11	2462	-12.66	8	Pass


Mode 4 : PSD Plot on 802.11g Channel 01



Date: 4.FEB.2011 15:45:36




Mode 5 : PSD Plot on 802.11g Channel 06



Date: 4.FEB.2011 15:32:36


Mode 6 : PSD Plot on 802.11g Channel 11



Date: 4.FEB.2011 15:20:39

Test Mode :	Mode 7, 8, 9	Temperature :	24~26℃
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%


Channel	Frequency (MHz)	802.11n (BW 20MHz) Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-12.41	8	Pass
06	2437	-11.00	8	Pass
11	2462	-12.49	8	Pass

Mode 7 : PSD Plot on 802.11n (BW 20MHz) Channel 01


Date: 4.FEB.2011 15:58:34




Mode 8 : PSD Plot on 802.11n (BW 20MHz) Channel 06



Date: 4.FEB.2011 16:09:48

Mode 9 : PSD Plot on 802.11n (BW 20MHz) Channel 11



Date: 4.FEB.2011 16:22:47

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Chiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + GPS Rx + Battery 1 + Earphone + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	41.3	Off	L1	19.4	24.7	66.0
0.190000	43.2	Off	L1	19.4	20.8	64.0
0.318000	37.4	Off	L1	19.3	22.4	59.8
0.518000	34.0	Off	L1	19.3	22.0	56.0
0.734000	34.5	Off	L1	19.4	21.5	56.0
1.126000	34.4	Off	L1	19.4	21.6	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	16.2	Off	L1	19.4	39.8	56.0
0.190000	32.9	Off	L1	19.4	21.1	54.0
0.318000	30.8	Off	L1	19.3	19.0	49.8
0.518000	24.2	Off	L1	19.3	21.8	46.0
0.734000	23.2	Off	L1	19.4	22.8	46.0
1.126000	24.9	Off	L1	19.4	21.1	46.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Chiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	CDMA2000 BC0 Idle + Bluetooth Link + WLAN Link + GPS Rx + Battery 1 + Earphone + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	39.8	Off	N	19.4	25.8	65.6
0.198000	41.7	Off	N	19.3	22.0	63.7
0.270000	33.8	Off	N	19.3	27.3	61.1
0.406000	32.7	Off	N	19.4	25.0	57.7
1.214000	34.9	Off	N	19.5	21.1	56.0
1.462000	34.9	Off	N	19.5	21.1	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	14.8	Off	N	19.4	40.8	55.6
0.198000	28.0	Off	N	19.3	25.7	53.7
0.270000	22.0	Off	N	19.3	29.1	51.1
0.406000	23.0	Off	N	19.4	24.7	47.7
1.214000	24.5	Off	N	19.5	21.5	46.0
1.462000	24.2	Off	N	19.5	21.8	46.0

3.7 Radiated Emission Measurement

3.7.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


- The testing follows the guidelines in FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.7.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	David Yang	Temperature :	23~24℃	
		Relative Humidity :	47~49%	

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.7.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	23~24℃
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.81	19.72	-20.28	40	34.37	16.27	0.54	31.46	-	-	Peak
161.49	17.66	-25.84	43.5	37.7	10.26	1.22	31.52	-	-	Peak
257.61	23.85	-22.15	46	40.9	12.79	1.58	31.42	-	-	Peak
391.7	25.98	-20.02	46	38.74	16.32	2.12	31.2	131	145	Peak
589.8	23	-23	46	31.66	19.61	2.66	30.93	-	-	Peak
687.8	25.67	-20.33	46	32.84	20.75	2.91	30.83	-	-	Peak
2389.42	53.34	-20.66	74	48.98	32.18	6.03	33.85	113	359	Peak
2389.42	41.18	-12.82	54	36.82	32.18	6.03	33.85	113	359	Average
2412	104.74	-	-	100.34	32.2	6.07	33.87	113	359	Peak
2412	100.89	-	-	96.49	32.2	6.07	33.87	113	359	Average
2484	36.38	-17.62	54	31.82	32.28	6.18	33.9	113	359	Average
2484	48.04	-25.96	74	43.48	32.28	6.18	33.9	113	359	Peak
4824	51.18	-22.82	74	64.44	34.07	9.12	56.45	112	301	Peak
4824	48.64	-5.36	54	61.9	34.07	9.12	56.45	112	301	Average

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.62	23.48	-16.52	40	38.35	16.04	0.55	31.46	-	-	Peak
54.57	24.14	-15.86	40	47.73	7.24	0.72	31.55	-	-	Peak
101.01	34.51	-8.99	43.5	55.18	9.87	1	31.54	112	91	Peak
343.4	21.58	-24.42	46	36.15	14.81	1.92	31.3	-	-	Peak
491.8	21.14	-24.86	46	31.7	18.09	2.42	31.07	-	-	Peak
687.8	24.47	-21.53	46	31.64	20.75	2.91	30.83	-	-	Peak
2389.61	52.02	-21.98	74	47.66	32.18	6.03	33.85	100	189	Peak
2389.61	40.13	-13.87	54	35.77	32.18	6.03	33.85	100	189	Average
2412	102.72	-	-	98.32	32.2	6.07	33.87	100	189	Peak
2412	98.61	-	-	94.21	32.2	6.07	33.87	100	189	Average
2484	35.25	-18.75	54	30.69	32.28	6.18	33.9	100	189	Average
2484	47.38	-26.62	74	42.82	32.28	6.18	33.9	100	189	Peak
4824	51.56	-22.44	74	64.82	34.07	9.12	56.45	102	310	Peak
4824	49.09	-4.91	54	62.35	34.07	9.12	56.45	102	310	Average

Test Mode :	Mode 2	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.7	18.16	-21.84	40	33.27	15.8	0.56	31.47	-	-	Peak
101.82	16.1	-27.4	43.5	36.68	9.96	1	31.54	-	-	Peak
295.14	23.51	-22.49	46	39.73	13.38	1.73	31.33	-	-	Peak
391.7	26.13	-19.87	46	38.89	16.32	2.12	31.2	141	158	Peak
491.8	24.97	-21.03	46	35.53	18.09	2.42	31.07	-	-	Peak
589.8	23.96	-22.04	46	32.62	19.61	2.66	30.93	-	-	Peak
2390	48.35	-25.65	74	43.99	32.18	6.03	33.85	113	7	Peak
2390	35.75	-18.25	54	31.39	32.18	6.03	33.85	113	7	Average
2437	106.45	-	-	101.98	32.24	6.11	33.88	113	7	Peak
2437	102.41	-	-	97.94	32.24	6.11	33.88	113	7	Average
2484	48.35	-25.65	74	43.79	32.28	6.18	33.9	113	7	Peak
2484	36.93	-17.07	54	32.37	32.28	6.18	33.9	113	7	Average
4874	46.75	-27.25	74	60.03	34.08	9.13	56.49	100	0	Peak

Test Mode :	Mode 2	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
56.46	25.9	-14.1	40	50	6.71	0.74	31.55	111	205	Peak
101.01	25.4	-18.1	43.5	46.07	9.87	1	31.54	-	-	Peak
236.82	26.39	-19.61	46	44.6	11.71	1.51	31.43	-	-	Peak
343.4	22.53	-23.47	46	37.1	14.81	1.92	31.3	-	-	Peak
491.8	21.58	-24.42	46	32.14	18.09	2.42	31.07	-	-	Peak
687.8	25.27	-20.73	46	32.44	20.75	2.91	30.83	-	-	Peak
2390	48.38	-25.62	74	44.02	32.18	6.03	33.85	100	188	Peak
2390	35.24	-18.76	54	30.88	32.18	6.03	33.85	100	188	Average
2437	104.81	-	-	100.34	32.24	6.11	33.88	100	188	Peak
2437	100.5	-	-	96.03	32.24	6.11	33.88	100	188	Average
2484	48.46	-25.54	74	43.9	32.28	6.18	33.9	100	188	Peak
2484	36.22	-17.78	54	31.66	32.28	6.18	33.9	100	188	Average
4874	48.91	-25.09	74	62.18	34.08	9.14	56.49	100	0	Peak

Test Mode :	Mode 3	Temperature :	23~24℃
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
48.36	20.55	-19.45	40	42.32	9.08	0.68	31.53	-	-	Peak
147.18	16.96	-26.54	43.5	36.07	11.24	1.21	31.56	-	-	Peak
254.1	19.15	-26.85	46	36.28	12.73	1.55	31.41	-	-	Peak
343.4	30.78	-15.22	46	45.35	14.81	1.92	31.3	126	195	Peak
491.8	24.94	-21.06	46	35.5	18.09	2.42	31.07	-	-	Peak
687.8	25.34	-20.66	46	32.51	20.75	2.91	30.83	-	-	Peak
2382	45.72	-28.28	74	41.38	32.16	6.03	33.85	113	356	Peak
2382	34.33	-19.67	54	29.99	32.16	6.03	33.85	113	356	Average
2462	102.66	-	-	98.15	32.26	6.14	33.89	113	356	Average
2462	106.76	-	-	102.25	32.26	6.14	33.89	113	356	Peak
2483.85	54.08	-19.92	74	49.52	32.28	6.18	33.9	113	356	Peak
2483.85	42.23	-11.77	54	37.67	32.28	6.18	33.9	113	356	Average
4924	48.01	-25.99	74	61.29	34.09	9.15	56.52	100	0	Peak

Test Mode :	Mode 3	Temperature :	23~24℃
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
54.3	26	-14	40	49.59	7.24	0.72	31.55	123	144	Peak
101.01	23.17	-20.33	43.5	43.84	9.87	1	31.54	-	-	Peak
269.22	29.79	-16.21	46	46.54	12.98	1.64	31.37	-	-	Peak
343.4	21.8	-24.2	46	36.37	14.81	1.92	31.3	-	-	Peak
491.8	21.64	-24.36	46	32.2	18.09	2.42	31.07	-	-	Peak
687.8	25.52	-20.48	46	32.69	20.75	2.91	30.83	-	-	Peak
2382	45.54	-28.46	74	41.2	32.16	6.03	33.85	100	180	Peak
2382	33.3	-20.7	54	28.96	32.16	6.03	33.85	100	180	Average
2462	99.88	-	-	95.37	32.26	6.14	33.89	100	180	Average
2462	103.91	-	-	99.4	32.26	6.14	33.89	100	180	Peak
2483.5	53.34	-20.66	74	48.78	32.28	6.18	33.9	100	180	Peak
2483.5	41.39	-12.61	54	36.83	32.28	6.18	33.9	100	180	Average
4924	49.3	-24.7	74	62.58	34.09	9.15	56.52	100	0	Peak

Test Mode :	Mode 4	Temperature :	23~24°C
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.7	18.13	-21.87	40	33.24	15.8	0.56	31.47	-	-	Peak
184.17	20.61	-22.89	43.5	41.82	9.05	1.26	31.52	-	-	Peak
269.22	23.8	-22.2	46	40.55	12.98	1.64	31.37	-	-	Peak
343.4	30.67	-15.33	46	45.24	14.81	1.92	31.3	124	93	Peak
491.8	24.77	-21.23	46	35.33	18.09	2.42	31.07	-	-	Peak
687.8	25.62	-20.38	46	32.79	20.75	2.91	30.83	-	-	Peak
2389.99	65.34	-8.66	74	60.98	32.18	6.03	33.85	114	358	Peak
2389.99	45.4	-8.6	54	41.04	32.18	6.03	33.85	114	358	Average
2412	103.96	-	-	99.56	32.2	6.07	33.87	114	358	Peak
2412	91.49	-	-	87.09	32.2	6.07	33.87	114	358	Average
2484	35.02	-18.98	54	30.46	32.28	6.18	33.9	114	358	Average
2484	47.78	-26.22	74	43.22	32.28	6.18	33.9	114	358	Peak

Test Mode :	Mode 4	Temperature :	23~24℃
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
55.65	27.49	-12.51	40	51.34	6.97	0.73	31.55	109	354	Peak
101.01	24.49	-19.01	43.5	45.16	9.87	1	31.54	-	-	Peak
295.41	30.19	-15.81	46	46.38	13.4	1.74	31.33	-	-	Peak
302.1	23.53	-22.47	46	39.53	13.55	1.78	31.33	-	-	Peak
491.8	20.99	-25.01	46	31.55	18.09	2.42	31.07	-	-	Peak
687.8	25.26	-20.74	46	32.43	20.75	2.91	30.83	-	-	Peak
2389.99	61.94	-12.06	74	57.58	32.18	6.03	33.85	100	190	Peak
2389.99	44.16	-9.84	54	39.8	32.18	6.03	33.85	100	190	Average
2412	101.32	-	-	96.92	32.2	6.07	33.87	100	190	Peak
2412	88.66	-	-	84.26	32.2	6.07	33.87	100	190	Average
2484	34.07	-19.93	54	29.51	32.28	6.18	33.9	100	190	Average
2484	46.84	-27.16	74	42.28	32.28	6.18	33.9	100	190	Peak
4824	46.93	-27.07	74	60.19	34.07	9.12	56.45	100	0	Peak

Test Mode :	Mode 5	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
33.78	17.2	-22.8	40	32.53	15.57	0.57	31.47	-	-	Peak
101.82	15.83	-27.67	43.5	36.41	9.96	1	31.54	-	-	Peak
233.85	21.05	-24.95	46	39.48	11.5	1.5	31.43	-	-	Peak
343.4	30.46	-15.54	46	45.03	14.81	1.92	31.3	127	142	Peak
491.8	24.89	-21.11	46	35.45	18.09	2.42	31.07	-	-	Peak
687.8	26.17	-19.83	46	33.34	20.75	2.91	30.83	-	-	Peak
2390	48.03	-25.97	74	43.67	32.18	6.03	33.85	114	24	Peak
2390	34.1	-19.9	54	29.74	32.18	6.03	33.85	114	24	Average
2437	103.65	-	-	99.2	32.22	6.11	33.88	114	24	Peak
2437	91.94	-	-	87.47	32.24	6.11	33.88	114	24	Average
2484	48.57	-25.43	74	44.01	32.28	6.18	33.9	114	24	Peak
2484	34.71	-19.29	54	30.15	32.28	6.18	33.9	114	24	Average

Test Mode :	Mode 5	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
55.38	28.08	-11.92	40	51.93	6.97	0.73	31.55	133	185	Peak
101.01	25.95	-17.55	43.5	46.62	9.87	1	31.54	-	-	Peak
246.81	28.62	-17.38	46	46.04	12.46	1.53	31.41	-	-	Peak
343.4	22.28	-23.72	46	36.85	14.81	1.92	31.3	-	-	Peak
592.6	21.35	-24.65	46	29.96	19.65	2.67	30.93	-	-	Peak
687.8	25.03	-20.97	46	32.2	20.75	2.91	30.83	-	-	Peak
2390	46.91	-27.09	74	42.55	32.18	6.03	33.85	100	12	Peak
2390	33.78	-20.22	54	29.42	32.18	6.03	33.85	100	12	Average
2437	101.47	-	-	97.02	32.22	6.11	33.88	100	12	Peak
2437	89.52	-	-	85.05	32.24	6.11	33.88	100	12	Average
2484	45.91	-28.09	74	41.35	32.28	6.18	33.9	100	12	Peak
2484	33.15	-20.85	54	28.59	32.28	6.18	33.9	100	12	Average

Test Mode :	Mode 6	Temperature :	23~24℃
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.97	17.63	-22.37	40	32.74	15.8	0.56	31.47	-	-	Peak
169.86	16.41	-27.09	43.5	36.93	9.77	1.23	31.52	-	-	Peak
295.14	23.5	-22.5	46	39.72	13.38	1.73	31.33	-	-	Peak
343.4	30.46	-15.54	46	45.03	14.81	1.92	31.3	131	175	Peak
491.8	25.26	-20.74	46	35.82	18.09	2.42	31.07	-	-	Peak
687.8	26.04	-19.96	46	33.21	20.75	2.91	30.83	-	-	Peak
2382	44.8	-29.2	74	40.46	32.16	6.03	33.85	113	25	Peak
2382	33.48	-20.52	54	29.14	32.16	6.03	33.85	113	25	Average
2462	92.21	-	-	87.7	32.26	6.14	33.89	113	25	Average
2462	104.82	-	-	100.31	32.26	6.14	33.89	113	25	Peak
2483.66	61.51	-12.49	74	56.95	32.28	6.18	33.9	113	25	Peak
2483.66	42.13	-11.87	54	37.57	32.28	6.18	33.9	113	25	Average

Test Mode :	Mode 6	Temperature :	23~24℃
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
53.49	27.6	-12.4	40	50.93	7.5	0.72	31.55	108	342	Peak
101.82	24.16	-19.34	43.5	44.74	9.96	1	31.54	-	-	Peak
219.54	31.83	-14.17	46	51.41	10.47	1.41	31.46	-	-	Peak
343.4	21.77	-24.23	46	36.34	14.81	1.92	31.3	-	-	Peak
491.8	21.75	-24.25	46	32.31	18.09	2.42	31.07	-	-	Peak
687.8	24.34	-21.66	46	31.51	20.75	2.91	30.83	-	-	Peak
2390	44.84	-29.16	74	40.48	32.18	6.03	33.85	100	180	Peak
2390	33.19	-20.81	54	28.83	32.18	6.03	33.85	100	180	Average
2462	88.72	-	-	84.21	32.26	6.14	33.89	100	180	Average
2462	101.51	-	-	97	32.26	6.14	33.89	100	180	Peak
2483.5	61.97	-12.03	74	57.41	32.28	6.18	33.9	100	180	Peak
2483.5	41.04	-12.96	54	36.48	32.28	6.18	33.9	100	180	Average



Test Mode :	Mode 7	Temperature :	23~24℃
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.62	17.48	-22.52	40	32.35	16.04	0.55	31.46	-	-	Peak
147.18	16.7	-26.8	43.5	35.81	11.24	1.21	31.56	-	-	Peak
254.37	21.39	-24.61	46	38.52	12.73	1.55	31.41	-	-	Peak
343.4	31.13	-14.87	46	45.7	14.81	1.92	31.3	141	122	Peak
491.8	25	-21	46	35.56	18.09	2.42	31.07	-	-	Peak
687.8	25.53	-20.47	46	32.7	20.75	2.91	30.83	-	-	Peak
2389.61	65.8	-8.2	74	61.44	32.18	6.03	33.85	113	0	Peak
2389.61	44.58	-9.42	54	40.22	32.18	6.03	33.85	113	0	Average
2412	103.02	-	-	98.62	32.2	6.07	33.87	113	0	Peak
2412	89.67	-	-	85.27	32.2	6.07	33.87	113	0	Average
2486	35.17	-18.83	54	30.61	32.28	6.18	33.9	113	0	Average
2486	47.97	-26.03	74	43.41	32.28	6.18	33.9	113	0	Peak



Test Mode :	Mode 7	Temperature :	23~24℃
Test Channel :	01	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
54.57	24.39	-15.61	40	47.98	7.24	0.72	31.55	112	74	Peak
101.82	23.74	-19.76	43.5	44.32	9.96	1	31.54	-	-	Peak
244.65	27.46	-18.54	46	45.09	12.26	1.53	31.42	-	-	Peak
340.6	24.67	-21.33	46	39.36	14.72	1.89	31.3	-	-	Peak
491.8	21.95	-24.05	46	32.51	18.09	2.42	31.07	-	-	Peak
750.1	23.12	-22.88	46	29.09	21.67	3.06	30.7	-	-	Peak
2389.42	61.72	-12.28	74	57.36	32.18	6.03	33.85	100	192	Peak
2389.42	42.31	-11.69	54	37.95	32.18	6.03	33.85	100	192	Average
2412	100.18	-	-	95.78	32.2	6.07	33.87	100	192	Peak
2412	86.42	-	-	82.02	32.2	6.07	33.87	100	192	Average
2484	33.96	-20.04	54	29.4	32.28	6.18	33.9	100	192	Average
2484	45.8	-28.2	74	41.24	32.28	6.18	33.9	100	192	Peak

Test Mode :	Mode 8	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.97	17.52	-22.48	40	32.63	15.8	0.56	31.47	-	-	Peak
147.18	17	-26.5	43.5	36.11	11.24	1.21	31.56	-	-	Peak
234.93	21.23	-24.77	46	39.59	11.57	1.5	31.43	-	-	Peak
343.4	30.42	-15.58	46	44.99	14.81	1.92	31.3	122	148	Peak
491.8	24.77	-21.23	46	35.33	18.09	2.42	31.07	-	-	Peak
786.5	29.69	-16.31	46	35	22.26	3.12	30.69	-	-	Peak
2390	45.49	-28.51	74	41.13	32.18	6.03	33.85	111	352	Peak
2390	33.33	-20.67	54	28.97	32.18	6.03	33.85	111	352	Average
2437	103.21	-	-	98.74	32.24	6.11	33.88	111	352	Peak
2437	90.03	-	-	85.56	32.24	6.11	33.88	111	352	Average
2484	47.19	-26.81	74	42.63	32.28	6.18	33.9	111	352	Peak
2484	34.86	-19.14	54	30.3	32.28	6.18	33.9	111	352	Average

Test Mode :	Mode 8	Temperature :	23~24℃
Test Channel :	06	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
54.57	26.15	-13.85	40	49.74	7.24	0.72	31.55	114	299	Peak
101.01	24.42	-19.08	43.5	45.09	9.87	1	31.54	-	-	Peak
219.54	27.81	-18.19	46	47.39	10.47	1.41	31.46	-	-	Peak
343.4	22.19	-23.81	46	36.76	14.81	1.92	31.3	-	-	Peak
491.8	21.24	-24.76	46	31.8	18.09	2.42	31.07	-	-	Peak
687.8	23.39	-22.61	46	30.56	20.75	2.91	30.83	-	-	Peak
2390	44.81	-29.19	74	40.45	32.18	6.03	33.85	126	7	Peak
2390	33.16	-20.84	54	28.8	32.18	6.03	33.85	126	7	Average
2437	100.63	-	-	96.18	32.22	6.11	33.88	126	7	Peak
2437	87.61	-	-	83.14	32.24	6.11	33.88	126	7	Average
2484	45.07	-28.93	74	40.51	32.28	6.18	33.9	126	7	Peak
2484	33.32	-20.68	54	28.76	32.28	6.18	33.9	126	7	Average

Test Mode :	Mode 9	Temperature :	23~24℃
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.05	18.11	-21.89	40	33.44	15.57	0.57	31.47	-	-	Peak
101.82	16.58	-26.92	43.5	37.16	9.96	1	31.54	-	-	Peak
241.14	21.36	-24.64	46	39.2	12.05	1.53	31.42	-	-	Peak
343.4	30.72	-15.28	46	45.29	14.81	1.92	31.3	112	185	Peak
491.8	25.1	-20.9	46	35.66	18.09	2.42	31.07	-	-	Peak
786.5	28.94	-17.06	46	34.25	22.26	3.12	30.69	-	-	Peak
2388	45.56	-28.44	74	41.2	32.18	6.03	33.85	112	26	Peak
2388	33.16	-20.84	54	28.8	32.18	6.03	33.85	112	26	Average
2462	91.35	-	-	86.84	32.26	6.14	33.89	112	26	Average
2462	103.51	-	-	99	32.26	6.14	33.89	112	26	Peak
2483.5	59.88	-14.12	74	55.32	32.28	6.18	33.9	112	26	Peak
2483.5	41.64	-12.36	54	37.08	32.28	6.18	33.9	112	26	Average

Test Mode :	Mode 9	Temperature :	23~24°C
Test Channel :	11	Relative Humidity :	47~49%
Test Engineer :	David Yang	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
54.3	26.85	-13.15	40	50.44	7.24	0.72	31.55	116	101	Peak
132.33	27.07	-16.43	43.5	45.9	11.58	1.16	31.57	-	-	Peak
255.45	30.16	-15.84	46	47.27	12.75	1.56	31.42	-	-	Peak
309.8	23.39	-22.61	46	39.17	13.76	1.79	31.33	-	-	Peak
491.8	20.48	-25.52	46	31.04	18.09	2.42	31.07	-	-	Peak
687.8	24.31	-21.69	46	31.48	20.75	2.91	30.83	-	-	Peak
2318	44.96	-29.04	74	40.77	32.09	5.92	33.82	115	3	Peak
2318	32.64	-21.36	54	28.45	32.09	5.92	33.82	115	3	Average
2462	87.36	-	-	82.85	32.26	6.14	33.89	115	3	Average
2462	100.43	-	-	95.92	32.26	6.14	33.89	115	3	Peak
2483.5	55.23	-18.77	74	50.67	32.28	6.18	33.9	115	3	Peak
2483.5	37.76	-16.24	54	33.2	32.28	6.18	33.9	115	3	Average

3.8 Antenna Requirements

3.8.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.8.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.8.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Jun. 08, 2009	Jun. 07, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 11, 2010	Jun. 10, 2011	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	N/A	Feb. 18, 2011	Feb. 17, 2012	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	N/A	Feb. 18, 2011	Feb. 17, 2012	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Jul. 30, 2010	Jul. 29, 2011	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9KHz – 30MHz	Dec. 03, 2010	Dec. 02, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9KHz – 30MHz	Dec. 01, 2010	Nov. 30, 2011	Conduction (CO05-HY)
AC Power Source	APC	APC-1000 W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
System Simulator	R&S	CMU200	117591	N/A	Oct. 18, 2010	Oct. 17, 2011	Conduction (CO05-HY)
GPS Station	T&E	GS-50	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32 dB.GAIN	Mar. 29, 2010	Mar. 28, 2011	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal ($k=2$)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal ($k=2$)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal ($k=2$)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				