

Antenna H/W Specification

Project Name :	Dunton	Date:	07/07/2005
Project Manager:	Mason Chiang	Rev.:	1.2

Countersign:

Chung-I Chou _____

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

Revision History

Revision	Revision History	Date	Author(s)
1.0		01/24/2005	Chung-I Chou
1.1	Spec modification	06/24/2005	Chung-I Chou
1.2	Spec modification	07/07/2005	Chung-I Chou

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

CONTENTS

Embedded Penta-Band Antenna Specification	P.4
Embedded Bluetooth Antenna Specification.....	P.10

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

Embedded Penta-Band Antenna

1. Overview

The document is the specification of the embedded Penta-band antenna for PHONE applications. Penta-band includes GSM850, GSM900, DCS1800, PCS1900, WLAN2400.

1.1 Denotations

dBi: Decibel relative isotropic antenna

VSWR: **V**oltage **S**tanding **W**ave **R**atio

Tx: Transmit frequency

Rx: Receive frequency

GSM: **G**lobal **S**ervice for **M**obile communication

PCS: **P**ersonal **C**ommunication **S**ystem

DCS: **D**igital **C**ommunication **S**ystem

WLAN: **W**ireless **L**ocal **A**rea **N**etwork

SAR: **S**pecific **A**bsorption **R**ate

Peak Gain: The peak value of the antenna gain

Average Gain: The average value of the antenna gain

2. Measurement Parameters

2.1 VSWR

VSWR indicates the matching characteristics of the antenna. VSWR can be measured by a network analyzer.

2.2 Antenna Gain and Pattern

Antenna gain and far-field pattern can be determined by two measurement skills, depending on the own equipments. One is the far-field measurement; the other is the 3-D measurement system.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

3. Electrical Requirements

3.1 VSWR

	GSM850	GSM900	DCS1800	PCS1900	WLAN2400
Free space	2.5:1	2.5:1	2.5:1	2.5:1	2.5:1

Notably: The VSWR value will be degraded due to mechanical and space constrains.

3.2 Gain and Patterns (Total Field)

	GSM850	GSM900	DCS1800	PCS1900	WLAN2400
Peak gain	0.0 dBi	0.0 dBi	0.0 dBi	0.0 dBi	0.0 dBi
Average gain	-4.0 dBi	-4.0 dBi	-4.0 dBi	-4.0 dBi	-4.0 dBi

Notably: The target values (peak and average gains) will be degraded due to mechanical and space constrains.

3.3 Total Efficiency

	GSM900	DCS1800	PCS1900	WLAN2400
Total efficiency	50%	40%	40%	40%

Notably: The antenna total efficiency will be degraded due to mechanical and space constrains.

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

4. Environmental Performance

4.1 Test Methods

All of the tests should be carried out with the antenna mounted on the real PHONE to the maximum extent that is possible. Notably, T_o is $20^{\circ}\text{C} \pm 3^{\circ}\text{C}$ (T_o : room temperature).

4.1.1 Temperature (steady state)

The test is according to IEC 60068-2-1 Test Ab (Cold) and IEC 60068-2-2 Test Bb (Dry heat).

The antenna is stored in a climatic chamber with the following climate and time periods (Figs. 1 and 2):

Low temperature/Duration: $T_1 = -5^{\circ}\text{C} / t_1 = 48\text{hr}$ (Fig. 1)

High temperature/Duration: $T_2 = +45^{\circ}\text{C} / t_2 = 48\text{hr}$ (Fig. 2)




Fig. 1

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL




Fig. 2

4.1.2 Temperature (cycling)

The test is according to IEC 60068-2-14 Test Na (Change of temperature, Fig. 3)

Low temperature (T_1): -5°C

High temperature (T_2): $+45^{\circ}\text{C}$

Steady state time (t_1): 1hr

Transition time (t_2): $<5\text{ min}$

Duration: 4cycles

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL




Fig. 3

4.1.3 Vibration test

The test is according to IEC 60068-2-6 Test Fc and IEC 60068-2-64 Test Fh

(a) Sinusoidal: (IEC 60068-2-6 Test Fc)

10-15.8 Hz Amplitude: 2.0 mm

15.8-1000-15.8 Hz Acceleration: 20 m/s²

15-8-10 Hz Amplitude: 2.0 mm

1 Octave/minute

Direction: x-, y-, and z-axis

Duration: 3cycles/axis (One cycle is from 10 Hz to 1000 Hz and back to 10 Hz)

(b) Random: (IEC 60068-2-64 Test Fh)

Frequency: 10-1000 Hz

3 axes, 1hr/axis, 6 Grms

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

4.2 Environmental Requirements

4.2.1 Temperature (steady state)

The antenna should fulfill the mechanical and electrical requirements after recovered to the room temperature. No visual deterioration should occur.

4.2.2 Temperature (cycling)

The antenna should fulfill the mechanical and electrical requirements after recovered to the room temperature.

4.2.3 Vibration test

The antenna should fulfill the mechanical and electrical requirements after the test.

5. Antenna Materials

The antenna can not have the materials of plumbum (Pb), halogen and mercury (Hg).

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL

Embedded Bluetooth Antenna

Frequency range	2400 MHz ~ 2500 MHz
VSWR	2.5 : 1
Peak gain	0 dBi
Average gain	4.0 dBi
Reference impedance	50 ohm

Notably: The VSWR and gain values will be degraded due to mechanical and space constrains.

PROPRIETARY NOTE


THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO HIGH TECH COMPUTER CORP. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF HIGH TECH COMPUTER CORP.

HTC CONFIDENTIAL


Model	Faraday 1.5 第1頁											
Test / Position	Gain / Free Space (TX)											
Band	GSM850			GSM900			GSM1800			GSM1900		
Channel	824.2	836.4	848.8	880.2	898.4	914.8	1710.2	1747.4	1784.8	1850.2	1880	1909.8
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-3.69	-3.38	-3.38	-3.52	-3.69	-4.19	-2.84	-2.24	-1.85	-2.16	-2.07	-2.28
Peak EIRP (dBm)	-1.42	-1.08	-1.00	-1.26	-1.40	-1.86	2.76	3.34	3.70	3.11	3.13	2.82
Directivity (dBi)	2.27	2.31	2.38	2.26	2.29	2.33	5.60	5.58	5.55	5.27	5.20	5.10
Efficiency (dB)	-3.69	-3.38	-3.38	-3.52	-3.69	-4.19	-2.84	-2.24	-1.85	-2.16	-2.07	-2.28
Gain (dBi)	-1.42	-1.08	-1.00	-1.26	-1.40	-1.86	2.76	3.34	3.70	3.11	3.13	2.82
NHPRP ±Pi/4 (dBm)	-4.38	-4.07	-4.07	-4.21	-4.38	-4.88	-4.33	-3.76	-3.34	-3.59	-3.46	-3.64
NHPRP ±Pi/6 (dBm)	-5.46	-5.15	-5.14	-5.29	-5.45	-5.94	-6.16	-5.64	-5.21	-5.43	-5.33	-5.53
NHPRP ±Pi/8 (dBm)	-6.44	-6.12	-6.11	-6.26	-6.42	-6.91	-7.63	-7.12	-6.70	-6.88	-6.79	-7.01
Front/Back Ratio (dB)	0.40	0.58	0.67	0.49	1.07	1.38	9.01	8.27	7.99	7.17	7.22	6.63
Phi BW (°)	182.00	182.00	182.00	182.00	182.00	182.00	87.00	86.00	86.00	96.00	106.00	105.00
+ Phi BW (°)	91.00	91.00	91.00	91.00	91.00	91.00	34.00	34.00	34.00	33.00	40.00	37.00
- Phi BW (°)	91.00	91.00	91.00	91.00	91.00	91.00	53.00	52.00	52.00	63.00	66.00	68.00
Theta BW (°)	94.00	95.00	96.00	99.00	97.00	93.00	69.00	66.00	61.00	59.00	57.00	57.00
+ Th. BW (°)	49	53	54	56	40	46	47	46	42	40	34	35
- Th. BW (°)	45.00	42.00	42.00	43.00	57.00	47.00	22.00	20.00	19.00	19.00	23.00	22.00
Boresight Phi (°)	225.00	210.00	210.00	210.00	210.00	120.00	150.00	150.00	150.00	150.00	135.00	135.00
Boresight Th. (°)	90.00	90.00	90.00	90.00	105.00	105.00	120.00	120.00	120.00	120.00	120.00	120.00
Maximum Power (dBm)	-1.42	-1.08	-1.00	-1.26	-1.40	-1.86	2.76	3.34	3.70	3.11	3.13	2.82
Minimum Power (dBm)	-19.38	-18.89	-18.80	-18.13	-17.71	-18.17	-16.56	-16.51	-17.38	-15.42	-15.27	-14.90
Average Power (dBm)	-4.96	-4.65	-4.64	-4.77	-4.93	-5.42	-2.71	-2.10	-1.78	-2.25	-2.29	-2.56
Max/Min Ratio (dB)	17.96	17.81	17.80	16.87	16.32	16.31	19.32	19.84	21.08	18.53	18.40	17.72
Max/Avg Ratio (dB)	3.54	3.57	3.64	3.51	3.54	3.56	5.47	5.44	5.48	5.36	5.42	5.38
Min/Avg Ratio (dB)	-14.42	-14.24	-14.16	-13.36	-12.78	-12.75	-13.85	-14.40	-15.60	-13.17	-12.98	-12.34
Average Gain (dB)	-3.69	-3.38	-3.38	-3.52	-3.69	-4.19	-2.84	-2.24	-1.85	-2.16	-2.07	-2.28
Note												
Model	Faraday 1.5											
Test / Position	Gain / Free Space (RX)											
Band	GSM850			GSM900			GSM1800			GSM1900		
Channel	869.2	881.4	893.8	925.2	943.4	959.8	1805.2	1842.4	1879.8	1930.2	1960	1989.8
Ant. Port Input Pwr. (dBm)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Tot. Rad. Pwr. (dBm)	-3.09	-3.16	-3.43	-4.07	-4.63	-5.21	-2.08	-2.10	-1.87	-2.27	-2.60	-3.15
Peak EIRP (dBm)	-0.76	-0.88	-1.16	-1.69	-2.34	-2.95	3.08	2.90	3.01	2.23	1.60	0.75
Directivity (dBi)	2.33	2.28	2.27	2.39	2.29	2.26	5.16	5.00	4.87	4.50	4.20	3.90
Efficiency (dB)	-3.09	-3.16	-3.43	-4.07	-4.63	-5.21	-2.08	-2.10	-1.87	-2.27	-2.60	-3.15
Gain (dBi)	-0.76	-0.88	-1.16	-1.69	-2.34	-2.95	3.08	2.90	3.01	2.23	1.60	0.75
NHPRP ±Pi/4 (dBm)	-3.75	-3.83	-4.10	-4.74	-5.32	-5.94	-3.56	-3.54	-3.31	-3.68	-4.00	-4.55
NHPRP ±Pi/6 (dBm)	-4.82	-4.90	-5.17	-5.79	-6.40	-7.04	-5.37	-5.34	-5.15	-5.57	-5.89	-6.41
NHPRP ±Pi/8 (dBm)	-5.78	-5.87	-6.14	-6.75	-7.36	-8.01	-6.77	-6.74	-6.57	-7.03	-7.35	-7.82
Front/Back Ratio (dB)	0.48	0.38	1.25	1.32	1.40	1.62	6.88	6.69	6.27	5.42	4.87	6.65
Phi BW (°)	182.00	182.00	182.00	182.00	182.00	182.00	94.00	109.00	110.00	114.00	120.00	133.00
+ Phi BW (°)	91.00	91.00	91.00	91.00	91.00	91.00	38.00	38.00	36.00	33.00	39.00	66.00
- Phi BW (°)	91.00	91.00	91.00	91.00	91.00	91.00	56.00	71.00	74.00	81.00	81.00	67.00
Theta BW (°)	93.00	93.00	94.00	93.00	95.00	98.00	77.00	71.00	64.00	59.00	64.00	62.00
+ Th. BW (°)	53.00	53.00	47.00	47.00	50.00	55.00	58.00	51.00	46.00	44.00	44.00	15.00
- Th. BW (°)	40.00	40.00	47.00	46.00	45.00	43.00	19.00	20.00	18.00	15.00	20.00	47.00
Boresight Phi (°)	210.00	210.00	120.00	120.00	120.00	120.00	150.00	150.00	150.00	150.00	135.00	75.00
Boresight Th. (°)	90.00	90.00	105.00	105.00	105.00	105.00	120.00	120.00	120.00	120.00	120.00	135.00
Maximum Power (dBm)	-0.76	-0.88	-1.16	-1.69	-2.34	-2.95	3.08	2.90	3.01	2.23	1.60	0.75
Minimum Power (dBm)	-19.17	-18.81	-18.52	-18.83	-19.02	-18.30	-15.79	-14.86	-12.83	-12.49	-11.73	-10.52
Average Power (dBm)	-4.42	-4.49	-4.74	-5.36	-5.87	-6.39	-1.98	-2.10	-1.99	-2.50	-2.86	-3.40
Max/Min Ratio (dB)	18.41	17.93	17.36	17.14	16.68	15.34	18.87	17.76	15.84	14.71	13.33	11.27
Max/Avg Ratio (dB)	3.66	3.61	3.58	3.67	3.53	3.44	5.06	5.01	5.00	4.73	4.46	4.15
Min/Avg Ratio (dB)	-14.75	-14.32	-13.78	-13.47	-13.15	-11.90	-13.81	-12.75	-10.84	-9.99	-8.87	-7.12
Average Gain (dB)	-3.09	-3.16	-3.43	-4.07	-4.63	-5.21	-2.08	-2.10	-1.87	-2.27	-2.60	-3.15
Note												

GSM850 CH189 881.4MHz


Total



Total




Total





GSM900 CH42 943.4MHz

Total




Total






GSM1800 CH698 1842.4MHz


Total



Total




Theta




GSM1900 CH661 1960MHz


Total



Total




Total




GSM850 CH189 836.4MHz


Total



Total




Total





GSM900 CH42 898.4MHz

Total




Total






GSM1800 CH698 1747.4MHz


Total



Total




Theta




GSM1900 CH661 1880MHz


Total



Total



Total



Tornado Bluetooth Chip Antenna Spec:

Frequency range	2400 MHz ~ 2500 MHz
VSWR	2.5 : 1
Peak gain	0 dBi
Average gain	-4.0 dBi
Reference impedance	50 ohm

Notably: The VSWR and gain values will be degraded due to mechanical and space constrains.

Antenna Pattern (2450MHz)

(1) E1-plane:




778 In120 neihu rd sec1
taipei, taiwan r.o.c.
tel:+886-2-26594900
fax:+886-2-26594833
http://www.audio.com

Data#: 120

File#: C:\Program Files\al\ANT\Tornado_Douton_ANT

Date: 2005-06-20 1



equency: 2441 MHz

in, V-Plan, B-Plan:119

Site : site

Total Gain: Avg: -3.25dBi, Max: 147.0deg -0.74dBi, Min: 11.0deg -6.58dBi

V-Plan : Avg: -6.50dBi, Max: 132.0deg -5.13dBi, Min: 270.0deg -8.86dBi

H-Plan : Avg: -6.03dBi, Max: 147.0deg -2.54dBi, Min: 104.0deg -16.03dBi

project : Douton 0620 BT_1

Phase : DVT

CH : 39

plane : E1

date : 2005/06/20

(1) H-plane:




7F8 la120 neiku rd sec1
nipei, taiwan r.o.c.
tel:+886-2-26594900
fax:+886-2-26594833
http://www.autilix.com

Data#: 122

File#: C:\Program Files\at\ANT\Tornado_Debug.ANT

Date: 2005-06-20 T



frequency: 2441 MHz
 blue, V-Plan, H-Plane (dB)
 Site : site
 Total Gain: Avg: -7.26dBi, Max: 46.0deg -5.11dBi, Min: 112.0deg -12.30dBi
 V-Plan : Avg: -12.86dBi, Max: 360.0deg -8.69dBi, Min: 80.0deg -17.31dBi
 H-Plan : Avg: -8.66dBi, Max: 46.0deg -5.77dBi, Min: 310.0deg -15.79dBi
 project : Dostun 0620 NT_1
 Phase : DVT
 CH : 39
 plane : H
 date : 2005/06/20

(3) E2-plane:



7f8 (n) 20 nellu rd sec 1
taipei, taiwan r.o.c.
tel:+886-2-26594900
fax:+886-2-26594833
http://www.audio.com


Data#: 124

File#: C:\Program Files\1\ANT\Tornado_Douton.ANT

0)

0

Date: 2005-06-20 1



equency: 2441 MHz
in, V-Plan, is 2441 MHz

180
Azimuth (deg)

Site : site

Total Gain: Avg: -5.82 dBi, Max: 170.0 deg -1.74 dBi, Min: 270.0 deg -14.54 dBi

V-Plan : Avg: -9.71 dBi, Max: 196.0 deg -5.91 dBi, Min: 266.0 deg -18.02 dBi

H-Plan : Avg: -8.10 dBi, Max: 173.0 deg -3.48 dBi, Min: 215.0 deg -25.80 dBi

project : Douton 0620 BT_1

Phase : DVT

CH : 39

plane : E2

date : 2005/06/20