

MPE CALCULATION

Grayhill

FCC ID: NMAEZCOMLPM

TITLE: Grayhill MPE CALCULATION		 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT		W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com	
PROJECT: GRAYHILL EZ-COM LPM CERTIFICATION					
DRAWN BY: JOHN LOFGREN SR. ENGR.	DATE: March 10, 2003	SIZE: A	DRAWING NUMBER: GRAYHILL-MPE-V1.0		REVISION: 0.5
CHECKED BY: BRIAN PETTED VP ENG	DATE: March 10, 2003				
APPROVED BY: BRIAN PETTED VP ENG	DATE: March 10, 2003				
FILENAME, FILES AFFECTED: Grayhill_MPE_Calculation_v0.51 May 29.doc		SCALE: NOT TO SCALE		SHEET: 1 OF 6	

TABLE OF CONTENTS

1.0	SCOPE.....	3
2.0	REVISION CONTROL	3
3.0	APPLICABLE DOCUMENTS	3
4.0	MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS.....	4

TITLE:	GRAYHILL MPE CALCULATION	 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT:	GRAYHILL EZ-COM LPM CERTIFICATION		
FILENAME, FILES AFFECTED:	Grayhill_MPE_Calculation_v0.51 May 29.doc	REVISION:	PAGE:
		0.5	2 OF 6

1.0 SCOPE

This report demonstrates the Maximum Permissible Exposure (MPE)
Calculation required for an Intentional Radiator equipment authorization.

2.0 REVISION CONTROL

DATE	CHANGES	REVISION
03/10/03	ORIGINAL RELEASE	0.0
03/19/03	ADD CALCULATIONS FOR MOBILE UNITS, CHANGE PRESENTATION FORMAT	0.1
03/31/03	CORRECT ANTENNA GAIN AND SEPARATION DISTANCE MISPRINTS FOR YAGI AND OMNI ANTENNAS	0.2
04/03/03	CORRECT DISTANCES FROM 3000CM TO 300CM IN YAGI AND OMNI CALCULATIONS	0.3
04/08/03	CHANGE DISTANCE FOR YAGI AND OMNI FROM 3m TO 2m	0.4
04/08/03	CORRECT YAGI GAIN FROM 9.9dbd TO 9.2 dbd	0.5

3.0 APPLICABLE DOCUMENTS

[1] "Code of Federal Regulations Title 47, Volume 1, Sec. 1.1310
Radiofrequency radiation exposure limits" **47CFR1.1310**, Revised as of October
1, 2001, Page 297-298.

[2] "Code of Federal Regulations Title 47, Volume 1, Sec. 2.1091
Radiofrequency radiation exposure evaluation: mobile devices." **47CFR2.1091**,
Revised as of October 1, 2001, Page 588-589.

[3] "Evaluating Compliance with FCC Guidelines for Human Exposure to
Radiofrequency Electromagnetic Fields", Supplement C, OET Bulletin 65, Edition
97-01

TITLE:	GRAYHILL MPE CALCULATION	 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT:	GRAYHILL EZ-COM LPM CERTIFICATION		
FILENAME, FILES AFFECTED:	Grayhill_MPE_Calculation_v0.51 May 29.doc	REVISION:	PAGE:
		0.5	3 OF 6

4.0 MAXIMUM PERMISSIBLE EXPOSURE CALCULATIONS

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 27.0 (dBm)

Maximum peak output power at antenna input terminal: 501.19 (mW)

Antenna gain(typical): 0.0 (dBi)

Maximum antenna gain: 1.00 (numeric)

Prediction distance: 10 (cm)

Prediction frequency: 915 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 0.61 (mW/cm²)

Power density at prediction frequency: 0.40 (mW/cm²)

Maximum allowable antenna gain: 1.85 (dBi)

Margin of Compliance at 10cm = 1.83 dB

Calculation 1. Portable unit with 0 dBi helical antenna and 10 cm separation.

TITLE: GRAYHILL MPE CALCULATION		 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT: GRAYHILL EZ-COM LPM CERTIFICATION			
FILENAME, FILES AFFECTED: Grayhill MPE Calculation v0.51 May 29.doc		REVISION: 0.5	PAGE: 4 OF 6

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 27.00 (dBm)

Maximum peak output power at antenna input terminal: 501.19 (mW)

Antenna gain(typical): 9.14 (dBi)

Maximum antenna gain: 8.20 (numeric)

Prediction distance: 200 (cm)

Prediction frequency: 915 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 0.6 (mW/cm²)

Power density at prediction frequency: 8.180 (μW/cm²)

Maximum allowable antenna gain: 27.79 (dBi)

Margin of Compliance at 2m = 18.7dB

Calculation 2. Mobile unit with 7 dBd (9.14 dBi) omnidirectional antenna and 2 meter separation.

TITLE: GRAYHILL MPE CALCULATION		 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com	
PROJECT: GRAYHILL EZ-COM LPM CERTIFICATION				
FILENAME, FILES AFFECTED: Grayhill MPE Calculation v0.51 May 29.doc		REVISION: 0.5	PAGE: 5 OF 6	

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 27.00 (dBm)

Maximum peak output power at antenna input terminal: 501.19 (mW)

Antenna gain(typical): 11.34 (dBi)

Maximum antenna gain: 13.61 (numeric)

Prediction distance: 200 (cm)

Prediction frequency: 915 (MHz)

MPE limit for uncontrolled exposure at prediction frequency: 0.6 (mW/cm²)

Power density at prediction frequency: 13.575 (μW/cm²)

Maximum allowable antenna gain: 27.79 (dBi)

Margin of Compliance at 2m = 16.5dB

Calculation 3. Mobile unit with 9.2 dBd (11.34 dBi) Yagi antenna and 2 meter separation.

TITLE: GRAYHILL MPE CALCULATION		 L.S. RESEARCH, Inc. WIRELESS PRODUCT DEVELOPMENT	W66 N220 COMMERCE COURT CEDARBURG, WI 53012, USA (262)-375-4400 FAX: (262)-375-6731 email: eng@lsr.com, http://www.lsr.com
PROJECT: GRAYHILL EZ-COM LPM CERTIFICATION			
FILENAME, FILES AFFECTED: Grayhill_MPE_Calculation_v0.51_May_29.doc		REVISION: 0.5	PAGE: 6 OF 6